



No. 4Z782



No. 48LR62

BOSTITCH Senco
Pneumatic Coil Roofing Nailers and Nails

These nailers feature depth-of-drive adjustment for added versatility. No. 4Z782 has contact trip trigger and magnesium housing for durability. Features fixed exhaust, single-action canister, rubber housing pads that prevent sliding, and tool-free shingle gauge. Hardened nose with carbide inserts resists wear. No. 48LR62 features an innovative firing valve that reduces air consumption without a reduction in speed or power. Includes an adjustable and removable shingle guide.

Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Wt.	Brand	Mfr. Model	Item No.
Straight								
15°	Wire	3/4" to 1 1/4"	0.120"	120	4.90 lb.	Bostitch	RN46-1	4Z782
Angled								
15°	Wire	3/4" to 1 1/4"	0.120"	120	5.20 lb.	Senco	ROOFFPRO 445XP	48LR62
L	Mfr. Model	Item No.	Pkg. Qty.	L	Mfr. Model	Item No.	Pkg. Qty.	
Bostitch® Smooth, 15°, 0.120" Shank Dia.				Senco® Smooth, 15°, 0.120" Shank Dia.				
1"	CR2D GAL	5W012	7200	3/4"	M003101	48LR63	7200	
1 1/4"	CR3D GAL	2W762	7200	7/8"	M003102	48LR64	7200	
1 1/2"	CR4D GAL	2W763	7200	1"	M003103	48LR65	7200	
1 3/4"	CR5D GAL	2W764	7200	1 1/2"	M003105	48LR66	7200	
Senco® Smooth, 0°, 0.120" Shank Dia.				1 3/4"	M003106	48LR67	7200	
1 1/4"	M003104	21U158	7200					



No. 31CC52



No. 4Z931

BOSTITCH SPEEDAIRE Senco
Pneumatic Coil Framing Nailers and Nails

Aluminum housing
Quick-driving nailers are easy to handle. No. 31CC52 includes 5mm and 6mm hex wrenches. No. 4Z931 has adjustable exhaust.

Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Wt.	Brand	Mfr. Model	Item No.
Air Framing Nailer								
15°	Wire	1/2" to 3/4"	0.099" to 0.130"	300	8.16 lb.	Speedaire	31CC52	31CC52
15°	Wire	1 1/2" to 3/4"	0.099" to 0.120"	300	8.40 lb.	Bostitch	N80CB-1	4Z931
15°	Wire	2" to 3/2"	0.099" to 0.131"	225/275	8.00 lb.	Senco	SGN65XP	48LR11
L	Shank Dia.	Shank	Finish	Point Type	Mfr. Model	Item No.	Pkg. Qty.	
Bostitch® Wire Collation Type, 15° Collation Angle, Framing Nails								
2"	0.099"	Smooth	Coated	Diamond	C6P99D	5W014	3600	
2 1/2"	0.120"	Smooth	Coated	Diamond	C8P120D	5W016	2700	
3"	0.120"	Smooth	Coated	Diamond	C10P120D	5W017	2700	
3"	0.120"	Smooth	Thickcoat Galvanized	Diamond	C10P120DG	3HZH6	2700	
3 1/4"	0.120"	Smooth	Coated	Diamond	C12P120D	5W018	2700	
3 1/4"	0.120"	Smooth	Thickcoat Galvanized	Diamond	C12P120DG	3HZH7	2700	
Bostitch® Wire Collation Type, 15° Collation Angle, Siding Nails								
2 1/2"	0.099"	Ring	Coated	Blunt Diamond	C8R99BD	3HZJ3	3600	
2 1/2"	0.099"	Ring	Thickcoat Galvanized	Blunt Diamond	C8R99BDG	3HZJ2	3600	



No. 3HZF8

BOSTITCH Senco DUO-FAST
Pneumatic Coil Siding/Utility Nailers and Nails

These nailers drive wire and plastic-sheet collated nails and have adjustable depth of drive. No. 31CC55 has tool-less depth adjustment and a transparent magazine cover. No. 3HZF8 features tool-free adjustable exhaust and soft rubber foot. No. 21U132 has a trigger to select the operation mode.

Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Wt.	Brand	Mfr. Model	Item No.
Angled								
15°	Wire/Plastic	1 1/4" to 2 1/2"	0.080" to 0.090"	300 to 350	4.70 lb.	Bostitch	N66C-1	3HZF8
15°	Wire/Plastic	1 1/4" to 2 1/2"	0.082" to 0.113"	250 to 375	5.1 lb.	Senco	SCN49XP	21U132
Length	Shank Dia.	Shank	Finish	Mfr. Model	Item No.	Pkg. Qty.		
Bostitch®, Wire Collation, 15° Coil Siding/Utility Nails								
1 3/8"	0.100"	Spiral	Mechanically Galvanized	C4DCSBALG	5KNH6	3600		
2"	0.092"	Ring	Thickcoat Galvanized	C6R90BDG	3HZH8	3600		
2 3/8"	0.090"	Ring	Thickcoat Galvanized	C7R90BDG	3HZH9	3600		
2 1/2"	0.090"	Ring	Thickcoat Galvanized	C8R90BDG	3HZJ1	3600		
Duo-Fast®, Plastic Collation, 0° Coil Siding/Utility Nails								
1 7/8"	0.086"	Ring	Hot Dipped Galvanized	650392	6KVX2	3600		
2 1/4"	0.092"	Ring	Hot Dipped Galvanized	650394	6KVX3	3600		
Senco 15° Full Round Shank Coil Siding/Utility Nails								
2 1/4"	0.092"	Smooth	Electro Galvanized	ED23AABH	48LP97	3600		
2 1/4"	0.092"	Smooth	Hot Dipped Galvanized	EJ23ASBC	48LP98	3600		
Senco 15° Ring Shank Coil Siding/Utility Nails								
1 3/4"	0.092"	Ring	Hot Dipped Galvanized	EL19ASBH	21U147	3600		
2"	0.092"	Ring	Hot Dipped Galvanized	EL21ASBH	21U148	3600		



No. 48LP96

Senco
Pneumatic Pallet Nailer and Nails

Features high load capacity and an adjustable nail canister that accepts nails up to 2 1/4". Has a rugged driver and piston bumper for long life, and side steel wear plates for added housing protection. Ideal for boxes, crates, and pallet applications.

Collation Angle	Collation Type	Fastener Range	Shank Dia.	Magazine Cap.	Tool Wt.	Mfr. Model	Item No.
Angled							
15°	Wire	1" to 2 1/4"	0.082" to 0.092"	300/350	5.90 lb.	PALLETPRO57FXP	48LP96
Length	Shank Dia.	Shank	Finish	Point Type	Mfr. Model	Item No.	Pkg. Qty.
Wire Collation Type, 15° Collation Angle Framing Nails							
2 1/4"	0.092"	Ring	Hot Dipped Galvanized	Diamond	EL23ASBH	48LP99	3600