



## Pneumatic Industrial-Duty Belt Sanders

Note: See page 2364 for abrasive belts. For contact arm assemblies and tune up kits, go to Grainger.com®.



Chicago  
Pneumatic



Ingersoll Rand



Belt Size	Free Speed	Average CFM @ 15-sec. Run Time	CFM @ Full Load†	Exhaust Type	Includes	Overall Length	Brand	Mfr. Model	Item No.
<b>Sanders</b>									
1/8 to 1/2 in W x 24 in L	20,000 RPM	7.75 cfm	31 cfm	Front	Mfg. Model 11218 Contact Arm	14 3/4 in	Dynabrade	14000	11X731
1/8 to 1/2 in W x 12 in L	25,000 RPM	5 cfm	20 cfm	Front and Rear	Mfg. Model 15026 Contact Arm, Mfg. Model 15118 Drive Wheel	11 3/4 in	Dynabrade	15003	11X737
3/4 to 1 in W x 18 in L	20,000 RPM	7 cfm	28 cfm	Front	Mfg. Model 11206 Contact Arm	14 1/4 in	Dynabrade	40320	11X733
1/4 to 3/4 in W x 20 1/2 in L	20,000 RPM	7 cfm	28 cfm	Front	Mfg. Model 11287 Contact Arm	14 1/4 in	Dynabrade	40326	11X735
3/8 in W x 13 in L	22,000 RPM	14 cfm	28 cfm	Rear	—	12 in	Chicago Pneumatic	CP9779	11C997
1/2 in W x 12 in L	12,000 RPM	4.75 cfm	19 cfm	Rear	—	10 3/4 in	Ingersoll Rand	G1A120RS812	1TDH6
1/2 in W x 24 in L	20,000 RPM	10.8 cfm	21.6 cfm	Rear	—	15 1/2 in	Chicago Pneumatic	CP5080-4200D24	22P496
1/2 in W x 18 in L	20,000 RPM	10.8 cfm	21.6 cfm	Rear	—	13 3/4 in	Chicago Pneumatic	CP5080-4200H18	22P497
1/2 in W x 12 in L	26,000 RPM	8.9 cfm	17.8 cfm	Rear	Mfg. Model 11203 Contact Arm	14 1/4 in	Dynabrade	40335	25H829
1/2 in W x 12 in L	26,000 RPM	8.9 cfm	17.8 cfm	Rear	—	11 3/4 in	Chicago Pneumatic	CP5080-3260D12	22P495
1 in W x 18 in L	22,000 RPM	13.55 cfm	27.1 cfm	Rear	—	13 3/4 in	Chicago Pneumatic	CP5080-5220H18	22P512
<b>Kits</b>									
1/8 to 1/2 in W x 24 in L	20,000 RPM	7.75 cfm	31 cfm	Front	(5) Contact Arms, Assortment of Abrasive Belts, Case	14 3/4 in	Dynabrade	14010	11X732
3/4 to 1 in W x 18 in L	20,000 RPM	7 cfm	28 cfm	Front	(2) Wrenches, (3) Contact Arms, (3) Platen Pads, (8) Abrasive Belts, 1/4 in Collet For Die Grinder Use, Case	14 1/4 in	Dynabrade	40321	11X734
1/2 in W x 18 in L	20,000 RPM	8.9 cfm	21.6 cfm	Rear	(1) Hex Key, (3) Contact Arms, (5) Belts	13 3/4 in	Chicago Pneumatic	CP5080-4200H18K	22P511
1/2 in W x 12 in L	20,000 RPM	4.2 cfm	24 cfm	Rear	(2) Surface Prep Belt, 3mm Hex Key, Grinding Belt #120, Grinding Belt #60	12 3/4 in	Speedaire	21AC03	21AC03
	26,000 RPM	4.4 cfm	17.8 cfm	Rear	(1) Hex Key, (3) Contact Arms, (5) Belts	11 3/4 in	Chicago Pneumatic	CP5080-3260D12K	22P510
3/4 in W x 18 in L	18,000 RPM	4.5 cfm	12.5 cfm	Rear	4mm Hex Key, Grinding Belt #60, Grinding Belt #80, Handle	15 1/2 in	Speedaire	21AC02	21AC02

† Avg. cfm is based on a 1-min. run time.



## Pneumatic Random Orbital and Geared Dual-Action Sanders

- Vinyl pad face
- 3/16" orbit, except 3YY25, and 3YY26 have 3/32" orbit

**Geared Dual Action (DA)**—Dual-action motion pad provides swirl-free finishes. Come with a 6" foam-backed pad that accepts PSA sandpaper.

For Use With	Brand	Mfr. Model	Item No.
<b>Tune Up Kits, include Bearings O-Rings, Muffler Components, Rotor and Vane Set</b>			
56815, 56818, 56819, 56826	Dynabrade	96024	13F716
13F636, 13F637, 13F638, 13F639	Dynabrade	96620	13F717
13F632, 13F633, 13F634, 13F635	Dynabrade	96510	13F718

\* Nonvacuum sanders use PSA (pressure sensitive adhesive) sandpaper. See Index under "Sandpaper, PSA Disc." † Avg. cfm is based on 1-min. run time.

HP	Pad Size	Pad Face Type	Orbit Dia.	Free Speed	CFM @ Full Load†	Overall Length	Brand	Mfr. Model	Item No.
<b>Geared Dual Action (DA)</b>									
<b>Self Generating Vacuum</b>									
0.25 hp	6"	PSA	3/16 in	12,000 RPM	17 cfm	9 3/4 in	Ingersoll Rand	311A	6Z563
	8"	PSA	3/16 in	825 RPM	16 cfm	7 1/4 in	Ingersoll Rand	328B	4Y368
0.3 hp	6"	PSA	3/16 in	10,000 RPM	18 cfm	4 1/2 in	Chicago Pneumatic	CP870	11C967
<b>Light Duty Mini Kit</b>									
0.2 hp	2" and 3"	Hook-and-Loop	3/32 in	15,000 RPM	21 cfm	5 4/64 in	Chicago Pneumatic	CP7200S	11C917
	3"	Hook-and-Loop	3/16 in	15,000 RPM	14.7 cfm	18 1/4 in	Ingersoll Rand	3128XPA	12T594
<b>Random Orbital Sanders</b>									
<b>Central Vacuum</b>									
0.25 hp	5"	PSA	3/16 in	12,000 RPM	14 cfm	7 1/4 in	Dynabrade	59024	13F635
0.26 hp	5"	PSA	3/16 in	12,000 rpm	16.0	7 1/4 in	Dynabrade	69024	13F639
0.28 hp	5"	PSA	3/16 in	12,000 RPM	18 cfm	7 1/4 in	Dynabrade	56819	13F643
0.3 hp	6"	PSA	3/16 in	12,000 RPM	16 cfm	8 4/64 in	Chicago Pneumatic	CP7255CV	11C923
<b>Nonvacuum</b>									
0.08 hp	1 1/4"	Locking	3/16 in	7,500 RPM	6 cfm	5 in	Dynabrade	57502	25H968
	3 1/2"	PSA	3/16 in	12,000 RPM	15.8 cfm	7 in	Ingersoll Rand	RS23B-PLV-1	3YY27
	5"	PSA	3/16 in	12,000 RPM	15.8 cfm	7 in	Ingersoll Rand	R025B-PSV-1	3JF08 *
	5"	PSA	3/32 in	12,000 RPM	15.8 cfm	7 in	Ingersoll Rand	R025B-PSV-2	3YY25
0.2 hp	5"	PSA	3/16 in	12,000 RPM	16 cfm	6 1/2 in	Chicago Pneumatic	CP3511	11C903
	6"	PSA	3/16 in	12,000 RPM	15.8 cfm	7 1/2 in	Ingersoll Rand	R026B-PSV-1	3JF13 *
	6"	PSA	3/32 in	12,000 RPM	15.8 cfm	7 1/2 in	Ingersoll Rand	R026B-PSV-2	3YY26
	5"	PSA	3/16 in	12,000 RPM	14 cfm	6 1/2 in	Dynabrade	59020	13F632
0.25 hp	5"	Vinyl	3/32 in	12,000 RPM	14 cfm	6 1/2 in	Dynabrade	59035	25J005
	6"	PSA	3/16 in	12,000 RPM	14 cfm	6 1/2 in	Dynabrade	59005	25H994
	6"	PSA	3/16 in	12,000 RPM	14 cfm	7 in	Dynabrade	59025	13F633
0.26 hp	5"	PSA	3/16 in	12,000 rpm	16.0	7 in	Dynabrade	69025	13F637
0.26 hp	5"	PSA	3/16 in	12,000 RPM	16 cfm	6 1/2 in	Dynabrade	69020	13F636
	5"	PSA	3/16 in	12,000 RPM	18 cfm	6 1/2 in	Dynabrade	56815	13F640
0.28 hp	5"	Vinyl	3/32 in	12,000 RPM	18 cfm	6 1/2 in	Dynabrade	56850	25H957
	6"	PSA	3/16 in	12,000 RPM	18 cfm	7 in	Dynabrade	56826	13F641
	5"	PSA	3/16 in	10,000 RPM	18.5 cfm	7 in	Ingersoll Rand	R035A-PSV	3JF18 *
0.3 hp	5"	PSA	3/32 in	12,000 RPM	16 cfm	7 1/2 in	Chicago Pneumatic	CP7225	11C920
	6"	PSA	3/16 in	12,000 RPM	16 cfm	7 3/4 in	Chicago Pneumatic	CP7255	11C922
	6"	Hook-and-Loop	3/16 in	12,000 RPM	16 cfm	7 3/4 in	Chicago Pneumatic	CP7255E	11C924
0.45 hp	6"	Hook-and-Loop	3/16 in	12,000 RPM	23 cfm	11 1/4 in	Dynabrade	58435	13F648
—	3 3/8 in x 7 in	Vinyl or Hook	3/32"	10,000 RPM	16 cfm	7 1/4 in	Dynabrade	57810	25H971
<b>Nonvacuum, Palm</b>									
0.3 hp	6"	PSA	3/16 in	10,000 RPM	18.5 cfm	7 1/2 in	Ingersoll Rand	R036A-PSV	3JF24 *
<b>Self Generating Vacuum</b>									
0.2 hp	5"	PSA	3/16 in	12,000 RPM	15.8 cfm	7 in	Ingersoll Rand	R025B-VLV-1	3JF09
0.25 hp	5"	PSA	3/16 in	12,000 RPM	14 cfm	8 1/2 in	Dynabrade	59023	13F634
0.28 hp	5"	PSA	3/16 in	12,000 RPM	18 cfm	8 1/2 in	Dynabrade	56818	13F642
	3 1/16" x 6 3/4"	PSA	—	8,000 RPM	12 cfm	9 in	Ingersoll Rand	312A	5LA61
0.3 hp	3 3/8" x 6 1/2"	Foam Rubber	3/32 in	8,000 RPM	17.6 cfm	7 3/4 in	Speedaire	21AC01	21AC01
	6"	PSA	3/16 in	12,000 RPM	16 cfm	9 1/4 in	Chicago Pneumatic	CP7255SV	11Z511
<b>Vacuum Ready</b>									
0.2 hp	5"	PSA	3/16 in	12,000 RPM	15.5 cfm	7 in	Ingersoll Rand	4151-5	5RAE9
	6"	PSA	3/16 in	12,000 RPM	15.5 cfm	7 in	Ingersoll Rand	4151	1MM30
	6"	PSA	—	12,000 RPM	15.5 cfm	7 1/2 in	Ingersoll Rand	4152	45A254
0.26 hp	5"	PSA	3/16 in	12,000 rpm	16.0	8 1/2 in	Dynabrade	69021	13F638
0.3 hp	5"	PSA	3/16 in	10,000 RPM	18.5 cfm	7 in	Ingersoll Rand	R035A-CSV	3JF15
	6"	PSA	3/16 in	10,000 RPM	18.5 cfm	7 1/2 in	Ingersoll Rand	R036A-CSV	3JF21