

1-800-GRAINGER (472-4643)



## Washdown & Pressure Washer Spring-Return Hose Reels

Reels hold water hoses for heavy-duty cleaning applications. Spring-return hose reels help retract hose onto the reel without an external power source. The spring-return has a locking ratchet and pawl that locks into place once users have pulled the hose to the desired length. The ratchet is released by pulling the hose out, and then hose can be rewound onto the reel. Stainless steel reels withstand rust, corrosion, contaminants, and saltwater. **Pressure washer reels** hold hoses that use high pressure to remove dirt, grease, and grime in food processing plants, pulp and paper plants, and equipment. **Washdown reels** handle hoses for low- to high-water volume output with a range of psi requirements for low- or high-pressure applications such as cleaning service bays, food processing plants, and fleet maintenance. 3MJJ5 includes hose.



Hose Cap.	Hose End Configuration	Maximum Operating Pressure	Overall Dim.	Swivel Material	Brand	Item No.
<b>Corrosion-Resistant Stainless Steel Washdown Spring-Return Hose Reels</b>						
<b>Hose Not Included</b>						
25 ft (½ in I.D.)	—	300 psi	7 in L x 17 ½ in W x 18 ¾ in H	Stainless Steel	Coxreels	16X545
25 ft (¾ in I.D.)	—	300 psi	19 ½ in L x 9 ¾ in W x 25 ½ in H	Stainless Steel	Coxreels	16X548
50 ft (½ in I.D.)	—	500 psi	19 ¾ in L x 7 in W x 20 ¼ in H	Stainless Steel	Reelcraft	6Z785
50 ft (¾ in I.D.)	—	300 psi	23 in L x 9 ¾ in W x 25 ½ in H	Stainless Steel	Coxreels	271F16
70 ft (¾ in I.D.)	—	300 psi	19 ¾ in L x 8 ½ in W x 20 ½ in H	Brass	Reelcraft	38EE94
100 ft (½ in I.D.)	—	500 psi	24 in L x 10 ½ in W x 25 ¾ in H	Stainless Steel	Reelcraft	5KPC2
<b>Hose Included</b>						
50 ft (½ in I.D.)	½ in MNPT	300 psi	20 ¾ in L x 8 7/8 in W x 22 ½ in H	Stainless Steel	Speedaire	2CUD4
<b>Corrosion-Resistant Stainless Steel Dual-Pedestal Washdown Spring-Return Hose Reels</b>						
<b>Hose Not Included</b>						
50 ft (¾ in I.D.)	—	500 psi	24 in L x 10 ½ in W x 25 ¾ in H	Stainless Steel	Reelcraft	38L549
50 ft (1 in I.D.)	—	500 psi	24 in L x 15 ¾ in W x 25 ¾ in H	Stainless Steel	Reelcraft	5KPC3
75 ft (¾ in I.D.)	—	500 psi	24 in L x 13 in W x 25 ¾ in H	Stainless Steel	Reelcraft	6Z786
<b>Corrosion-Resistant Stainless Steel Pressure-Washer Spring-Return Hose Reel</b>						
<b>Hose Not Included</b>						
50 ft (¾ in I.D.)	—	3,000 psi	19 ½ in L x 8 ¼ in W x 21 ¼ in H	Stainless Steel	Coxreels	16X549
<b>Enclosed Corrosion-Resistant Stainless Steel Air or Water Spring-Return Hose Reels</b>						
<b>Hose Not Included</b>						
50 ft (¾ in I.D.)	—	300 psi	21 ¾ in L x 8 ½ in W x 21 ¾ in H	Stainless Steel	Coxreels	29PY05
50 ft (½ in I.D.)	—	300 psi	21 ¾ in L x 8 ½ in W x 21 ¾ in H	Stainless Steel	Coxreels	33N085
<b>Pressure-Washer Spring-Return Hose Reels</b>						
<b>Hose Not Included</b>						
50 ft (¾ in I.D.)	—	5,000 psi	19 ¾ in L x 7 in W x 20 ¼ in H	Nickel Plated Steel	Reelcraft	2CAG9
100 ft (¾ in I.D.)	—	5,000 psi	19 ¼ in L x 12 ¾ in W x 21 ¼ in H	Steel	Speedaire	45U254
100 ft (¾ in I.D.)	—	5,000 psi	24 in L x 10 ½ in W x 25 ¾ in H	Nickel Plated Steel	Reelcraft	4NB25
<b>Hose Included</b>						
50 ft (¾ in I.D.)	¼ in MNPT	4,800 psi	19 ¾ in L x 7 in W x 20 ¼ in H	Nickel Plated Steel	Reelcraft	38EE39
75 ft (¾ in I.D.)	¼ in MNPT	4,800 psi	19 ¾ in L x 8 ¼ in W x 20 ¼ in H	Nickel Plated Steel	Reelcraft	48ZX02
<b>Washdown Spring-Return Hose Reel</b>						
50 ft (½ in I.D.)	½ in MNPT	232 psi	19 ¾ in L x 9 ¾ in W x 22 in H	Brass	Reelcraft	3MJJ5



## Pre-Rinse & Potable Water Spring-Return Hose Reels

- Spring-return retracts hose without external power source
- Reels mount to floor, walls, or ceiling
- Adjustable hose guide included
- Includes hose

**Pre-rinse reels** hold hoses that carry water to highly corrosive environments and are powder-coated. **Enclosed pre-rinse reel** shields out any contaminants to protect and extend the life of the reel, the hose, and the components inside. Both types are rated for hot water washdown and food prep in restaurants and commercial kitchens. **Potable water reel** connects hoses to drinking water systems. This single-pedestal reel has a full-flow stainless steel fluid path with a PVC swivel, drain, and standard female garden hose fitting. It holds low-pressure water hoses to bring potable water to water purification plants, water storage tanks, and food and beverage plants.



Hose Cap.	Hose End Configuration	Maximum Operating Pressure	Overall Dim.	Swivel Material	Item No.
<b>Pre-Rinse Spring-Return Hose Reels</b>					
25 ft (¾ in I.D.)	Spray Valve x ¾ in MNPT	125 psi	12 ¾ in L x 7 in W x 12 ¾ in H	Brass	38L556
35 ft (¾ in I.D.)	¾ in MNPT x ¾ in FNPT	125 psi	14 ¼ in L x 6 ½ in W x 14 ¾ in H	Brass	4NB27
<b>Enclosed Pre-Rinse Spring Return Hose Reel</b>					
35 ft (¾ in I.D.)	¾ in MNPT	125 psi	16 ¼ in L x 7 in W x 15 in H	Brass	3MJJ1
<b>Potable Water Spring Return-Hose Reel</b>					
35 ft (½ in I.D.)	¾ in FGHT x ¾ in FNH	150 psi	14 ¼ in L x 6 ½ in W x 14 ¾ in H	PVC	4NB26

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**