30G254

22mm E-Stops, **Mushroom-Head**

- **Push Buttons— Complete Units** Red, 40mm dia. head
- Maintained contact

Dayton

■ NEMA 1, 2, 3, 4, 4X, 12, and 13 rated

Action	Contact Form	PLASTIC Item No.	CHROME DIE CASTALUMINUM Item No.
Push / Turn To Release	1NC	30G252	30G253
Push / Turn To Release	1NO/1NC	30G254	30G255
Push / Pull - Trigger Release	1NO/1NC	30G250	30G251
Push / Pull	1NC	30G248	30G249
Push / Key Release	1NC	30G256	30G257
Push / Key Release	1NO/1NC	32UK35	30G258

2UZD4

Schneider Electric

22mm Emergency **Stop Mushroom-Head Push Buttons-Complete Units**

Red, 40mm dia. triggeraction operator

SAFETY, TECHNOLOGY

- No-notch mounting
- NEMA 1, 2, 3, 4, 4X, 12, and 13 rated



Include operator, cap, and contact block for easy installation. UL Listed, CSA Certified, and CE Certified. Meet IEC standards

Action	Form	Item No.	Item No.
Maintained Push / Maintained Pull	1NO/1NC	2UZD4	6HK82
Maintained Push / Turn To Release	1NO/1NC	6HL63	6HK79
Maintained Push / Key Release	1NO/1NC	2UZD6	6HK80
Maintained Push / Maintained Pull	1NC	33HP38	33HP36
Maintained Push / Turn To Release	1NC	33HP37	33HP33
Maintained Push / Turn To Release	2NC	_	33HP34
Maintained Push / Key Release	1NC	_	33HP35

Emergency Stop Switches, Enclosure, and Legend Plates



SWITCHES Switches allow direct disconnect of circuit contacts in emergency situations. Easy to spot, access, and use. On/Off operation, push to lock, turn to reset. Plastic construction Safety lock mechanism prevents operating errors; finger protection mechanism Red operator for added safety. Easy mounting and removal of switch blocks, using a lever.

Oil-resistant to IP65. UL Listed and CE Certified.

		NONLIGHTED		LIGHTED			
Contact Type	Size	Mfr. Model	ltem No.	Size	Voltage	Mfr. Model	Item No.
16mm Mount, 5A at 12	5VAC, 3A at	250VAC					
SPST-NC	16 mm	A165E-S-01	2LCB3	16 mm	24V AC/DC	A165E-LS-24D-01	2LCB1
DPST-NC	16 mm	A165E-S-02	2LCB4	16 mm	24V AC/DC	A165E-LS-24D-02	2LCB2
22mm Mount, 10A at 1	10VAC, 6A at	t 220VAC					
DPST-NC	22 mm	A22E-M-02	2LCB8	22 mm	24V AC/DC	A22ELM24A02	2LCB7
DPST-NC	22 mm	A22EM02B	2LCB9 *	_		_	_
DPST-NC, SPST-NO	22 mm	A22E-M-12	2LCC1	_	_	_	_
DPST-NC	22 mm	A22F-L-02	2LCB6	_	_		_

* With integrated control box.

No. of Holes	Hole Size	H (in.)	W (in.)	D (in.)	Contact Block Depth (in.)	Mfr. Model	Item No.
Control B	ox Pushbi	itton Énc	losure, N	EMÀ 4X, Y	ellow Plastic		
1	22 mm	2.67	2.67	2.73	2.15	A22Z-B101Y	2LCC2

2LCB6

2LCB1

Description	woaei	NO.
Legend Plates		
Blank, For Use with 16mm Push-Buttons, Yellow Field	A16Z-5070	2LCB5
"Emergency Stop", For Use with 22mm Push-Buttons, Black Letters on Yellow Field	A22Z-3466-1	2LCC3
"Emergency Off", For Use with 22mm Push-Buttons, Black Letters on Yellow Field	A22Z-3466-2	2LCC4

FATON

22mm and 30mm Emergency Stop Push Buttons

- Red mushroom head
- Nonilluminated

	Contact		Head	Mfr.	Item		
Action	Form	Legend	Material	Model	No.		
22 mm Hole Dia., 45mm Mushroom Head							
Main. Push / Main. Pull	1NC	No Legend	Plastic	M22-PV-K01	30XF74		
Main. Push / Turn To Release	1NC	No Legend	Plastic	M22-PVT-K01	30XF75		
Main. Push / Turn To Release	2NC	No Legend	Plastic	M22-PVT-K02	30XF73		
30 mm Hole Dia., 40mm Mushroom I	Head						
Main. Push / Main. Inter. / Mom. Pull	1NC	No Legend	Metal	10250T9B62-3X	39P798		
Main. Push / Main. Pull	1NC	Emergency Stop	Metal	10250T5B63-71X	39P790		
Main. Push / Main. Pull	1NC	No Legend	Plastic	10250T5B62-71X	39P789		
Main. Push / Main. Pull	1NO/1NC	Emergency Stop	Metal	10250T5B63-1X	39P794		
Main. Push / Main. Pull	1NO/1NC	No Legend	Metal	10250T5B62-1X	39P793		
Mom. Push / Main. Inter. / Mom. Pull	1NC	No Legend	Metal	10250T4B62-3X	39P802 †		
Mom. Push / Main. Inter. / Mom. Pull	1NC	No Legend	Metal	10250T10B62-1X	39P804 ±		
30 mm Hole Dia., 65mm Mushroom I	Head						
Main. Push / Main. Pull	1NC	Emergency Stop	Metal	10250T5J63-71X	39P792		
Main. Push / Main. Pull	1NC	No Legend	Metal	10250T5J62-71X	39P791		
Main. Push / Main. Pull	1NO/1NC	Emergency Stop	Aluminum	10250T5J63-1X	39P795		
Main. Push / Main. Pull	1NO/1NC	Emergency Stop	Aluminum	10250ED1080-2	39P796 *		
* Special security jumbo mushroom	* Special security jumbo mushroom head. † Contact configuration: XX OX OO						
# Contact configuration: OX OO XO	/ 00	gurum	07. 0	•			
7 Contact Configuration. Ox CO XC							

30XF73

39P798

Hoffman

Emergency Push-Button Stations

- 600VAC
- Contact: 1NC
- Contact rating: 10A, A600/Q300

Designed with red operator. Wall-mountable. Metallic series includes legend. UL Listed, CSA Certified.



29YK60

Type of Operator	Н	w	D	Mfr. Model	Item No.
Non-Metallic, NEMA 4X					
Push Button with Mushroom Head	2.83 in	2.83 in	2.1 in	ESNM	29YK51
Cast Aluminum, NEMA 4X					
Push Button with Mushroom Head	3.43 in	3.43 in	2.95 in	VS-ESCA	29YK60
Mushroom Head with Key	3.43 in	3.43 in	2.95 in	ESCAK	29YK62
Stainless Steel, NEMA 4X					
Push Button with Mushroom Head	5 in	3.5 in	4.25 in	VS-ESSS	29YK57
Push Button with Key	5 in	3.5 in	4.25 in	ESSSK	29YK59
Carbon Steel, NEMA 12					
Push Button with Mushroom Head	5 in	3.5 in	4.25 in	VS-ESCS	29YK54
Mushroom Head with Key	5 in	3.5 in	4.25 in	VS- ESCSK	29YK56