



Class 9007 Heavy-Duty Limit Switches

- Enclosures: NEMA 1, 2, 4, 6, 6P, 12, and 13 (IP65, IP66, IP67)
- Contacts rated 10A, 600V
- Limit switch arm required
- 1/2" NPT conduit entry

Bodies and heads are die-cast zinc alloy. Oiltight for efficient operation. For additional limit switch replacement parts, see Grainger.com®. UL Listed and CSA and CE Certified. Hazardous location units are UL Listed for Class I Div. 1 Groups B, C, D and Class II Groups E, F, G.



Lever Arm
5B087



Side Plunger
5B083



Wobble Stick
5B081



Adjustable
Lever Arm
5B065



Standard
Lever Arm
5B058



Forked Lever Arm
5B060



Replacement
Contact Body
2EG11



Replacement
Receptacle
2EG22



Looped Arm
5B066



Stainless Steel Rod
5B069

Description	Contact Form	Mfr. Model	Item No.	ROLLER DIA. x WIDTH			Item No.
				0.63 in x 0.25 in	0.63 in x 0.63 in	0.75 in x 0.63 in	
Lever Arm Types Adjustable CW and CCW, Spring Return, Lever Arm Required				Standard 10" Travel	Low Differential 5" Travel	Light Torque 25 oz./in. 10" Travel	Maintained Lever Arms
Standard Box Plug-In	1NC/1NO	9007C54	5B087	5B088	5B080	5B086	5B086
Standard Box Plug-In	2NC/2NO	9007C62	5B078	5B079	2UYH3	5B077	5B077
Standard Box Plug-In, 2-Stage	2NC/2NO	9007C66	2EF92	—	2UYH4	—	—
Compact Box Plug-In	1NC/1NO	9007C52	2EF74	2EF73	2EF80	2UYH7	2UYH7
Hazardous Location	1NC/1NO	9007CR53	2EG17	—	2UYH5	2UYH8	2UYH8
Hazardous Location	2NC/2NO	9007CR61	2EG19	—	2UYH6	2UYH9	2UYH9
Replacement Heads for Above	—	9007	2EF50	2EF27	2EG92	2EF71	2EF71
Neutral (Off)	2NC/2NO	9007C68T	5B071	5B070	—	—	—
Side Plunger Types Spring Return				Side Roller Vertical	Side Push Rod	Adj. Side Push Rod	Maintained Push Rod
Standard Box Plug-In	1NC/1NO	9007C54	5B083	5B082	6B407	2UYJ9	2UYJ9
Standard Box Plug-In	2NC/2NO	9007C62	5B074	5B073	6B408	2UYK1	2UYK1
Compact Box Plug-In	1NC/1NO	9007C52	2EF77	—	2UYJ7	2UYK2	2UYK2
Hazardous Location	1NC/1NO	9007CR53	2UYJ3	2UYJ5	—	2UYK3	2UYK3
Hazardous Location	2NC/2NO	9007CR61	2UYJ4	2UYJ6	2UYJ8	2UYK4	2UYK4
Replacement Heads for Above	—	9007	2EG54	2EG61	2EG62	2UYK5	2UYK5
Top Plunger Types Spring Return				Roller	Push Rod	Adj. Push Rod	Palm Operated
Standard Box Plug-In	1NC/1NO	9007C54	5B085	5B084	2EF85	2UYL4	2UYL4
Standard Box Plug-In	2NC/2NO	9007C62	5B076	5B075	2UYK9	—	—
Compact Box Plug-In	1NC/1NO	9007C52	2EF75	2EF76	2UYL1	2UYL6	2UYL6
Hazardous Location	1NC/1NO	9007CR53	2EG18	2UYK7	2UYL2	—	—
Hazardous Location	2NC/2NO	9007CR61	2UYK6	2UYK8	2UYL3	2UYL8	2UYL8
Replacement Heads for Above	—	9007	2EG24	2EG35	2EG53	2UYL9	2UYL9
Wobble Stick Types				Wire Extensions	Delrin® Extensions	Coil Spring Extensions	Cat Whiskers
Standard Box Plug-In	1NC/1NO	9007C54	2EF95	5B081	2F990	2F992	2F992
Standard Box Plug-In	2NC/2NO	9007C62	2UYN2	5B072	2UYN6	2UYP1	2UYP1
Compact Box Plug-In	1NC/1NO	9007C52	2UYN3	2EF79	2UYN7	—	—
Hazardous Location	1NC/1NO	9007CR53	2UYN4	—	2UYN8	2UYP3	2UYP3
Hazardous Location	2NC/2NO	9007CR61	2UYN5	2UYN1	2UYN9	2UYP4	2UYP4
Replacement Heads for Above	—	9007	2EG75	2EG74	2EG82	2EG83	2EG83
				ROLLER DIA. x WIDTH			
Actuator Type	Roller Material	Arm Length	0.63 in x 0.25 in	0.63 in x 0.63 in	0.75 in x 0.63 in	0.75 in x 0.63 in	1.0 in x 0.63 in
Lever Arms for Rotary Heads							
Standard Roller	Oil Impregnated Sintered Iron	1.38 in	2EF62	2EF67	2EF63	2UYP6	—
Standard Roller	Oil Impregnated Sintered Iron	1.5 in	2EG86	2UYP5	5B059	2EG87	—
Standard Roller	Oil Impregnated Sintered Iron	2 in	2EF94	2EG02	2EF95	2UYP7	—
Standard Roller	Oil Impregnated Sintered Iron	2.5 in	2EG26	—	2EG27	2EG28	—
Standard Roller	Oil Impregnated Sintered Iron	3 in	2EG38	—	2EG39	2EG40	—
Standard Roller	Nylon	1.38 in	2UYP8	2UYR4	2UYR9	—	2UYT1
Standard Roller	Nylon	1.5 in	2UYP9	2UYR5	5B058	—	2UYT2
Standard Roller	Nylon	2.5 in	—	2UYR7	—	—	—
Standard Roller	Nylon	3 in	—	2UYR8	—	—	—
Forked Roller	Oil Impregnated Sintered Iron	1.5 in	2EG84	—	5B060	—	—
Bendable Roller	Oil Impregnated Sintered Iron	0.88 in to 4.00 in	5B063	2EG72	—	—	—
Adjustable Roller	Oil Impregnated Sintered Iron	0.88 in to 4.00 in	5B065	2EG64	—	—	—
Adjustable Roller	Nylon	0.88 in to 4.00 in	5B064	—	—	—	2EG67
Replacement Contact Bodies				Replacement Receptacles			
Standard Body	1NO/1NC	9007C054	2EG11	Stainless Steel			
Standard Body	2NO/2NC	9007C062	2EG13	Steel Spring			
Compact Body	1NO/1NC	9007C052	2EG10	2" Looped Arm			
Standard Body 2-Stage	2NO/2NC	9007C066	2UYJ1	Delrin® Spring			
Standard Body Neutral Off	2NO/2NC	9007C068	2UYJ2	Delrin® Extension			
				Coil Spring Extension			
For Use With Standard Body, 1NO/1NC Units	1NO/1NC	9007CT54	2EG22	10 in			
For Use With Standard Body, 2NO/2NC Units	2NO/2NC	9007CT62	2EG23	12 in			
For Use With Compact Body, 1NO/1NC Units	1NO/1NC	9007CT52	2EG21	5.5 in			
				12 in			
				3.5 in			
				3.5 in			

Looking for more Dayton and Honeywell Heavy-Duty Switches? See Grainger.com for even more options.



Top Push Rod
Plunger
Adjustable
11X452



12V052

