

Daytor

Motor Shaft Botation

Dayton

ltem





3YB61





Horizontal-Mount 5ZNT6



Hydraulic-Drive **1MDB4** 

ntor Sneed

**4WXW2** Discharge Pressure Flow Rate

Electric Motor

**Belt-Driven** 

**4WXV7** 

## **Roller Spray Pumps**

DELAVAN YPRO

Use a series of rotating rollers to draw in, trap, and push liquids through the pump and out through the discharge port. Self-priming and require initial priming before first use. Commonly used to spray weed repellents in lawn care applications or can be attached to a tractor with a power take-off (PTO) coupler to spray pesticides in agricultural applications. Repair kit must match the pump's brand and manufacturer model number.


No. of Rollers	Flow Rate (Maximum)	Operating Pressure (Maximum)	Motor Speed (Maximum)	Shaft Outer Diameter	Port Combined	Brand	CCWSE Item No.	CWSE Item No.
Roller Spra								
6	22.8 gpm	150 psi	1,000 RPM	5⁄8 in	3/4 in NPT 3/4 in NPT	Delavan Ag Pumps		55NL46
304 Stainle	ess Steel Housir	1g						
6	22.8 gpm	150 psi	1,000 RPM	5⁄8 in	3/4 in NPT 3/4 in NPT	Delavan Ag Pumps	55NL49	55NL50
8	24 gpm	300 psi	1,000 RPM	1 in	1 in NPT 1 in NPT	Delavan Ag Pumps	55NL51	—
Cast Iron H	lousing							
4	9.2 gpm	150 psi	1,800 RPM	5⁄8 in	3/4 in NPT 3/4 in NPT	Delavan Ag Pumps		55NL44
6	21.8 gpm	300 psi	1,200 RPM	5⁄8 in	3/4 in FNPT 3/4 in FNPT	Hypro	3LFK5	_
0	22.8 gpm	150 psi	1,000 RPM	5⁄8 in	3/4 in NPT 3/4 in NPT	Delavan Ag Pumps	55NL45	_
8	24 gpm	300 psi	1,000 RPM	1 in	1 in NPT 1 in NPT	Delavan Ag Pumps	55NL47	55NL48
Ni-Resist H	lousing	•						
8	22.5 gpm	300 psi	1,000 RPM	1 in	3/4 in NPT 3/4 in NPT	Dayton	3YB44	_
Silver Cast	t Housing							
6	21.8 gpm	300 psi	1,200 RPM	5⁄8 in	3/4 in NPT 3/4 in NPT	Dayton	3YB55	_
Roller Spra	ay Pump with 12	V DC Motor				-		
Silver Cast	Housing							
4	6.6 gpm	50 psi	1,900 RPM		3/4 in NPT 3/4 in NPT	Dayton	3YB61	_
C	ompatible with		Compatible			Mfr.		Item
Grai	nger Part Numb	er Pi	ımp Shaft Size		Includes	Model		No.
	s for Roller Spra							
3YB60, 3Y			157 1-	(1) O-R	ing for End Plate, (2)	3430-0390-1	0	3YB59
	'B44. 3YB56		<sup>15</sup> ⁄16 in		Shaft Seals, Rollers	3430-0213	-	3YB41
2.2.10,01	2, 2 . 800					0100 0210		

## **Pressure Washer Triplex Pumps**

- Ceramic plunger
- Lubrication: oil bath

Reach higher pounds per square inch (PSI) than sprayer pumps to clean debris, build-up, and dirt from various surfaces such as concrete, wooden decks, and sidings. See page 1533 for pressure washer accessories. New installations require a Rail-Style Mount Kit, sold separately on this page. Belt-Driven—Feature a shaft coupled to an

external motor with a belt or pulley.



NORTH

AMERICA

(

Electric Motor-Direct-drive pressure washer pumps have a flange mount that's compatible with electric motors.

Hydraulic-Drive—Pumps connect to a hydraulic motor which is connected to a hydraulic system. Flow from the hydraulic system powers the motor which activates the pump.

Mfr

(Maximum)	(Maximum)	Shaft	(Maximum)	1 Suction Port	Discharge Port	Flange Type	Brand	Mitr. Model	No.
Belt-Driven Pressure			(maximum)	ouction i oit	Discharge Fort	Trange Type	Drana	model	140.
316 Stainless Steel		5							
1,500 psi	2 gpm	24 mm Hollow	1.750 RPM	1/2 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MDB3	1MDB3
Forged Brass Pump I		211111110100	1,700 111 11	72111001	70111 201	Honzontai Hangoi Famp	, and Hortan , another		
2.200 psi	11 gpm	24 mm Solid	1.450 RPM	3/4 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MDB1	1MDB1
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,_,	2.5 gpm	24 mm Solid	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Dayton	4WXW6	4WXW6
0.500	3 gpm	1 1/8 in Hollow	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	A.R. North America	4WXX6	4WXX6
2,500 psi	3 gpm	24 mm Solid	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Davton	4WXV7	4WXV7
	3.5 gpm	24 mm Solid	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Davton	4WXV8	4WXV8
2,900 psi	4 gpm	24 mm Solid	1.450 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Davton	5ZNU1	5ZNU1
	4 gpm	24 mm Solid	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Davton	5ZNT5	5ZNT5
3,000 psi	4.75 gpm	24 mm Solid	1,750 RPM	3/4 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	4WXW9	4WXW9
	7.92 gpm	1 1/8 in Hollow	1.750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	A.R. North America	4WXX5	4WXX5
3,500 psi	5.55 apm	24 mm Solid	1,750 RPM	3/4 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MCY2	1MCY2
· · ·	3.96 gpm	24 mm Solid	1,750 RPM	1/2 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MCX7	1MCX7
4,000 psi	3.96 gpm	24 mm Solid	1,750 RPM	3/4 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MCX8	1MCX8
	5.55 gpm	24 mm Solid	1,750 RPM	1/2 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	1MCX9	1MCX9
5,000 psi	4 gpm	24 mm Solid	1,450 RPM	1/2 in BSP	3% in BSP	Horizontal Plunger Pump	A.R. North America	1MCY1	1MCY1
7,250 psi	4 gpm	24 mm Solid	1,450 RPM	1/2 in BSP	3/8 in BSP	Horizontal Plunger Pump	A.R. North America	4WXX1	4WXX1
Nickel Plated Brass									
1,800 psi	24 gpm	30 mm Solid	1,450 RPM	1 in BSP	1/2 in BSP	Horizontal Plunger Pump	A.R. North America	RTX100	19RT41
2,900 psi	12 gpm	30 mm Solid	1,450 RPM	1 in BSP	1/2 in BSP	Horizontal Plunger Pump	A.R. North America	RTX50	19RT39
4,000 psi	18.5 gpm	35 mm Solid	1,000 RPM	1 1/2 in BSP	1 in BSP	Horizontal Plunger Pump	A.R. North America	RTJ70N	4WXX4
Horizontal-Mount Ga		t-Drive Pressure Wa	isher Pumps						
Forged Brass Pump I									
3,600 psi	3 gpm	1 in Hollow	3,400 RPM	1/2 in BSP	3/8 in BSP	Horizontal Gas Engine	Dayton	5ZNT6	5ZNT6
3,700 psi	4 gpm	1 in Hollow	3,400 RPM	1/2 in BSP	3/8 in BSP	Horizontal Gas Engine	Dayton	5ZNU0	5ZNU0
4,000 psi	4 gpm	1 in Hollow	3,400 RPM	3% in BSP	⅔ in BSP	Horizontal Gas Engine	Dayton	4WXX8	4WXX8
	8 gpm	1 in Solid	3,400 RPM	1/2 in BSP	3/8 in BSP	Horizontal Gas Engine	A.R. North America	1MCY8	1MCY8
Electric Motor Moun		Pressure Washer Pı	imps						
316 Stainless Steel I									
1,500 psi	3 gpm	5% in Hollow	1,750 RPM	1/2 in BSP	⅔ in BSP	NEMA 56-C	A.R. North America	1MDB2	1MDB2
Forged Brass Pump I									
	2 gpm	5% in Hollow	1,750 RPM	1/2 in BSP	3% in BSP	NEMA 182-184	Dayton	4WXW2	4WXW2
2,500 psi	2 gpm	5% in Hollow	3,450 RPM	1/2 in BSP	3% in BSP	NEMA 182-184	Dayton	4WXW3	4WXW3
	3 gpm	5% in Hollow	1,750 RPM	1/2 in BSP	3/8 in BSP	NEMA 56-C	Dayton	4WXW4	4WXW4
	3 gpm	5% in Hollow	3,450 RPM	1/2 in BSP	⅔ in BSP	NEMA 56-C	Dayton	4WXW5	4WXW5
3,000 psi	4 gpm	1 1/8 in Hollow	1,750 RPM	1/2 in BSP	3/8 in BSP	NEMA 182-184	Dayton	5ZNT9	5ZNT9
Hydraulic-Drive Pres	sure Washer P	umps							
Forged Brass Pump								(1155)	
3,000 psi	4 gpm	Solid	1,450 RPM	1 1/16 in BSP	1 1/16 in BSP	Horizontal Hydraulic Drive	A.R. North America	1MDB4	1MDB4
	Overall	Overall	Overall	_				Mfr.	Item
Material	Height	Length	Width	Compa	tible with Graing	er Part Number	Brand	Model	No.
<b>Rail-Style Mount Kit</b>								0.0155	
Steel	1.25 in	6.88 in	1.75 in		1MCY1, 1MDB1,		A.R. North America	4YNP5	4YNP5
Steel	1.75 in	6.5 in				B3, 4WXW8, 4WXX5, 4WXX6	A.R. North America	4YNP6	4YNP6
Steel	2.63 in	6.5 in	1.75 in	1MCX7, 1MCX9, 1M	эүх, 1MDB2, 1MD	B3, 4WXW8, 4WXX5, 4WXX6	A.R. North America	4YNP7	4YNP7



Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)