



## Split-Phase Carbonator Pump Motors

- Enclosure: open dripproof
- Thermal protection: auto
- Bearings: ball
- Max. ambient temp.: 40°C

Motors have a threaded conduit hole. Short, slotted shaft permits close-coupling the carbonator pump to the motor. Extended hub for direct-mounting pump to motor. Use for liquid transfer pumps, vending machine pumps, and other hub-mounted pump applications. See page 2698 for an assortment of suitable pumps.



**Cradle Base-Mount  
484H28**



**Rigid Base-Mount  
5U254**

HP	Nameplate RPM	Frame	Motor Shaft Rotation	Voltage	Hz	Full Load Amps	Motor Service Factor	Ins. Class	Shaft Dia.	Brand	Mfr. Model	Item No.
<b>Cradle Base-Mount</b>												
1/4	1,725	48Y	CW/CCW	115V AC	60	5.0	1	B	1/2 in	Marathon	5KH32DN5587X	3K067
	1,725	48YZ	CW/CCW	120/240V AC	60/50	5.1-5.0/2.6-2.5	1	B	5/8 in	Dayton	484H28	484H28
	1,725	48	CW/CCW	115V AC	60	6.5	1	B	5/8 in	Dayton	484H30	484H30
	1,725	48Y	CW/CCW	115/230V AC	60/50	5.6-5.5/2.8-2.7	1	B	5/8 in	Marathon	5KH32GN5587X	5U257
1/2	1,725	48Y	CW/CCW	115/230V AC	60	5.6-5.5/2.8-2.7	1	B	5/8 in	Marathon	5KH32GNB811X	3K987
	1,725	48Y	CW/CCW	115V AC	60	5.6	1.15	B	1/2 in	Marathon	5KH32FN5586X	3K068
	1,725	48Y	CW/CCW	115V AC	60	6.1	1	B	5/8 in	Marathon	5KH32ENA443X	5U256
	1,725	48Y	CW/CCW	230V AC	60	2.7	1	B	5/8 in	Marathon	5KH32GNB812X	2K457
3/4	1,725	48YZ	CW/CCW	120/240V AC	60/50	5.7-5.6/2.8-2.8	1	B	5/8 in	Dayton	484H31	484H31
	1,725	48Y	CW/CCW	115/230V AC	60	7.1-7.2/3.4-3.6	1	B	5/8 in	Marathon	5KH36MNA445X	5U258
	1,725	48Y	CW/CCW	115V AC	60	7.2	1.2	B	5/8 in	Marathon	5KH36MNB637X	5XB87
	1,725	48YZ	CW/CCW	115V AC	60	8.4	1	B	5/8 in	Dayton	484H33	484H33
1	1,725	48YZ	CW/CCW	120/240V AC	60/50	7.7-7.6/3.9-3.9	1	F	5/8 in	Dayton	484H32	484H32
	1,725	48Y	CW/CCW	115/230V AC	60	10.4/5.2	1	B	5/8 in	Marathon	5KH37PNA479X	10A276
<b>Rigid Base-Mount</b>												
1/4	1,725	48Y	CW/CCW	115V AC	60	5.0	1	B	1/2 in	Marathon	5KH32DN5597X	5U253
	1,725	48Y	CW/CCW	115/230V AC	60	5.6/2.8	1	B	1/2 in	Marathon	5KH32GNB815X	3VG37
1/2	1,725	48Y	CW/CCW	115V AC	60	5.6	1.15	B	1/2 in	Marathon	5KH32FN5598X	5U254
	1,725	48YZ	CWSE	115V AC	60	6.0	1	B	5/8 in	Dayton	484H29	484H29

\* Has 1/2" x 1 1/2" rear shaft extension.



**Open Dripproof  
with Face/Base-Mount  
4UX55**

**Open Dripproof  
with Rigid Base-Mount  
454X49**



## 1-Phase Pressure Washer Pump Motors

- Rotation: CW/CCW, except 4UX55 is CWSE
- Thermal protection: manual
- Bearings: ball
- Max. ambient temp.: 40°C

Corrosion-resistant; for use in hot and cold water high-pressure washer applications.



**Totally Enclosed  
Fan-Cooled  
with Rigid Base-Mount  
21AJ16**

HP	Nameplate RPM	Frame	Voltage	Full Load Amps	Motor Service Factor	Ins. Class	Shaft Dia.	Brand	Mfr. Model	Item No.
<b>Open Dripproof, Face/Base-Mount, Capacitor-Start</b>										
5	3,450	56HCZ	208-230V AC	22.0-20.0	1.15	B	3/4 in	Dayton	4UX55	4UX55 *
<b>Open Dripproof, Rigid Base-Mount, Capacitor-Start/Run</b>										
2	3,450	56	115/230V AC	17.8/8.9	1.15	B	5/8 in	Marathon	056B34D15537	454X49
<b>Totally Enclosed Fan-Cooled, Rigid Base-Mount, Capacitor-Start</b>										
3/4	1,725	56C	115/208-230V AC	11.0/5.4-5.5	1.15	B	5/8 in	Marathon	056C17F5955	21AJ16
	1,725	56C	115/208-230V AC	13.4/6.8-6.7	1.15	B	5/8 in	Marathon	056C17F5956	21AJ17
<b>Totally Enclosed Fan-Cooled, Rigid Base-Mount, Capacitor-Start/Run</b>										
2	3,450	56HC	115/230V AC	17.5/8.7	1.15	B	5/8 in	Marathon	056B34F5312	21AJ14

\* 3/4" x 1 1/8" shaft.