



Portable Self-Priming Utility Pumps

Pump repair kits for select models are sold separately.

CENTRIFUGAL PUMPS

5PXY0—For irrigation, general water transfer, and other continuous-duty applications. Model has ball bearings and comes with a mechanical carbon ceramic/stainless steel/Buna N seal. Open-type impeller.

4HEX4 and 33RW83—Use to water lawns, pump out flooded basements, and boost city water pressure. Intermittent duty with mechanical carbon/ceramic seals. 4HEX4 has permanently lubricated shielded ball bearings, external brush holders, rubber feet and suction screen; 33RW83 has ball bearings and replacement brushes.

5YU12—Provides high head and high pressures to move water quickly. On/Off switch and a large hand-tightened prime plug with internal funnel design to ease priming. Intermittent duty with ball bearings, mechanical carbon/ceramic/Buna N seals, and a stainless steel retention plate helps extend seal life by retaining water on the shaft seal. Open-type impeller.

FLEXIBLE IMPELLER PUMPS

Ideal for transferring liquids and emptying bowls, sinks, tanks, bilges, and have a dual inlet and outlet. Intermittent duty.

3YU61—Pump comes with ball bearings, Buna N lip seal, suction screen, 6-ft. garden hose and a lightweight plastic housing.

5UXL8 to 5UXN6—Feature stainless steel shaft and ball bearings, except 5UXN4 to 5UXN6 have sleeve bearings. Each includes 2 impellers and gasket. 5UXL7 and 5UXL9 have thermally protected motors.

SPRINKLER/UTILITY CENTRIFUGAL PUMPS

Continuous duty pumps.

3YU60—Use to transfer water, run multiple lawn sprinklers, or boost city water pressure. Ball bearings and mechanical carbon/ceramic/Buna N seal. Model has overload protection and an On/Off switch.

4CUK6—Suitable for transferring liquids and emptying bowls, sinks, tanks, and bilges. Has ball bearings, stainless steel shaft, and mechanical carbon/ceramic seal.

Impeller	HP	Voltage	Amps AC	Motor Encl.	Motor Type	Cord	Inlet/Outlet (in.)	Body Material†	GPM of Water @ Total Ft. of Head*				Max. Head (ft.)	Max. Suction Lift (ft.)	Max. Liquid Temp. (°F)	Brand	Mfr. Model	Item No.
									5	10	20	40						
Centrifugal Pumps																		
Aluminum	1/2 hp	115V	2	ODP	Capacitor-Start	8 ft.	1" NPT	AL	41	38	32	6	46	—	180	Dayton	5PXY0	5PXY0
Thermoplastic	1/2 hp	115V	2	Nema 1	AC	20 ft.	1" NPT	CI	23	22.5	21.5	18	115	—	120	Zoeller	314-0002	4HEX4
Fiberglass, Nylon	1/2 hp	115V	2	ODP	AC/DC Brush	10 ft.	1" NPT	FG, PP	22.7	21.6	19	14.2	118	—	120°	Dayton	33RW83	33RW83
Thermoplastic	1/2 hp	115V	2	Nema Type 3	AC/DC Brush	20 ft.	1" NPT	CA	23	22	19	15	105	—	135	Liberty Pumps	331	5YU12
Flexible Impeller Pumps																		
Rubber	1/2 hp	115V	2	ODP	AC/DC Brush	10 ft.	1" NPT	P	5.5	5.0	4	1	43	—	77	Dayton	3YU61	3YU61
Buna-N	1/4 hp	12 V DC	6.5 to 10	Open	DC	7 ft	3/8 ID; 3/4 OD Garden Hose	NPB	3.72 gpm	3.32 gpm	2.31 gpm	—	36.7 ft	7 ft	140 °F	Dayton	5UXL8	5UXL8
Buna-N	1/4 hp	12 V DC	6.5 to 10	Open	DC	7 ft	3/8 ID; 3/4 OD Garden Hose	SS	3.72 gpm	3.32 gpm	2.31 gpm	—	36.7 ft	7 ft	140 °F	Dayton	5UXN0	5UXN0
Buna-N	1/4 hp	12 V DC	7.0	Totally Enclosed Nonventilated	DC Brush	12 in Leads	3/4 in Male GHT / 3/8 in FNPT	NPB	—	—	—	—	46 ft	7 ft	120 °F	Little Giant	555602	5UXN5
Buna-N	1/4 hp	115 V	1.6	Open	Universal AC/DC	6 ft	3/8 ID; 3/4 OD Garden Hose	NPB	5.2 gpm	4.43 gpm	3.05 gpm	—	37.3 ft	7 ft	140 °F	Dayton	5UXL7	5UXL7
Buna-N	1/4 hp	115 V	1.6	Open	Universal AC/DC	6 ft	3/8 ID; 3/4 OD Garden Hose	SS	5.2 gpm	4.43 gpm	4.5 gpm	—	37.3 ft	7 ft	140 °F	Dayton	5UXL9	5UXL9
Buna-N	1/4 hp	115 V	1.6	Open Fan Cooled	AC Brush	6 ft	3/4 in male garden hose thread and 3/8 in FNPT	NPB	—	—	—	—	48 ft	7 ft	120 °F	Little Giant	555112	5UXN4
Buna-N	1/4 hp	115 V	1.6	Open Fan Cooled	AC Brush	6 ft with NEMA 5-15P Plug	3/4 in Male GHT / 3/8 in FNPT	SS	—	—	—	130 gpm	48 ft	7 ft	120 °F	Little Giant	555110	5UXN6
Sprinkler/Utility Centrifugal Pumps																		
Plastic with Brass Insert, SS Wear Ring	1/2 hp	115V	2	ODP	PSC	10 ft.	1" NPT	P	10.3	9.9	9.6	4.2	134	—	90	Dayton	3YU60	3YU60
Thermoplastic	1/2 hp	115V	2	ODP	PSC	5 1/2 ft.	1" NPT	SS	—	—	—	—	148	—	90	Dayton	4CUK6	4CUK6

Pump Repair Kits	For Use With	Includes	Brand	Item No.
	5UXL7, 5UXL8, 5UXL9, 5UXN0	Cam, 2 Gaskets, 2 Impellers	Dayton	5UXN1
	5UXL7, 5UXL8, 5UXL9, 5UXN0	2 Gaskets, 2 Impellers	Dayton	5UXN2
	360S, 555909, Mir. No. 360	(2) Gaskets, (2) Impellers	Little Giant	6EDW3
	360S, 555909, Mir. No. 360	(1) Felt Washer, (1) Retainer Ring, (1) Viton U-Cup Seal, (2) Gaskets, (2) Impellers	Little Giant	6EDW4

* To convert to psi, divide total feet of head by 2.31. † AL = aluminum, CA = cast aluminum, CI = cast iron, FG = fiberglass, NPB = nickel plated brass, P = plastic, PP = polypropylene, SS = stainless steel.