



Pond and Fountain Pumps

Corrosion-resistant materials.

POND AND WATERFALL PUMPS

Suitable for high flow, low head height, low pressure, and solids handling capability with fewer clogs. Pumps provide a high flow rate per watt for energy-efficient continuous operation, and are safe for fish and plants. Ideal for filtration systems, water courses, and waterfalls.

ABS—Continuous-duty water gardening pumps have a PSC motor in an ABS housing.

FOUNTAIN PUMPS

Suitable for high head pressure and high height clean water applications. Small fountain pumps can be used for bubbling stones, decorative, and statuary decorative fountains. Higher head pressure pumps are ideal for demanding fountain applications, larger water features, and spray nozzles. Pond Boss models have an automatic low water shut-off to help prevent pump damage.

Brass—Designed for fountains, coolant systems, evaporative coolers, and other liquid-moving applications. Continuous-duty PSC motor has thermal overload protection. Discharge rotates in 90° increments. Mechanical seal has Buna N, stainless steel and carbon/ceramic parts. Horizontal mount.

Note: Brass models are not safe for fish and plants.

Polypropylene—Oil-free direct-drive pumps produce greater starting torque and flow pressure for continuous operation. Innovative dual discharge for waterfall and stream effects. Noryl impeller and nitrile shaft seal. CSA Certified.

WATER GARDEN PUMPS

13L283 features a non-clogging vortex impeller and an auto reset thermal overload to help prevent pump and motor damage. Pump can pass solids up to 1 3/16" dia.

AUTO FILL VALVE

For permanent and temporary installations to automatically maintain water levels in a skimmer vault or other pond equipment. Includes 1/2" PVC slip and 3/4" garden hose adapters.



HP	Outlet	Voltage	GPH of Water @ Total ft. of Head				Max. Head	Cord Length	L	H	Brand	Mfr. Model	Item No.		
			5	10	20	30									
Pond and Waterfall Pumps															
ABS															
5/64 hp	2 in (M)NPT	120V AC	1,200	0	—	—	9.5 ft	20 ft	11 in	5 1/2 in	Oase	57620	38EF21		
5/64 hp	2 in (M)NPT	120V AC	1,200	0	—	—	10 ft	20 ft	13 1/2 in	6 1/2 in	Oase	57499	38EF22		
3/32 hp	2 in (M)NPT	120V AC	540	0	—	—	8 ft	20 ft	11 in	5 1/2 in	Oase	40347	38EF20		
3/32 hp	1 1/2 in	120V AC	600	120	—	—	14 ft	16 ft	9 1/4 in	6 in	Pond Boss	52717	38EF30		
1/8 hp	2 in (M)NPT	120V AC	1,740	300	—	—	11 ft	20 ft	11 in	9 in	Oase	57621	38EF23		
5/64 hp	2 in (M)NPT	120V AC	1,620	240	—	—	11 ft	20 ft	13 1/2 in	6 1/2 in	Oase	57500	38EF24		
5/64 hp	1 1/2 in	120V AC	1,860	0	—	—	16 ft	16 ft	9 1/4 in	6 in	Pond Boss	52719	38EF31		
3/16 hp	1.5 in MNPT	120V AC	2,095	961	96	—	14.9 ft	20 ft	10 in	7 3/8 in	Little Giant	566725	36N479		
1/16 hp	2 in (M)NPT	120V AC	2,640	1,140	—	—	13 ft	20 ft	11 in	5 1/2 in	Oase	57623	38EF25		
7/32 hp	2 in (M)NPT	120V AC	2,520	900	—	—	13 ft	20 ft	13 1/2 in	6 1/2 in	Oase	57501	38EF26		
1/16 hp	2 in	120V AC	2,880	1,560	120	—	18 ft	16 ft	10 1/2 in	6 in	Pond Boss	52353	38EF33		
1/32 hp	2 in MNPT	120V AC	2,897	1,922	—	—	18.8 ft	20 ft	13 1/4 in	8 in	Little Giant	566726	36N480		
1/64 hp	1 1/2 in	120V AC	1,980	1,380	—	—	20 ft	20 ft	14 in	7 in	Oase	57096	38EF32		
3/8 hp	2 in	120V AC	3,540	1,680	320	—	22 ft	16 ft	10 1/2 in	6 in	Pond Boss	52355	38EF34		
7/8 hp	2 in MNPT	120V AC	5,929	4,664	2,042	—	28 ft	40 ft	13 1/4 in	8 in	Little Giant	566729	36N481		
Fountain Pumps															
ABS															
1/64 hp	5/8 in	120V AC	—	—	—	—	4.1 ft	16 ft	3 1/2 in	2 in	Pond Boss	52341	38EF35		
1/64 hp	5/8 in	120V AC	—	—	—	—	4.1 ft	16 ft	3 1/2 in	2 in	Pond Boss	52768	38EF36 *		
3/64 hp	5/8 in	120V AC	—	—	—	—	9.4 ft	16 ft	4 5/8 in	2 5/8 in	Pond Boss	52342	38EF37		
3/64 hp	5/8 in	120V AC	—	—	—	—	9.4 ft	16 ft	4 5/8 in	2 5/8 in	Pond Boss	52343	38EF38 *		
Brass															
1/2 hp	1 in (F)NPT	120V AC	—	3,720	2,820	1,320	34 ft	12 ft	15 3/4 in	8 in	Dayton	5RWG1	5RWG1		
1/2 hp	1 in (F)NPT	120V AC	—	4,680	3,840	2,760	43 ft	12 ft	15 3/4 in	8 in	Dayton	5RWG2	5RWG2		
3/4 hp	1 in (F)NPT	230V AC	—	5,880	5,100	4,080	50 ft	12 ft	15 3/4 in	8 in	Dayton	5RWG5	5RWG5		
3/4 hp	1 in (F)NPT	120V AC	—	5,880	5,100	4,080	50 ft	12 ft	15 3/4 in	8 in	Dayton	5RWG3	5RWG3		
3/4 hp	—	120V AC	—	5,700	5,100	4,080	—	12 ft	15 3/4 in	8 1/8 in	Barnes	SFU71-GIS	32ZV58		
1 1/2 hp	1 1/4 in (F)NPT	230V AC	—	6,900	6,120	5,400	60 ft	12 ft	15 3/4 in	8 1/2 in	Dayton	5RWG6	5RWG6		
1 hp	1 in (F)NPT	230V AC	—	6,300	5,580	4,800	55 ft	12 ft	15 3/4 in	8 in	Dayton	5RWG4	5RWG4		
2 hp	1 1/4 in (F)NPT	230V AC	—	7,920	6,720	6,180	68 ft	12 ft	15 3/4 in	8 1/2 in	Dayton	5RWG7	5RWG7		
Polypropylene															
1/8 hp	1 1/4 in	120V AC	1,250	785	—	—	20 ft	16 ft	9 3/8 in	8 7/8 in	Little Giant	507902	4RK88		
5/8 hp	1 1/4 in	120V AC	4,000	3,500	2,200	—	30 ft	16 ft	11 in	8 7/8 in	Little Giant	507903	4RK89		
Water Garden Pumps															
Cast Iron															
3/4 hp	2 in (F)NPT	120V AC	—	4,345	—	—	36 ft	19 ft	6 13/16 in	14 1/16 in	Little Giant	566069	13L283		
Auto Fill Valve															
Material		Includes				Brand		Mfr. Model		Item No.					
Plastic		1/2 in PVC Slip and 3/4 in Garden Hose Adapters				Little Giant		566901		2EHN4					
Description		Cord Length		Brand		Mfr. Model		Item No.							
Accessories															
Pond Vacuums															
PondoVac 3, Pond Vacuum, 2 Chambers, 120V AC								12 ft		Oase		50409		38CD18	
PondoVac 4, Pond/Pool Vacuum, 2 Chambers, 120V AC										Oase		37230		38CD19	
Pond Filter/Clarifiers															
Vitronic 18W UV Pond Clarifier, 110 VV								16 ft		Oase		56455		38EJ50	
Vitronic 36W UV Pond Clarifier, 110 VV										Oase		40350		38EJ51	
SwimSkin Floating Surface Skimmer/Air Injector, 110 VV								15 ft		Oase		50040		38EJ52	
AquaSkim In-Pond Surface Skimmer										Oase		57395		38EJ53	
Lighting															
LunAqua 3W LED Light 12V								25 ft		Oase		56463		38CD24	
3 LED Accent Light Kit 12V								26 ft		Pond Boss		52369		38CD27	

* Includes LED light.



Pond Fountain Pump Systems

Pumps operate in a minimum of 5 ft. of water and draw water from below the pond surface; a 6" PVC screen filters mosquitoes, algae, and other vegetation to improve aeration and extend motor life. All parts are plastic and stainless steel for maximum corrosion resistance. Include foam-filled flotation system and 3 nozzles for different fountain patterns. 100-ft. cord. Preassembled for simple installation.

2VAN2 to 2VAN4 feature a lockable, rainproof control center with internally mounted ground fault interrupter, adjustable 24-hr. timers and heat shrink splice kit for the motor cable.

Fountain Lighting System—Stainless steel housings with clear lenses can be easily installed onto the float to create dramatic nighttime displays. Include 3 white LED flood lamps, waterproof splice kit, and mounting hardware. 120V, 120 watt lamps.



2VJ23

HP	Voltage	Full Load Amps	Spray Pattern	Max. Spray Width	Max. Spray Height	L	H	Item No.
Pond Aerating Fountain Systems								
1/2 hp	115V	12 A	(3) Spray Patterns Sky Cannon 15 ft High, Trumpet 13 ft High, Water Lily 15 ft	30 ft	15 ft	14 1/2 in	32 in	2VJ23
	230V	6 A		30 ft	15 ft	14 1/2 in	32 in	2VAN2
3/4 hp	230V	8 A	(3) Spray Patterns Sky Cannon 35 ft High, Trumpet 20 ft High, Water Lily 22 ft	32 ft	15 ft	20 in	34 in	2VAN3
1 hp	230V	9.8 A	(3) Spray Patterns Sky Cannon 41 ft High, Trumpet 22 ft High, Water Lily 24 ft	46 ft	15 ft	20 in	39 in	2VAN4
Description				No. of Lamps	For Use With			Item No.
Fountain Lighting System				3	2VAN2, 2VAN3, 2VAN4			3CPW1
Fountain Lighting System, 100 ft Cord								