

1-800-GRAINGER (472-4643)

Dayton

22mm E-Stops, Mushroom-Head Push Buttons—Complete Units

- Red, 40mm-dia. head
- Maintained contact
- NEMA 1, 2, 3, 4, 4X, 12, and 13 rated



30G254

Action	Contact Form	PLASTIC Item No.	CHROME DIE CAST ALUMINUM Item No.
Push / Turn To Release	1NC	30G252	30G253
Push / Turn To Release	1NO/1NC	30G254	30G255
Push / Pull - Trigger Release	1NO/1NC	30G250	30G251
Push / Pull	1NC	30G248	30G249
Push / Key Release	1NC	30G256	30G257
Push / Key Release	1NO/1NC	32UK35	30G258

Schneider Electric

22mm Emergency Stop Mushroom-Head Push Buttons—Complete Units

- Red, 40mm dia. trigger-action operator
- No-notch mounting
- NEMA rated 1, 2, 3, 4, 4X, 12, and 13



2UZD4

Include operator, cap, and contact block for easy installation. UL Listed, CSA Certified, and CE Certified. Meet IEC standards.

Description	Contact Form	PLASTIC Item No.	CHROME Item No.
Turn to Release, Maintained, Trigger Release	1NO/1NC	6HL63	6HK79
Turn to Release, Maintained, Trigger Release	1NC	33HP37	—
Push-Pull, Maintained, Trigger Release	1NO/1NC	2UZD4	6HK82
Push-Pull, Maintained	1NC	33HP38	33HP36
Key Release, Maintained, Trigger Release	1NO/1NC	2UZD6	6HK80

Emergency Stop Switches, Enclosure, and Legend Plates

SWITCHES

- Plastic construction
 - Red operator
- Switches allow direct disconnect of circuit contacts in emergency situations. Easy to spot, access, and use. On/Off operation, push to lock, turn to reset. Safety lock mechanism prevents operating errors; finger protection mechanism for added safety. Easy mounting and removal of switch blocks, using a lever.
- Oil-resistant to IP65. UL Listed and CE Certified.

ST SAFETY TECHNOLOGY & INNOVATION
OMRON



2LCB1

Contact Type	Size	NONLIGHTED		Size	Voltage	LIGHTED	
		Mfr. Model	Item No.			Mfr. Model	Item No.
16mm Mount, 5A at 125VAC, 3A at 250VAC							
SPST-NC	16 mm	A165E-S-01	2LCB3	16 mm	24V AC/DC	A165E-LS-24D-01	2LCB1
DPST-NC	16 mm	A165E-S-02	2LCB4	16 mm	24V AC/DC	A165E-LS-24D-02	2LCB2
22mm Mount, 10A at 110VAC, 6A at 220VAC							
DPST-NC	22 mm	A22E-M-02	2LCB8	22 mm	24V AC/DC	A22ELM24A02	2LCB7
DPST-NC	22 mm	A22EM02B	2LCB9 *	—	—	—	—
DPST-NC, SPST-NO	22 mm	A22E-M-12	2LCC1	—	—	—	—
DPST-NC	22 mm	A22E-L-02	2LCB6	—	—	—	—

* With integrated control box.

No. of Holes	Hole Size	H (in.)	W (in.)	D (in.)	Contact Block Depth (in.)	Mfr. Model	Item No.
1	22 mm	2.67	2.67	2.73	2.15	A22Z-B101Y	2LCC2

Description	Mfr. Model	Item No.
Blank, For Use with 16mm Push-Buttons, Yellow Field	A16Z-5070	2LCB5
"Emergency Stop", For Use with 22mm Push-Buttons, Black Letters on Yellow Field	A22Z-3466-1	2LCC3
"Emergency Off", For Use with 22mm Push-Buttons, Black Letters on Yellow Field	A22Z-3466-2	2LCC4

EATON

22mm and 30mm Emergency Stop Push Buttons

- Red mushroom head
- Nonilluminated



30XF73



39P798

Action	Contact Form	Legend	Head Material	Mfr. Model	Item No.
22 mm Hole Dia., 45mm Mushroom Head					
Main, Push / Main, Pull	1NC	No Legend	Plastic	M22-PV-K01	30XF74
Main, Push / Turn To Release	1NC	No Legend	Plastic	M22-PVT-K01	30XF75
Main, Push / Turn To Release	2NC	No Legend	Plastic	M22-PVT-K02	30XF73
30 mm Hole Dia., 40mm Mushroom Head					
Main, Push / Main, Inter. / Mom. Pull	1NC	No Legend	Metal	10250T9B62-3X	39P798
Main, Push / Main, Pull	1NC	Emergency Stop	Metal	10250T5B63-71X	39P790
Main, Push / Main, Pull	1NC	No Legend	Plastic	10250T5B62-71X	39P789
Main, Push / Main, Pull	1NO/1NC	Emergency Stop	Metal	10250T5B63-1X	39P794
Main, Push / Main, Pull	1NO/1NC	No Legend	Metal	10250T5B62-1X	39P793
Mom. Push / Main, Inter. / Mom. Pull	1NC	No Legend	Metal	10250T4B62-3X	39P802 †
Mom. Push / Main, Inter. / Mom. Pull	1NC	No Legend	Metal	10250T10B62-1X	39P804 ‡
30 mm Hole Dia., 65mm Mushroom Head					
Main, Push / Main, Pull	1NC	Emergency Stop	Metal	10250T5J63-71X	39P792
Main, Push / Main, Pull	1NC	No Legend	Metal	10250T5J62-71X	39P791
Main, Push / Main, Pull	1NO/1NC	Emergency Stop	Aluminum	10250T5J63-1X	39P795
Main, Push / Main, Pull	1NO/1NC	Emergency Stop	Aluminum	10250ED1080-2	39P796 *

* Special security jumbo mushroom head. † Contact configuration: XX 0X 00 ‡ Contact configuration: 0X 00 0X

Emergency Push-Button Stations

- 600VAC
 - Contact: 1NC
 - Contact rating: 10A, A600/Q300
- Designed with red operator. Wall-mountable. Metallic series includes legend. UL Listed, CSA Certified.

GE



29YK60

Type of Operator	H	W	D	Mfr. Model	Item No.
Non-Metallic, NEMA 4X					
Push Button with Mushroom Head	2.83 in	2.83 in	2.1 in	ESNM	29YK51
Push Button with Flag	2.83 in	2.83 in	2.1 in	ESNMF	29YK52
Mushroom Head with Key	2.83 in	2.83 in	2.1 in	ESNMK	29YK53
Cast Aluminum, NEMA 4X					
Push Button with Mushroom Head	3.43 in	3.43 in	2.95 in	ESCA	29YK60
Mushroom Head with Flag	3.43 in	3.43 in	2.95 in	ESCAF	29YK61
Mushroom Head with Key	3.43 in	3.43 in	2.95 in	ESCAK	29YK62
Stainless Steel, NEMA 4X					
Push Button with Mushroom Head	5 in	3.5 in	4.25 in	ESSS	29YK57
Push Button with Flag	5 in	3.5 in	4.25 in	ESSSF	29YK58
Push Button with Key	5 in	3.5 in	4.25 in	ESSSK	29YK59
Carbon Steel, NEMA 12					
Push Button with Mushroom Head	5 in	3.5 in	4.25 in	ESCS	29YK54
Push Button with Flag	5 in	3.5 in	4.25 in	ESCSF	29YK55
Mushroom Head with Key	5 in	3.5 in	4.25 in	ESCSK	29YK56

Dayton

Emergency Push-Button Stations

- Contact: 1NC
- Contact rating: 10A at 600VAC
- Maintained operators are push/pull action

Gray enclosures. Red plastic operator heads have imprinted "Emergency Stop." UL Listed and CSA Certified.

Description	H	W	D	Momentary Item No.	Maintained Item No.
Stainless Steel, NEMA 4X					
40mm Dia. Head	5.5 in	3.5 in	4.25 in	36UX17	36UX18
65mm Dia. Head	5.5 in	3.5 in	4.25 in	36UX19	36UX20
40mm Dia. Illum. Head, 24VAC/DC	5.5 in	3.5 in	4.25 in	36UX21	36UX22
40mm Dia. Illum. Head, 120VAC/DC	5.5 in	3.5 in	4.25 in	36UX23	36UX24
Carbon Steel, NEMA 12					
40mm Dia. Head	5.5 in	3.5 in	4.25 in	36UX25	36UX26
65mm Dia. Head	5.5 in	3.5 in	4.25 in	36UX27	36UX28
40mm Dia. Illum. Head, 24VAC/DC	5.5 in	3.5 in	4.25 in	36UX29	36UX30
40mm Dia. Illum. Head, 120VAC/DC	5.5 in	3.5 in	4.25 in	36UX31	36UX32
Valox, NEMA 4X					
40mm Dia. Head	4.36 in	3.18 in	3.66 in	36UX33	36UX34
65mm Dia. Head	4.36 in	3.18 in	3.66 in	36UX35	36UX36
40mm Dia. Illum. Head, 24VAC/DC	4.36 in	3.18 in	3.66 in	36UX37	36UX38
40mm Dia. Illum. Head, 120VAC/DC	4.36 in	3.18 in	3.66 in	36UX39	36UX40



36UX17