
























TrueSeal™

Potable Water & Food Processing Push-to-Connect Tube Fittings

Also called push fittings, they connect tubing without the use of special tools, glue, soldering, or unions. Tubing is pushed into the fitting and held in place by a grab ring which disconnects the tubing for frequent changes.















Acetal Fittings—Made from acetal plastic, also called polyacetal and polyoxymethylene (POM), a general purpose thermoplastic that resists corrosive and sensitive media, plus withstands changes in temperature and humidity.

Connec.: Push-to-Connect x ...			Pipe Size	Max. Operating Temp.	Max. Operating Pressure	Color	Brand	Item No.	Pkg. Qty.
Acetal Push-to-Connect Tube Fittings									
90° Elbow									
	Push-to-Connect	¼ in x ¼ in	—	150 °F	150 psi	White	John Guest	1WTG8	10
		¾ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	4HN20	10
		¾ in x ¾ in	—	150 °F	150 psi	White	John Guest	1WTG9	10
		½ in x ½ in	—	150 °F	150 psi	Gray	John Guest	4HN21	10
90° Elbow Adapter									
	NPTF	¼ in	¼ in	150 °F	150 psi	Gray	John Guest	4HN26	10
		¾ in	¼ in	150 °F	150 psi	Gray	John Guest	4HN28	10
		¾ in	¾ in	150 °F	150 psi	Gray	John Guest	4HN29	10
	Push-to-Connect	¾ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	1WTD6	10
		½ in x ½ in	—	150 °F	150 psi	Gray	John Guest	1WTD7	10
90° Reducing Elbow									
	Push-to-Connect	¾ in x ¼ in	—	150 °F	150 psi	Gray	John Guest	3ZLF6	10
90° Swivel Elbow Adapter									
	NPTF	¼ in	¼ in	150 °F	150 psi	Gray	John Guest	1WR92	10
		½ in	¾ in	150 °F	150 psi	Gray	John Guest	1WR97	10
		½ in	½ in	150 °F	150 psi	Gray	John Guest	1WR98	10
Straight Adapter									
	FNPTF	¼ in	¼ in	150 °F	150 psi	Gray	John Guest	3ZLG1	10
		¾ in	¼ in	150 °F	150 psi	Gray	John Guest	3ZLG2	10
	MBSPPP	¾ in	¼ in	150 °F	150 psi	Gray	John Guest	3ZLC6	10
		¾ in	¾ in	150 °F	150 psi	Gray	John Guest	1WR13	10
	MBSPT	½ in	¾ in	150 °F	150 psi	Gray	John Guest	1WR14	10
		½ in	½ in	150 °F	150 psi	Gray	John Guest	1WR15	10
		½ in	¼ in	150 °F	150 psi	Gray	John Guest	1WRP9	10
		¼ in	¼ in	150 °F	150 psi	Gray	John Guest	4HN10	10
	MNPTF	¼ in	¼ in	150 °F	150 psi	Gray	John Guest	4HN11	10
		¼ in	¾ in	150 °F	150 psi	Gray	John Guest	1WR11	10
		¾ in	¾ in	150 °F	150 psi	Gray	John Guest	4HN13	10
		¾ in	½ in	150 °F	150 psi	Gray	John Guest	1WR15	10
	NPTF	½ in	¾ in	150 °F	150 psi	Gray	John Guest	4HN14	10
		½ in	½ in	150 °F	150 psi	Gray	John Guest	4HN15	10
		¾ in	¼ in	150 °F	150 psi	Gray	John Guest	4HN12	10
	Tube Stem	¼ in	¾ in	150 °F	150 psi	Gray	John Guest	1WRW7	10
	Tube Stem x FNPT	¾ in	¼ in	158 °F	145 psi	Gray	John Guest	1WRV2	10
Straight Bulkhead Union Adapter									
	Push-to-Connect	¼ in x ¼ in	—	150 °F	150 psi	Gray	John Guest	1WTB9	10
		¾ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	1WTC2	10
Straight Connector									
	Push-to-Connect	¼ in x ¼ in	—	150 °F	150 psi	Gray	John Guest	4HN22	10
		¼ in x ¼ in	—	150 °F	150 psi	White	John Guest	1WTH1	10
		¾ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	1WRU5	10
		¾ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	4HN23	10
		¾ in x ¾ in	—	150 °F	150 psi	White	John Guest	1WTH2	10
		½ in x ½ in	—	150 °F	150 psi	Gray	John Guest	4HN24	10
Straight Reducing Connector									
	Push-to-Connect	¾ in x ¼ in	—	150 °F	150 psi	Gray	John Guest	1WTC6	10
		¾ in x ¼ in	—	150 °F	150 psi	Gray	John Guest	1WTC8	10
		½ in x ¾ in	—	150 °F	150 psi	Gray	John Guest	1WTD1	10
Nylon Push-to-Connect Tube Fittings									
90° Elbow									
	Push-to-Connect	¼ in x ¼ in	—	200 °F	230 psi	White	Parker	40L311	10
		¾ in x ¾ in	—	200 °F	230 psi	White	Parker	40L312	10
90° Elbow Adapter									
	NPTF	¾ in	¾ in	200 °F	230 psi	White	Parker	5UMU0	10

Nylon Fittings—Made of strong plastic with resistance to chemicals and corrosion.

Polypropylene Fittings (PP)—A lightweight, thermoplastic polymer with a wide variety of applications. They offer impact and abrasion resistance, surface hardness, plus resist a variety of acids, alkalis, and solvent solutions.

PVDF Fittings—PVDF, or polyvinylidene fluoride, tube fittings offer excellent chemical and heat resistance.

Connec.: Push-to-Connect x ...		For Tube OD	Pipe Size	Max. Operating Temp.	Max. Operating Pressure	Color	Brand	Item No.	Pkg. Qty.	
Straight Adapter										
	MNPTF	¼ in	¼ in	200 °F	230 psi	White	Parker	5UMT1	10	
		¾ in	¼ in	200 °F	230 psi	White	Parker	5UMT2	10	
		¾ in	¾ in	200 °F	230 psi	White	Parker	5UMT3	10	
		½ in	½ in	200 °F	230 psi	White	Parker	5UMT5	5	
Straight Connector										
	Push-to-Connect	¼ in x ¼ in	—	200 °F	230 psi	White	Parker	40L314	10	
		¼ in x ¾ in	—	200 °F	230 psi	White	Parker	40L319	10	
		¾ in x ¾ in	—	200 °F	230 psi	White	Parker	40L315	10	
		½ in x ½ in	—	200 °F	230 psi	White	Parker	40L316	5	
Polypropylene Push-to-Connect Tube Fittings										
90° Elbow										
	NPTF	¼ in	¼ in	150 °F	150 psi	White	John Guest	1WTU6	10	
		¾ in	¼ in	150 °F	150 psi	White	John Guest	1WTU8	10	
		¾ in	¾ in	150 °F	150 psi	White	John Guest	1WTU9	10	
	Push-to-Connect	¼ in x ¼ in	—	150 °F	150 psi	White	John Guest	1WTL3	10	
		¾ in x ¾ in	—	150 °F	150 psi	White	John Guest	1WTL5	10	
		½ in x ½ in	—	150 °F	150 psi	White	John Guest	1WTL6	10	
Straight Adapter										
	FUNEF	¾ in	¾ in	150 °F	150 psi	White	John Guest	400L16	10	
	MNPT	¾ in	¾ in	150 °F	150 psi	White	John Guest	400L27	10	
		¾ in	½ in	150 °F	150 psi	Black	John Guest	400L28	10	
	MNPTF	¼ in	⅛ in	150 °F	150 psi	White	John Guest	1WTJ9	10	
		¼ in	¼ in	150 °F	150 psi	White	John Guest	1WTK1	10	
		¼ in	¾ in	150 °F	150 psi	White	John Guest	1WTK2	10	
		¼ in	½ in	140 °F	150 psi	White	John Guest	400L11	10	
		¾ in	¼ in	150 °F	150 psi	White	John Guest	1WTK3	10	
		¾ in	¾ in	150 °F	150 psi	White	John Guest	1WTK4	10	
		¾ in	½ in	150 °F	150 psi	White	John Guest	1WTK5	10	
		½ in	¾ in	150 °F	150 psi	White	John Guest	1WTK6	10	
		½ in	½ in	150 °F	150 psi	White	John Guest	1WTK7	10	
		Straight Connector								
		Push-to-Connect	¼ in x ¼ in	—	150 °F	150 psi	Black	John Guest	400L34	10
	¼ in x ¼ in		—	150 °F	150 psi	White	John Guest	1WTL7	10	
	¼ in x ¾ in		—	150 °F	150 psi	Black	John Guest	400L35	10	
	¾ in x ¾ in		—	150 °F	150 psi	White	John Guest	1WTL9	10	
	½ in x ½ in		—	150 °F	150 psi	White	John Guest	1WTN1	10	
Straight Reducing Connector										
	Push-to-Connect	½ in x ½ in	—	150 °F	150 psi	White	John Guest	1WTT2	10	
Tee										
	Push-to-Connect	¼ in x ¼ in	—	149 °F	150 psi @ 70°F	White	John Guest	1WTK8	10	
		¼ in x ¼ in	—	140 °F	150 psi @ 70°F	White	John Guest	400L29	10	
		¾ in x ¾ in	—	149 °F	150 psi @ 70°F	White	John Guest	1WTL1	10	
		½ in x ½ in	—	149 °F	150 psi @ 70°F	White	John Guest	1WTL2	10	
PVDF Push-to-Connect Tube Fittings										
90° Elbow Adapter										
	MNPTF	¼ in	⅛ in	275 °F	300 psi	Black	Trueseal	60NL44	1	
		¼ in	¼ in	275 °F	300 psi	Black	Trueseal	60NL45	1	
		¾ in	¼ in	275 °F	300 psi	Black	Trueseal	60NL61	1	
		¾ in	¾ in	275 °F	300 psi	Black	Trueseal	60NL62	1	
Straight Adapter										
	MNPTF	¼ in	¼ in	275 °F	300 psi	Black	Trueseal	60NL42	1	
		¾ in	¼ in	275 °F	300 psi	Black	Trueseal	60NL58	1	
		¾ in	¾ in	275 °F	300 psi	Black	Trueseal	60NL59	1	
		¾ in	½ in	275 °F	300 psi	Black	Trueseal	60NL60	1	
Straight Connector										
	Push-to-Connect	¼ in x ¼ in	—	275 °F	300 psi	Black	Trueseal	60NL52	1	
		¾ in x ¼ in	—	275 °F	300 psi	Black	Trueseal	60NL73	1	
		½ in x ½ in	—	275 °F	250 psi	Black	Trueseal	60NL30	1	
Wye										
	Push-to-Connect	¼ in x ¼ in	—	275 °F	300 psi @ 275°F	Black	Trueseal	60NL31	1	
		¾ in x ¾ in	—	275 °F	300 psi @ 275°F	Black	Trueseal	60NL33	1	
		½ in x ½ in	—	275 °F	300 psi @ 275°F	Black	Trueseal	60NL35	1	