




















**CONTINUED** **PVC Pressure Pipe Fittings, Schedule 40**

| Description   | Fitting Pipe Size            | Pipe Fitting Connection Type | Max. Oper. Press. (psi) | Temp. Range   | Item No. |
|---|------------------------------|------------------------------|-------------------------|---------------|----------|
| <b>Threaded x Threaded Schedule 40 Pipe Fittings (Cont.)</b>                        |                              |                              |                         |               |          |
| <b>Union</b>  |                              |                              |                         |               |          |
|    | 1/2 in x 1/2 in              | FNPT                         | 600                     | 32° to 140° F | 22FM79   |
|   | 3/4 in x 3/4 in              | FNPT                         | 480                     | 32° to 140° F | 22FM80   |
|   | 1 in x 1 in                  | FNPT                         | 450                     | 32° to 140° F | 22FM81   |
|   | 1 1/4 in x 1 1/4 in          | FNPT                         | 370                     | 32° to 140° F | 22FM82   |
|   | 1 1/2 in x 1 1/2 in          | FNPT                         | 330                     | 32° to 140° F | 22FM83   |
|   | 2 in x 2 in                  | FNPT                         | 280                     | 32° to 140° F | 22FM84   |
| <b>Socket x Threaded Schedule 40 Pipe Fittings</b>                                  |                              |                              |                         |               |          |
| <b>90° Elbow</b>  |                              |                              |                         |               |          |
|    | 1/2 in x 1/2 in              | F Socket x FNPT              | 600                     | 32° to 140° F | 22FJ88   |
|   | 3/4 in x 3/4 in              | F Socket x FNPT              | 480                     | 32° to 140° F | 22FJ89   |
|   | 1 in x 1 in                  | F Socket x FNPT              | 450                     | 32° to 140° F | 22FJ83   |
|   | 1 1/4 in x 1 1/4 in          | F Socket x FNPT              | 280                     | 32° to 140° F | 22FJ79   |
|   | 1 1/2 in x 1 1/2 in          | F Socket x FNPT              | 370                     | 32° to 140° F | 22FJ76   |
|   | 2 in x 2 in                  | F Socket x FNPT              | 280                     | 32° to 140° F | 22FJ92   |
|   | 3 in x 3 in                  | F Socket x FNPT              | 330                     | 32° to 140° F | 22FL89   |
| <b>90° Reducing Elbow</b>   |                              |                              |                         |               |          |
|    | 3/4 in x 1/2 in              | F Socket x FNPT              | 480                     | 32° to 140° F | 22FL30   |
|   | 1 in x 1/2 in                | F Socket x FNPT              | 450                     | 32° to 140° F | 22FL31   |
|   | 1 in x 3/4 in                | F Socket x FNPT              | 450                     | 32° to 140° F | 22FL32   |
|   | 2 in x 1 in                  | F Socket x FNPT              | 280                     | 32° to 140° F | 22FL92   |
| <b>90° Side Inlet Elbow</b>   |                              |                              |                         |               |          |
|    | 1/2 in x 1/2 in x 1/2 in     | F Socket x F Socket x NPT    | 600                     | 32° to 140° F | 22FL28   |
|   | 3/4 in x 1/2 in x 1/2 in     | F Socket x F Socket x NPT    | 480                     | 32° to 140° F | 22FL38   |
|   | 1 in x 1/2 in x 1/2 in       | F Socket x F Socket x NPT    | 450                     | 32° to 140° F | 22FL37   |
| <b>90° Street Elbow</b>   |                              |                              |                         |               |          |
|    | 1/2 in x 1/2 in              | MNPT x F Socket              | 600                     | 32° to 140° F | 22FJ89   |
|   | 3/4 in x 3/4 in              | MNPT x F Socket              | 480                     | 32° to 140° F | 22FK01   |
|   | 1 in x 1 in                  | MNPT x F Socket              | 450                     | 32° to 140° F | 22FJ84   |
|   | 1 1/4 in x 1 1/4 in          | MNPT x F Socket              | 450                     | 32° to 140° F | 22FJ80   |
|   | 1 1/2 in x 1 1/2 in          | MNPT x F Socket              | 370                     | 32° to 140° F | 22FJ77   |
|   | 2 in x 2 in                  | MNPT x F Socket              | 280                     | 32° to 140° F | 22FJ93   |
| <b>Female Adapter</b>   |                              |                              |                         |               |          |
|    | 1/2 in x 1/2 in              | F Socket x FNPT              | 600                     | 32° to 140° F | 22FJ18   |
|   | 3/4 in x 3/4 in              | F Socket x FNPT              | 480                     | 32° to 140° F | 22FJ24   |
|   | 1 in x 1 in                  | F Socket x FNPT              | 450                     | 32° to 140° F | 22FJ16   |
|   | 1 1/4 in x 1 1/4 in          | F Socket x FNPT              | 370                     | 32° to 140° F | 22FJ12   |
|   | 1 1/2 in x 1 1/2 in          | F Socket x FNPT              | 330                     | 32° to 140° F | 22FJ09   |
|   | 2 in x 2 in                  | F Socket x FNPT              | 280                     | 32° to 140° F | 22FJ21   |
|   | 2 1/2 in x 2 1/2 in          | F Socket x FNPT              | 300                     | 32° to 140° F | 22FM26   |
|   | 6 in x 6 in                  | F Socket x FNPT              | 180                     | 32° to 140° F | 22FM28   |
|   | 8 in x 8 in                  | F Socket x FNPT              | 160                     | 32° to 140° F | 22FM29   |
| <b>Male Adapter</b>   |                              |                              |                         |               |          |
|   | 1/2 in x 1/2 in              | MNPT x F Socket              | 600                     | 32° to 140° F | 22FJ19   |
|   | 3/4 in x 3/4 in              | MNPT x F Socket              | 480                     | 32° to 140° F | 22FJ25   |
|   | 1 in x 1 in                  | MNPT x F Socket              | 450                     | 32° to 140° F | 22FJ17   |
|   | 1 1/4 in x 1 1/4 in          | MNPT x F Socket              | 330                     | 32° to 140° F | 22FJ13   |
|   | 1 1/2 in x 1 1/2 in          | MNPT x F Socket              | 330                     | 32° to 140° F | 22FJ10   |
|   | 2 in x 2 in                  | MNPT x F Socket              | 280                     | 32° to 140° F | 22FJ22   |
|   | 2 1/2 in x 2 1/2 in          | MNPT x F Socket              | 300                     | 32° to 140° F | 22FM30   |
|   | 6 in x 6 in                  | MNPT x F Socket              | 180                     | 32° to 140° F | 22FM31   |
| <b>Reducing Adapter</b>   |                              |                              |                         |               |          |
|  | 1/2 in x 3/4 in              | F Socket x FNPT              | 480                     | 32° to 140° F | 22FL25   |
|   | 1/2 in x 3/4 in              | MNPT x F Socket              | 480                     | 32° to 140° F | 22FJ26   |
|   | 3/4 in x 1/2 in              | FNPT x F Socket              | 480                     | 32° to 140° F | 22FL26   |
|   | 3/4 in x 1 in                | F Socket x FNPT              | 450                     | 32° to 140° F | 22FL21   |
|   | 1 in x 3/4 in                | FNPT x F Socket              | 450                     | 32° to 140° F | 22FL22   |
|   | 1 in x 1 in                  | F Socket x FNPT              | 450                     | 32° to 140° F | 22FL23   |
|   | 1 in x 1 1/4 in              | MNPT x F Socket              | 370                     | 32° to 140° F | 22FJ15   |
|   | 1 1/4 in x 1 1/2 in          | MNPT x F Socket              | 370                     | 32° to 140° F | 22FJ14   |
|   | 1 1/2 in x 1 1/4 in          | MNPT x F Socket              | 370                     | 32° to 140° F | 22FJ11   |
|   | 1 1/2 in x 2 in              | MNPT x F Socket              | 330                     | 32° to 140° F | 22FJ23   |
|   | 2 in x 1 1/2 in              | Male NPT x Female Hub        | 280                     | 32° to 140° F | 22FL24   |
|   | 2 in x 2 1/2 in              | MNPT x F Socket              | 280                     | 32° to 140° F | 22FM33   |
|   | 2 in x 3 in                  | FNPT x F Socket              | 260                     | 32° to 140° F | 22FM34   |
|   | 3 in x 4 in                  | MNPT x F Socket              | 260                     | 32° to 140° F | 22FM35   |
| <b>Reducing Tee</b>   |                              |                              |                         |               |          |
|  | 3/4 in x 1/2 in x 3/4 in     | F Socket x F Socket x FNPT   | 480                     | 32° to 140° F | 22FK90   |
|   | 1 in x 1/2 in x 3/4 in       | F Socket x F Socket x FNPT   | 450                     | 32° to 140° F | 22FK84   |
|   | 1 1/4 in x 1/2 in x 1 1/4 in | F Socket x F Socket x FNPT   | 370                     | 32° to 140° F | 22FK77   |
|   | 1 1/4 in x 3/4 in x 1 1/4 in | F Socket x F Socket x FNPT   | 370                     | 32° to 140° F | 22FK79   |
|   | 1 1/2 in x 1/2 in x 1 1/2 in | F Socket x F Socket x FNPT   | 330                     | 32° to 140° F | 22FK73   |
|   | 1 1/2 in x 3/4 in x 1 1/2 in | F Socket x F Socket x FNPT   | 370                     | 32° to 140° F | 22FK75   |
|   | 2 in x 3/4 in x 2 in         | F Socket x F Socket x FNPT   | 280                     | 32° to 140° F | 22FK86   |
|   | 2 1/2 in x 3/4 in x 2 1/2 in | F Socket x F Socket x FNPT   | 300                     | 32° to 140° F | 22FL72   |
|   | 3 in x 1 in x 3 in           | F Socket x F Socket x FNPT   | 260                     | 32° to 140° F | 22FL76   |
| <b>Tee</b>  |                              |                              |                         |               |          |
|  | 1/2 in                       | F Socket x FNPT x F Socket   | 600                     | 32° to 140° F | 22FL79   |
|   | 1/2 in                       | F Socket x F Socket x FNPT   | 600                     | 32° to 140° F | 22FL03   |
|   | 3/4 in                       | F Socket x FNPT x F Socket   | 480                     | 32° to 140° F | 22FL39   |
|   | 3/4 in                       | F Socket x F Socket x FNPT   | 480                     | 32° to 140° F | 22FK98   |
|   | 1 in                         | F Socket x F Socket x FNPT   | 450                     | 32° to 140° F | 22FK96   |
|   | 1 1/4 in                     | F Socket x F Socket x FNPT   | 370                     | 32° to 140° F | 22FK94   |
|   | 1 1/2 in                     | F Socket x F Socket x FNPT   | 330                     | 32° to 140° F | 22FL66   |
| <b>Spigot x Threaded Schedule 40 Pipe Fittings</b>                                  |                              |                              |                         |               |          |
| <b>90° Street Elbow</b>   |                              |                              |                         |               |          |
|  | 3/4 in x 3/4 in              | M Spigot x FNPT              | 480                     | 32° to 140° F | 22FL99   |
| <b>Reducing Bushing</b>   |                              |                              |                         |               |          |
|  | 1/2 in x 1/2 in              | M Spigot x FNPT              | 600                     | 32° to 140° F | 22FM52   |
|   | 1/2 in x 3/4 in              | M Spigot x FNPT              | 480                     | 32° to 140° F | 22FM53   |
|   | 3/4 in x 1/2 in              | M Spigot x FNPT              | 480                     | 32° to 140° F | 22FK67   |
|   | 1 in x 1/2 in                | M Spigot x FNPT              | 450                     | 32° to 140° F | 22FK45   |
|   | 1 in x 3/4 in                | M Spigot x FNPT              | 450                     | 32° to 140° F | 22FK42   |
|   | 1 1/4 in x 1/2 in            | M Spigot x FNPT              | 370                     | 32° to 140° F | 22FK37   |
|   | 1 1/4 in x 3/4 in            | M Spigot x FNPT              | 370                     | 32° to 140° F | 22FK40   |
|   | 1 1/4 in x 1 in              | M Spigot x FNPT              | 370                     | 32° to 140° F | 22FK35   |

| Description   | Fitting Pipe Size   | Pipe Fitting Connection Type | Max. Oper. Press. (psi) | Temp. Range   | Item No.     |        |
|---|---|------------------------------|-------------------------|---------------|--------------|--------|
|    | 1 1/2 in x 1 1/2 in   | M Spigot x FNPT              | 330                     | 32° to 140° F | 22FK27       |        |
|   | 1 1/2 in x 3/4 in   | M Spigot x FNPT              | 330                     | 32° to 140° F | 22FK30       |        |
|   | 1 1/2 in x 1 in   | M Spigot x FNPT              | 330                     | 32° to 140° F | 22FK25       |        |
|   | 1 1/2 in x 1 1/4 in   | M Spigot x FNPT              | 330                     | 32° to 140° F | 22FK32       |        |
|   | 2 in x 1/2 in   | M Spigot x FNPT              | 280                     | 32° to 140° F | 22FK59       |        |
|   | 2 in x 3/4 in   | M Spigot x FNPT              | 280                     | 32° to 140° F | 22FK60       |        |
|   | 2 in x 1 in   | M Spigot x FNPT              | 280                     | 32° to 140° F | 22FK62       |        |
|   | 2 1/2 in x 1 in   | M Spigot x FNPT              | 300                     | 32° to 140° F | 22FM54       |        |
|   | 2 1/2 in x 1 1/2 in   | M Spigot x FNPT              | 300                     | 32° to 140° F | 22FM55       |        |
|   | 2 1/2 in x 2 in   | M Spigot x FNPT              | 300                     | 32° to 140° F | 22FK48       |        |
|   | 3 in x 1 in   | M Spigot x FNPT              | 260                     | 32° to 140° F | 22FM56       |        |
|   | 3 in x 1 1/2 in   | M Spigot x FNPT              | 260                     | 32° to 140° F | 22FM57       |        |
|    | 3 in x 2 in   | M Spigot x FNPT              | 260                     | 32° to 140° F | 22FK69       |        |
|   | 4 in x 2 in   | M Spigot x FNPT              | 220                     | 32° to 140° F | 22FM58       |        |
|   | 4 in x 2 1/2 in   | M Spigot x FNPT              | 220                     | 32° to 140° F | 22FK71       |        |
|   | 4 in x 3 in   | M Spigot x FNPT              | 220                     | 32° to 140° F | 22FK72       |        |
|   | Spigot x Spigot Schedule 40 Pipe Fittings   |                              |                         |               |              |        |
|   | Hex Head Plug   |                              |                         |               |              |        |
|   | 1 1/4 in  | Spigot                       | 370                     | 0° to 140° F  | 22FK14       |        |
|   | 3 in  | Spigot                       | 260                     | 0° to 140° F  | 22FM74       |        |
|   | 4 in  | Spigot                       | 220                     | 0° to 140° F  | 22FM75       |        |
|   |  | 1/2 in                       | Spigot                  | 600           | 0° to 140° F | 22FK16 |
|   |   | 3/4 in                       | Spigot                  | 480           | 0° to 140° F | 22FK18 |
|   |   | 1 in                         | Spigot                  | 450           | 0° to 140° F | 22FK15 |
| 1 1/2 in  |   | Spigot                       | 330                     | 0° to 140° F  | 22FK13       |        |
| Socket x Spigot Schedule 40 Pipe Fittings   |   |                              |                         |               |              |        |
| 90° Street Elbow  |   |                              |                         |               |              |        |
|    | 1/2 in x 1/2 in   | M Spigot x F Socket          | 600                     | 32° to 140° F | 22FJ90       |        |
|   | 3/4 in x 3/4 in   | M Spigot x F Socket          | 480                     | 32° to 140° F | 22FK02       |        |
|   | 1 in x 1 in   | M Spigot x F Socket          | 450                     | 32° to 140° F | 22FJ85       |        |
|   | 1 1/4 in x 1 1/4 in   | M Spigot x F Socket          | 370                     | 32° to 140° F | 22FJ81       |        |
|   | 1 1/2 in x 1 1/2 in   | M Spigot x F Socket          | 330                     | 32° to 140° F | 22FJ78       |        |
|   | 2 in x 2 in   | M Spigot x F Socket          | 280                     | 32° to 140° F | 22FJ94       |        |
|   | 2 1/2 in x 2 1/2 in   | M Spigot x F Socket          | 300                     | 32° to 140° F | 22FL96       |        |
|   | 3 in x 3 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FL97       |        |
| P-Trap  |   |                              |                         |               |              |        |
|    | 1/2 in x 1/2 in   | F Socket x M Spigot          | 600                     | 32° to 140° F | 22FK19       |        |
|   | 1/2 in x 3/4 in   | F Socket x M Spigot          | 480                     | 32° to 140° F | 22FK91       |        |
| Reducing Bushing  |   |                              |                         |               |              |        |
|   | 3/4 in x 1/2 in   | M Spigot x F Socket          | 480                     | 32° to 140° F | 22FK68       |        |
|   | 1 in x 1/2 in   | M Spigot x F Socket          | 450                     | 32° to 140° F | 22FK46       |        |
|   | 1 in x 3/4 in   | M Spigot x F Socket          | 450                     | 32° to 140° F | 22FK43       |        |
|   | 1 1/4 in x 3/4 in   | M Spigot x F Socket          | 370                     | 32° to 140° F | 22FK41       |        |
|   | 1 1/4 in x 1 in   | M Spigot x F Socket          | 370                     | 32° to 140° F | 22FK36       |        |
|   | 1 1/2 in x 1 1/2 in   | M Spigot x F Socket          | 330                     | 32° to 140° F | 22FK28       |        |
|   | 1 1/2 in x 3/4 in   | M Spigot x F Socket          | 330                     | 32° to 140° F | 22FK31       |        |
|   | 1 1/2 in x 1 in   | M Spigot x F Socket          | 330                     | 32° to 140° F | 22FK26       |        |
|   | 1 1/2 in x 1 1/4 in   | M Spigot x F Socket          | 330                     | 32° to 140° F | 22FK32       |        |
|   | 2 in x 3/4 in   | M Spigot x F Socket          | 280                     | 32° to 140° F | 22FK61       |        |
|   | 2 in x 1 in   | M Spigot x F Socket          | 280                     | 32° to 140° F | 22FK63       |        |
|   | 2 in x 1 1/4 in   | M Spigot x F Socket          | 280                     | 32° to 140° F | 22FK57       |        |
|   | 2 in x 1 1/2 in   | M Spigot x F Socket          | 280                     | 32° to 140° F | 22FK55       |        |
|   | 2 1/2 in x 1 in   | M Spigot x F Socket          | 300                     | 32° to 140° F | 22FM39       |        |
|   | 2 1/2 in x 1 1/4 in   | M Spigot x F Socket          | 300                     | 32° to 140° F | 22FK52       |        |
|   | 2 1/2 in x 1 1/2 in   | M Spigot x F Socket          | 300                     | 32° to 140° F | 22FK50       |        |
|   | 2 1/2 in x 2 in   | M Spigot x F Socket          | 300                     | 32° to 140° F | 22FK49       |        |
|   | 3 in x 3/4 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FM40       |        |
|   | 3 in x 1 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FM41       |        |
|   | 3 in x 1 1/2 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FM43       |        |
|   | 3 in x 2 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FK70       |        |
|   | 3 in x 2 1/2 in   | M Spigot x F Socket          | 260                     | 32° to 140° F | 22FK65       |        |
|   | 4 in x 2 1/2 in   | M Spigot x F Socket          | 220                     | 32° to 140° F | 22FM44       |        |
|   | 5 in x 4 in   | M Spigot x F Socket          | 190                     | 32° to 140° F | 22FM45       |        |
| 6 in x 2 in   | M Spigot x F Socket   | 180                          | 32° to 140° F           | 22FM46        |              |        |
| 6 in x 3 in   | M Spigot x F Socket   | 180                          | 32° to 140° F           | 22FM47        |              |        |
| 6 in x 5 in   | M Spigot x F Socket   | 180                          | 32° to 140° F           | 22FM48        |              |        |
| 8 in x 4 in   | M Spigot x F Socket   | 160                          | 32° to 140° F           | 22FM50        |              |        |
| 8 in x 6 in   | M Spigot x F Socket   | 160                          | 32° to 140° F           | 22FM51        |              |        |
| Socket x Socket Schedule 40 Pipe Fittings   |   |                              |                         |               |              |        |
| 22-1/2" Elbow   |   |                              |                         |               |              |        |
|  | 1 1/2 in x 1 1/2 in   | F Socket                     | 330                     | 32° to 140° F | 22FM87       |        |
|   | 2 in x 2 in   | F Socket                     | 280                     | 32° to 140° F | 22FM88       |        |
|   | 3 in x 3 in   | F Socket                     | 260                     | 32° to 140° F | 22FM89       |        |
|   | 4 in x 4 in   | F Socket                     | 220                     | 32° to 140° F | 22FM90       |        |
| 45° Elbow   |   |                              |                         |               |              |        |
|  | 1/2 in x 1/2 in   | F Socket                     | 600                     | 32° to 140° F | 22FJ66       |        |
|   | 3/4 in x 3/4 in   | F Socket                     | 480                     | 32° to 140° F | 22FJ69       |        |
|   | 1 in x 1 in   | F Socket                     | 450                     | 32° to 140° F | 22FJ65       |        |
|   | 1 1/4 in x 1 1/4 in   | F Socket                     | 370                     | 32° to 140° F | 22FJ63       |        |
|   | 1 1/2 in x 1 1/2 in   | F Socket                     | 330                     | 32° to 140° F | 22FJ62       |        |
|   | 2 in x 2 in   | F Socket                     | 280                     | 32° to 140° F | 22FJ67       |        |
|   | 2 1/2 in x 2 1/2 in   | F Socket                     | 300                     | 32° to 140° F | 22FJ64       |        |
|   | 3 in x 3 in   | F Socket                     | 260                     | 32° to 140° F | 22FJ68       |        |
|   | 4 in x 4 in   | F Socket                     | 220                     | 32° to 140° F | 22FJ70       |        |
|   | 6 in x 6 in   | F Socket                     | 180                     | 32° to 140° F | 22FJ71       |        |
| 90° Elbow   |   |                              |                         |               |              |        |
|  | 8 in x 8 in   | F Socket                     | 160                     | 32° to 140° F | 22FM06       |        |
|   | 3/8 in x 3/8 in   | F Socket                     | 480                     | 32° to 140° F | 22FL82       |        |
|   | 1/2 in x 1/2 in   | F Socket                     | 600                     | 32° to 140° F | 22FJ91       |        |
|   | 3/4 in x 3/4 in   | F Socket                     | 480                     | 32° to 140° F | 22FK03       |        |
|   | 1 in x 1 in   | F Socket                     | 450                     | 32° to 140° F | 22FJ86       |        |
|   | 1 1/4 in x 1 1/4 in   | F Socket                     | 370                     | 32° to 140° F | 22FJ73       |        |
|   | 1 1/2 in x 1 1/2 in   | F Socket                     | 330                     | 32° to 140° F | 22FJ72       |        |
|   | 2 in x 2 in   | F Socket                     | 280                     | 32° to 140° F | 22FJ95       |        |
|   | 2 1/2 in x 2 1/2 in   | F Socket                     | 300                     | 32° to 140° F | 22FJ75       |        |
|   | 3 in x 3 in   | F Socket                     | 260                     | 32° to 140° F | 22FJ96       |        |
| 4 in x 4 in   | F Socket  | 220                          | 32° to 140° F           | 22FK04        |              |        |
| 5 in x 5 in   | F Socket  | 190                          | 32° to 140° F           | 22FL83        |              |        |
| 6 in x 6 in   | F Socket  | 180                          | 32° to 140° F           | 22FK05        |              |        |
| 8 in x 8 in   | F Socket  | 160                          | 32° to 140° F           | 22FL84        |              |        |