

















For ABS Solvent Cement, see page 2710.

CONTINUED **PVC Pressure Pipe Fittings, Schedule 40**

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Oper. Press. (psi)	Temp. Range	Item No.
<b>Socket x Socket Schedule 40 Pipe Fittings (Cont.)</b>					
	<b>90° Reducing Elbow</b>				
	¾ in x ½ in	F Socket	480	32° to 140° F	22FL33
	2 in x 1 in	F Socket	280	32° to 140° F	22FL86
	<b>90° Side Outlet Elbow</b>				
	2 in x 1½ in	F Socket	280	32° to 140° F	22FL87
	1½ in	F Socket x F Socket x Socket	330	32° to 140° F	22FM04
	<b>Cap</b>				
	½ in	F Socket	600	0° to 140° F	22FJ34
	¾ in	F Socket	480	0° to 140° F	22FJ40
	1 in	F Socket	450	0° to 140° F	22FJ32
	1½ in	F Socket	370	0° to 140° F	22FJ30
	2 in	F Socket	330	0° to 140° F	22FJ28
	2½ in	F Socket	300	0° to 140° F	22FJ37
	3 in	F Socket	260	0° to 140° F	22FJ38
	4 in	F Socket	220	0° to 140° F	22FJ41
	5 in	F Socket	190	0° to 140° F	22FM69
	<b>Coupling</b>				
	½ in x ½ in	F Socket	600	32° to 140° F	22FJ48
	¾ in x ¾ in	F Socket	480	32° to 140° F	22FJ53
	1 in x 1 in	F Socket	450	32° to 140° F	22FJ46
	1¼ in x 1¼ in	F Socket	370	32° to 140° F	22FJ44
	1½ in x 1½ in	F Socket	330	32° to 140° F	22FJ43
	2 in x 2 in	F Socket	280	32° to 140° F	22FJ50
	2½ in x 2½ in	F Socket	300	32° to 140° F	22FJ49
	3 in x 3 in	F Socket	260	32° to 140° F	22FJ51
	4 in x 4 in	F Socket	220	32° to 140° F	22FJ54
	<b>Deep Socket Coupling</b>				
	½ in x ½ in	F Socket	600	32° to 140° F	22FJ48
	¾ in x ¾ in	F Socket	480	32° to 140° F	22FJ53
	1 in x 1 in	F Socket	450	32° to 140° F	22FJ46
	1¼ in x 1¼ in	F Socket	370	32° to 140° F	22FJ44
	1½ in x 1½ in	F Socket	330	32° to 140° F	22FJ43
	2 in x 2 in	F Socket	280	32° to 140° F	22FJ50
	2½ in x 2½ in	F Socket	300	32° to 140° F	22FJ49
	3 in x 3 in	F Socket	260	32° to 140° F	22FJ51
	4 in x 4 in	F Socket	220	32° to 140° F	22FJ54
	<b>Long Socket Coupling</b>				
	½ in x ½ in	F Socket	600	32° to 140° F	22FJ48
	¾ in x ¾ in	F Socket	480	32° to 140° F	22FJ53
	1 in x 1 in	F Socket	450	32° to 140° F	22FJ46
	1¼ in x 1¼ in	F Socket	370	32° to 140° F	22FJ44
	1½ in x 1½ in	F Socket	330	32° to 140° F	22FJ43
	2 in x 2 in	F Socket	280	32° to 140° F	22FJ50
	2½ in x 2½ in	F Socket	300	32° to 140° F	22FJ49
	3 in x 3 in	F Socket	260	32° to 140° F	22FJ51
	4 in x 4 in	F Socket	220	32° to 140° F	22FJ54
	<b>Reducing Coupling</b>				
	¾ in x ½ in	F Socket	480	32° to 140° F	22FK22
	1¼ in x 1 in	F Socket	370	32° to 140° F	22FM17
	2 in x 1¼ in	F Socket	330	32° to 140° F	22FM18
	2½ in x 1½ in	F Socket	280	32° to 140° F	22FM19
	3 in x 2 in	F Socket	260	32° to 140° F	22FK21
	4 in x 3 in	F Socket	220	32° to 140° F	22FM20
	6 in x 4 in	F Socket	180	32° to 140° F	22FM21
	8 in x 6 in	F Socket	160	32° to 140° F	22FM22
	<b>Reducing Tee</b>				
	¾ in x ½ in x ¾ in	F Socket	480	32° to 140° F	22FK89
	1 in x 1 in x 1 in	F Socket	450	32° to 140° F	22FK80
	1 in x ¾ in x 1 in	F Socket	450	32° to 140° F	22FK81
	1 in x 1 in x ½ in	F Socket x F Socket x FNPT	450	32° to 140° F	22FK83
	1½ in x ¾ in x 1½ in	F Socket	330	32° to 140° F	22FK74
	1½ in x 1 in x 1½ in	F Socket	330	32° to 140° F	22FK82
	1½ in x 2 in x 1½ in	F Socket	330	32° to 140° F	22FL48

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Oper. Press. (psi)	Temp. Range	Item No.
<b>Reducing Tee (Cont.)</b>					
	2 in x 1½ in x 2 in	F Socket	280	32° to 140° F	22FK85
	2 in x 2 in x 2 in	F Socket	280	32° to 140° F	22FL05
	2½ in x 1 in x 2½ in	F Socket	300	32° to 140° F	22FL51
	2½ in x 2½ in x 4 in	F Socket	300	32° to 140° F	22FL04
	3 in x ¾ in x 3 in	F Socket	260	32° to 140° F	22FL54
	3 in x 1 in x 3 in	F Socket	260	32° to 140° F	22FL55
	3 in x 1½ in x 3 in	F Socket	260	32° to 140° F	22FL57
	3 in x 2 in x 3 in	F Socket	260	32° to 140° F	22FL60
	4 in x 1 in x 4 in	F Socket	220	32° to 140° F	22FL61
	4 in x 2 in x 4 in	F Socket	220	32° to 140° F	22FL62
	4 in x 3 in x 4 in	F Socket	220	32° to 140° F	22FL63
	6 in x 2 in x 6 in	F Socket	180	32° to 140° F	22FL64
	6 in x 3 in x 6 in	F Socket	180	32° to 140° F	22FL65
	6 in x 4 in x 6 in	F Socket	180	32° to 140° F	22FL65
	<b>Repair Coupling</b>				
	1 in x 1 in	F Socket	150	32° to 113° F	1WJX8
	1¼ in x 1¼ in	F Socket	150	32° to 113° F	1WJY1
	1½ in x 1½ in	F Socket	150	32° to 113° F	1WJY3
	2 in x 2 in	F Socket	150	32° to 113° F	1WJY5
	2½ in x 2½ in	F Socket	150	32° to 113° F	1WJY7
	<b>Standard Cross</b>				
	½ in	F Socket	600	32° to 140° F	22FJ59
	¾ in	F Socket	480	32° to 140° F	22FJ61
	1 in	F Socket	450	32° to 140° F	22FJ58
	1¼ in	F Socket	370	32° to 140° F	22FJ57
	1½ in	F Socket	330	32° to 140° F	22FJ56
	<b>Tee</b>				
	2 in	F Socket	280	32° to 140° F	22FJ60
	3 in	F Socket	260	32° to 140° F	22FM08
	4 in	F Socket	220	32° to 140° F	22FM09
	¾ in	F Socket	480	32° to 140° F	22FL40
	1½ in	F Socket	600	32° to 140° F	22FL02
	<b>Union</b>				
	¾ in	F Socket	480	32° to 140° F	22FL08
	1 in	F Socket	450	32° to 140° F	22FK99
	1¼ in	F Socket	370	32° to 140° F	22FK95
	1½ in	F Socket	330	32° to 140° F	22FK93
	3 in	F Socket	260	32° to 140° F	22FL06
	4 in	F Socket	220	32° to 140° F	22FL10
	5 in	F Socket	190	32° to 140° F	22FL11
	6 in	F Socket	180	32° to 140° F	22FL12
	8 in	F Socket	160	32° to 140° F	22FL41
	<b>Wye</b>				
	½ in x ½ in	F Socket	600	32° to 140° F	22FL14
	¾ in x ¾ in	F Socket	480	32° to 140° F	22FL19
	1 in x 1 in	F Socket	450	32° to 140° F	22FL13
	1¼ in x 1¼ in	F Socket	370	32° to 140° F	22FL16
	1½ in x 1½ in	F Socket	330	32° to 140° F	22FL15
	2 in x 2 in	F Socket	280	32° to 140° F	22FL17
	3 in x 3 in	F Socket	260	32° to 140° F	22FL18
	4 in x 4 in	F Socket	220	32° to 140° F	22FL20
	4 in x 4 in x 4 in	F Socket	220	32° to 140° F	22FM92

**Schedule 40 Clear Pipe & Fittings**

- Temp. range: 73° to 180°F, except caps are 0° to 140°F

Clear PVC pipe is used for quick identification and visual leak detection in medical/hospital use, chemical processing, and beverage processing. Compatible with PVC cleaners, primers, and cements. Schedule 40 pipe has thicker walls than Schedule 10, but not as thick as Schedule 80 pipe.

Description	Nominal Pipe Size	8 ft Item No.
<b>Schedule 40 Clear Unthreaded Low Pressure Pipe</b>		
	½ in	1AAZ4
	¾ in	1AAZ5
	1 in	1AAZ6
	1¼ in	5REW3
	1½ in	1AAZ7
	2 in	1AAZ8
	2½ in	5REW4
	3 in	1AAZ9
	4 in	1ABA1

Fitting Pipe Size	Pipe Fitting Connection Type	Max. Operating Pressure	Item No.
<b>Socket x Threaded Schedule 40 Pipe Fittings</b>			
<b>Female Adapter</b>			
½ in	FNPT x F Socket	360 psi @ 73° F	2CFA3
¾ in	FNPT x F Socket	280 psi @ 73° F	2CFA4
1 in	FNPT x F Socket	270 psi @ 73° F	2CFA5
1½ in	FNPT x F Socket	200 psi @ 73° F	2CFA7
2 in	FNPT x F Socket	170 psi @ 73° F	2CFA8
4 in	FNPT x F Socket	130 psi @ 73° F	2CFC2
<b>Male Adapter</b>			
½ in	MNPT x M Socket	360 psi @ 73° F	2CFC3
¾ in	MNPT x M Socket	280 psi @ 73° F	2CFC4
1 in	MNPT x M Socket	270 psi @ 73° F	2CFC5
1½ in	MNPT x M Socket	200 psi @ 73° F	2CFC7
2 in	MNPT x M Socket	170 psi @ 73° F	2CFC8
2½ in	MNPT x M Socket	180 psi @ 73° F	2CFC9
<b>Socket x Socket Schedule 40 Pipe Fittings</b>			
<b>45° Elbow</b>			
½ in	F Socket	360 psi @ 73° F	2CEY3
¾ in	F Socket	280 psi @ 73° F	2CEY4
1 in	F Socket	270 psi @ 73° F	2CEY5
2 in	F Socket	170 psi @ 73° F	2CEY8
2½ in	F Socket	180 psi @ 73° F	2CEY9
3 in	F Socket	155 psi @ 73° F	2CEZ1
4 in	F Socket	130 psi @ 73° F	2CEZ2
<b>90° Elbow</b>			
½ in	F Socket	360 psi @ 73° F	2CEX3
¾ in	F Socket	280 psi @ 73° F	2CEX4
1 in	F Socket	270 psi @ 73° F	2CEX5
1¼ in	F Socket	220 psi @ 73° F	2CEX6
1½ in	F Socket	200 psi @ 73° F	2CEX7
2 in	F Socket	170 psi @ 73° F	2CEX8
2½ in	F Socket	180 psi @ 73° F	2CEX9
4 in	F Socket	130 psi @ 73° F	2CEY2

Fitting Pipe Size	Pipe Fitting Connection Type	Max. Operating Pressure	Item No.
<b>Cap</b>			
½ in	Socket	180 psi @ 73° F	2CFD3
¾ in	Socket	180 psi @ 73° F	2CFD3
1 in	Socket	144 psi @ 73° F	2CFD4
1½ in	Socket	132 psi @ 73° F	2CFD5
2 in	Socket	102 psi @ 73° F	2CFD7
3 in	Socket	84 psi @ 73° F	2CFD8
4 in	Socket	90 psi @ 73° F	2CFD9
6 in	Socket	78 psi @ 73° F	2CFE1
<b>Coupling</b>			
½ in	F Socket	360 psi @ 73° F	2CEZ3
¾ in	F Socket	280 psi @ 73° F	2CEZ4
1 in	F Socket	270 psi @ 73° F	2CEZ5
1¼ in	F Socket	220 psi @ 73° F	2CEZ6
1½ in	F Socket	200 psi @ 73° F	2CEZ7
2 in	F Socket	170 psi @ 73° F	2CEZ8
3 in	F Socket	155 psi @ 73° F	2CFA1
4 in	F Socket	130 psi @ 73° F	2CFA2
<b>Tee</b>			
½ in	F Socket	360 psi @ 73° F	2CEW3
¾ in	F Socket	280 psi @ 73° F	2CEW4
1 in	F Socket	270 psi @ 73° F	2CEW5
1¼ in	F Socket	220 psi @ 73° F	2CEW6
1½ in	F Socket	200 psi @ 73° F	2CEW7
2 in	F Socket	170 psi @ 73° F	2CEW8
2½ in	F Socket	180 psi @ 73° F	2CEW9
4 in	F Socket	130 psi @ 73° F	2CEX2