

PLUMBING

Drinking Water Filter Housings & Filtration Systems

Scan. Order. Done.
Details on page A1.



Flow Rate	Connec. Size	Max. Pressure	Overall Height	Overall Dia.	Color	Housing Material	Max. Pressure	Maximum Temperature	Mfr. Model	Item No.
3M Aqua-Pure										
8 gpm	3/4"	300 psi	12"	4 1/4"	Silver	304 Stainless Steel	300 psi	200 °F	5592001	6YJ19
16 gpm	3/4"	125 psi	24 1/2"	4 5/8"	Clear	Acetal/Isoplast	125 psi	100 °F	5530008	1ZKK5
20 gpm	1"	100 psi	14 1/2"	7 1/8"	Blue	Polypropylene	100 psi	100 °F	AP801B	61HJ88
20 gpm	1"	100 psi	14 1/2"	7 1/8"	Clear	Polypropylene	100 psi	100 °F	AP801T	61HJ90
45 gpm	1 1/2"	100 psi	24 1/2"	7 1/8"	Blue	Polypropylene	100 psi	100 °F	AP802B	61HJ89
Culligan										
4 gpm	3/4"	125 psi	12 1/2"	5"	Blue	Polypropylene	125 psi	100 °F	HF-150A	29AH40
8 gpm	1"	100 psi	15 5/8"	8 3/8"	Clear	Styrene Acrylonitrile	100 psi	100 °F	WH-HD200-C	53CP05
10 gpm	1"	100 psi	13 3/4"	7 1/8"	Blue	Polypropylene	100 psi	100 °F	HD-950A	29AH47
Pentair/Pentek										
8 gpm	3/4"	125 psi	11 3/4"	4 3/8"	Black	Nylon	125 psi	160 °F	158319-75	4BB50
	3/4"	125 psi	12 1/4"	5 1/8"	Blue	Polypropylene	125 psi	125 °F	150067-75	1ECP4
	3/4"	125 psi	12 5/8"	5 1/4"	Clear	Styrene Acrylonitrile	125 psi	125 °F	150435-75	1ECP8
10 gpm	3/4"	125 psi	12 5/8"	5 1/4"	Clear	Styrene Acrylonitrile	125 psi	125 °F	150071-75	53DP10
	3/4"	125 psi	22 3/8"	5 1/8"	Blue	Polypropylene	125 psi	125 °F	150069-75	1ECP5
	3/4"	250 psi	12 1/2"	4 1/8"	Silver	304 Stainless Steel	250 psi	275 °F	156017-75	4PPC1
	1"	90 psi	13 1/4"	7 1/2"	Blue	Polypropylene	90 psi	100 °F	150237-75	4BA76
	1"	90 psi	23 1/4"	7 1/2"	Blue	Polypropylene	90 psi	100 °F	150233-75	4BA77
15 gpm	3/4"	90 psi	23"	7 3/8"	Blue	Polypropylene	90 psi	100 °F	150467-75	1ECP9
	3/4"	100 psi	12 3/4"	7 3/8"	Blue	Polypropylene	100 psi	100 °F	150469-75	1ECP1
20 gpm	1 1/2"	90 psi	13 1/2"	7 1/2"	Blue	Polypropylene	90 psi	100 °F	150239-75	1ECP7
	1 1/2"	90 psi	23 3/4"	7 1/2"	Blue	Polypropylene	90 psi	100 °F	150235-75	1ECP6



Drinking Water Filter Housings

Housings hold compatible drinking water filter cartridges. They are composed of two parts: the filter cap and the filter sump. The sump is the container that holds the filter cartridge in place and channels water through it for filtering. The filter cap allows water to flow in and out of the sump correctly.



Whole-House Drinking Water Filtration Systems

- Include filter, housing, & head

Filters connect to water supply lines entering houses or buildings to remove contaminants, protect pipes and appliances, and improve water quality.

Reduces	Micron Rating	Flow Rate	Service Life	Connec. Size	H	W	Includes Valve	Max. Pressure	Maximum Temperature	Mfr. Model	Brand	Item No.
Chlorine Taste and Odor, Particulates	5 micron	20 gpm	100,000 gal	1"	25 1/2"	4 1/2"	Yes	125 psi	100 °F	5621102	3M	2MHW7
Chlorine Taste and Odor, Particulates, Rust, Scale	5 micron	20 gpm	100,000 gal	1"	25"	4 1/2"	Yes	125 psi	100 °F	5621104	3M Aqua-Pure	49Y028
Chlorine Taste and Odor, Rust, Scale, Sediment	5 micron	8 gpm	—	3/4"	13 1/2"	4 5/8"	—	125 psi	100 °F	5529902	3M Aqua-Pure	3BU37
	5 micron	8 gpm	—	3/4"	14 9/16"	4 5/8"	—	125 psi	100 °F	5530002	3M Aqua-Pure	2P275
Chlorine Taste and Odor, Sediment	5 micron	1 gpm	5,000 gal	3/4"	12 1/4"	5 1/8"	Yes	125 psi	125 °F	150522-75	Pentair/Pentek	1ECP3
	25 micron	2 gpm	50,000 gal	1"	13 1/4"	7 1/4"	Yes	100 psi	100 °F	150518-75	Pentair/Pentek	1ECP2
Dirt, Rust, Scale, Sediment, Silt	5 micron	1.5 gpm	8,000 gal	3/4"	13"	5"	—	125 psi	100 °F	HF-360A	Culligan	29AH41
Particulates	5 micron	20 gpm	100,000 gal	1"	25 1/8"	4 1/2"	Yes	125 psi	100 °F	5621101	3M	2MHW6
Rust, Silt	20 micron	5 gpm	15,000 gal	3/4"	13 1/4"	5"	Yes	100 psi	100 °F	WF3P38001C	Dupont	25CA63
	20 micron	10 gpm	30,000 gal	1"	13 3/4"	7 1/8"	No	100 psi	100 °F	WFHD13001B	Dupont	25CA62
Scale	Not Rated	10 gpm	35,800 gal	3/4"	10 1/4"	2 3/4"	No	125 psi	100 °F	AP43011	3M Aqua-Pure	3P776
Sediment	5 micron	2 gpm	—	3/8"	7 3/8"	4 3/8"	Yes	125 psi	125 °F	158581-75	Pentair/Pentek	1ECP5



Under-Sink Drinking Water Filtration Systems

- Include filter, housing, & head

Under-sink filters install to a single water connection to reduce contaminants and improve water quality at the faucet.

Reduces	Micron Rating	Flow Rate	Service Life	Connec. Size	H	W	Includes Valve	Max. Pressure	Maximum Temperature	Mfr. Model	Brand	Item No.
Atrazine, Bacteria, Chlorine Taste and Odor, Cyst, Lead, Lindane, Turbidity, Viruses	1 micron	1 gpm	1,000 gal	1/4"	11 3/4"	12"	No	100 psi	100 °F	WFQT390005	Dupont	25CA76
Atrazine, Chloramine, Chlorine Taste and Odor, Cyst, Lead, Lindane, Mercury, Methyl Tertiary Butyl Ether (MTBE), Particulates, Sediment, Turbidity, Volatile Organic Compounds (VOCs)	0.5 micron	0.5 gpm	500 gal	1/4"	14"	3 3/4"	Yes	100 psi	100 °F	US-EZ-4	Culligan	29AH55
Atrazine, Chlorine Taste and Odor, Cyst, Lead, Lindane, Sediment	0.5 micron	0.6 gpm	750 gal	3/8"	12 1/4"	3 1/2"	Yes	100 psi	100 °F	F1000-B1B	Pentair	245DC3
Atrazine, Chlorine Taste and Odor, Cyst, Lead, Lindane, Sediment, Volatile Organic Compounds (VOCs)	0.5 micron	0.6 gpm	675 gal	3/8"	12 1/2"	8"	Yes	100 psi	100 °F	F2000-B2M	Pentair	245DC4
Bacteria, Chlorine Taste and Odor, Cyst, Lead, Sediment, Trihalomethanes (THM)	0.5 micron	0.6 gpm	675 gal	3/8"	12 1/2"	11 1/4"	Yes	100 psi	100 °F	F3000-B2M	Pentair	245DC5
Chlorine Taste and Odor	0.5 micron	0.5 gpm	480 gal	3/8"	19"	4 1/4"	No	125 psi	100 °F	EV927570-75	Pentair/Everpure	23MU14
Chlorine Taste and Odor, Cyst, Dirt, Lead, Methyl Tertiary Butyl Ether (MTBE), Rust, Volatile Organic Compounds (VOCs)	5 micron	1 gpm	1,000 gal	3/8"	12"	4"	Yes	125 psi	100 °F	US-600A	Culligan	29AH61
Chlorine Taste and Odor, Cyst, Lead	0.5 micron	0.6 gpm	625 gal	1/4"	15 3/4"	10 7/8"	No	125 psi	100 °F	5583101	3M Aqua-Pure	5PR95
Chlorine Taste and Odor, Cyst, Lead	0.2 micron	2.5 gpm	6,000 gal	3/8"	16"	4 1/2"	No	125 psi	100 °F	5616318	3M Aqua-Pure	35Z834
Chlorine Taste and Odor, Cyst, Lead, Mercury, Particulates, Volatile Organic Compounds (VOCs)	0.5 micron	0.8 gpm	750 gal	1/4"	12 5/8"	3"	Yes	120 psi	100 °F	40-99535	3M	56GW03
Chlorine Taste and Odor, Cyst, Particulates, Sediment	0.5 micron	2 gpm	2,000 gal	3/8"	15 1/8"	3 1/4"	Yes	125 psi	100 °F	5609223	3M Aqua-Pure	5REE6
Chlorine Taste and Odor, Dirt, Rust	5 micron	1.7 gpm	2,000 gal	3/8"	9 5/8"	4 5/8"	No	125 psi	100 °F	5528901	3M Aqua-Pure	2P075
Chlorine Taste and Odor, Sediment	3 micron	0.5 gpm	2,000 gal	1/4"	11 3/4"	3"	No	100 psi	100 °F	WFQT130005	Dupont	25CA78
Cyst, Lead, Sediment	0.5 micron	0.8 gpm	750 gal	1/4"	10 1/2"	3"	Yes	125 psi	100 °F	AP EASY LC COOLER	3M Aqua-Pure	1MZU8



Reverse Osmosis Quick Connect Water Filters



These filters use a multistage process including prefilters and semi-permeable membranes to filter water for drinking and appliances. Replacement is fast and easy without a filter wrench.

Reduces	Micron Rating	Flow Rate	Service Life	Overall Height	Filter Media	Item No.	Pkg. Qty.
3M Aqua-Pure Particulates	5 micron	0.6 gpm	2,500 gal	14 3/8"	3 1/4"	Carbon	5PT07 2
Dupont Cadmium, Cyst, Nitrate/Nitrite, Particulates, Arsenic, Selenium, Total Dissolved Solids (TDS), Chromium (Trivalent)	0.025 micron	2 gpm	3,000 gal	13"	3"	Carbon	25CA83 1
Chlorine Taste and Odor	1 micron	2 gpm	3,000 gal	13"	3"	Carbon	25CA81 1