



## Complete Appliance Water Filtration Systems

All systems and replacement cartridges are certified for use in potable water applications.

**Coldrink 2-MC<sup>2</sup> System, 6XWU0**—Improves the taste of fountain beverages and helps retain the beverage's carbonation. Micro-Pure II media helps inhibit bacteria growth. Protects beverage system seals, pump, tubing, and small orifices from abrasive wear, clogging, and corrosion.

**QL3-BH2 Coffee Filter, 6XWU1**—Provides premium quality filtered water for coffee and beverage applications. Reduces scale buildup and prevents lime scale from forming in brewers. Micro-Pure II media helps inhibit bacteria growth.

**Kleensteam II Single System, 5WFG5 & Twin System, 6XWU2**—Systems deliver high-quality filtered water for steam applications, and have scale inhibitors and deliming capabilities. Cartridge design is suitable for low- or high-flow capacity steamers. Improve the performance and help extend the life of steam equipment.

**Kleenware HTS-11 System, 5WFH4**—Inhibits mineral deposits and provides corrosion protection. Helps extend the life of food service equipment. Suitable for use in commercial glassware washers, dishwashers, and warewashing booster heaters.

**SR-X Scale Inhibitor Feeder and Deliming System, 5WFH3**—Provides scale reduction for steam applications as well as deliming capabilities. Include clear SR-X housing, SS-10 cartridge, dip tube assembly, and 2.2-lb. package of ScaleKleen for scale removal and deliming.

**E10 Coarse, 5WFH1 and 5WFH2**—Prefilter cartridges feature tightly spun media.

**Insurice Filtration Systems, 5WFG3 and 5WFG4**—Reduce problems in ice machines caused by scale buildup from dirt and dissolved minerals. 5WFG4 features a water shutoff, flushing valve, and outlet pressure gauge.

**Insurice Single PF-i2000, 6XWT9**—Filter system reduces scale buildup from dissolved minerals and dirt, and helps reduce clogging of distribution lines, evaporator plate, and pump. Micro-Pure II media help inhibit bacteria growth.

**QC71 Filter Head Assembly 5WFG6 and 5WFG8**—Include a built-in water shutoff valve, pressure gauge, and mounting hardware. Accept many Everpure specialty cartridges including cartridges for ice, coffee, espresso, and fountain beverage machines.

**ScaleKleen Scale Remover/Delimer, 5WFH0**—Can be fed into the water system without the use of hazardous chemicals or special piping.

### Replacement Filter Cartridges

- Max. pressure: 125 psi



**Ice Machine 6XWT9**



**Appliance Water Filter Head 5WFG6**

Micron Rating (micron)	Description	Reduces	Flow Rate (gpm)	Service Life (gal.)	Connec. Size	Includes Valve	Overall Height	W	Number of Cartridges Required	Max. Press. (psi)	Max. Temp.	Std.	Mfr. Model	Item No.
0.5	Coldrink 2-MC <sup>2</sup> System	Bacteria, Chlorine Taste and Odor, Cyst, Scale, Sediment	3.3	18,000	¾"	Yes	25½"	21½"	3	125	100 °F	NSF 42, NSF 53	EV932802-75	6XWU0
<b>Hot Water &amp; Steam Filtration Systems</b>														
0.5	QL3-BH2 Coffee Filter	Bacteria, Chlorine Taste and Odor, Cyst, Scale, Sediment	0.5	3,000	¼"	Yes	16½"	3¾"	1	125	100 °F	NSF 42, NSF 53	EV927200-75	6XWU1
5	KleenSteam II Single System	Chlorine Taste and Odor, Scale, Sediment	2.5	10,000	¾"	Yes	25½"	5"	2	125	100 °F	NSF 42	EV979721-75	5WFG5
5	Kleensteam II Twin System	Chlorine Taste and Odor, Scale, Sediment	5	20,000	¾"	Yes	25½"	20½"	3	125	100 °F	NSF 42	EV979722-75	6XWU2
—	Kleenware HTS-11 Scale Control Hot Water System	Scale	15	—	¾"	No	12½"	4¾"	1	200	200 °F	NSF 60	EV979911-75	5WFH4
—	SR-X Scale Inhibitor Feeder and Deliming System	Scale	6	—	¾"	No	12½"	5¼"	3	125	125 °F	NSF 42	EV979720-75	5WFH3
10	E10 10" Coarse Prefilter Cartridge	Sediment	4	9,000	¾"	No	12½"	5¼"	1	125	100 °F	NSF 42	EV979580-75	5WFH1
10	E10 20" Coarse Prefilter Cartridge	Sediment	8	9,000	¾"	No	22½"	5½"	1	125	100 °F	NSF 42	EV979590-75	5WFH2
<b>Ice Machine Filtration Systems</b>														
0.5	Insurice 2000 Single System	Bacteria, Chlorine Taste and Odor, Cyst, Scale, Sediment	1.7	9,000	¾"	Yes	26¼"	16½"	1	125	100 °F	NSF 42, NSF 53	EV932401-75	5WFG3
0.5	Insurice 2000 Twin System	Bacteria, Chlorine Taste and Odor, Cyst, Scale, Sediment	3.3	18,000	¾"	Yes	25¼"	20½"	2	125	100 °F	NSF 42, NSF 53	EV932402-75	5WFG4
0.5	Insurice Single PF-i2000	Bacteria, Chlorine Taste and Odor, Cyst, Scale, Sediment	1.7	9,000	¾"	Yes	28"	20"	2	125	100 °F	NSF 42, NSF 53	EV932421-75	6XWT9
<b>Appliance Water Filter Heads</b>														
<b>QC71 Single Filter Head</b>														
¾" in	FNPT	7 ½" in	5 ¼" in	NSF 42	125 psi	100 °F	EV927241-75	5WFG6						
<b>QC71 Twin Parallel Head</b>														
¾" in	MINPT	8 ½" in	5 ½" in	NSF 42	125 psi	1,000 °F	EV927222-75	5WFG8						
<b>Item Size Function For Use With Mfr. Model Item No.</b>														
<b>Scale Remover/Delimer</b>														
Scale Kleen	2 lb 3 oz	Reduces Scale	EV9797-20, Mfr. No. EV9797-21	EV979835-75	5WFH0									
Micron Rating (micron)	Description	Reduces	Flow Rate (gpm)	Service Life (gal.)	Overall Height	Dia.	Max. Temp.	For Use With		Std.	Mfr. Model	Item No.		
<b>Beverage Machine Water Filters</b>														
0.5	4C Replacement Cartridge	Cyst, Chlorine Taste and Odor	0.5	3,000	14¾"	3"	100 °F	Drinking Water Systems		NSF 42, NSF 53	EV960100-75	5WFF7		
0.5	AC Replacement Cartridge		0.5	750	10½"	3"	100 °F	Drinking Water Systems		NSF 42, NSF 53	EV960112-75	5WFF8		
0.5	MC2 Replacement Cartridge		1.7	9,000	21"	3"	100 °F	Filtration System		NSF 42, NSF 53	EV961255-75	5WFF9		
0.5	XC2 Replacement Cartridge		1.7	12,000	25¼"	3"	100 °F	Fountain Beverage Systems		NSF 42, NSF 53	EV961397-75	5WFF3		
1	EC01 10" Prefilter Cartridge	Sediment	10	—	9¾"	—	125 °F	Mfr. No. EV9795-80		NSF 42	25481-43-75	5WFH6		
10	EC110 10" Prefilter Cartridge		8	—	9¾"	—	80 °F	Mfr. No. EV9795-80		NSF 42	EV953440-75	5WFG1		
10	EC210 20" Prefilter Cartridge		8	—	20½"	—	80 °F	Plastic Prefilter System		NSF 42	EV953420-75	5WFG2		
<b>Hot Water &amp; Steam Filters</b>														
0.5	4H Replacement Cartridge	Cyst, Sediment	0.5	3,000	14½"	3¼"	100 °F	Filtration System		NSF 42, NSF 53	EV961100-75	53GK23		
0.5	BH2 Replacement Cartridge	Chlorine Taste and Odor, Scale	0.5	3,000	14¾"	3"	100 °F	Filtration System		NSF 42, NSF 53	EV961251-75	5WFF1		
0.5	MH2 Replacement Cartridge	Cyst, Chlorine Taste and Odor, Scale	1.7	9,000	21"	3"	100 °F	Coffee Filtration Systems		NSF 42, NSF 53	EV961326-75	5WFF4		
0.5	OC5 <sup>2</sup> Replacement Cartridge	Scale	0.5	1,500	3"	3"	100 °F	Coffee Equipment		NSF 42, NSF 53	EV961807-75	6TFD6		
5	4CB5 Replacement Cartridge	Scale	1.7	6,000	3"	3"	100 °F	Filtration System		NSF 42	EV961716-75	6TFD4		
5	4CB5S Replacement Cartridge	Scale	1.7	6,000	12¾"	3"	100 °F	Ice Filtration Systems		NSF 42	EV961726-75	6TFD5		
5	7CB5 Replacement Cartridge	Scale	2.5	10,000	21"	3"	100 °F	Steam Treatment Systems		NSF 42	EV961816-75	5WFF2		
5	Claris XL Replacement Cartridge	Chlorine Taste and Odor	1	1,900	18¾"	5¾"	86 °F	Filtration System		NSF 42	EV433913-75	34D334		
5	Claris XXL Replacement Cartridge	Chlorine Taste and Odor	1	3,490	18¾"	6¾"	86 °F	Filtration System		NSF 42	EV433914-75	34D335		
5	ES0 7 Replacement Cartridge	Chlorine Taste and Odor, Scale	0.5	9,000	21"	3"	100 °F	Filtration System		NSF 42, NSF 53	EV960725-75	5WFG7		
—	7S0 Replacement Cartridge	Scale	0.5	2,000	20¾"	3¼"	100 °F	Water Filtration Systems		—	EV960704-75	53GK22		
—	HT-10 Replacement Cartridge	Scale	15	60,000	9¾"	2½"	150 °F	Ware Washers		NSF 42	EV979922-75	5WFH5		
—	SS-10 Replacement Cartridge	Scale	2	—	10"	1¾"	150 °F	Steam Treatment Systems		NSF 42, NSF 53	EV979902-75	5WFG0		
<b>Ice Machine Water Filters</b>														
0.5	4S1 Replacement Cartridge	Scale	2	15,000	14½"	3¼"	100 °F	Filtration System		NSF 42, NSF 53	EV960651-75	32UL49		
0.5	7S1 Replacement Cartridge	Scale	3.5	25,000	20¾"	3"	100 °F	Filtration System		NSF 42, NSF 53	EV960601-75	32UL48		
0.5	I20002 Replacement Cartridge	Cyst, Chlorine Taste and Odor, Scale	1.7	9,000	21"	3"	100 °F	Ice Filtration Systems		NSF 42, NSF 53	EV961227-75	5WFF8		
0.5	I40002 Replacement Cartridge	Chlorine Taste and Odor, Scale	1.7	12,000	25¼"	3"	100 °F	Filtration System		NSF 42, NSF 53	EV961237-75	5WFF0		
0.5	OW200L Replacement Cartridge	Scale, Trihalomethanes (TTHM)	0.5	480	3.25"	3.25"	100 °F	Filtration System		NSF 42, NSF 53	EV961906-75	6TFD7		
0.5	SR-X Feeder, 6 gpm, 12 ½ inH, 5 ½ in Dia.	Scale	6	500	12½"	5¼"	100 °F	Steam Treatment Systems		NSF 42	EV979845-75	53GK34		
—	SS-IMF Replacement Cartridge	Scale	2	—	8½"	1¾"	150 °F	Combination Systems		NSF 42	EV979932-75	5WFF9		