



Pipe Thread Sealant Tape & Gasket-Making Tape

■ PTFE material

Anti-Seize Sealant Tape is made with copper-filled PTFE (polytetrafluorethylene) to provide extra lubrication for tightening and loosening pipe and fittings. Not intended for use on stainless steel pipe. **General Purpose Pipe Sealant Tape** is for applications that involve non-corrosive media. **Pipe Sealant Tape for**



Gas is for fuel or oxygen pipe lines. **Pipe Sealant Tape for Stainless Steel** is made from nickel-filled PTFE (polytetrafluorethylene), and is ideal when high corrosion resistance is required. **PTFE Gasket-Making Tape** are continuous rolls and can be cut to the length needed to replace a precut gasket on a flanged joint. Resist heat, chemicals, and friction.

For Max. Thread Diameter	Overall W x L	Max. Oper. Press. for Liquids	Max. Oper. Press. for Gases	Grade	Thick.	Item No.
Anti-Seize Sealant Tape, Copper -400° to 500°F						
1 1/2 in	1/2 in x 50 ft	2,250 psi	2,250 psi	High	0.0039	21TF38
General Purpose Pipe Sealant Tape, White -400° to 550°F						
1/4 in	1/2 in x 43 ft	10,000 psi	100 psi	Medium	0.0039	21TF28
1/2 in	1/2 in x 21 ft	10,000 psi	300 psi	Low	0.0031	21TF19
3/4 in	1/2 in x 21 ft	10,000 psi	2,000 psi	Medium	0.0039	21TF27
1 in	1/2 in x 21 ft	10,000 psi	2,250 psi	Extra-High	0.0039	21TF34
1 1/4 in	1/2 in x 43 ft	10,000 psi	300 psi	Low	0.0031	21TF20
1 1/2 in	1/2 in x 43 ft	10,000 psi	2,000 psi	High	0.0039	21TF25
1 3/4 in	1/2 in x 43 ft	10,000 psi	2,000 psi	Medium	0.0039	21TF29
2 in	1/2 in x 43 ft	10,000 psi	300 psi	Low	0.0031	21TF21
2 1/4 in	1/2 in x 43 ft	10,000 psi	2,000 psi	High	0.0039	21TF26
2 1/2 in	1/2 in x 43 ft	10,000 psi	2,000 psi	Medium	0.0039	21TF30
2 3/4 in	1/2 in x 43 ft	10,000 psi	2,250 psi	Extra-High	0.0039	21TF36
3 in	1 1/2 in x 43 ft	10,000 psi	2,250 psi	Extra-High	0.0039	21TF37
Pipe Sealant Tape for Gas Lines, Yellow -400° to 500°F						
1 1/2 in	1/2 in x 50 ft	2,250 psi	2,250 psi	Extra-High	0.0039	21TF42
-400° to 550°F						
3/4 in	1/2 in x 21 ft	300 psi	300 psi	Extra-High	0.0039	21TF22
1 in	1/2 in x 43 ft	10,000 psi	2,000 psi	Extra-High	0.0039	21TF23
Pipe Sealant Tape for Stainless Steel, Gray -400° to 500°F						
1/2 in	1/2 in x 50 ft	2,250 psi	2,250 psi	High	0.0039	21TF40
3/4 in	1/2 in x 50 ft	2,250 psi	2,250 psi	High	0.0039	21TF41
1 in	1/2 in x 21 ft	10,000 psi	2,000 psi	High	0.0039	21TF32
PTFE Gasket-Making Tape, White -450° to 600°F						
1 1/2 in	3/8 in x 25 ft	3,000 psi	3,000 psi	—	0.13	21TF48
-400° to 600°F						
1/4 in	1/4 in x 50 ft	3,000 psi	3,000 psi	—	0.11	21TF47
1/2 in	1/2 in x 15 ft	3,000 psi	3,000 psi	—	0.19	21TF49
3/4 in	1/2 in x 15 ft	3,000 psi	3,000 psi	—	0.27	21TF50

Ductile Iron Service Saddles



Single-Strap
3ET Y8



- Epoxy Iron saddle ■ Max. temp.: 180°F
- Buna-N gasket

Ductile iron is lighter and stronger than cast iron. Connect to new or existing pipe, to install air or vacuum valves, drain valves, or pitot tubes. Double-bale feature two U-bolts that wrap around for extra stability to the connection.

For Pipe Size	Outlet Connec.	For Outside Dia.	Single-Strap, SS* Bolt, Max. Oper. Press.: 200 psi	Double-Bale, Steel Bolt, Max. Oper. Press.: 300 psi
1"	3/4"-NPT	1 3/8" - 1 3/8"	3ET Y8	—
1 1/4" - 1 1/2"	1"-CC	1 5/8" - 1 29/32"	—	3EUA6
	3/4"-NPT	2 1/32" - 2 3/16"	3ET Z2	3EUA7
	1"-NPT	2 1/32" - 2 3/16"	—	3EUA8
2"	1"-CC	2 1/32" - 2 3/16"	5LGN2	3EUA9
	1 1/2"-NPT	2 3/32" - 3 1/32"	—	3EUC2
3"	3/4"-CC	2 3/32" - 3 1/32"	3ET Z6	3EUC3
3" - 4"	3/4"-NPT	4 1/32" - 4 1/16"	5LGN5	—
	1"-NPT	2 3/32" - 3 1/32"	3ET Z7	3EUC7
3"	1 1/2"-NPT	2 3/32" - 3 1/32"	—	3EUC4
	3/4"-NPT	4 1/32" - 4 1/16"	3EUA1	3EUC6
	1"-NPT	4 1/32" - 4 1/16"	3EUA2	—
4"	1"-CC	4 1/32" - 4 1/16"	5LGP0	3EUC8
	1 1/2"-NPT	4 1/32" - 4 1/16"	—	—
	2"-NPT	4 1/32" - 4 1/16"	3EUA5	3EUD1
	3/4"-NPT	5 15/16" - 6 29/32"	5LGP3	3EUD2
6"	1"-NPT	5 15/16" - 6 29/32"	5LGP5	—
	1"-CC	5 15/16" - 6 29/32"	5LGP6	—
	1 1/2"-NPT	5 15/16" - 6 29/32"	5LGP9	—
	2"-NPT	5 15/16" - 6 29/32"	5LGR1	—
8"	3/4"-NPT	7 1/16" - 9 1/16"	5LGR2	—
	1"-CC	7 1/16" - 9 1/16"	5LGR5	—
	2"-NPT	7 1/16" - 9 1/16"	5LGT0	—
10"	2"-IP	11 1/32" - 11 1/16"	5LGT9	—
12"	2"-NPT	12 3/4"	5LGT8	—

* Stainless Steel.

Plastic & Rubber Flexible Pipe Fittings

- Clamp material: 300 series stainless steel
- Max. operating pressure: 4.3 psi

Fittings connect pieces of pipe together, with or without a change in direction. They connect same or different sizes of pipes using worm clamps (use cordless screw-driver 5HXN0, sold on page 652), and may divert, divide, or return the flow of air, water, gasoline, and chemicals in the pipe.

Shielded Couplings—Create rigid pipe joints that resist shear forces and a stainless steel band resist degradation from ozone, sunlight, oxidation, sand, snow, and dust. Shield material is made of 300 series stainless steel.

Tap Saddle PVC—Fittings are shaped like a half moon to sit on top or around a sewer pipe for faster, less costly connections.

Specific Fitting Shape	For Nominal Pipe Size	Inside Diameter	Overall Length	Pipe Fitting Material	Number of Clamps Included	Item No.
PVC Flexible Pipe Fittings						
	Flexible 90° Elbow	1 1/2 in	1 1/2 in x 1 1/2 in	6 3/4 in	PVC	2 2ZJ97
		2 in	2 1/4 in x 2 1/4 in	7 3/4 in	PVC	2 2ZJ98
		3 in	3 3/8 in x 3 3/8 in	11 3/4 in	PVC	2 2ZJ99
		4 in	4 7/8 in x 4 7/8 in	14 3/4 in	PVC	2 2ZU10
		3/4 in	1 in x 1 1/2 in	2 3/4 in	PVC	2 2ZJ91
		1 in	1 1/4 in x 1 1/4 in	2 3/4 in	PVC	2 2ZJ92
		1 1/4 in	1 7/8 in x 1 7/8 in	2 3/4 in	PVC	2 2ZJ14
		1 1/2 in	1 3/4 in x 1 3/4 in	3 1/2 in	PVC	2 4P003
		1 3/4 in, -1-1/2 in	1 3/4 in x 1 3/4 in	3 1/2 in	PVC	2 4P004
		1 1/2 in	2 1/4 in x 1 1/2 in	3 1/2 in	PVC	2 4P005
	Flexible Coupling	1 1/2 in	2 1/4 in x 2 1/4 in	3 1/2 in	PVC	2 3HDC7
		2 in	2 3/4 in x 2 3/4 in	3 1/2 in	PVC	2 3HDC8
		2 in, -1-1/2 in	2 3/4 in x 2 3/4 in	3 1/2 in	PVC	2 4P006
		3 in	3 3/4 in x 3 3/4 in	4 in	PVC	2 4P007
		3 in	3 1/2 in x 3 1/2 in	3 15/16 in	PVC	2 4P009
		3 in	3 1/2 in x 3 1/2 in	4 in	PVC	2 2ZJ89
		3 in	3 1/2 in x 2 15/16 in	4 in	PVC	2 3HDC9
		4 in	4 1/2 in x 4 1/2 in	4 in	PVC	2 3HDD1
		5 in	5 1/2 in x 4 1/2 in	4 in	PVC	2 3HC23
		6 in	6 1/2 in x 6 1/2 in	5 3/4 in	PVC	2 3HC28
	Flexible Drain Trap	1 1/2 in, -1-7/16 in	1 7/8 in x 1 7/8 in	2 1/4 in	PVC	2 2ZU12
		1 1/4 in	1 3/8 in x 1 3/8 in	—	PVC	2 2ZU11
		1 1/4 in, -2 in	1 3/8 in x 2 3/8 in	2 3/4 in	PVC	2 2ZU13
		1 1/2 in, -3 in	3 3/8 in x 1 7/8 in	4 in	PVC	2 3HCY6
		1 1/2 in, -4 in	4 3/8 in x 1 7/8 in	4 in	PVC	2 3HCY7
		2 in, -6 in	6 3/8 in x 2 3/8 in	5 3/4 in	PVC	2 3HC24
		2 1/4 in, -2-3/8 in	3 3/8 in x 2 3/8 in	3 3/4 in	PVC	2 3HDC4
		3 in	3 15/16 in x 3 15/16 in	4 in	PVC	2 3HDC5
		3 in, -2 in	3 1/2 in x 2 3/8 in	4 in	PVC	2 4P008
		3 in, -4 in	4 3/8 in x 3 1/2 in	4 in	PVC	2 4P010
	Flexible Reducing Coupling	4 in	4 3/8 in x 4 3/8 in	3 15/16 in	PVC	2 2ZJ90
		4 in	4 1/8 in x 4 1/2 in	4 in	PVC	2 3HDC6
		4 in, -2 in	4 3/8 in x 2 3/8 in	4 in	PVC	2 3HCY8
		4 in, -5 in	5 3/8 in x 4 1/4 in	4 in	PVC	2 3HC22
		4 in, -6 in	6 3/8 in x 4 1/2 in	5 3/4 in	PVC	2 3HC26
		6 in	6 1/8 in x 6 1/2 in	5 3/4 in	PVC	2 3HDD2
		6 in, -3 in	6 3/8 in x 3 3/8 in	5 3/4 in	PVC	2 3HC25
		6 in, -8 in	8 1/2 in x 6 1/2 in	6 in	PVC	2 3HDA1
		8 in, -4 in	8 1/2 in x 4 3/8 in	6 in	PVC	2 3HC29
		8 in, -10 in	10 1/4 in x 8 3/8 in	6 in	PVC	2 3HDA3
	Flexible Tee	1 1/2 in	1 3/8 in x 1 1/2 in x 1 1/2 in	5 15/16 in	PVC	3 2ZJ93
		2 in	2 1/4 in x 2 1/4 in x 2 1/4 in	7 3/4 in	PVC	3 2ZJ94
		3 in	3 3/8 in x 3 3/8 in x 3 3/8 in	10 3/8 in	PVC	3 2ZJ95
		4 in	4 7/8 in x 4 7/8 in x 4 7/8 in	12 7/8 in	PVC	3 2ZJ96
		1 1/2 in	—	1 1/2 in	PVC	1 2ZU15
		2 in	—	1 1/2 in	PVC	1 2ZU16
		3 in	—	1 1/2 in	PVC	1 2ZU17
		4 in	—	1 1/2 in	PVC	1 2ZU18
		5 in	—	2 in	PVC	1 3HDA9
		6 in	—	2 in	PVC	1 3HDC1
Shielded Transition Couplings						
	No Hub Coupling	1 1/2 in	1 1/2 in x 1 1/2 in	2 1/2 in	Neoprene	2 2ZU19
		2 in	2 3/8 in x 2 3/8 in	2 1/2 in	Neoprene	2 2ZU20
		3 in	3 3/8 in x 3 3/8 in	2 1/2 in	Neoprene	2 2ZU21
		4 in	4 3/8 in x 4 3/8 in	2 1/2 in	Neoprene	2 2ZU22
		6 in	6 3/8 in x 5 1/2 in	3 in	Neoprene	2 3HDC2
		1 1/4 in, -1-1/2 in	1 1/4 in x 1 1/2 in	2 1/2 in	Neoprene	2 3HDE1
		1 1/2 in	1 1/2 in x 2 in	2 1/2 in	Neoprene	2 2ZJ87
		1 1/2 in	2 in x 1 1/2 in x 3 1/8 in	2 1/2 in	Neoprene	2 2ZJ83
		1 1/2 in, -2 in	2 3/4 in x 1 1/2 in	2 1/2 in	Neoprene	2 3HDE2
		2 in, -1-1/2 in	1 1/4 in x 1 1/2 in	2 1/2 in	Neoprene	2 3HDD4
	Shielded Transition Coupling	2 in	2 1/2 in x 2 1/2 in	2 1/2 in	Neoprene	2 2ZJ88
		2 in	2 5/8 in x 2 1/4 in	2 1/2 in	Neoprene	2 2ZJ84
		3 in	3 3/8 in x 3 1/8 in	2 1/2 in	Neoprene	2 3HDE3
		3 in	3 3/8 in x 3 3/8 in	2 1/2 in	Neoprene	2 2ZJ85
		4 in	4 3/8 in x 4 1/2 in	2 1/2 in	Neoprene	2 3HDE5
		4 in	4 3/8 in x 4 1/2 in	2 1/2 in	Neoprene	2 2ZJ86
		5 in, -3 in	5 1/2 in x 3 1/2 in	4 in	PVC	2 3HC21
		6 in	6 3/8 in x 6 1/4 in	3 in	Neoprene	2 3HDD7
		8 in	8 1/2 in x 8 3/8 in	3 15/16 in	Neoprene	2 3HDD8
Tap Saddle PVC Flexible Pipe Fittings						
	Flexible Tap Saddle Wye	4 in	4 1/2 in x 4 1/2 in	—	PVC	3 3HDF3
		6 in	6 3/8 in x 6 3/8 in	—	PVC	3 3HDF4