



Tower Lights, 40, 60, and 100mm Diameter

- IP54 polybutylene housing
- For outdoor or indoor use

Towers have up to 5 super-bright LEDs for optimum luminosity. Assembled and prewired. For long-distance indication of the operating states or sequences of a machine. 1 1/16" lights are primarily used in the food-processing and medical sectors. 2 3/8" lights are used in semiconductor factories or on conveyor belts. UL Listed, CSA and CE Certified.

Mode	Voltage	Mfr. Model	RED Item No.	RED, ORANGE Item No.	RED, ORANGE, GREEN Item No.	RED, ORANGE, GREEN, BLUE Item No.	RED, ORANGE, GREEN, BLUE, CLEAR Item No.
40mm Diameter, Base Mounting							
Steady	24V AC/DC	XVC4B	5FTK6	5FTK7	5FTK8	5FTK9	5FTL0
40mm Diameter, Support Tube Mounting							
Steady	24V AC/DC	XVC4B	5FTJ6	5FTJ7	5FTJ8	5FTJ9	5FTK0
Steady	100 to 240V AC	XVC4M	—	34D589	34D593	—	—
Steady, Flashing with Buzzer	24V AC/DC	XVC4B	5FTK1	5FTK2	5FTK3	5FTK4	5FTK5
Steady, Flashing with Buzzer	100 to 240V AC	XVC4M	34D594	—	34D604	—	—
60mm Diameter, Base Mounting							
Steady	24V AC/DC	XVC6B	—	—	5FTN5	—	5FTN7
Steady	100 to 240V AC	XVC6M	34D585	—	34D592	—	—
Steady, Flashing with Buzzer	24V AC/DC	XVC6B	5FTN8	5FTN9	5FTP0	5FTP1	5FTP2
Steady, Flashing with Buzzer	100 to 240V AC	XVC6M	34D590	—	34D601	—	34D613
60mm Diameter, Support Tube Mounting							
Steady	24V AC/DC	XVC6B	—	—	5FTL5	5FTL6	5FTL7
Steady	100 to 240V AC	XVC6M	34D588	—	34D597	34D603	—
Steady, Flashing with Buzzer	24V AC/DC	XVC6B	—	5FTL9	5FTN0	5FTN1	5FTN2
Steady, Flashing with Buzzer	100 to 240V AC	XVC6M	34D595	—	34D605	34D610	—
100mm Diameter, Base Mounting							
Steady, Flashing	100 to 240V AC	XVC1M	—	—	34D619	—	34D623
Description							
Accessories							Item No.
Die-Cast Mounting Base For Pole-Mount Style 40mm Tower Light							5FTL1
Die-Cast Mounting Base For Pole-Mount Style 60mm Tower Light							5FTP3
Stamped Metal Plate For Base-Mount Style 60mm Tower Light							5FTP4



Illuminated Beacons, 60 and 70mm Diameter



Highly visible 360° beacons provide instant communication within work groups and across factory floors, enabling factory personnel to monitor and control production quality in large automated areas. NEMA 1, 4X, 12, and IP65. For indoor use only. UL Listed, CE and CSA Certified.

Description	Voltage	Mfr. Model	RED Item No.	AMBER/ORANGE Item No.	YELLOW Item No.	GREEN Item No.	BLUE Item No.	CLEAR/WHITE Item No.
60mm Stackable Lens Units without Base or Cover								
Steady w/Lamp	24V AC/DC	XVUC2	30EF24	30EF25	—	30EF23	30EF26	30EF27
Flashing, Steady, Blinking, Rotating, w/Multi-Color Lamp	24V AC/DC	XVUC29	30EF28	30EF28	30EF28	30EF28	30EF28	30EF28
70mm Nonstackable Illuminated Beacons with Base								
Strobe w/Lamp	24V AC/DC	XVBL8B	6KX89	5GAD9	5GAE2	—	5GAE0	5GAE1
Strobe w/Lamp	120V AC	XVBL8G	6KX95	6KX62	6KX62	—	6KX96	6KX97
Steady w/o Lamp	250V AC/DC	XVBL3	6HM55	6HM56	6HM59	6HM54	6HM57	6HM58
Flashing w/o Lamp	24V AC/24 to 48V DC	XVBL4B	6KX77	6KX78	6KX81	6KX76	6KX79	—
Flashing w/o Lamp	48 to 230V AC	XVBL4M	—	—	6KX87	—	—	—
70mm Stackable Lens Units without Base or Cover								
Steady w/Lamp	240V AC	XVBC3	6HM32	6HM33	6HM36	6HM31	6HM34	6HM35
Flashing w/o Lamp	48V AC/DC	XVBC4B	6HM38	—	6HM42	6HM37	6HM40	—
Flashing w/o Lamp	240V AC	XVBC4M	6HM44	6HM45	—	—	6HM46	—
LED Lamps for 70mm Beacons								
Steady	24V AC/24V DC	DL1BDB	6HJ97	—	6HJ99	—	—	—
Steady	120V AC	DL1BDG	6HK03	—	6HK05	6HK02	6HK04	6HK01
Flashing	24V AC/24V DC	DL1BKB	—	—	—	—	—	3XB56

Description	Mfr. Model	Item No.
Audible Sounders		
60 mm, 24V AC/DC, 85 dB, Black	XVUC9S	30EF29
60 mm, 24V AC/DC, 85 dB, Silver	XVUC9SQ	30EF30
70mm, 12 to 48VAC/DC, 90 dB Nonadjustable	XVBC9B	6HM52
70mm, 120 to 230VAC, 70-90 dB Adjustable	XVBC9M	6HM53
60mm Accessories		
Body Extender, Black	XVUC020	30EF16
Tower Body, Black, 3 1/16" in H, 24VAC/DC	XVUC21B	30EF18
Tower Body, Silver, 3 1/16" in H, 24VAC/DC	XVUC21BQ	30EF19
Tower Body, Black, 5 5/16" in H, 100-240VAC, NPN	XVUC21M	30EF20
Tower Body, Black, 5 5/16" in H, 100-240VAC, PNP	XVUC21MP	30EF21
Mounting Plate, Black	XVUZ01	30EF31
Mounting Plate, Silver	XVUZ01Q	30EF32
Fixing Plate, Black	XVUZ02	30EF33

Description	Mfr. Model	Item No.			
Fixing Plate, Silver	XVUZ02Q	30EF34			
Adjustment Pole, Black	XVUZ05	30EF35			
70mm Accessories					
Side Entry for Cable Only	XVBC14	6HM29			
Rear Conduit Adapter	XVBC00	6HM23			
Stackable Base and Cover for Component Lenses	XVBC21	6HM30			
Beacon Support Base, 2 3/4"H, Black Aluminum	XVBZ02	1CNP2			
Incandescent Lamps for 50, 60, or 70mm, T6 Lamp Shape, LumaPro Brand					
Watts	12V ACVAC/DC Item No.	24V ACVAC/DC Item No.	48V ACVAC/DC Item No.	120V ACVAC/DC Item No.	230V ACVAC/DC Item No.
5W	—	4VCW7	—	—	—
7W	4VCX1	4VCW6	4VCW8	4VCW9	4VCX2
10W	4VCX6	4VCX3	4VCX4	4VCX5	4VCX7