



SENSORFLO®

SLOAN®

American Standard



KOHLER®

TOTO®



Sensor Single-Hole Deck-Mount Bathroom Faucets

Brand	Series	Faucet Body Material	Flow Rate	Flow Outlet Type	Power Source	Temperature Control	Spout Length	Spout Height	Mfr. Model	Item No.		
Straight-Spout												
American Standard	Moments Selectronic	Cast Brass	0.5 gpm	Laminar	Lithium Battery	No	5 in	5 in	2506155.002	41H809		
Kohler	Insight	Brass	0.5 gpm	Aerated	—	No	5 in	—	K-13461-CP	493J89 #		
		Brass	0.5 gpm	Aerated	—	No	5 in	—	K-13463-CP	493J90		
Sloan	Optima	Brass	0.5 gpm	Aerated	Battery	Yes	4 1/2 in	5 1/2 in	EA250-ISM	5YJP3 ‡		
		Brass	0.5 gpm	Aerated	Solar and Battery Powered	Yes	4 1/2 in	5 1/2 in	EA275-ISM	5YJP4		
Angled Straight-Spout												
Sloan	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EPX350.000.0000	23MF35		
		Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EPX650.000.0000	23MF42 *		
		Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EPX650.010.0000	23MF44		
		Cast Zinc	0.5 gpm	Laminar	Battery	No	5 1/2 in	6 1/2 in	EPX250.000.0000	23MF26		
		Cast Zinc	0.5 gpm	Laminar	Battery	Yes	4 in	5 in	EPX350.110.0000	23MF38		
		Cast Zinc	0.5 gpm	Laminar	Battery	Yes	6 1/2 in	10 in	EPX150.500.0000	23MF17		
		Cast Zinc	0.5 gpm	Laminar	Electronic	Yes	4 in	5 in	EPX300.500.0000	23MF34		
		Cast Zinc	0.5 gpm	Laminar	Self Sustaining	No	4 in	5 in	EPX380.010.0000	23MF41		
		Cast Zinc	0.5 gpm	Laminar	Self Sustaining	No	4 in	5 in	EPX680.010.0000	23MF47		
		Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	No	4 in	5 in	EPX375.000.0000	23MF40		
		Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	No	5 1/2 in	6 1/2 in	EPX275.000.0000	23MF27		
		Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	Yes	5 1/2 in	6 1/2 in	EPX277.500.0000	23MF31		
		Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EPX350.012.0000	23MF37		
		Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EPX650.002.0000	23MF43		
		Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EPX650.012.0000	23MF45 *		
		Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	No	5 1/2 in	6 1/2 in	EPX275.002.0000	23MF28		
		Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	Yes	5 1/2 in	6 1/2 in	EPX277.502.0000	23MF32		
		Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	Yes	6 1/2 in	10 in	EPX175.502.0000	23MF19		
		Gooseneck-Spout										
		American Standard	Selectronic	Cast Brass	0.35 gpm	Spray	Lithium Battery	No	2 in	7 in	6055164.002	41H846
Metal	0.5 gpm			Laminar	Lithium Battery	No	7 in	7 in	6055165.002	4THG5		
Chicago Faucets	HyTronic	Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	No	5 3/8 in	11 3/8 in	116.203.AB.1	5UTW6		
		Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	Yes	5 3/8 in	11 3/8 in	116.213.AB.1	5UTP3		
		Cast Brass	0.5 gpm	Laminar	AC Powered	Yes	5 1/4 in	11 3/8 in	116.429.AB.1	6XAE8		
		Cast Brass	0.5 gpm	Laminar	AC Powered	Yes	5 3/8 in	11 3/8 in	116.113.AB.1	5UTP1		
		Cast Brass	1.0 gpm	Laminar	6V Lithium CRP2	No	5 1/4 in	11 3/8 in	116.430.AB.1	6XAG4		
		Cast Brass	1.5 gpm	Laminar	12V AC Transformer	No	5 1/4 in	11 3/8 in	116.427.AB.1	21FD43		
		Cast Brass	1.5 gpm	Laminar	6V Lithium CRP2	Yes	5 1/4 in	11 3/8 in	116.432.AB.1	6XAG6		
		Brass	0.5 gpm	Aerated	—	No	6 3/8 in	—	K-13473-CP	493J96		
Kohler	Insight	Brass	0.5 gpm	Aerated	—	No	6 3/8 in	—	K-13473-CP	493J95 #		
		Brass	0.5 gpm	Spray	AC Powered	No	8 7/8 in	8 in	SF-9200	55MJ20		
Sensorflo	SENSORFLO®	Brass	0.5 gpm	Spray	Battery	No	8 7/8 in	8 in	SF-9100	55M.15		
		Brass	2.2 gpm	Laminar	6V DC Plug-In Power Converter	No	5 1/4 in	10 in	SF2200-4	5UVA2		
Sloan	—	Brass	2.2 gpm	Laminar	Battery	No	5 1/4 in	10 in	SF2250-4	5WHW9		
		Brass	2.2 gpm	Laminar	Plug-In	Yes	8 7/8 in	12 1/4 in	ETF-700-4-PLG-TEE-CP-2.2GPM-LAM-IR-S-FCT	491G82		
Zurn	AquaSense	Cast Brass	1.5 gpm	Laminar	Battery	Yes	5 3/8 in	12 in	Z6920-XL	30PT27		

* Integrated base body faucet. † Grid strainer. ‡ Drain with pop-up rod. # Includes (2) AAA batteries. ** Thermostatic mixing valve. †† SST mixing valve. †† Includes metal throat plate.



5UTW7



5YJR0



46CD94



468D23



SLOAN®

ZURN®

Gooseneck-Spout Sensor Single-Hole Wall-Mount Bathroom Faucets

Hands-free sensor eliminates the spread of germs and starts/stops water flow without touching faucet. Tall gooseneck-spout extends above counter and curves to point straight down into sink. Single wall-mount hole installation saves counter space. Chrome finish. ADA Compliant.

Brand	Series	Faucet Body Material	Flow Rate	Flow Outlet Type	Power Source	Spout Length	Spout Height	Mfr. Model	Item No.
Chicago Faucets	HyTronic	Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	5 3/8 in	12 in	116.204.AB.1	5UTW7
Sloan	Optima	Brass	2.2 gpm	Laminar	Electronic, Plug in Transformer	10 1/4 in	10 1/4 in	ETF500-P	5YJR0
Zurn	AquaSense	Brass	0.5 gpm	Laminar	Battery	6 1/2 in	12 in	Z6922-XL-F	46CD94
		Brass	1.5 gpm	Laminar	Sustainable/Hydropower	5 3/8 in	12 in	Z6922-XL-GEN	468D23