



Low-Arc-Spout
Chicago Faucets
26Y226



Straight-Spout
Chicago Faucets
26Y196



Straight-Spout
Dominion Faucets
45L026



Double-Joint-Spout
Chicago Faucets
26Y184

For information on faucet spout shapes, see page 2733.

Two-Hole Widespread Wall-Mount Kitchen Sink Faucets



DOMINION FAUCETS
 BY HESLER & CO. INC.

Faucets install into walls or vertical surfaces that have two centered holes that are 8" apart when measured from center-of-hole to center-of-hole. Wall-mount faucets save counter space in tight or busy kitchens. All faucets are aerated and include lever handles. Chrome finish.

Brand	Series	Faucet Body Material	Flow Rate	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
Low-Arc-Spout								
Chicago Faucets	445	Cast Brass	2.2 gpm	8 in	5 1/2 in	Yes	445-L8ABCP	26Y226
Straight-Spout								
Chicago Faucets	540	Cast Brass	2.2 gpm	12 in	5 in	Yes	540-LDL12ABCP	26Y196
Dominion Faucets	Silver	Brass	2.2 gpm	8 in	—	No	77-8600	45L026
Double-Joint-Spout								
Chicago Faucets	445	Cast Brass	2.2 gpm	13 in	4 1/2 in	Yes	445-DJ13ABCP	26Y250
Chicago Faucets	445	Cast Brass	2.2 gpm	18 in	4 1/2 in	Yes	445-DJ18ABCP	26Y184



Low-Arc-Spout
Chicago Faucets
26Y234



Low-Arc-Spout
American Standard
448N19



Low-Arc-Spout
Delta
4NLK3



Angled Straight-Spout
Kohler
493J33



Low-Arc-Spout
Moen
4NEH8



Straight-Spout
Moen
40D673



Gooseneck-Spout
Zurn
468D46



Three-Hole Widespread Deck-Mount Kitchen Sink Faucets

Faucets install into a sink, counter, or horizontal surface with three holes where the outermost holes are 8" apart when measured from center-of-hole to center-of-hole. All faucets are aerated and have a chrome finish. ADA Compliant.

Brand	Series	Faucet Body Material	Flow Rate	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
Low-Arc-Spout								
Dome Lever								
Chicago Faucets	1888	Cast Brass	2.2 gpm	9 1/2 in	6 3/4 in	1888-ABCP		26Y234
Joystick								
American Standard	Colony Pro	Cast Brass	1.5 gpm	8 1/2 in	4 29/32 in	7074000.002		448N19
Delta	NA	Brass	1.8 gpm	8 1/4 in	8 3/4 in	100-DST		4NLK3
Angled Straight-Spout								
Kohler	Coralais®	Metal	1.5 gpm	8 1/2 in	6 1/4 in	K-15171-F-CP		493J33
Low-Arc-Spout								
Moen	Chateau	Brass	1.5 gpm	9 1/4 in	6 1/4 in	7425		4NEH8
Moen	Chateau	Cast Metal	1.5 gpm	9 1/4 in	8 1/2 in	67425		40D685
Lever								
Chicago Faucets	201	Cast Brass	2.2 gpm	9 1/2 in	8 1/4 in	201-AABCP		6XAE9
Straight-Spout								
Wristblade								
American Standard	Monterrey	Cast Brass	1.5 gpm	7 3/4 in	7 3/4 in	6405170.002		24PR20
Moen	M-Bition	Cast Metal	1.5 gpm	8 3/4 in	12 1/2 in	8799		40D673
Gooseneck-Spout								
Lever								
Zurn	AquaSpec	Cast Brass	2.2 gpm	3 1/2 in	9 1/2 in	Z831A1-XL		468D46



Low-Arc-Spout
American Standard
448N21



Low-Arc-Spout
Chicago Faucets
29RR69



Low-Arc-Spout
Delta
4NLK4



Gooseneck-Spout
Trident
12U344



Four-Hole Widespread with Sprayer Deck-Mount Kitchen Sink Faucets

Faucets install onto kitchen sinks or counters and require three holes for the faucet unit with the outermost holes being 8" apart. A fourth hole is also required for the handheld sprayer. All faucets are aerated.

Brand	Series	Faucet Body Material	Flow Rate	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
Low-Arc-Spout								
Joystick								
American Standard	Colony Pro	Cast Brass	1.5 gpm	8 1/2 in	4 29/32 in	Yes	7074040.002	448N21
Chicago Faucets	430	Brass	1.5 gpm	9 in	6 in	Yes	432-ABCP	29RR69
Delta	Classic	Brass	1.8 gpm	8 1/4 in	8 3/4 in	Yes	400-DST	4NLK4
Gooseneck-Spout								
Lever								
Trident	—	Brass	1.8 gpm	8 5/8 in	10 3/8 in	Yes	12U344	12U344



Deck-Mount
T&S
5WMY2



Wall-Mount
Encore
20HK67



Wall-Mount
T&S
5WMX8



Gooseneck Pre-Rinse Faucets

Sprays water for dishwashing, food processing, and washdown applications. Gooseneck extends above counter and curves to point directly into sink basin. Install on deck or wall, into sinks, counters, or horizontal surfaces that have two centered holes that are 8" apart when measured from center-of-hole to center-of-hole. Chrome-plated finish with lever handles

Brand	Series	No. of Holes	Faucet Body Material	Flow Rate	Spout Length	H	Mfr. Model	Item No.
Deck-Mount								
T&S Brass								
—	1	Brass	1.42 gpm	12 in	40 1/2 in	B-2338		5WMY2
—	1	Brass	1.42 gpm	14 1/2 in	38 1/2 in	B-2250-B		5WMY1
—	1	Brass	1.42 gpm	14 1/2 in	42 1/2 in	B-0113-B		5WMX7
Wall-Mount								
Encore	KL53	3	Brass	1.6 gpm	16 1/2 in	35 in	KL53-1000 - BR	20HK67
T&S Brass	—	2	Brass	1.42 gpm	14 1/2 in	33 3/4 in	B-0133-B	5WMX8

* ADA Compliant.