

1-800-GRAINGER (472-4643)

Glass Filler, Bar Sink, Laundry and Eyewash Faucets

For information on faucet spout shapes, see page 2733.



Single-Hole Wall-Mount Glass Fillers

Glass fillers install into one hole on a vertical surface such as a wall. They provide a narrow stream of water for filling drinking glasses or water bottles. Straight-spout faucets extend straight out from the body of the faucet. Glass-activated push lever handles except 26Y282 is metering requiring users to push to start, shuts off automatically. Chrome finish.



Chicago Faucets 41N760



Metering Chicago Faucets 26Y282



T&S 2MCU2

Brand	Series	Faucet Handle Material	Faucet Body Material	Flow Rate	Flow Outlet Type	Spout Length	Spout Height	ADA Compliance	Mr. Model	Item No.
Chicago Faucets	312	Metal	Cast Brass	1 gpm	Laminar	4 3/8 in	1 1/2 in	Yes	312-ABCP	41N760
Chicago Faucets	324	Metal	Cast Brass	0.25 gpm	Laminar	4 in	1 1/2 in	Yes	324-665PSHABCP	26Y282
Chicago Faucets	712	Metal	Cast Brass	1 gpm	Aerated	4 in	9 3/8 in	No	712-ABCP	41N759
T&S Brass	—	Plastic	Brass	0.25-2.25 gpm	Aerated	4 1/8 in	4 3/8 in	Yes	B-1200	2MCU2

Gooseneck Bar Sink Faucets

Bar sink faucets are compact with a tall spout. Install on small sinks in tight areas where food is prepared or beverages are served, such as bars and restaurants. Feature metal faucet handles, aerated flow spouts, and chrome finish. **Single-Hole Faucets** install into one hole on a bar sink or counter. **Two-Hole Centerset Faucets** install onto sinks, counters, walls or other vertical or horizontal surfaces that have with two centered holes that are 4" apart when measured from center-of-hole to center-of-hole. **Three-Hole Widespread Faucets** install into a sink or counter with three holes where the outermost holes are 8" apart when measuring from center-of-hole to center-of-hole.



Single-Hole Chicago Faucets 48YD70



Two-Hole Deck-Mount Moen 6MPT6



Two-Hole Wall-Mount T&S 10C480



Two-Hole Off Center Delta 4NLK5



Three-Hole Moen 52JN02

Brand	Series	No. of Handles	Faucet Body Material	Flow Rate	Flow Outlet Type	Spout Length	Spout Height	ADA Compliance	Mr. Model	Item No.
Single Hole Deck-Mount Lever Handle										
Chicago Faucets	50	2	Cast Brass	1.5 gpm	Aerated	5 1/4 in	13 3/8 in	Yes	50-E35-XKABCP	48YD70
T&S Brass	—	2	Brass	8.67 gpm	Aerated	5 1/4 in	13 1/2 in	No	B-0300	4XKK7
Two-Hole Centerset Deck-Mount Wristblade Handle										
Moen	M-Bition	2	Cast Metal	1.2 gpm	Aerated	4 3/4 in	8 7/8 in	Yes	8948	6MPT6
Moen	M-Bition	2	Metal	1.5 gpm	Aerated	4 3/8 in	10 1/2 in	Yes	8938	4NEJ5
Two-Hole Centerset Wall-Mount Lever Handle										
T&S Brass	—	2	Brass	13.8 gpm	Laminar	10 3/8 in	6 3/4 in	Yes	B-0341	10C480
Two-Hole Off Center-Right Deck-Mount Joystick Handle										
Delta	Classic	1	Brass	1.5 gpm	Aerated	5 in	10 in	Yes	1903-DST	4NLK5
Three-Hole Widespread Deck-Mount Wristblade Handle										
Moen	M-Dura	2	Brass	1.5 gpm	Aerated	5 1/4 in	10 3/4 in	Yes	8248	52JN02
Moen	M-Dura	2	Brass	1.5 gpm	Aerated	8 in	13 1/4 in	Yes	8225smf15	46KK55
Moen	M-Dura	2	Brass	2.2 gpm	Aerated	8 in	13 1/4 in	Yes	8225	6MPT7

Two-Hole Laundry Sink Faucets

Faucets provide water for washing laundry and fabrics in commercial and residential laundry facilities. These chrome-finish faucets have a short low-arc-spout and two handles. **Centerset Faucets** install onto horizontal (deck-mount) or vertical (wall-mount) surfaces with two centered holes that are 4" apart when measured from center-of-hole to center-of-hole. **Widespread Faucets** install into walls or vertical surfaces that have two centered holes that are 8" apart when measured from center-of-hole to center-of-hole. ADA Compliant.



Deck-Mount American Standard 448N36



Deck-Mount T&S 5NRE9



Wall-Mount T&S 5NRF5



Wall-Mount Zurn 46CE16

Brand	Series	Faucet Handle Type	Faucet Body Material	Flow Rate	Mounting Type	Flow Outlet Type	Spout Length	Spout Height	Mr. Model	Item No.
Centerset Deck-Mount										
American Standard	7074	Lever	Cast Brass	1.5 gpm	Deck	Laminar	7 1/2 in	4 3/8 in	7074240.002	448N36
—	—	Lever	Brass	2.2 gpm	Deck	Aerated	6 in	—	B-1120	5NRE8
—	—	Lever	Brass	2.2 gpm	Deck	Aerated	6 in	6 1/8 in	B-1110	5NRE9
—	—	Lever	Brass	2.2 gpm	Deck	Aerated	8 in	6 3/4 in	B-1121	4XKJ9
T&S Brass	—	Lever	Brass	18.39 gpm	Deck	Aerated	12 in	10 in	B-0221	4XKK5
—	—	Lever	Brass	18.39 gpm	Deck	Aerated	18 in	12 in	B-0220	4XKK6
—	—	Lever	Brass	23.09 gpm	Deck	Aerated	6 in	8 in	B-0222	4XKK4
Centerset Wall-Mount										
T&S Brass	—	Lever	Brass	2.2 gpm	Wall	Aerated	6 in	5 1/8 in	B-1115	5NRF5
—	Big-Flo	Cross	Brass	44.27 gpm	Wall	Aerated	12 in	8 1/8 in	B-0290	5NRF2
Widespread Wall-Mount										
T&S Brass	—	Lever	Brass	2.2 gpm	Wall	Aerated	6 in	—	B-0230-01	5NRF1
—	—	Lever	Cast Brass	23.09 gpm	Wall	Aerated	12 in	7 1/2 in	B-0231	5NRF0
Zurn	AquaSpec	Lever	Brass	0.5 gpm	Wall	Aerated	9 1/2 in	6 3/4 in	Z843J1-XL-3F	46CE16

Service Sink Faucet with Eyewash **SPEAKMAN**

Eyewash (2WLL7) is attached directly to faucet's cold water integral stop port. Faucet and eyewash can operate independently. Includes eyewash, drench hose with twin plastic spray heads, and wall-mount bracket. Chrome finish.



2WLL7



3HEP9

Series	Flow Rate	Faucet Spout Shape	Connection	No. of Holes	Mounting Hole Center to Center	Spout Length	Mr. Model	Item No.
Service Sink Faucet with Eyewash								
Eyesaver	2.66 gpm	Straight	1/2 in FNPT	2	8 in	9 in	SEF-9000	2WLL7
Accessories								
Eyewash Spray Head Assembly (SEF1800's)							RPG38-0388	4NGX7
Flip Top Dust Covers							RPG07-0104	3HER1
Sprayhead Assembly (SEF-490/495)							RPG38-0390	3HEP9
Seal Replacement Kit for SEF-1800							RPG49-0003	4NGX4

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**