



For information on faucet spout shapes, see page 2733.



**Low-Arc-Spout**  
2LYP9



**Straight-Spout**  
2LYJ3

## Single-Hole Wall-Mount Inside Sill Faucets



Faucets install at about windowsill height on the inside of a building. Hoses can be attached for wash-down applications. Cast-brass body with chrome finish, laminar flow outlet, and one blade handle.

Brand	Water Inlet Connection Size	Faucet Handle Material	Flow Rate	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
<b>Low-Arc-Spout</b>								
Chicago Faucets	1/2 in	Metal	7.0 gpm	2 3/4 in	4 in	No	952-12CP	2LYP9
	3/4 in	Metal	7.0 gpm	2 3/4 in	4 in	No	952-CP	2P955
<b>Straight-Spout</b>								
Chicago Faucets	1/2 in	Metal	7.0 gpm	1 1/2 in	—	No	293-CP	5E963
	1/2 in	Metal	7.0 gpm	1 1/2 in	—	Yes	293-RCF	2LYJ3
	3/4 in	Metal	7.0 gpm	1 1/2 in	—	No	387-CP	2LYJ8



26Y299



6XAE5

## Water Supply Stops and Pedals



Water supply stops shut off water supply to faucets, toilets, etc. Foot pedals allow hands-free faucet operation. Tempering valve controls water flow, pressure, and temperature from a faucet spout.

Description	Conn. (in.)	Mfr. Model	Item No.
<b>Water Supply Stops</b>			
Straight Stop Fitting	1/2 in FNPT	45-ABCP	26Y299
Straight Stop Loose Key Fitting	1/2 in FNPT	45-LKABCP	26Y284
Multi-Turn Supply Stop	1/2 in FNPT	442-LKABCP	5UTU1
Angle Stop Fitting Loose Key	1/2 in FNPT / 3/4 in Compression	1013-ABCP	6XAE5
Angle Stop Fitting w/Supply Tube	1/2 in FNPT / 3/4 in Compression	1017-ABCP	6XAE6
Angle Stop Fitting w/Supply Tube	1/2 in FNPT / 1/2 in Compression	1006-ABCP	6XAE4
<b>Faucet</b>			
6 1/2 in L Rigid/Swing Gooseneck Spout, 1.5 gpm, Deck Mount	1/2 in NPSM	626-FCABCP	6XAF3
<b>Foot Pedals</b>			
Foot Pedal, Single	1/2 in FNPT	628-ABCP	5UTU7
Foot Pedal, Double	1/2 in FNPT / 3/4 in FNPT	625-ABCP	5UTU6
Knee-Activated Valve Assembly	1/2 in FNPT / 3/4 in FNPT	745-VOABCP	26Y204
Combination Pedal Box	1/2 in FNPT / 3/4 in FNPT	834-EPABCP	26Y246
<b>Tempering Valve</b>			
Tempering Valve, 3/4 in Compression	3/4 in Compression	131-ABNF	6XAH7



5UTU7



26Y204

## Faucet Sprayer Pre-Rinse Hose Reels



Pull hose out to desired length and it stays in position; reel automatically retracts with a slight tug. With 3/4 in FNPT inlet, heat-resistant handle, and adjustable hose bumper. FNPT connection.



6MT85



10C483

Reel Length	Flow Rate	Includes	Mfr. Model	Item No.
15 ft	3.7 gpm	Ceiling or Under Counter Mounting, Heatresistant Handle and Adjustable Hose Bumper, Multifit Bracket for Wall	B-7212-01	6MT85
30 ft	4.28 gpm	Spray Valve	B-7222-C01	10C483
35 ft	3.89 gpm	Heat Resistant Handle and Adjustable Hose Bumper, Hose, Multifit Bracket	B-7232-01	6MT84



**Fixed & Handheld Showerhead**  
22LU06



**Fixed Showerhead**  
22MN5



**Exposed Showerhead**  
4NGW9



## Shower Faucets

1/2 in connection

Faucets include fixed and/or handheld showerheads, attachment hardware, faucet control handles, and matching trim. Components are interchangeable without altering the behind-the-wall plumbing. All showerheads are single function, except 22LU07, which is dual function. For a complete list of standards, go to Grainger.com and search for individual products.

**American Standard**—One-piece cartridge simplifies installation and maintenance.

**Bradley**—Adjustable showerhead for a 25° to 30° spray angle.

**Moen**—Install 4ZF99 with Posi-Temp Pressure Balancing Control Valve to maintain water temperature control in the shower. 52RR02 has an adjustable temperature limit stop.

**Powers**—Thermostatic valves respond almost instantly to dramatic pressure changes. Self-contained cartridge simplifies maintenance and repair.

**Speakman**—Have chrome-plated, 4-arm handles with color-coded indexes. Reversible valve body and 1/4-turn ceramic cartridges. Galvanized gooseneck with support strap.

**Zurn**—Feature two service stops/check stops and adjustable limit stop.

Brand	Series	Fixed Showerhead Flow Rate	Connec. Type	Trim Finish	Showerhead Material	Showerhead Spray Pattern	Showerhead Shape	No. of Handles	Faucet Handle Type	ADA Compliance	Mfr. Model	Item No.
<b>Shower Faucets With Fixed Showerheads</b>												
Bradley	SafeCare	2 gpm	NPT	Chrome	Brass	Regular	Trumpet	1	Knob	No	S77-952	23MU63
Moen	Chateau	2.5 gpm	CC	Chrome	Brass	Regular	Bulb	1	Lever	Yes	L2352	4ZF99
Powers	Biltmore 900	4.6 gpm	IPS	Chrome	—	Regular	Trumpet	1	Lever	Yes	P910GK1	22MN5
<b>Shower Faucets With Fixed &amp; Handheld Showerheads</b>												
Amer. Std.	Commercial	1.5 gpm	FNPT	Polished-Chrome	Metal, Plastic	Regular	Bulb	1	Lever	Yes	TU662213.002	55DM42
Amer. Std.	Commercial	2.5 gpm	FNPT	Polished-Chrome	Metal, Plastic	Regular	Bulb	1	Lever	Yes	TU662223.002	55DM44
Moen	Commercial	1.5 gpm	NPT	Chrome	Brass, Stainless Steel	Regular	Flat Circle	1	Lever	Yes	8342EP15	52RR02
Powers	Biltmore 900	2.5 gpm	NPT	Chrome	Brass	Regular	Trumpet	1	Lever	Yes	P910GK1-5YW	22MN6
Zurn	Temp Gard III Z7300	2.5 gpm	FNPT	Polished-Chrome	Ceramic, Metal, Stainless Steel	Regular	Bulb	1	Lever	Yes	Z7300-SS-MT-HW	22LU06
Zurn	Temp Gard III Z7301	2.5 gpm	FNPT	Polished-Chrome	Ceramic, Metal, Plastic, Stainless Steel	Regular	Bulb	1	Lever	Yes	Z7301-SS-MT-DV-2P-HW	22LU07
<b>Exposed Shower Faucets With Fixed Showerheads</b>												
Speakman	Commander	2 gpm	NPT	Chrome	Plastic	Jet	Bulb	2	Cross	No	SC-1220-AF	4NGW9
Speakman	Sentinel Mark II	2 gpm	NPT	Chrome	Plastic	Jet	Bulb	1	Lever	Yes	S-1496-AF	34D882
Speakman	Sentinel Mark II	2.5 gpm	NPT	Polished-Chrome	Plastic	Jet	Bulb	1	Lever	No	S-1495-AF	455D36