

CONTINUED

Metal Cam and Groove Fittings

Coupling Size		Max. Working Pressure @ 70°F	316 Stainless Steel Item No.	Aluminum Item No.	Coupling Size		Max. Working Pressure @ 70°F	316 Stainless Steel Item No.	Aluminum Item No.
Type DC Includes Locking Arm					Type DL Includes Locking Arm				
1/2"	150 psi	55MW13	55MV51		2"	250 psi	26W686	26W683	
3/4"	250 psi	55MW14	55MV52		3"	125 psi	26W687	26W684	
1 1/4"	250 psi	55MW15	55MV53		4"	100 psi	26W688	26W685	
2 1/2"	150 psi	55MW16	55MV54		No Locking Arm				
4"	100 psi	55MW17	—		1"	250 psi	55MF83	—	
5"	75 psi	55MW18	55MV55		1 1/2"	250 psi	55MF87	—	
6"	75 psi	55MW19	55MV56		6"	75 psi	55MG16	—	
Type DD Includes Locking Arm					Type DP No Locking Arm				
2" x 3"	125 psi	26W675	26W670		1/2"	150 psi	55MV66	55MV07	
2"	250 psi	26W674	26W669		3/4"	250 psi	55MV67	55MV08	
3" x 4"	100 psi	—	26W672		1 1/4"	250 psi	55MV68	55MV09	
3"	125 psi	26W676	26W671		2 1/2"	150 psi	55MV69	55MV10	
4"	100 psi	—	26W673		4"	100 psi	55MV70	—	
No Locking Arm					5"	75 psi	55MV71	55MV11	
1 1/2"	250 psi	55MF86	—		6"	75 psi	55MV72	55MV12	
Coupling Size		Hose Fitting Size	Max. Working Pressure @ 70°F	316 Stainless Steel Item No.	316 Stainless Steel Item No.	Aluminum Item No.	Forged Brass Item No.		
Type C Includes Locking Arm									
1/2"	1/2"	150 psi	—	55MV96	55MV36	55MH40	—		
3/4"	3/4"	250 psi	—	55MV97	55MV37	—	—		
1"	1"	250 psi	—	3LW97	3LW96	5CGC9	—		
1"	1"	250 psi	—	—	55MG21	—	—		
1 1/4"	1 1/4"	250 psi	—	55MV98	55MV38	55MG47	—		
1 1/2"	1 1/2"	250 psi	—	3LX14	3LX13	5CGD7	—		
1 1/2"	1 1/2"	250 psi	—	—	4YGC5	—	—		
2"	1 1/2"	250 psi	—	—	55MV39	—	—		
2"	2"	250 psi	—	3LX31	3LX30	5CGE5	—		
2 1/2"	2 1/2"	150 psi	—	55MV99	55MV40	55MG96	—		
3"	2"	125 psi	—	55MW01	55MV41	—	—		
3"	3"	125 psi	—	3LX47	3LX46	5CGF3	—		
3"	3"	250 psi	—	—	4YGC7	—	—		
4"	3"	100 psi	—	55MW02	55MV42	—	—		
4"	4"	100 psi	—	55MW03	3LX63	5CGG1	—		
4"	4"	250 psi	—	—	4YGC8	—	—		
5"	5"	75 psi	—	55MW04	55MV43	55MH22	—		
6"	6"	75 psi	—	55MW05	55MV44	—	—		
No Locking Arm									
1/2"	1/2"	150 psi	743P33	—	—	—	—		
3/4"	3/4"	150 psi	743P34	—	—	—	—		
1"	1"	250 psi	743P35	—	—	—	—		
1 1/4"	1 1/4"	250 psi	55EF45	—	—	—	—		
1 1/2"	1 1/2"	250 psi	—	55MF90	—	—	—		
1 1/2"	1 1/2"	250 psi	743P36	—	—	—	—		
2"	2"	250 psi	743P37	—	—	—	—		
2 1/2"	2 1/2"	225 psi	55EF46	—	—	—	—		
3"	2 1/2"	125 psi	—	55MG09	—	—	—		
3"	3"	200 psi	743P38	—	—	—	—		
3"	3"	100 psi	—	—	55MG10	—	—		
4"	3"	100 psi	—	—	—	—	—		
4"	4"	100 psi	743P39	—	—	—	—		
5"	5"	75 psi	55EF47	—	—	—	—		
6"	6"	75 psi	55EF48	—	—	—	—		
Type E No Locking Arm									
1/2"	1/2"	150 psi	743P47	55MV73	55MV13	55MH52	—		
3/4"	3/4"	150 psi	743P48	—	—	—	—		
3/4"	3/4"	250 psi	—	55MV74	55MV14	55MH75	—		
1"	1"	250 psi	743P49	3LX06	3LX05	5CGD3	—		
1 1/4"	1 1/4"	250 psi	55EF53	55MV75	55MV15	55MG81	—		
1 1/2"	1 1/2"	250 psi	—	55MF93	—	—	—		
1 1/2"	1 1/2"	250 psi	743P50	3LX22	3LX21	5CGE1	—		
2"	1 1/2"	250 psi	—	55MF99	55MV16	—	—		
2"	2"	250 psi	743P51	3LX39	3LX38	5CGE9	—		
2 1/2"	2 1/2"	150 psi	—	55MV76	55MV17	55MH07	—		
2 1/2"	2 1/2"	225 psi	55EF54	—	—	—	—		
3"	2"	125 psi	—	55MV77	55MV18	—	—		
3"	3"	125 psi	—	3LX55	3LX54	5CGF7	—		
3"	3"	200 psi	743P52	—	—	—	—		
4"	3"	100 psi	—	55MV78	55MV19	—	—		
4"	3"	125 psi	—	—	55MH16	—	—		
4"	4"	100 psi	743P53	55MV79	3LX71	5CGG5	—		
5"	5"	75 psi	55EF55	55MV80	55MV20	55MH30	—		
6"	6"	75 psi	55EF56	55MV81	55MV21	—	—		
Coupling Size		Max. Working Pressure @ 70°F	316 Stainless Steel Item No.	Aluminum Item No.	Coupling Size		Max. Working Pressure @ 70°F	316 Stainless Steel Item No.	Aluminum Item No.
Type DC, Dust Cap Includes Locking Arm									
1"	250 psi	3LX02	250 psi	3LX01					
1 1/2"	250 psi	3LX18	250 psi	3LX17					
2"	250 psi	3LX35	250 psi	3LX34					
3"	125 psi	3LX51	125 psi	3LX50					
3"	—	—	250 psi	4YKW7					
4"	—	—	100 psi	3LX67					
4"	—	—	250 psi	4YKW8					
Type DP, Dust Plug No Locking Arm									
1"	250 psi	3LX04	250 psi	3LX03					
1 1/2"	250 psi	3LX20	250 psi	3LX19					
2"	250 psi	3LX37	250 psi	3LX36					
3"	125 psi	3LX53	125 psi	3LX52					
4"	—	—	100 psi	3LX69					



41H428



Cam and Groove Gaskets

■ Pkg qty. 1, except Nitrile Black Gaskets are 10

Flat cam and groove gaskets fit in the grooves of the female camlock or cam and groove couplings. The pressure of the fitting pushes against the gasket to create a tight seal.

For Coupling Size	Inside Dia.	Outside Dia.	Gasket Type	Thickness	Color	Code Stripe	Brand	Item No.
EPDM, Black								
3/4"	7/8"	1 3/8"	Flat	0.2"	1 White	Banjo	1MJV4	
1", -1-1/4"	1 1/8"	1 3/8"	Flat	0.3"	1 White	Banjo	1DPK5	
1 1/2"	1 5/8"	2 3/8"	Flat	0.25"	1 White	Banjo	1DPN2	
2"	2"	2 5/8"	Flat	0.3"	1 White	Banjo	1MJR8	
2 1/2"	2 3/8"	2 1/2"	Flange	0.65"	1 Green, 1 Red	Anvil	46KK81	
3"	3 1/4"	3"	Flange	0.65"	1 Green, 1 Red	Anvil	46KK82	
3"	3"	3 23/32"	Flat	0.3"	1 White	Banjo	1MJT8	
4"	4 3/8"	4"	Flange	0.66"	1 Green, 1 Red	Anvil	46KK83	
5"	5 1/4"	5"	Flange	0.66"	1 Green, 1 Red	Anvil	46KK84	
5"	5"	5"	Roughneck	1.92"	1 Green	Anvil	46KK76	
6"	6 3/8"	6"	Flange	0.66"	1 Green, 1 Red	Anvil	46KK85	
6"	6 1/8"	6"	Roughneck	1.92"	1 Green	Anvil	46KK77	
8"	8 3/8"	8"	Flange	0.79"	1 Green, 1 Red	Anvil	46KK86	
FKM, Green								
3/4"	7/8"	1 3/8"	Flat	0.22"	None	—	—	41H424
1"	1 1/8"	1 3/8"	Flat	0.25"	None	—	—	41H425
1 1/2"	1 5/8"	2 3/8"	Flat	0.25"	None	—	—	41H426
2"	2"	2 5/8"	Flat	0.25"	None	—	—	41H427
3"	3"	3 3/4"	Flat	0.25"	None	—	—	41H428
4"	4"	4 3/8"	Flat	0.25"	None	—	—	41H429
Food-Grade Nitrile, White								
3"	3"	3 3/4"	Flat	0.25"	None	—	—	41H433
Nitrile, Black								
1"	1 1/8"	1 3/8"	Flat	0.25"	1 Blue	—	—	41H419
1 1/2"	1 5/8"	2 3/8"	Flat	0.25"	1 Blue	—	—	41H420
2"	2"	2 5/8"	Flat	0.25"	1 Blue	—	—	41H421
3"	3"	3 3/4"	Flat	0.25"	1 Blue	—	—	41H422
4"	4"	4 3/8"	Flat	0.25"	1 Blue	—	—	41H423



Hydrant Wrenches

For use in lawn care, in-plant maintenance, and municipal hydrant applications.

Item	Fits	L	Head Material	Handle Material	Brand	Item No.
	1 1/2 in to 3 in Nut	16 3/8 in	Iron	Iron	—	6AKC0
	2 1/2 in Pin Lug Couplings, 2 1/2 to 5 in Rocker Lug Couplings, Up to 1 3/4 in Pentagon Nut, 1 1/2 in Square Nut	16 1/8 in	Cast Iron	Stainless Steel	Elkhart	15Z087
Adjustable Hydrant Wrench	3/4 to 6 in Nuts and Pin, Rocker or Navy Slot Lugs 1/4 to 1/2 in	19 in	Painted Steel	Plated Steel	Moon	6ANU9
	All Sizes of Pentagon or Square Hydrant nuts. Spanner Hook Fits Pin, Rocker or Navy Slot Lugs 1/4 to 1/2 in	18 in	Steel	Iron	Moon	3LX25
	Less than 1 3/4 in Pentagon Nut	17 5/8 in	Plated Steel	Plated Steel	Moon	20JP20
Adjustable Storz Hydrant Wrench	All Sizes of Square and Pentagon Hydrant Nuts, Storz Hook Fits 4, 5 and 6 in Pin and Rocker Lug Fittings, Spanner Hook Fits Pin, Rocker or Navy Slot Lugs 1/4 to 1/2 in	18 in	Painted Steel	Plated Steel	Moon	6ANV0
Five Hole Hydrant Wrench	All Common Hydrant Nuts	14 1/4 in	Plated Iron	Plated Iron	Dixon	6CLV4
Pigtail Adjustable Hydrant Wrench	Less Than 1 1/2 in Nut, 1 1/2 to 6 in Rocker Lugs, 2 to 4 1/2 in Pin Lug, 1 1/2 in Square Nuts	16 1/4 in	Plated Iron	Plated Steel	Dixon	6CLV2