CONTINUED

NIBCO

Cast Copper and Bronze Fittings

Description	Tube Fitting Mat.	Pipe Fitting Conn.	Tube Size		Outside Dia.	Max. Press. (psi @ °F) Bran	Item d No.
Flange		0	4 1-		41/:-	105 @ 100 N:L-	- 4000 115
1		C x Flange C x Flange	1 in 11/4 in	_	1½ in 1¾ in	105 @ 100 Nibo	
O		C v Elanga	1½ in	=	15% in	100 @ 100 Nibo	
	Cast Copper	C x Flange	2 in	=	21/8 in	100 @ 100 Nibo	
		C x Flange	2½ in		25% in	100 @ 100 Nibo	
-		C x Flange	3 in	_	31/8 in	95 @ 100 Nibo	o 1WLH7
Flush Adapt	er						
0		C x MNPT	½ in	½ in	5% in	722 @ 100 —	24W566
Hose Adapte	er						
	Cast Bronze	C x Hose	½ in	_	5⁄8 in x 1⁄2 in	577 @200 Nibo	o 36N491
Hy-Set Hang	er						
-	Cast Bronze	С	½ in	_	_	577 @200 Nibo	o 36N525
		С	¾ in	_	_	466 @200 Nibo	o 36N526
Reducing A	lapter						
	Cast Bronze		½ in		% in x % in	577 @200 Nibo	
Company of the last		FTG x FNPT	3∕4 in	½ in	% in x % in	466 @200 Nibo	o 36N488
		C x FNPT	11/4 in	3/4 in	1% in x % in	351 @200 Nibo	o 36N486
Reducing Te	e (run x run						
Alle	_	CxCxFNPT				577 @200 Nibo	
The state of the s		CxCxFNPT				466 @200 Nibo	
		C x FNPT x C				466 @200 Nibo	
		C x C x FNPT		1/2 IN		582 @ 100 —	
		C x FNPT x C C x C x FNPT		1/2 III	11% in x 5% in x 11% in 13% in x 13% in x 7% in	395 @200 NIDO	0 36N515
					11/8 in x 7/8 in x 11/8 in		
					11/8 in x 11/8 in x 3/4 in		
					1% in x 1% in x ½ in		
					1% in x 1% in x ¾ in		
					1% in x 1% in x % in		

Description Reducing W	Tube Fitting Mat. ve	Pipe Fitting Conn.	Tube Size		Outside Dia.	Max. Press. (psi @ °F) E	Brand	Item No.
30	Cast Bronze	CxCxC	2 in x 2 in x 1 ½ in		2½ in x 2½ in x 1½ in	395 @200 N	Nibco	36N549
Special Drop	Adapter							
of Car	Cast Bronze-	C x FNPT	½ in	½ in	5⁄8 in	577 @200 N		
Tee		C x FNPT	3/4 in	3/4 in	7⁄8 in	466 @200 N	Vibco	36N490
Tube Nut	Cast Bronze C Cast Copper C Cast Bronze C Cast Copper C	X C x FNPT X FNPT x C	½ in ¾ in	½ in ½ in ¾ in ¾ in	5% in 5% x 5% in 7% in 7% in	577 @200 M 722 @ 100 466 @200 M 582 @ 100 M	Vibco	24W589 36N521
	Cast Bronze		_	1 in	_	175 N	Nibco	36N483
Union		C x C	1/4 in		3/8 in	912 @ 100 N	liboo	11/// 10
000	Cast Copper	C X C C X C C X MNPT C X MNPT C X MNPT C X MNPT C X C X C X C X C X C X C X C X C X C	% in ½ in ½ in ½ in ½ in ½ in ½ in ¾ in ¾ in 1 in 1 in 1 in 1 ¼ in 1 ½ in 2 in 2 in 2 ½ in 3 in 3 in	9/2 in 1/2 in 3/4 in 3/4 in	1/2 in 5/4 in 5/4 in 5/4 in 5/4 in 5/4 in 5/4 in 7/4 in 1/4 in 1/	779 © 100 ° 722 © 100 ° 722 © 100 ° 722 © 100 ° 722 © 100 ° 722 © 100 ° 722 © 100 ° 580 © 100 ° 582 © 100 ° 584 ©	Vibco	1WLJ3 5P162 24W569 5P168 24W564 24W565 5P163 24W565 5P169 5P164 24W571 5P165 24W572 24W573 5P166 5P167 24W574 1WLJ4 24W574
Vent Elbow								
	Cast Bronze	C x C C x C	½ in ¾ in 1 in	Ξ	5% in 7% in 11% in	577 @200 M 466 @200 M 395 @200 M	Vibco	36N495
		0 x 0	1 111	_	1 78 111	033 @200 F	AIDCO	0011430

NIBCO

Lead-Free Cast Bronze Fittings

■ Temp. range: -20° to 200°F

Meet NSF/ANSI 61 Annex G, except 40F183 to 40F268 meet ASTM B584 Alloy C87850, Third-Party Certified To NSF/ANSI 61 Annex G, and ASME B16.18. Certified for use in potable water applications.

	•					
	Pipe Fitting		Pipe Size -		_ Max.	Item
Description 45° Wye	Connection Type	Tube Size	Pipe Fitting	Outside Dia.	Pressure	No.
45 Wye	0 4 0 4 0	16 in		54 in	E77 poi	405050
A second	C x C x C	½ in		5% in	577 psi	
1000	CxCxC	3/4 in	_	7⁄8 in	466 psi	40F253
	CxCxC	1 in	_	11/8 in	395 psi	40F254
90° Drop Ear Elbow						
(many)	C x FNPT	½ in	3/8 in	5⁄8 in x 1∕2 in	577 psi	40F187
100	C x FNPT	½ in	½ in	5⁄8 in x 1⁄2 in	577 psi	5EFW3
(PE) 100	C x FNPT	3/4 in	½ in	⅓ in x ½ in	466 psi	5GEV3
Carrie Con	C x FNPT	3/4 in	3/4 in	⅓ in x ¾ in	466 psi	5GEV2
	C x FNPT	1 in	1 in	11/8 in x 1 in	395 psi	5GEV4
90° Elbow				0/1		
g 18 20	C x FNPT	1/4 in	1/4 in	3/8 in	729 psi	40F207
	C x FNPT	3/8 in	3/8 in	½ in	623 psi	
	C x MNPT	3% in	3/8 in	½ in	623 psi	40F222
	C x FNPT	½ in	½ in	5/8 in x 1/2 in	577 psi	5EFW0
	C x MNPT	½ in	½ in	5⁄8 in x 1⁄2 in	577 psi	5GEV6
	C x MNPT C x FNPT	½ in ¾ in	½ in ¾ in	% in % in x ¾ in	577 psi 466 psi	40F223 5EFW1
	C x MNPT	3/4 in	3/4 in	% in x ¾ in	466 psi	5GEV7
	C x MNPT	3/4 in	3/4 in	78 III X 94 III	466 psi	40F224
	CXFNPT	1 in	1 in	1½ in x 1 in	395 psi	5EFW2
	C x MNPT	1 in	1 in	11/8 in x 1 in	395 psi	5GEV8
	C x MNPT	1 in	1 in	11/8 in	385 psi	40F225
	CXFNPT	1½ in	1½ in	13/8 in	351 psi	40F216
	C x FNPT	1½ in	1½ in	15/8 in	327 psi	40F217
	C x FNPT	2 in	2 in	21/4 in	291 psi	40F218
	C x MNPT	2 in	2 in	21/4 in	291 psi	40F221
90° Elbow, HY Set	•					
	C x C	½ in	_	5⁄8 in	577 psi	5GEW3
	C x FNPT	½ in	1/2 in	5% in x ½ in	577 psi	5GEV5
90° Elbow, Sink Fla	inged					
	C x FNPT	½ in	½ in	% in x ½ in	577 psi	5GEW5
90° Elbow, Vent		4				
To.	C x C	½ in		5% in	577 psi	5EFV8
	CxC	3/4 in	_	7⁄8 in	466 psi	5EFV9
	CxC	1 in		11/8 in	395 psi	40F204

	Pipe Fitting		Pipe Size -		Max.	Item
Description	Connection Type	Tube Size	Pipe Fitting	Outside Dia.	Pressure	No.
90° Reducing Elbow	·					
and the last	C x FNPT	½ in	1/4 in	5% in x 3% in	577 psi	40F211
107	C x FNPT	½ in	3/8 in	5⁄8 in x 1⁄2 in	577 psi	40F210
	C x FNPT	½ in	3/4 in	5/8 in x 7/8 in	577 psi	40F209
	C x MNPT	½ in ¾ in	3/4 in	5⁄8 in x 7⁄8 in	577 psi 466 psi	40F219
	C x FNPT C x MNPT	3/4 in	½ in ½ in	⅓ in x ⅓ in ⅓ in x ⅓ in		40F213 40F220
0	CXFNPT	3/4 in	1 in	78 in x 11/8 in	466 psi 466 psi	40F212
	CxC	1 ¼ in x ¾ in		13% in x 7% in	351 psi	40F205
	CxC	1 ½ in x 1 in		1% in x 1% in	327 psi	40F206
	C x FNPT	1 in	½ in	11/8 in x 5/8 in	385 psi	40F215
	C x FNPT	1 in	3/4 in	11/8 in x 7/8 in	385 psi	40F214
90° Union Elbow	•					
-						
	$C \times C$	1/2 in	_	5/s in	623 psi	40F226

Adapter						
	C x FNPT	½ in	1 in	5/8 in x 11/8 in	395 psi	40F194
(3)	C x FNPT	3/4 in	½ in	⅓ in x ½ in	466 psi	5EFV4
100	C x FNPT	1 in	3/4 in	11/8 in x 3/4 in	395 psi	5EFV5
Baseboard Tee	O X I W I		74 111	170 111 X 74 111	000 poi	OL: VO
Dusonouru 100						
44	C x FNPT	3/4 in	1/8 in	_	466 psi	40F188
- A	O X I WI I	74 111	70 111		400 psi	701 100
Class 150 Companio	n Elango					
Glass 130 Guilleaniu	C	1 in		41/4 in	395 psi	40F256
A STATE OF	Č	1½ in		45% in	351 psi	40F257
	Č	1½ in		5 in	327 psi	40F258
(m) (C. (m) 3//	Č	2 in		6 in	291 psi	40F259
0	C	21/2 in		7 in	269 psi	40F260
	C	3 in		7½ in	254 psi	40F261
	Ĉ	4 in		9 in	235 psi	40F262
	C	5 in		10 in	215 psi	40F263
	C	6 in		11 in	201 psi	40F264
Class 150 Threaded		e Oir		01/ :	004:	405005
A STATE OF THE PARTY OF THE PAR	C	2 in 2½ in		21/8 in 25/8 in	291 psi	40F265 40F266
12	C	3 in		31/8 in	269 psi 254 psi	40F267
0 0	<u>C</u>	4 in		41/8 in	235 psi	40F268
Drain Coupling		7 111		7/0111	200 psi	701 200
Drain Gouping	00	1/ :		6/ !	F77:	405400
Colonia B	CxC	½ in		5⁄8 in	577 psi	40F193
The same of the sa	CxC	3/4 in	_	7/8 in	466 psi	40F185
Drop Ear Tee		71		70111	100 poi	101 100
DLOH EAL 166				5% in x 5/8		
O D	C x C x FNPT	½ in	½ in	in x ½ in	577 psi	5GEX6
		0/1		% in x %		
	C x C x FNPT	3/4 in	3/4 in	in x ¾ in	466 psi	5GEX7
Drop Tee						
600						
	$C \times C \times C$	½ in	_	5/8 in	577 psi	40F234
30						