

PLUMBING Copper Press Fittings

Scan. Order. Done.
Details on page A1.



CONTINUED

Lead-Free Cast Bronze Fittings NIBCO

Description	Pipe Fitting Connection Type	Tube Size	Pipe Size - Pipe Fitting	Outside Dia.	Max. Pressure	Item No.
Fitting Union						
	C x FNPT	¼ in	¼ in	¾ in	729 psi	40F247
	C x FNPT	¾ in	¾ in	½ in	623 psi	40F248
Reducing Adapter						
	C x FNPT	¾ in	¾ in	¾ in x ½ in	466 psi	40F195
Reducing Cross						
	C x C x C x C	½ in	—	¾ in	577 psi	40F251
Reducing Male Adapter						
	C x MNPT	¾ in	1 ¼ in	¾ in x 1 ¼ in	466 psi	40F197
Reducing Tee (run x run x outlet)						
	C x C x FNPT	½ in	¾ in	¾ in x ¾ in x ½ in	577 psi	40F236
	C x FNPT x C	½ in	½ x ½ x ½ in	¾ in x ¼ in x ¾ in	577 psi	40F202
	FNPT x FNPT x C	½ in	¾ in x ½ in	¾ in x ¾ in x ¾ in	577 psi	40F231
	C x FNPT x C	½ in	¾ in	¾ in x ¾ in x ¾ in	577 psi	40F229
	C x C x FNPT	¾ in	¾ in	¾ in x ¾ in x ½ in	466 psi	40F237
	C x FNPT x C	¾ in	½ in	¾ in x ¾ in x ¾ in	466 psi	40F245
	FNPT x FNPT x C	¾ in	¾ in x ½ in	¾ in x ¾ in x ¾ in	466 psi	40F230
	C x C x C	1 ¼ in x ½ in x 1 in	—	1 ¾ in x ¾ in x 1 ¼ in	391 psi	40F233
	C x FNPT x C	1 in	¾ in	1 ¼ in x ¼ in x 1 ¼ in	395 psi	40F203
	C x FNPT x C	1 in	½ in	1 ¼ in x ¾ in x 1 ¼ in	395 psi	40F246
	C x C x FNPT	1 ¼ in	¾ in	1 ¾ in x 1 ¾ in x ¾ in	391 psi	40F238
	C x C x FNPT	1 ½ in	¾ in	1 ¾ in x 1 ¾ in x ¾ in	327 psi	40F239
	C x C x FNPT	2 in	¾ in	2 ¼ in x 2 ¼ in x ¾ in	291 psi	40F241
	C x C x FNPT	2 in	1 in	2 ½ in x 2 ½ in x 1 ¼ in	291 psi	40F240

Description	Pipe Fitting Connection Type	Tube Size	Pipe Size - Pipe Fitting	Outside Dia.	Max. Pressure	Item No.
Special Drop Adapter						
	C x FNPT	½ in	½ in	¾ in x ½ in	577 psi	5EFV6
	C x FNPT	¾ in	¾ in	¾ in x ¾ in	466 psi	5EFV7
Tee						
	C x C x FNPT	½ in	¼ in	¾ in x ¾ in x ¼ in	577 psi	5GEW7
	C x C x FNPT	½ in	½ in	¾ in x ¾ in x ½ in	577 psi	5GEW6
	C x C x MNPT	½ in	½ in	¾ in	577 psi	40F242
	C x FNPT x C	½ in	½ in	¾ in	577 psi	40F243
	C x C x FNPT	½ in	¾ in	¾ in x ¾ in x ¾ in	577 psi	40F235
	C x C x FNPT	¾ in	½ in	¾ in x ¾ in x ½ in	466 psi	5GEW9
	C x C x FNPT	¾ in	¾ in	¾ in x ¾ in x ¾ in	466 psi	5GEW8
	C x FNPT x C	¾ in	¾ in	¾ in x ¾ in x ¾ in	466 psi	5GEX8
	FNPT x FNPT x C	¾ in	¾ in	¾ in	466 psi	40F228
	FNPT x MNPT x C	¾ in	¾ in	¾ in	466 psi	40F232
	C x C x FNPT	1 in	½ in	1 ½ in x 1 ½ in x ½ in	395 psi	5GEX2
	C x C x FNPT	1 in	¾ in	1 ½ in x 1 ½ in x ¾ in	395 psi	5GEX1
	C x FNPT x C	1 in	¾ in	1 ½ in x ¾ in x 1 ½ in	395 psi	5GEY0
	C x C x FNPT	1 in	1 in	1 ½ in x 1 ½ in x 1 in	395 psi	5GEX0
	C x FNPT x C	1 in	1 in	1 ½ in x 1 in x 1 ½ in	395 psi	5GEX9
	C x C x FNPT	1 ¼ in	½ in	1 ¾ in x 1 ¾ in x ½ in	351 psi	5GEX4
	C x C x FNPT	1 ½ in	1 in	1 ¾ in x 1 ¾ in x 1 in	351 psi	5GEX3
	C x C x FNPT	1 ½ in	1 in	1 ¾ in x 1 ¾ in x 1 in	327 psi	5GEX5
Union						
	C x MNPT	¼ in	¼ in	¾ in	729 psi	40F249
	C x MNPT	¾ in	¾ in	½ in	623 psi	40F250
	C x FNPT	½ in	½ in	¾ in x ½ in	577 psi	5GEB3
	C x MNPT	½ in	½ in	¾ in x ¾ in	577 psi	5GEB8
	C x FNPT	¾ in	¾ in	¾ in x ¾ in	466 psi	5GEG4
	C x MNPT	¾ in	¾ in	¾ in x ¾ in	466 psi	5GEG9
	C x FNPT	1 in	1 in	1 ½ in x 1 in	395 psi	5GEG5
	C x C	1 ¼ in	—	1 ¾ in	351 psi	5GEG1
	C x FNPT	1 ¼ in	1 ¼ in	1 ¾ in x 1 ¼ in	351 psi	5GEG6
	C x MNPT	1 ¼ in	1 ¼ in	1 ¾ in x 1 ¼ in	351 psi	5GEG2
	C x C	1 ½ in	—	1 ¾ in	327 psi	5GEG2
	C x FNPT	1 ½ in	1 ½ in	1 ¾ in x 1 ½ in	327 psi	5GEG7
	C x MNPT	1 ½ in	1 ½ in	1 ¾ in x 1 ½ in	327 psi	5GEG2
	C x C	2 in	—	2 ½ in	291 psi	40F184
	C x MNPT	2 in	2 in	2 ½ in	291 psi	40F183
	C x FNPT	2 in	2 in	2 ½ in	291 psi	40F186
	C x C	2 ½ in	—	2 ¾ in	269 psi	40F189
	C x MNPT	2 ½ in	2 ½ in	2 ¾ in	269 psi	40F191
	C x FNPT	2 ½ in	2 ½ in	2 ¾ in	269 psi	40F192
	C x C	3 in	—	3 ½ in	254 psi	40F190



Copper Press Tools and PEX Press Jaws

Use to securely join Type K, L, or M copper tubing, with no flames, solder, or flux. Designed for ½" to 4" applications, with interchangeable jaws and rings. For use with potable and chilled water, hydronic heating, compressed air, and air vacuum (29.2" Hg max. at 68°F).

Pressing Ring Kits—Use with battery-powered or corded pressing tools to connect copper tubing in tight spaces; a swivel actuator allows the tool to be oriented ±90° to the tubing.

Compact Cordless Press Tool Kits—Compact and lightweight for tight spaces and overhead work, these press tools feature Bluetooth® connectivity to manage information such as battery life and cycle count. The handy LED light is ideal for low light conditions and the battery can provide up to 140 crimps per charge. Barrel swivels 180°. The included carrying case eases transport to and from the jobsite.

Viega MegaPress Jaws Kits—34TC11 and 34TC10 include ½" to 1" press jaws and a carrying case, 34TC10 adds 1 ¼" to 2" press rings and actuator.

Press Tool Accessories—Press Tool Pipe Cutter Attachment 5KAY4 eases cutting of cast-iron soil pipe. Simply connect unit to press tool, wrap chain around the pipe, and press. No ratcheting or additional tools required. Compatible with all Ridgid standard press tools.

PEX Press Jaws—Designed for use with Viega® system fittings. Compact jaws are ½" smaller than Standard models and are for use in tight spaces.

Description	Press Tool Jaw/ Pipe Capacity	Use With Pipe/ Tubing Material	Tool Length	Mfr. Model	Item No.
Compact Cordless Press Tool Kits					
Pistol Grip, 12 V DC, (4) Jaws, Case	½ in to 1 in	Copper	13 ½ in	RP-240	426J88
Pistol Grip, 12 V DC, (4) Jaws, Case	½ in to 1 ¼ in	Copper	13 ½ in	RP-240	426J87
In-Line Design, 12 V DC, (3) Jaws, Case	½ in to 1 in	Copper	15 ½ in	RP-241	426J90
In-Line Design, 12 V DC, (4) Jaws, Case	½ in to 1 ¼ in	Copper	15 ½ in	RP-241	426J89

Description	For Use With	Mfr. Model	Item No.
Press Tool Kit			
Pistol Grip, 18 V DC, (6) Jaws; Carrying Case; Battery; Charger	½ in to 2 in	Carbon Steel, Copper, PEX, Stainless Steel	67053 60UG31

Description	For Use With	Mfr. Model	Item No.
Press Tool			
Pistol Grip, 18 V DC, (4) Jaw, Power Adapter	½ in to 4 in	Carbon Steel, Copper, PEX, Stainless Steel	67068 60UG33

Description	For Pipe Size (in.)	For Use With	L (in.)	W (in.)	H (in.)	Mfr. Model	Item No.
Pressing Ring Kits, For Use With:							
CT-400, 320-E, RP 330-B, RP 330-C, or RP 340, RP 350) and ProPress XL-C	2 ½ to 4 ½ to 1 ¼ 1 ½ to 2	22XH23 and 22XH24	13 ½ in	12 in	12 ½ in	20483	2TE27
			15 ½ in	11 in	3 ½ in	27423	26ME8
						27428	26ME9

Description	For Use With	Mfr. Model	Item No.
Viega MegaPress Jaws Kits			
Press Jaws for ½" to 1"	½ to 1	Mfr. No. 44693, Mfr. No. RP340-B	18 in 14 in 8 in 48558 34TC11
	½ to 2	Mfr. No. RP340-B, RP340-C	48553 34TC10

Description	For Use With	Mfr. Model	Item No.
Batteries and Chargers			
Li-Ion Battery, 12V	RIDGID 12V Cordless Tools	55183	54HT32
Battery Charger, 150+ Crimps Off A Single Charge 12V	Mfr. No. PEX-One Tools, Mfr. No. RP240, Mfr. No. RP241	55193	54HT33
Li-Ion Battery, 18V DC	CS12x, CS65x, CS6x Versa, RE6, RE60, RP340, RP350	56513	61UM25
Battery Charger, 18V, 39 min. 82 min Charge Time	RIDGID 18V Lithium Batteries	64383	61UM26

Description	For Pipe Size (in.)	L (in.)	W (in.)	H (in.)	Mfr. Model	Item No.
Press Tool Accessories						
Press Tool Pipe Cutter Attachment	1 ½ to 4	9 in	17 in	3 in	34403R	5KAY4
Press Tool Carrying Case	—	9 ¾ in	17 ¼ in	6 in	34678	5KAY5
Compact MegaPress(R) Jaw	½	1 ½ in	4 ½ in	5 ¾ in	48433	453D73
Compact MegaPress(R) Jaw	¾	5 in	—	2 in	48438	453D74
X-LC MegaPress(R) Booster	—	20 in	14 in	4 in	60658	453D75
X-LC MegaPress(R) Jaw	2 ½	8 ¼ in	2 ¾ in	9 ½ in	60643	453D76
X-LC MegaPress(R) Jaw	3	8 ¼ in	2 ¾ in	9 ½ in	60648	453D77
X-LC MegaPress(R) Jaw	4	8 ¼ in	2 ¾ in	9 ½ in	60653	453D78
X-LC MegaPress(R) Jaw Kit	2 ½ to 4	27 in	17 in	8 ¾ in	60638	453D79

For Pipe Size (in.)	L (in.)	W (in.)	H (in.)	Mfr. Model	Compact Item No.	Standard Item No.
½	4 in	6 in	1 ½ in	17008	10E717	—
½	6 in	6 ½ in	3 ½ in	22653	—	10E720
¾	6 in	4 in	1 in	17013	10E718	—
¾	7 in	7 ½ in	2 in	22663	—	10E721
1	6 in	4 in	1 in	17018	10E719	—
1	7 in	7 ½ in	2 ¾ in	22668	—	10E722
1 ¼	7 in	7 ½ in	2 ¾ in	22673	—	10E723
1 ½	7 in	7 ½ in	2 ¾ in	22678	—	10E724