















Lead-Free PEX Crimp Fittings

- Max. pressure: 80 psi, except PEX Ball Valves are 160 psi at 73°F, 100 psi at 180°F, and 80 psi at 200°F
- Temp. range: 33° to 200°F
- Fittings are Zurn brand, except 40PR09, 40PR11, and 40PR12 are Oetiker brand

Easily install without flame, flux, or solder. Require no bonding agents, glue, or solvents. Fittings resist corrosion, mineral buildup, rust, and freeze damage. Suitable for new or retrofit construction and for hot or cold water distribution. Clamps 40PR09, 40PR11, and 40PR12 feature a narrow band for more concentrated compression and have a tamper-detectable design. 40PR09 and 40PR12 hold in place while crimped to ease installation. Fittings are certified for use in potable water applications. For a complete list of standards and specifications, go to Grainger.com and search for individual products.

Description	PEX Size	Zurn PEX Item No.
Coupling, PEX		
	3/8"	10A588
	1/2"	10A589
	3/4"	10A591
	1"	10A593
	1 1/4"	10A510
	1 1/2"	10A512
	2"	10A514
Crimp Clamp Ring, Clamp		
	1/2"	10A573
	3/4"	10A574
	1"	10A575
	1 1/4"	10A503
	1 1/2"	10A504
	2"	10A505
Drop Ear Elbow, 90°, PEX x FNPT		
	1/2"	10A580
	3/4"	10A581
Elbow, 90°, PEX		
	1/2"	10A603
	3/4"	10A604
	1"	10A605
	1 1/4"	10A515
	1 1/2"	10A516
	2"	10A517
Elbow, 90°, PEX x Female Swivel		
	1/2"	10A539
Elbow, 90°, PEX x MNPT		
	1/2"	10A602
Elbow Stubout, 90°, PEX		
	1/2"	10A607
	1/2"	10A609
	3/4"	10A610
	1"	10A611

Description	PEX Size	Zurn PEX Item No.
PEX and Pipe Adapter, PEX x Female Swivel		
	3/4"	10A541
	3/4"	10A542
	1"	10A543
PEX and Pipe Adapter, PEX x FNPT Nonswivel		
	1/2"	10A583
	3/4"	10A585
	1"	10A586
	1 1/4"	10A532
	1 1/2"	10A533
PEX and Pipe Adapter, PEX x MNPT		
	1/2"	10A582
	3/4"	10A584
	1"	10A587
	1 1/4"	10A518
	1 1/2"	10A519
	2"	10A520
PEX and Sweat Adapter, PEX x Female Sweat		
	1/2"	10A598
	3/4"	10A601
PEX and Sweat Adapter, PEX x Sweat		
	1/2"	10A597
	3/4"	10A599
	1 1/4"	10A507
	1 1/2"	10A508
	2"	10A506
Plug, PEX		
	1 1/4"	10A521
	1 1/2"	10A522
	2"	10A523
Reducing Coupling, PEX		
	3/4" x 1/2"	10A590
	1" x 3/4"	10A592
	1 1/4" x 1"	10A509
	1 1/2" x 1 1/4"	10A511
	2" x 1 1/2"	10A513

Description	PEX Size	Zurn PEX Item No.
Reducing Tee (run x run x outlet), PEX		
	1" x 3/4" x 3/4"	48UH65
	1" x 1" x 3/4"	48UH66
	1" x 1" x 1/2"	48UH67
	1 1/4" x 1 1/4" x 1/2"	10A524
	1 1/4" x 1 1/4" x 3/4"	10A525
	1 1/2" x 1 1/2" x 3/4"	10A527
	1 1/2" x 1 1/2" x 1"	10A528
	2" x 2" x 1"	10A530
Stubout, PEX		
	1/2"	10A606
Stubout, PEX with Flange		
	1/2"	10A612
Tee, PEX		
	1/2"	10A594
	3/4"	10A595
	1"	10A596
	1 1/4"	10A526
	1 1/2"	10A529
	2"	10A531
Transition Coupling, PEX		
	1/2"	10A544
	3/4"	10A545

Description	Connection	Nom. Size (in.)	W (in.)	Closed - Open (in.)	Oetiker Item No.
PEX Clamp					
	PEX Crimp	1/2	0.276	0.563-0.689	40PR12
	PEX Crimp	3/4	0.354	0.791-0.917	40PR09
	PEX Crimp	1	0.394	1.039-1.165	40PR11



Manual PEX Tools and PEX Manifolds

MANUAL PEX TOOLS

52DD79 to 52DD83 meet ASTM F1807.

10A618 and 10A619 apply the correct pressure to create a leak-free crimp connection. Use with annealed copper crimp rings, Qick/Sert1 or QickSert CR fittings, and Zurn PEX tubing.

10A622 is used to make a copper crimp ring connection. For use with 1 1/4", 1 1/2", and 2" Zurn PEX copper crimp rings on Zurn PEX DZR and Zurn PEX XL insert fittings.

40PR13 and 40PR14 used with ear clamps will not release until the clamp is fully closed to help ensure a leak-free connection.

QUICK PORT MANIFOLDS

- Max. working pressure: 100 psi
- Temp. range: 33° to 200°F

Use to supply different fixtures from a main line and feature controllable water distribution, increased water flow, and no inline below-floor fittings. Certified for use in potable water applications. Meet ASTM F877 F1807.



10A633

Item	Size	PEX Size	Includes	Brand	Item No.
Manual PEX Tools					
Crimp Clamp Ring	—	1/2 in	—	Zurn PEX	52DD79
	—	3/4 in	—	Zurn PEX	52DD80
	—	1 in	—	Zurn PEX	52DD81
	—	1 1/4 in	—	Zurn PEX	52DD82
	—	1 1/2 in	—	Zurn PEX	52DD83
Pex Crimp Tool	1/2 in, 3/4 in, 1 in, 1 1/4 in, 1 1/2 in	—	Crimp Ring Removal Tool and Go, No Go Gauge, Nylon Carrying Case	Zurn PEX	52DD87
PEX Tool	1/2 in	—	Crimp Gauge	Zurn PEX	10A618
	3/4 in	—	Crimp Gauge	Zurn PEX	10A619
	1 1/2 in, 1 1/4 in, 2 in	—	Crimp Gauge, Hex Wrench, Socket	Zurn PEX	10A622



10A618

Description	Material	Type	Brand	Item No.
Ratchet Pincers				
Ratchet Pincer	Forged Steel	PEX Fitting	Oetiker	40PR13
Ratchet Pincer with Handle	Forged Steel	PEX Fitting	Oetiker	40PR14

Inlet Size	Outlet Size	Pipe Fitting Connection Type	Overall Length	Mounting Hole Size	Brand	Item No.
Quick Port Manifolds						
1 in	1/2 in	MNPS	26 3/8 in	0.25 in	Zurn PEX	10A633
1 in	1/2 in	MNPS	26 3/8 in	0.25 in	Zurn PEX	10A636
1 in	1/2 in	MNPS	37 1/8 in	0.25 in	Zurn PEX	10A638

† 10A636 includes (24) 3/8" ball valves. 10A638 includes (36) 3/8" ball valves.