















For ABS Solvent Cement, see page 2822.

CONTINUED

PVC Pressure Pipe Fittings, Schedule 40


Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Oper. Press. (psi)	Temp. Range	Item No.
	3/4" x 1/2"	F Socket	480	32° to 140° F	22FL33
	2" x 1"	F Socket	280	32° to 140° F	22FL86
	2" x 1 1/4"	F Socket	280	32° to 140° F	22FL87
	1 1/2"	F Socket x F Socket x Socket	330	32° to 140° F	22FM04
	Cap				
	1/2"	F Socket	600	0° to 140° F	22FJ34
	3/4"	F Socket	480	0° to 140° F	22FJ40
	1"	F Socket	450	0° to 140° F	22FJ32
	1 1/4"	F Socket	370	0° to 140° F	22FJ30
	1 1/2"	F Socket	330	0° to 140° F	22FJ28
	2"	F Socket	280	0° to 140° F	22FJ37
	2 1/2"	F Socket	300	0° to 140° F	22FJ35
	3"	F Socket	260	0° to 140° F	22FJ38
	4"	F Socket	220	0° to 140° F	22FJ41
5"	F Socket	190	0° to 140° F	22FM69	
6"	F Socket	180	0° to 140° F	22FJ42	
8"	F Socket	160	0° to 140° F	22FM70	
	1/2" x 1/2"	F Socket	600	32° to 140° F	22FJ48
	3/4" x 3/4"	F Socket	480	32° to 140° F	22FJ53
	1" x 1"	F Socket	450	32° to 140° F	22FJ46
	1 1/4" x 1 1/4"	F Socket	370	32° to 140° F	22FJ44
	1 1/2" x 1 1/2"	F Socket	330	32° to 140° F	22FJ43
	2" x 2"	F Socket	280	32° to 140° F	22FJ50
	2 1/2" x 2 1/2"	F Socket	300	32° to 140° F	22FJ49
	3" x 3"	F Socket	260	32° to 140° F	22FJ51
	4" x 4"	F Socket	220	32° to 140° F	22FJ54
	5" x 5"	F Socket	220	32° to 140° F	22FM15
	6" x 6"	F Socket	180	32° to 140° F	22FJ55
	8" x 8"	F Socket	160	32° to 140° F	22FM16
	1 1/2" x 1 1/2"	F Socket	330	32° to 140° F	22FM93
	3" x 3"	F Socket	260	32° to 140° F	22FM94
	4" x 4"	F Socket	220	32° to 140° F	22FM95
	1 1/2" x 1 1/2"	F Socket	330	32° to 140° F	22FM12
	2" x 2"	F Socket	280	32° to 140° F	22FM13
	3/4" x 1/2"	F Socket	480	32° to 140° F	22FK22
	1 1/2" x 1"	F Socket	370	32° to 140° F	22FM17
	1 1/2" x 1 1/4"	F Socket	330	32° to 140° F	22FM18
	2" x 1 1/2"	F Socket	280	32° to 140° F	22FM19
	3" x 2"	F Socket	260	32° to 140° F	22FK21
	4" x 3"	F Socket	220	32° to 140° F	22FM20
	6" x 4"	F Socket	180	32° to 140° F	22FM21
	8" x 6"	F Socket	160	32° to 140° F	22FM22





Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Oper. Press. (psi)	Temp. Range	Item No.	
	3/4" x 1/2" x 3/4"	F Socket	480	32° to 140° F	22FK89	
	1" x 3/4" x 1"	F Socket	450	32° to 140° F	22FK81	
	1" x 1" x 1"	F Socket x F Socket x FNPT	450	32° to 140° F	22FK80	
	1" x 1" x 1"	F Socket	450	32° to 140° F	22FK83	
	1 1/2" x 3/4" x 1 1/2"	F Socket	330	32° to 140° F	22FK74	
	1 1/2" x 1" x 1 1/2"	F Socket	330	32° to 140° F	22FK82	
	1 1/2" x 2" x 1 1/2"	F Socket	330	32° to 140° F	22FL48	
	2" x 1 1/2" x 2"	F Socket	280	32° to 140° F	22FK85	
	2" x 2" x 2"	F Socket	280	32° to 140° F	22FL05	
	2 1/2" x 1" x 2 1/2"	F Socket	300	32° to 140° F	22FL51	
	2 1/2" x 2 1/2" x 4"	F Socket	300	32° to 140° F	22FL04	
	3" x 3/4" x 3"	F Socket	260	32° to 140° F	22FL54	
	3" x 1" x 3"	F Socket	260	32° to 140° F	22FL55	
	3" x 1 1/2" x 3"	F Socket	260	32° to 140° F	22FL57	
	3" x 2" x 3"	F Socket	260	32° to 140° F	22FL58	
	4" x 1" x 4"	F Socket	220	32° to 140° F	22FL60	
	4" x 2" x 4"	F Socket	220	32° to 140° F	22FL61	
	4" x 3" x 4"	F Socket	220	32° to 140° F	22FL62	
	6" x 2" x 6"	F Socket	180	32° to 140° F	22FL63	
	6" x 3" x 6"	F Socket	180	32° to 140° F	22FL64	
	6" x 4" x 6"	F Socket	180	32° to 140° F	22FL65	
		1/2"	F Socket	600	32° to 140° F	22FJ59
3/4"		F Socket	480	32° to 140° F	22FJ61	
1"		F Socket	450	32° to 140° F	22FJ58	
1 1/4"		F Socket	370	32° to 140° F	22FJ57	
1 1/2"		F Socket	330	32° to 140° F	22FJ56	
2"		F Socket	280	32° to 140° F	22FJ60	
	3"	F Socket	260	32° to 140° F	22FM08	
	4"	F Socket	220	32° to 140° F	22FM09	
	3/8"	F Socket	480	32° to 140° F	22FL40	
	1/2"	F Socket	600	32° to 140° F	22FL02	
	3/4"	F Socket	480	32° to 140° F	22FL08	
	1"	F Socket	450	32° to 140° F	22FK99	
	1 1/4"	F Socket	370	32° to 140° F	22FK95	
	1 1/2"	F Socket	330	32° to 140° F	22FK93	
	3"	F Socket	260	32° to 140° F	22FL06	
	4"	F Socket	220	32° to 140° F	22FL10	
	5"	F Socket	190	32° to 140° F	22FL11	
	6"	F Socket	180	32° to 140° F	22FL12	
	8"	F Socket	160	32° to 140° F	22FL41	
		1/2" x 1/2"	F Socket	600	32° to 140° F	22FL14
		3/4" x 3/4"	F Socket	480	32° to 140° F	22FL19
		1" x 1"	F Socket	450	32° to 140° F	22FL13
1 1/4" x 1 1/4"		F Socket	370	32° to 140° F	22FL16	
1 1/2" x 1 1/2"		F Socket	330	32° to 140° F	22FL15	
2" x 2"		F Socket	280	32° to 140° F	22FL17	
3" x 3"		F Socket	260	32° to 140° F	22FL18	
4" x 4"		F Socket	220	32° to 140° F	22FL20	
	4" x 4" x 4"	F Socket	220	32° to 140° F	22FM92	




Schedule 40 Clear Pipe & Fittings

Temp. range: 73° to 180°F, except caps are 0° to 140°F

Clear PVC pipe is used for quick identification and visual leak detection in medical/hospital use, chemical processing, and beverage processing. Compatible with PVC cleaners, primers, and cements. Schedule 40 pipe has thicker walls than Schedule 10, but not as thick as Schedule 80 pipe.

Description	Nominal Pipe Size	8 ft Item No.
Schedule 40 Clear Unthreaded Low Pressure Pipe		
	1/2"	1AAZ4
	3/4"	1AAZ5
	1"	1AAZ6
	1 1/4"	5REW3
	1 1/2"	1AAZ7
	2"	1AAZ8
	2 1/2"	5REW4
	3"	1AAZ9
	4"	1BA1

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Operating Pressure	Item No.
Socket x Threaded Schedule 40 Pipe Fittings				
Female Adapter				
	1/2"	FNPT x F Socket	360 psi @ 73° F	2CFA3
	3/4"	FNPT x F Socket	280 psi @ 73° F	2CFA4
	1"	FNPT x F Socket	270 psi @ 73° F	2CFA5
	1 1/2"	FNPT x F Socket	200 psi @ 73° F	2CFA7
	2"	FNPT x F Socket	170 psi @ 73° F	2CFA8
	4"	FNPT x F Socket	130 psi @ 73° F	2CFC2
Male Adapter				
	1/2"	MNPT x M Socket	360 psi @ 73° F	2CFC3
	3/4"	MNPT x M Socket	280 psi @ 73° F	2CFC4
	1"	MNPT x M Socket	270 psi @ 73° F	2CFC5
	1 1/2"	MNPT x M Socket	200 psi @ 73° F	2CFC7
	2"	MNPT x M Socket	170 psi @ 73° F	2CFC8
	2 1/2"	MNPT x M Socket	180 psi @ 73° F	2CFC9
Socket x Socket Schedule 40 Pipe Fittings				
45° Elbow				
	1/2"	F Socket	360 psi @ 73° F	2CEY3
	3/4"	F Socket	280 psi @ 73° F	2CEY4
	1"	F Socket	270 psi @ 73° F	2CEY5
	2"	F Socket	170 psi @ 73° F	2CEY8
	2 1/2"	F Socket	180 psi @ 73° F	2CEY9
	3"	F Socket	155 psi @ 73° F	2CEZ1
	4"	F Socket	130 psi @ 73° F	2CEZ2
90° Elbow				
	1/2"	F Socket	360 psi @ 73° F	2CEX3
	3/4"	F Socket	280 psi @ 73° F	2CEX4
	1"	F Socket	270 psi @ 73° F	2CEX5
	1 1/4"	F Socket	220 psi @ 73° F	2CEX6
	1 1/2"	F Socket	200 psi @ 73° F	2CEX7
	2"	F Socket	170 psi @ 73° F	2CEX8
	2 1/2"	F Socket	180 psi @ 73° F	2CEX9
	4"	F Socket	130 psi @ 73° F	2CEY2

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Max. Operating Pressure	Item No.
Cap				
		Socket	180 psi @ 73° F	2CFD3
	1/2 in	Socket	180 psi @ 73° F	2CFD3
	3/4 in	Socket	144 psi @ 73° F	2CFD4
	1 in	Socket	132 psi @ 73° F	2CFD5
	1 1/2 in	Socket	102 psi @ 73° F	2CFD7
	2 in	Socket	84 psi @ 73° F	2CFD8
	2 1/2 in	Socket	90 psi @ 73° F	2CFD9
	3 in	Socket	78 psi @ 73° F	2CFE1
Coupling				
	1/2"	F Socket	360 psi @ 73° F	2CEZ3
	3/4"	F Socket	280 psi @ 73° F	2CEZ4
	1"	F Socket	270 psi @ 73° F	2CEZ5
	1 1/4"	F Socket	220 psi @ 73° F	2CEZ6
	1 1/2"	F Socket	200 psi @ 73° F	2CEZ7
	2"	F Socket	170 psi @ 73° F	2CEZ8
	3"	F Socket	155 psi @ 73° F	2CFA1
	4"	F Socket	130 psi @ 73° F	2CFA2
Tee				
	1/2"	F Socket	360 psi @ 73° F	2CEW3
	3/4"	F Socket	280 psi @ 73° F	2CEW4
	1"	F Socket	270 psi @ 73° F	2CEW5
	1 1/4"	F Socket	220 psi @ 73° F	2CEW6
	1 1/2"	F Socket	200 psi @ 73° F	2CEW7
	2"	F Socket	170 psi @ 73° F	2CEW8
	2 1/2"	F Socket	180 psi @ 73° F	2CEW9
	4"	F Socket	130 psi @ 73° F	2CEX2