



5LB44

**ASHCROFT**  
**Harsh Environment Pressure Switches**

- 1/4" FNPT inlet port
- Stainless steel pressure connection
- Viton® actuator seal
- Temp. range: 20° to 300°F

For harsh environments using pumps, compressors, hydraulic systems, and HVAC equipment. Watertight enclosure meets NEMA 3, 4, 4X, and 13, and IP66. Fixed deadband. Switch rated 15A at 125/250VAC; 0.5A at 125VDC.

Range	Contact Form	Mfr. Model	Item No.
1.5 to 15 psi	SPDT	B424VXCYL15	5LB41
3 to 30 psi	SPDT	B424VXCYL30	5LB42
6 to 60 psi	SPDT	B424VXCYL60	5LB43
10 to 100 psi	SPDT	B424VXCYL100	5LB44
20 to 200 psi	SPDT	B424VXCYL200	5LB45
40 to 400 psi	SPDT	B424VXCYL400	5LB46
60 to 600 psi	SPDT	B424VXCYL600	36K013
100 to 1000 psi	SPDT	B424BXCYL1000	36K014
300 to 3000 psi	SPDT	B424BXCYL3000	36K015



232333

**Honeywell**  
**Pressure Switches**

- 5000 series
- 1/8"-27" MNPT Port
- Temp. range: -40° to 250°F
- Glass reinforced polyester enclosure
- Screw terminal connection

Range	Factory On/Off Setting	Contact Form	NEMA Rating	Mfr. Model	Item No.
1.1 to 3 psi	1.5/3 psi	SPST-NO	Not Rated	76051	232327
	1.5/3 psi	SPST-NC	Not Rated	76061	232333
3.1 to 7 psi	3.1/7 psi	SPST-NO	Not Rated	76575	232336
	4 psi	SPST-NC	Not Rated	76577	232337
8 to 13 psi	10 psi	SPST-NO	Not Rated	76576	232343
	8/13 psi	SPDT-NO/NC	Not Rated	76580	232345
14 to 24 psi	14/23 psi	SPST-NO	Not Rated	76052	232328
	15/24 psi	SPDT-NO/NC	Not Rated	76072	232341
25 to 50 psi	35 psi	SPST-NO	Not Rated	76053	232329
	60/90 psi	SPST-NO	Not Rated	76054	232330
51 to 90 psi	60 psi	SPST-NC	Not Rated	76064	232335
	60 psi	SPDT-NO/NC	Not Rated	76074	232342
91 to 150 psi	100 psi	SPST-NO	Not Rated	76055	232346
Pressure Switch Boot Direct Action Blade Contact				79380	232347



1A352

**SQUARE D**  
by Schneider Electric

**Industrial Pressure Switches**

- SPDT switch
- 1/4" female inlet, except male 3FJY9
- Rated 10A
- Ambient temp. range: -10° to 185°F
- Media temp. range: -40° to 250°F

Designed to control or monitor pressure using air, oil, water, or other compatible fluids. Easily adjustable range and differential. Buna N diaphragms. UL Listed and CSA Certified.

Range	Differential	Actuation Type	NEMA Rating	Mfr. Model	Item No.
0.2 to 10 psi	0.4 to 0.9 psi	Diaphragm	1	9012GNG1	3FJY6
1 to 40 psi	1.2 to 3.6 psi	Diaphragm	1	9012GNG3	3FJY7
1.5 to 75 psi	2.2 to 6.6 psi	Diaphragm	1	9012GNG4	3FJY8
1.5 to 75 psi	2.2 to 6.6 psi	Diaphragm	1	9012GNG4Z	3FJY9
3 to 150 psi	4.2 to 13.2 psi	Diaphragm	1	9012GNG5	1A352
5 to 250 psi	7.4 to 33.6 psi	Diaphragm	1	9012GNG6	1A353
5 to 250 psi	7.4 to 33.6 psi	Diaphragm	1	9012GNG6	3FJZ1
20 to 675 psi	19 to 58.8 psi	Diaphragm	1	9012GPG2	3FKD3
90 to 2900 psi	141 to 455 psi	Piston	1	9012GQG2	3FJZ2
170 to 5600 psi	200 to 950 psi	Piston	1	9012GQG3	3FJZ3
3 to 150 psi	4.2 psi	Diaphragm	1	9012GRG5	3FJZ4
1.5 to 75 psi	2.2 to 0.4 psi	Diaphragm	1	9012GR04	3FJZ5



35T575

**ifm** efector

**Pressure Transmitters**

- 1/4" NPT port

Provide high-burst and overpressure protection and exceptional reliability. Feature stainless steel housing. 0.15% of full range repeatability. Models available for vacuum, pneumatic, hydraulic, and hydrostatic level applications.

Range	9.6 to 32V DC, 4 to 20mA DC Output		16 to 32V DC, 0 to 10V DC Output	
	Mfr. Model	Item No.	Mfr. Model	Item No.
1/4 in MNPT				
-14.5 psi to 0 psi	PX3229	35T575	PX9119	35T587
0 to 100 in wc	PX3228	35T576	PX9118	35T588
0 to 15 psi	PX3227	35T577	PX9117	35T589
0 to 30 psi	PX3226	35T578	PX9116	35T590
0 to 100 psi	PX3224	35T579	PX9114	35T591
0 to 150 psi	PX3244	35T580	—	—
0 to 200 psi	PX3234	35T581	PX9134	35T592
0 to 250 psi	PX3233	35T582	—	—
0 to 500 psi	PX3223	35T583	—	—
0 to 1000 psi	PX3222	35T584	PX9112	35T593
0 to 3000 psi	PX3111	35T585	PX9111	35T594
0 to 5000 psi	PX3220	35T586	PX9110	35T595