

#### BROAN



# Panasonic. Speed Control and Switches





60NT44

Fit a single-gang box. **Speed Control** adjusts sound, speed, CFM, and energy usage. Faceplate not included. **Switches** control fans and lights, except 6XAU2 is only for fan control. **Timer** operates as both a fan and light switch, and features programmable delay and ventilation settings.

Switch Color	Plate Color	Type	Voltage	Max. Amps	Brand	Mfr. Model	ltem No.
Speed C	Control	-7,7-					
White	White	Adjustable Speed	120	3 A	Broan	SC100W	60NT44
Switche	es						
Black	White	Percentage Timer	24	_	Soler & Palau	SPTL	6XAU2
White	_	Rocker, 2-Function	120	_	Broan	P2RW	55NM01
White		Rocker, 3-Function	120	_	Broan	P3RW	55NM02
White	White	2-Function	120	15	Panasonic	FV-WCSW21-W	20JR13
Timer							
White	White	Delay Timer	120	15	Panasonic	FV-WCPT1-W	20JR18



## westaflex Non-Insulated Flexible Ducts

- Max. temp.: 500°F
- Compressed length: 30"

Connect to HVAC ducts and direct airflow around obstacles and corners. Constructed of a thin sheet of aluminum folded like an accordion, allowing them to bend and flex around obstacles. They can move higher-temperature air and withstand more abuse than non-insulated air connectors. Due to their increased durability and how they transfer heat to their surroundings, they are commonly used as part of a combustion system exhaust in mechanical spaces.

	15 ft	30 ft
Inside	Item	Item
Dia.	No.	No.
3 in	3C590	3XK03
4 in	3C591	3XK04
8 in	3XK02	3XK06
6 in	5C201	3XK05
10 in	59ZX58	3XK07
12 in	59ZX59	3XK08
5 in	59ZX56	59ZX60
7 in	59ZX57	59ZX61



#### **Roof, Wall, & Soffit Vent Caps**

**Roof Caps** have a weather hood that blocks rain and other debris from entering while also directing the exhaust gases in one direction along the mounting surface. They install onto the ends of roof exhaust vent pipes or ducts. **Rain Caps** prevent rain from entering under normal conditions and exhaust caps and particulates from root properties the unit of the ping exhaust connection.

**Rain Caps** prevent rain from entering under normal conditions and exhaust gases and particulates from re-entering the vent after being exhausted. Connect to the ends of roof vent pipes and have louvered vent slots on their sides that angle down toward the mounting surface. **Wall and Soffit Vent Caps** protect against weather and pest intrusion. Feature hoods or caps that block rain from entering the vent while allowing air to flow freely through the connected duct.

Note: Additional Rain Caps are found on page 2968.

Note: Additional Rain Caps are found on page 2968.								
For Duct Dimensions	Cap/Hood Material	Color	Screen Included	Backdraft Damper Included	Brand	Item No.		
Roof Caps								
For Rectangular Duct								
10 ¾ in H x 10 ¼ in	Steel	Black	Yes	Yes	Dayton	45PE68		
For Round Duct								
4 in Dia.	Steel	Black	Yes	Yes	Broan	2C905		
4 in Dia.	Steel	Black	Yes	Yes	Dayton	45PE70		
6 in Dia.	Steel	Black	Yes	Yes	Broan	4YG79		
6 in Dia.	Steel	Black	Yes	Yes	Dayton	45PE69		
8 in Dia.	Steel	Black	Yes	Yes	Broan	61HL78		
Rain Caps								
Star-Kap Hood With Pres								
4 in Dia.	Galvanized Steel	Silver	No	No	Dayton	3TZ72		
6 in Dia.	Galvanized Steel	Silver	No	No	Dayton	3TZ74		
Wall & Soffit Vent Caps								
Louvered Wall Cap								
10 in Dia.	Aluminum	Silver	Yes	No	Broan	4YG77		
Soffit Vent Cap								
4 in Dia., 5 în Dia.	Plastic	White	Yes	Yes	Fantech	15W869		
Wall Cap								
3 % in H x 10 ¼ in	Steel	Black	Yes	Yes	Dayton	45PE72		
4 in Dia.	Aluminum	Silver	No	Yes	Broan	4C388		
4 in Dia.	Aluminum	Silver	No	No	Dayton	45PE71		
4 in Dia. 7 ½ in H x 7 ½ in	Aluminum	Silver	Yes	No	Tjernlund	4C845		
4 in Dia.	Aluminum	Silver	No	Yes	_	499A83		
4 in Dia.	Aluminum	Silver	No	Yes	Field Controls			
4 in Dia.	Aluminum	Silver	Yes	Yes	Broan	793G36		
4 in Dia.	Aluminum	Silver	Yes	No	Field Controls			
6 in Dia.	Aluminum	Silver	Yes	Yes	Broan	4C849		
6 in Dia.	Aluminum	Silver	Yes	Yes	Dayton	45PE74		
6 in Dia.	Aluminum	Silver	Yes	No	Tjernlund	6KXZ2		
6 in Dia.	Aluminum	Silver	Yes	No	Field Controls			
6 in Dia.	Steel	Black	Yes	Yes	Broan	39W643		
8 in Dia.	Aluminum	Silver	No	Yes	Broan	4YG80		
8 in Dia.	Aluminum	Silver	No	Yes	Dayton	45PE73		
8 in Dia.	Aluminum	Silver	Yes	No	Tjernlund	6KXZ3		
10 in Dia.	Aluminum	Silver	Yes	No	Tjernlund	6KXZ4		



#### **Roof & Wall Vent Kits**

For 4" dia. round duct

Provide the essential components to install a weather-resistant duct termination.

Description	Cap/Hood Material	Color	Includes	Screen Included	Damper Included	Item No.
Roof Vent Kit	Steel	Black	Duct, Duct Connector, Mounting Screws, Nylon Zip Ties, Reducer	Yes	Yes	3WE95
Flexible Wall Ducting Kit	Plastic	White	(2) Nylon Zip Ties, 4 in Clamps, 4 to 3 in Foam Reducer, 5 ft Long x 4 in Diameter Flexible Metal Ducting, Square Louvered Wall Vent with Rigid Ducting on Back	No	No	3WE96

(S<sub>&</sub>P)



### **Dryer Booster Inline Duct Fans**

■ Duct: 4" dia. ■ Nominal voltage: 120V AC

Help to increase clothes dryer efficiency when long duct runs are involved. They install into the existing ductwork and help to move the dryer exhaust through the duct network. Sensors activate the fans when they detect the connected dryer is in use. For use where dryer duct runs exceed 25 ft. equivalent.

Soler and Palau have a totally enclosed motor with Class F insulation and backward inclined wheel to overcome extreme pressure in tough installations. Tjernlund handles up to 150 equivalent ft. of duct: straight duct length plus 5 ft. per elbow. Auto-syncs with clothes dryer. Horizontal or vertical duct connection. External motor and lintproof blower.

Airflow @	Motor			Overall Dimensions		Mfr.	ltem
0.000 in SP	Output Power	Motor IP Rating	Includes	HxW	Brand	Model	No.
153 cfm	84 W	IP44	Attached Pressure Switch, Mounting Bracket	7 ¾ in x 7 ¾ in	Soler & Palau	PV-100XPS	6XAR4
153 cfm	84 W	IP44	Current Sensor, Mounting Bracket	7 ¾ in x 7 ¾ in	Soler & Palau	DBF-100XC	6XAR5
160 cfm	7.5 W	_	LED Status Panel	14 1/8 in x 11 1/8 in	Tjernlund	LB2	45EA67
170 cfm	65 W	IP44	5 ½ ft Power Cord With Plug, Mounting Bracket	11 ¾ in x 8 in	Fantech	DBF 4XL	15W791

TJERNLUND 🍪 fantech

BROAN