



Pipe Repair Clamps

Use to repair pipe without dismantling connections and to join pipes without threaded connections. Have 304 stainless steel band and Nitrile gasket.

Redi-Clamp—Use for repairing pinhole leaks, punctures, and splits. Drop-in bolts allow easy installation. Ductile iron lugs and carbon steel nuts and bolts.

Full Circle—Fabricated stainless steel lugs can be installed in tight spaces and may be used to join plain pipe of the same diameter. 304 stainless steel stud bolts. Single-band clamps have 360° gasket seal for support, and a "keeper bar" that helps close clamp during installation. Steel nuts and bolts.

| Pipe Size | Redi-Clamp | | | |
|-----------|----------------------|----------------------|----------------------|-----------------------|
| | 3 in Length Item No. | 6 in Length Item No. | 9 in Length Item No. | 12 in Length Item No. |
| 3/4" | 4NWP2 | — | — | — |
| 1" | — | 4NWP3 | — | — |
| 1 1/2" | 4NWP4 | 4NWP5 | — | — |
| 2" | 4NWP6 | 4NWP7 | 4NWP8 | 4NWP9 |
| 3" | 4NWR1 | 4NWR2 | 4NWR3 | 4NWR4 |
| 4" | 4NWR5 | 4NWR6 | 4NWR7 | 4NWR8 |
| 6" | 4NWR9 | 4NWT1 | 4NWT2 | 4NWT3 |
| 8" | 4NWT4 | 4NWT5 | 4NWT6 | 4NWT7 |

| Pipe Size | Full Circle, Fabricated Stainless Steel Lugs | | | Full Circle, Single Band Ductile Lugs | | |
|-----------|--|---------------------------|-----------------------|---------------------------------------|---------------------------|-----------------------|
| | 7 1/2 in Length Item No. | 12 1/2 in Length Item No. | 15 in Length Item No. | 7 1/2 in Length Item No. | 12 1/2 in Length Item No. | 15 in Length Item No. |
| 2" | 4NWT8 | 5LGJ6 | 4NWT9 | 4NWN1 | 5LGK7 | 4NWN2 |
| 3" | 4NWU1 | 5LGJ7 | 4NWU2 | 4NWN3 | 5LGK8 | 4NWN4 |
| 4" | 4NWU3 | 5LGJ8 | 4NWU4 | 4NWN5 | 5LGK9 | 4NWN6 |
| 6" | 4NWU5 | 5LGJ9 | 4NWU6 | 4NWN7 | 5GLD | 4NWN8 |
| 8" | 4NWU7 | 5LGK0 | 4NWU8 | 4NWN9 | 5GL1 | 4NWP1 |
| 10" | 5LGK1 | 5LGK2 | 5LGK3 | 5GL2 | 5GL3 | 5GL4 |
| 12" | 5LGK4 | 5LGK5 | 5LGK6 | 5GL5 | 5GL6 | 5GL7 |



Two Bolt
24T954

Single Bolt
24T944

304 Stainless Steel Pipe Repair Clamps

For safe repair of cold and hot water lines. Clamps provide a positive seal and have plated malleable iron lugs and a neoprene gasket, except 3- and 4-Bolt Clamps have a gridded Buna N gasket. All models are tagged with pipe size.

| Pipe Size (in.) | Bolt Size (in.) | Item No. | Pipe Size (in.) | Bolt Size (in.) | Item No. |
|--------------------------------|-----------------|----------|-------------------------------|-----------------|----------|
| Single Bolt - 3" Length | | | Three Bolt - 9" Length | | |
| 3/8 | — | 24T944 | 3/4 | — | 5WMP4 |
| 1/2 | — | 24T945 | 1 | — | 5WMP6 |
| 3/4 | 3/8 x 3 | 24T946 | 1 1/4 | 3/8 | 5WMP8 |
| 1 | — | 24T947 | 1 1/2 | — | 5WMR0 |
| 1 1/4 | — | 24T948 | 2 | — | 5WMR2 |
| 1 1/2 | — | 24T949 | 2 1/2 | — | 5WMR4 |
| 2 | — | 24T950 | 3 | — | 5WMR6 |
| 2 1/2 | 3/8 x 4 | 24T951 | 3 1/2 | 7/16 | 5WMR8 |
| 3 | — | 24T952 | 4 | — | 5WMT0 |
| 4 | — | 24T953 | 5 | — | 5WMT2 |
| Two Bolt - 6" Length | | | Four Bolt - 12" Length | | |
| 1/2 | — | 24T954 | 6 | — | 5WMT6 |
| 3/4 | — | 24T955 | 1 | — | 5WMP5 |
| 1 | 3/8 x 3 | 24T956 | 1 1/4 | 3/8 | 5WMP7 |
| 1 1/4 | — | 24T957 | 1 1/2 | — | 5WMP9 |
| 1 1/2 | — | 24T958 | 2 | — | 5WMR1 |
| 2 | — | 24T959 | 2 1/2 | — | 5WMR3 |
| 2 1/2 | 3/8 x 4 | 24T960 | 3 | — | 5WMR5 |
| 3 | — | 24T961 | 4 | 7/16 | 5WMR9 |
| 4 | — | 24T962 | 5 | — | 5WMT1 |
| | | | 6 | — | 5WMT3 |
| | | | 8 | — | 5WMT7 |

Single, Weld Plate
2UKP6



Twin, Weld Plate
2UKR9



Mounting Rail
2UKW5



Weld-Plate and Rail-Mount Vibration Reduction Clamps

- Max. pressure: 1500 psi
- Temp. range: -22° to 194°F

Easy-to-assemble clamps are welded in place or rail mounted to secure hoses, piping, and tubing. Ribs in clamp bore and polypropylene cushioning reduce wear due to vibration, rubbing, and chafing. Meet ASSE standards.

Smooth Bore, Single—Chamfered, smooth core helps to reduce wear and extend the life of hoses.

Single Clamps—Recommended for systems without dynamic loads.

Twin Clamps—Ideal for general-duty applications subject to moderate levels of shock and vibration.

Single Line, Rail-Mount—Use with steel mounting rail 2UKW5 (sold separately) to install multiple clamps side-by-side. Once mounted, clamps can be slid along rail for proper alignment.

| FOR HOSE | | | | |
|---|---------|--------|---------|----------|
| Hose Size | L | W | H | Item No. |
| Smooth Bore, Single, Weld Plate Steel Hardware | | | | |
| 81/100 in | 1.96 in | — | 1.61 in | 2UKW8 |
| 93/100 in | 1.96 in | 1.2 in | 1.61 in | 2UKW9 |
| 1 1/10 in | 2.28 in | — | 1.88 in | 2UKX1 |
| 1 21/50 in | 2.75 in | — | 2.52 in | 2UKX2 |

| FOR TUBE | | | | |
|---|---------|--------|---------|----------|
| Tube Size | L | W | H | Item No. |
| Single, Weld Plate Steel Hardware | | | | |
| 1/4 in | 1.41 in | — | 1.25 in | 2UKP1 |
| 3/8 in | 1.41 in | — | 1.25 in | 2UKP2 |
| 1/2 in | 1.65 in | — | 1.54 in | 2UKP3 |
| 5/8 in | 1.65 in | — | 1.54 in | 2UKP4 |
| 3/4 in | 2.04 in | 1.2 in | 1.61 in | 2UKP5 |
| 7/8 in | 2.04 in | — | 1.61 in | 2UKP6 |
| 1 in | 2.04 in | — | 1.61 in | 2UKP7 |
| 1 1/4 in | 2.83 in | — | 2.52 in | 2UKP8 |
| 1 1/2 in | 2.83 in | — | 2.52 in | 2UKP9 |
| 2 in | 3.46 in | — | 2.83 in | 2UKR1 |
| Stainless Steel Hardware | | | | |
| 3/8 in | 1.41 in | — | 1.25 in | 2UKL9 |
| 1/2 in | 1.65 in | 1.2 in | 1.54 in | 2UKN2 |
| 3/4 in | 2.04 in | — | 1.61 in | 2UKN4 |
| 1 in | 2.04 in | — | 1.61 in | 2UKN5 |
| Single Line, Rail-Mount Steel Hardware | | | | |
| 1/2 in | 1.65 in | — | 1.54 in | 2UKU8 |
| 3/4 in | 2.04 in | — | 1.61 in | 2UKV1 |
| 1 in | 2.04 in | 1.2 in | 1.61 in | 2UKV3 |
| 1 1/2 in | 2.83 in | — | 2.52 in | 2UKV5 |
| 2 in | 3.46 in | — | 2.83 in | 2UKV6 |

| FOR TUBE | | | | |
|--|---------|--------|---------|----------|
| Tube Size | L | W | H | Item No. |
| Twin, Weld Plate Steel Hardware | | | | |
| 1/4 in | 1.45 in | — | 1.69 in | 2UKR9 |
| 3/8 in | 1.45 in | — | 1.69 in | 2UKT1 |
| 1/2 in | 2.16 in | 1.2 in | 1.71 in | 2UKT2 |
| 5/8 in | 2.16 in | — | 1.71 in | 2UKT3 |
| 3/4 in | 2.75 in | — | 2.14 in | 2UKT4 |
| 7/8 in | 2.75 in | — | 2.14 in | 2UKT5 |
| 1 in | 2.75 in | — | 2.14 in | 2UKT6 |
| 1 1/4 in | 4.33 in | — | 2.81 in | 2UKT7 |
| 1 1/2 in | 4.33 in | — | 2.81 in | 2UKT8 |

| FOR PIPE | | | | |
|---|---------|--------|---------|----------|
| Pipe Size | L | W | H | Item No. |
| Single, Weld Plate Steel Hardware | | | | |
| 1/2 in | 2.04 in | — | 1.61 in | 2UKR4 |
| 3/4 in | 2.36 in | — | 1.88 in | 2UKR5 |
| 1 in | 2.83 in | 1.2 in | 2.52 in | 2UKR6 |
| 1 1/4 in | 2.83 in | — | 2.52 in | 2UKR7 |
| 1 1/2 in | 3.46 in | — | 2.83 in | 2UKR8 |
| Stainless Steel Hardware | | | | |
| 1/2 in | 1.96 in | 1.2 in | 1.61 in | 2UKN8 |
| 3/4 in | 2.28 in | — | 1.88 in | 2UKN9 |
| Single Line, Rail-Mount Steel Hardware | | | | |
| 1/2 in | 2.04 in | — | 1.61 in | 2UKV9 |
| 3/4 in | 2.36 in | — | 1.88 in | 2UKW1 |
| 1 in | 2.83 in | 1.2 in | 2.52 in | 2UKW2 |
| 1 1/4 in | 2.83 in | — | 2.52 in | 2UKW3 |
| 1 1/2 in | 3.46 in | — | 2.83 in | 2UKW4 |
| Twin, Weld Plate Steel Hardware | | | | |
| 1/2 in | 2.75 in | 1.2 in | 2.14 in | 2UKU2 |
| 3/4 in | 3.34 in | — | 2.34 in | 2UKU3 |

| L | W | H | Item No. |
|-------|-------|-------|----------|
| 39 in | 28 mm | 11 mm | 2UKW5 |