





## High-Visibility Industrial Pedestal Fans



- Non-oscillating
- 115VAC
- Totally enclosed motors
- Ball bearings
- OSHA-compliant wire guards

Safety-yellow finish attracts attention to help prevent accidental damage to the fan. Pedestal adjusts from 41½" to 59". Fans include an extension cord (15 ft. for 7DJ29 and 14 ft. for 7DJ33) and a 3-position drop cord switch.

Blade Dia.	No. of Speeds	Air Flow	Motor HP	RPM	Amps	Cord Length	Assembly Req.	Item No.
24 in	2	3,800/6,100 cfm	¼ hp	1075/750	3.28/2.29	2 ft	Yes	7DJ29
30 in	2	8,712/9,375 cfm	½ hp	1075/750	3.7/3.12	2 ft	Yes	7DJ33



## Guards for Industrial Cooling Fans



- OSHA-compliant polyester powder-coated wire guards
- Replacement guards enclose fan blades to protect them from damage and prevent injuries from accidental contact. Guards mount to thru-bolts on yoke-mounted or rigid-base motors. Rear section of guard has 4 mounting slots to accommodate motor thru-bolts.

Note: Cradle-type motors cannot be used.

Guard Dia.	Fits Fan Blade Dia.	Color	Mounting Slot O.C.		For Use With	Item No.
			A	B		
19 in	16 in	Gray	2 1/8 in	4 in	48 in Frame Motors, 56 in Frame Motors	2ATB6 2ATB7 2ATB8 2ATB9
21 in	18 in		2 3/4 in	4 1/2 in	2ATC1 2ATC2 1VCH4, 1VCH5	
23 in	20 in					
27 in	24 in					
33 in	30 in					
39 in	36 in					
33 in	30 in	Yellow				1VCH7



## Industrial Pedestal Washdown Fans



- Non-oscillating
- Totally enclosed non-ventilated motors
- Ball bearings
- Hardwired
- OSHA-compliant wire guards

Can be hosed off or pressure washed during cleaning in areas that require regular washdowns. Secondary safety cable included.

Blade Dia.	No. of Speeds	Air Flow	Voltage	Motor HP	Amps	H	Assembly Req.	Item No.
20 in	1	2,670 cfm	115 V AC	1/5 hp	1.1	22 1/2 in	Yes	216NV2
24 in	1	5,220 cfm	115/230 V AC	1/4 hp	1.7/3.3	33 in	Yes	216NV3



## Industrial Pedestal Misting Fans



- Non-oscillating
- 115VAC
- Totally enclosed air-over motors
- OSHA-compliant wire guards

Feature a misting hub that connects to a water source for adding moisture to the air for rapid cooling.

**Schaefer**—4ARK3 has 10 gal. reservoir for up to 5 hr. of run time. 4ARK4 has 14 gal. reservoir for up to 7 hr. of run time and includes integrated wheels and handle.

- Sealed ball bearings

**Dayton**—Fans include pedestal and mounting hardware.

- Ball bearings

Blade Dia.	No. of Speeds	Air Flow	Motor HP	RPM	Amps	H	Height Adjustment	Cord Length	Assembly Req.	Brand	Item No.
<b>Schaefer, Industrial</b>											
18 in	3	1,400/1,800/2,200 cfm	1/10 hp	1000/1400/1570	1.5/1.3/1	42 in	—	25 ft	Yes	Schaefer	4ARK3
18 in	3	1,400/1,800/2,200 cfm	1/10 hp	1000/1400/1570	1.5/1.3/1	Adj 53 to 72 in	53 to 72 in	25 ft	Yes	Schaefer	4ARK4
<b>Dayton, Standard Duty</b>											
20 in	2	3,080/4,750 cfm	1/4 hp	1100/850	1.4/2.0	23 in	41 1/2 in to 59 in	10 ft.	Yes	Dayton	216NT4
24 in	2	3,850/6,200 cfm	1/4 hp	1100/850	3.0/3.6	27 in	41 1/2 in to 59 in	10 ft.	Yes	Dayton	216NT5
30 in	2	8,800/9,800 cfm	1/2 hp	1100/850	3.3/4.2	33 in	41 1/2 in to 59 in	10 ft.	Yes	Dayton	216NT6



## Industrial Fan Accessories

For more industrial fan accessories, go to Grainger.com.

Description	For Use With	Includes	Item No.
<b>Pedestals</b>			
Open Pedestal Base, Adjustable 41½ in to 58½ in		Assembly Hardware	1ZCP4
Pedestal Base, Base Dia. 27 in, Adjustable 41½ in to 59 in	Dayton Yoke-Mounted Fan Heads Up Through 30 in	Assembly Hardware	1ZCP2
Pedestal Base, Base Dia. 27 in, Adjustable 41½ in to 59 in, Safety Yellow	1VCH4, 1VCH5	Assembly Hardware	1ZCP3
Pedestal Base, Base Dia. 33 1/2 in, Open Base, Stainless Steel	1XUA1, 2LYW6, 2LYW5, 2LYW4, 22UK95	—	7DF09
<b>Wheel Kit for Industrial Fans</b>			
Closed Base, Galvanized	1ZCP2D, 1ZCP3D	Brackets, Mounting Hardware, Wheels	40PR87
<b>Misting Kit</b>			
Misting Hub Kit	1VCE7, 1VCE8, 1VCE9, 1VCF6, 1VCF7, 1VCF8, 1VCG3, 1VCG4, 1VCG5, 1VCG6, 1ZCN7, 1ZCN8, 3PEG9	(3) Plugs, (6) Nozzles, 12 ft Tubing, Hose Adapter, In-Line Filter Screen and Washer, Misting Ring, Nylon Zip Ties and Mounting Hardware, Shutoff Valve and Washer	44ZE09
<b>Mounting Brackets</b>			
Ceiling/Wall/Post, Gray	Dayton Yoke-Mounted Fan Heads up to 30 in. Not Intended for Greenhouse or Oscillating Fans when Ceiling Mounted	Secondary Safety Support Cable	1ZCP6
Heavy Duty, Ceiling/Wall/Post, Gray	Dayton Yoke-Mounted Fan Heads up to 36 in. Not Intended for Greenhouse or Oscillating Fans when Ceiling Mounted	Secondary Safety Support Cable	3PEH3
Rafter or I-Beam, Gray	Dayton Yoke-Mounted Non-Oscillating Fan Heads Up Through 30 in. Not intended to be used with Greenhouse or Oscillating Fans.	Secondary Safety Support Cable	1ZCP7
T-Beam or Column, Gray		Secondary Safety Support Cable	1ZCP8
<b>Switches for Industrial Fans</b>			
Drop Cord Rocker Switch, 2-Speed, 3-Position, Yellow	1VCH4, 1VCH5	—	1VCH6
Pull Chain Switch	Dayton 6ALE8D, 6ALE9D, 6ALF0D, 6ALF1D, 13FO45D, 1VCE7D, 1VCE8D, 1VCE9D, 3PEG9D, 13FO47D, 1VCF2D, 1VCF3D, 1VCF4D	3.5 in Chain, 90° Elbow, Extension String, Silver Knurled Nut, Washers	34G191