



1DKX3



3VU33



32MY65



## Portable Standard Electric Jobsite & Garage Heaters

Tubular heating element provides high-efficiency heating. Units use fan-forced air and feature overheat protection. Unit-mounted thermostat included.



3VU34



55VL95

Wattage Output	Voltage (AC)	NEMA Plug Config.	Air Temp. Rise	Thermal Overheat Protection Reset	Overall Height (in)	Overall Width (in)	Overall Depth (in)	Brand	Mfr. Model	Item No.
0.6kW/0.9kW/1.5kW	120V	5-15P	140 °F	Automatic	11 3/4	11 3/4	11 3/4	Air King	8900	1DKX3
	120V	5-15P	72 °F	Manual	15	11 1/2	11	Dayton	3VU31	3VU31
0.75kW/0.9kW/1.5kW	120V	5-15P	72 °F	Manual	15	11	12	Markel Products	188-TMC	31TR31
1.3kW/1.5kW	120V	5-15P	67 °F	Automatic	16	10	9 1/2	Tpi Corp.	188-TASA	31TR33
	120V	5-15P	170 °F	Manual	16	10	8	Dayton	3VU33	3VU33
1.5kW	120V	5-15P	74° to 119°F	Automatic	14	12	12	Pro-Temp	PT-515-120	32MY65
3kW	208/240V	L6-30P	89° to 140°F	Automatic	16	13	14 1/2	Pro-Temp	PT-53-240	32MY66
3kW/4kW	208/240V	6-30P	85 °F	Automatic	14	10 3/4	10 3/4	Dayton	3VU34	3VU34
3.6kW/4.8kW	208/240V	6-30P	48 °F	Automatic	17 1/2	13 1/2	11 1/2	Fostoria	HF684-TC	55VL95
	208/240V	6-30P	95 °F	Automatic	14	10 3/4	10 3/4	Dayton	3VU35	3VU35
4.2kW/5.6kW	208/240V	6-30P	67 °F	Manual	17 1/2	13 1/2	11 1/2	Fostoria	HF686-TC	55VL96
	208/240V	6-30P	105 °F	Automatic	15 1/2	11 1/2	11 1/2	Dayton	3VU36	3VU36



## Portable Salamander Electric Jobsite & Garage Heaters

Use fan-forced air to provide clean, odor-free tempered heat, which raises the area's temperature by a specified amount. Units heat enclosed spaces. Overheat protection prevents damage to the unit. Heaters also have an option to be used as a fan. Built-in thermostat included.

**Wall-Mounting Brackets**—Convert salamander heaters for wall- or ceiling-mount with horizontal air flow. Bottom of heater must be at least 6 ft. from the floor.

**Field-Installed Cable Kits**—Leads are terminated with #10 ring terminals. Cord grip (connector) is included.



52JP79

20HN58



49EL86



1RKT2

Wattage Output	Voltage	Phase	NEMA Plug Config.	Air Temp. Rise	Thermal Overheat Protection*	Overall Height (in)	Overall Width (in)	Overall Depth (in)	Brand	Mfr. Model	Item No.
<b>Heaters</b>											
6kW	208/240V AC	1	14-30P	100 °F	Automatic	17	12	20	Heat Wagon	P600	52JP79
	208/240V AC	1	14-50P	100 °F	Automatic	18	12	23	Heat Wagon	P900	52JP80
9kW	240V AC	1	14-50P	35 °F	Automatic	39	23 1/4	21 3/4	Fostoria	FES-0924-TC	20HN58
	240V AC	1	14-50P	39 °F	Automatic	39	23 1/4	21 3/4	Fostoria	FES-1024-1CA	31V29
10kW	240V AC	1	Hardwired	35° to 89°F	One-Time	40	30	24	Qmark	MEDH1021GKA	49EL86
	240V AC	1	Hardwired	46 °F	Automatic	38 3/4	40	25	Dayton	784J10	784J10
12kW/18kW	208/240V AC	3	Hardwired	100 °F	Automatic	20	14	30	Heat Wagon	P1800-1	5PFX2
	208/240V AC	3	Hardwired	70 °F	Automatic	20	14	30	Heat Wagon	P1800D	52JP81
	208/240V AC	3	Hardwired	100 °F	Automatic	20	14	30	Heat Wagon	P1800-3	5PFX3
	208V AC	3	Hardwired	35° to 88°F	One-Time	40	30	24	Qmark	MEDH1583A	49EL87
	208V AC	3	Hardwired	61 °F	Automatic	38 3/4	25	26 1/4	Dayton	784J11	784J11
	240V AC	1	Hardwired	46 °F	Automatic	38 3/4	25	26 1/4	Dayton	784J18	784J18
	240V AC	1	Hardwired	59° to 141°F	One-Time	40	30	24	Qmark	MEDH1521A	49EL88
	240V AC	3	Hardwired	59° to 141°F	One-Time	40	30	24	Qmark	MEDH1523A	49EL89
	240V AC	3	Hardwired	116 °F	Automatic	38 1/2	28 3/4	21 1/2	Dayton	1RKT2	1RKT2
	480V AC	3	Hardwired	45 °F	Automatic	39	27	21	Fostoria	P15-FES-3E	786DX4
	480V AC	3	Hardwired	46 °F	Automatic	38 3/4	25	26 1/4	Dayton	784J19	784J19
	480V AC	3	Hardwired	70° to 172°F	One-Time	40	30	24	Qmark	MEDH1543A	49EL90
	208V AC	3	Hardwired	45 °F	Automatic	39	27	21	Fostoria	F15-FES-3A	786DX1
	240V AC	1	Hardwired	45 °F	Automatic	39	27	21	Fostoria	H15-FES-1A	786DX3
	240V AC	3	Hardwired	45 °F	Automatic	39	27	21	Fostoria	H15-FES-3E	786DX2
16kW/32kW/40kW	440/480V AC	3	Hardwired	100 °F	Automatic	25	20	46	Heat Wagon	P4000	5PFX4
24kW/48kW/60kW	440/480V AC	3	Hardwired	100 °F	Automatic	25	20	46	Heat Wagon	P6000	5PFX5
	480V AC	3	Hardwired	83 °F	Automatic	39	27	23	Fostoria	P30-FES-3A	786DX5
	480V AC	3	Hardwired	142 °F	Automatic	38 3/4	25	26 1/4	Dayton	784J22	784J22
30kW	600V AC	3	Hardwired	35° to 89°F	Automatic	38 1/2	44	25 1/2	Qmark	SDH3093	2HDA3
	480V AC	3	Hardwired	64 °F	Automatic	39	23 1/4	45 1/2	Fostoria	FES-4548-3	5JNK8
45kW	480V AC	3	Hardwired	59° to 142°F	Automatic	38 1/2	44	25 1/2	Qmark	SDH4893	2HDA5
48kW	480V AC	3	Hardwired	74 °F	Manual	39 1/4	23	45 1/2	Fostoria	FES-6048-3	55VL73
60kW	480V AC	3	Hardwired	74 °F	Manual	39 1/4	23	45 1/2	Fostoria	FES-6048-3	55VL73

\*Automatic=Automatic Reset, One-Time=One-Time Thermal Fuse, Manual=Manual Reset

Sizing Chart	Max. Sq. Ft.*	Max. Ceiling Height
9 to 10 kW	750 up to 1000	12 ft.
15 kW	1000 up to 1500	15 ft.
30 kW	1500 up to 2000	18 ft.
45 kW	2000 up to 2400	24 ft.
60 kW	2400 up to 3600	36 ft.

\* Based on using one single unit.

Description	For Use With	Brand	Mfr. Model	Item No.
<b>Accessories</b>				
Dayton Electric Salamander Heaters: 1RKT2C, 1RKT3C, 1RKT4C, 1RKT5C, 1RKT9C, 1RKT2C		Dayton	1RKT1	1RKT1
Wall Mounting Bracket	Fostoria, FES-09, FES-10, FES-15 & FES-30 Model Salamander Heaters	Fostoria	WMK-FES	3WB11
Field Installed Cable Kit, 4/3 SO	Mfr. No. FES-1524-1A, YES-1524-1A	Fostoria	SO 4/3	3LY29
Field Installed Cable Kit, 6/4 SO	3E216, 3U073, 49EL87, 49EL89, 5E168	Fostoria	SO 6/4	3LY30
Field Installed Cable Kit, 12/4 SO	Mfr. No. FES-1548-3E, YES-1548-3E, FES-1560-3A, YES-1560-3A	Fostoria	SO 12/4	3LY32



3NPV5



2ELP2



49K236

Heating Capacity	Wattage Output	Voltage	NEMA Plug Config.	Air Flow	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
<b>For Use With Work Tents</b>										
5,115 BtuH	1,500 W	120V AC	5-15P	115 cfm	12 in	8 in	12 in	Allegro	9401-50	3NPV5
<b>For Use With SVH-3 Ducting</b>										
23,900 BtuH	3,500 W	240V AC	L6-30P	1,000 cfm	16 in	15 1/2 in	27 1/2 in	Air Systems International	SVF-7KW-8	2ELP2
<b>For Use With Structural Drying, Sanitizing, and Emergency Heating</b>										
37,000 BtuH	11 kW	200/240V AC	Requires Cord	475 cfm	18 in	11 in	30 in	Omnitec Design Inc.	OVH230	49K236
37,000 BtuH	11 kW	200/240V AC	Requires Cord	475 cfm	18 in	11 in	30 in	Omnitec Design Inc.	OVH230RT	49K237



## Portable Electric Ducted & Tent Heaters

Used for heating tents and other confined work areas. 49K236 is variable-speed.