



## Suspended Electric Wall and Ceiling Unit Heaters

■ Accessories available on page 2950 and Grainger.com

Suspend from a bracket or threaded rod for use in downflow or horizontal applications and to save limited floorspace. Units use fan-forced air to provide primary or supplementary heating in large or exposed areas like factories, warehouses, and stock rooms. Find more Electric Wall and Ceiling Heaters on Grainger.com.

Wattage Output	Voltage	Phase	Air Temp. Rise	Air Flow	Overall Height	Overall Width	Overall Depth	Vertical Mounting H	Horizontal Air Throw	Mfr. Model	Item No.
<b>Dayton Heaters (Accessories available on page 2950)</b>											
1.8kW/3.7kW, 2.5kW/5kW	208/240V AC	1	60 °F	270 cfm	12 1/2 in	14 in	11 1/4 in	11 ft	12 ft	3UG73	3UG73
2.2 kW, 3 kW	208/240V AC	1	27 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU58	2YU58
2.5kW/1.9kW	208/240V AC	1	46°F, 60°F	150/130 cfm	12 1/2 in	14 in	14 in	—	—	2HDA1	2HDA1
2.5kW/3.7kW, 3.3kW/5kW	208/240V AC	1	71 °F	210 cfm	16 in	21 in	8 in	15 ft	12 ft	4E169	4E169
3 kW	208V AC	1	27 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU61	2YU61
3 kW	277 V AC	1	27 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	804T11	804T11
3 kW	480V AC	3	27 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU59	2YU59
3.7 kW, 5 kW	208/240V AC	1 or 3	45 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU62	2YU62
5 kW	208V AC	1 or 3	45 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU65	2YU65
5 kW	277V AC	1	45 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU64	2YU64
5 kW	480V AC	3	45 °F	350 cfm	16 in	14 in	8 1/2 in	9 ft	12 ft	2YU63	2YU63
5.6 kW, 7.5 kW	208/240V AC	1 or 3	37 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU66	2YU66
7.5 kW	208V AC	1 or 3	37 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU68	2YU68
7.5 kW	480V AC	3	37 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU67	2YU67
7.5 kW, 10 kW	208/240V AC	1 or 3	49 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU69	2YU69
10 kW	208V AC	1 or 3	49 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU71	2YU71
10 kW	480V AC	3	49 °F	650 cfm	21 3/4 in	19 in	8 1/2 in	14 ft	18 ft	2YU70	2YU70
11.2 kW, 15 kW	208/240V AC	3	52 °F	910 cfm	21 3/4 in	19 in	13 3/4 in	20 ft	35 ft	2YU72	2YU72
15 kW	208V AC	1 or 3	52 °F	910 cfm	21 3/4 in	19 in	13 3/4 in	20 ft	35 ft	2YU74	2YU74
15 kW	480V AC	3	52 °F	910 cfm	21 3/4 in	19 in	13 3/4 in	20 ft	35 ft	2YU73	2YU73
15 kW, 20 kW	208/240V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	13 3/4 in	23 ft	41 ft	2YU75	2YU75
20 kW	480V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	13 3/4 in	23 ft	41 ft	2YU76	2YU76
22.5 kW, 30 kW	208/240V AC	3	45°F/53°F	1,800/2,100 cfm	30 in	26 3/4 in	13 3/4 in	20 ft	50 ft	2YU77	2YU77
25 kW	480V AC	3	38°F/44°F	1,800/2,100 cfm	30 in	26 3/4 in	13 3/4 in	20 ft	50 ft	3END3	3END3
30 kW	208V AC	3	45°F/53°F	1,800/2,100 cfm	30 in	26 3/4 in	13 3/4 in	20 ft	50 ft	2YU79	2YU79
30 kW	480V AC	3	45°F/53°F	1,800/2,100 cfm	30 in	26 3/4 in	13 3/4 in	20 ft	50 ft	2YU78	2YU78
37.5 kW, 50 kW	208/240V AC	3	61 °F	2,600/3,000 cfm	30 in	26 3/4 in	18 1/2 in	25 ft	60 ft	804T14	804T14
40 kW	480V AC	3	42°F/49°F	2,600/3,000 cfm	30 in	26 3/4 in	18 1/2 in	25 ft	60 ft	3END4	3END4
50 kW	480V AC	3	53°F/61°F	2,600/3,000 cfm	30 in	26 3/4 in	18 1/2 in	25 ft	60 ft	2YU81	2YU81
60kW	480V AC	3	60°F	3,400 cfm	35 1/2 in	30 1/2 in	14 1/2 in	31 ft	50 ft	4TDH7	4TDH7
80 kW	480V AC	3	55 °F	5,000 cfm	39 1/2 in	37 1/2 in	18 1/2 in	40 ft	65 ft	4TDH9	4TDH9
<b>Markel Products</b>											
2.5 kW, 3.3 kW	240/208 V	1, 3	26 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5103NHF2B	786LL9
3.3 kW	208 V	1, 3	26 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5103NF2F	786LL8
3.7 kW, 5 kW	240/208 V	1, 3	40 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5105NHF2B	786LM2
5 kW	208 V	1, 3	40 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5105NF2F	786LM0
5 kW	277 V	1	40 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5105NG1G	786LM1
5 kW	480 V	3	40 °F	400 cfm	17 3/4 in	14 1/2 in	6 1/2 in	9 ft	12 ft	5105CAINP3P	786LM3
5.6 kW, 7.5 kW	240/208 V	1, 3	34 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	12 ft	22 ft	5107CA1LHF2B	786LM5
7.5 kW	208 V	1, 3	34 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	12 ft	22 ft	5107CA1LF2F	786LM4
7.5 kW	480 V	3	34 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	12 ft	22 ft	5107CA1NP3P	786LM7
7.5 kW, 10 kW	240/208 V	1, 3	45 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	14 ft	22 ft	5110CA1LHF2B	786LM9
9.9 kW	208 V	1, 3	45 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	14 ft	22 ft	5110CA1LF2F	786LM8
10 kW	277 V	1	45 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	14 ft	22 ft	5110CA1LG1G	786LN0
10 kW	480 V	3	45 °F	700 cfm	24 3/4 in	21 1/2 in	6 1/2 in	14 ft	22 ft	5110CA1NP3P	786LN1
11.2 kW, 15 kW	240/208 V	3	43 °F	1,100 cfm	28 1/4 in	21 1/2 in	6 1/2 in	20 ft	32 ft	5115CA1LHF3B	786LN2
15 kW	480 V	3	43 °F	1,100 cfm	28 1/4 in	21 1/2 in	6 1/2 in	20 ft	32 ft	5115CA1NP3P	786LN3
18.7 kW, 25 kW	240/208 V	3	40/44°F	1,800/2,000 cfm	34 in	29 1/4 in	10 1/4 in	22 ft	45 ft	5125CA1LHF3B	786LN4
25 kW	480 V	3	40/44°F	1,800/2,000 cfm	34 in	29 1/4 in	10 1/4 in	22 ft	45 ft	5125CA1NP3P	786LN5
30 kW	480 V	3	47/53°F	1,800/2,000 cfm	34 in	29 1/4 in	10 1/4 in	20 ft	40 ft	5130CA1NP3P	786LN7
39 kW	480 V	3	40/45°F	2,800/3,100 cfm	34 in	29 1/4 in	10 1/4 in	24 ft	55 ft	5140CA1NP3P	786LN8
50 kW	480 V	3	51/56°F	2,800/3,100 cfm	34 in	29 1/4 in	10 1/4 in	22 ft	50 ft	5150CA1NP3P	786LP0
<b>QMark Heaters (Accessories available on page 2950)</b>											
2.2 kW, 3 kW	208/240V AC	1	27 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0321	25D231
3 kW	208V AC	1	27 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0381	25D233
3 kW	277V AC	1	27 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0371	20CA07
3 kW	480V AC	3	27 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0341	25D232
3.7 kW, 5 kW	208/240V AC	1 or 3	45 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0521	25D234
5 kW	208V AC	1 or 3	45 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0581	25D236
5 kW	277V AC	1	45 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0571	20CA10
5 kW	480V AC	3	45 °F	350 cfm	16 in	14 in	7 1/2 in	9 ft	12 ft	MUH0541	25D235
5.6 kW, 7.5 kW	208/240V AC	1 or 3	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH072	25D237
7.5 kW	208V AC	1 or 3	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH078	25D262
7.5 kW	277V AC	1	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH077	20CA13
7.5 kW	347V AC	1	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH073	20CA11
7.5 kW	480V AC	3	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH074	25D238
7.5 kW	600V AC	3	37 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH076	20CA12
7.5 kW, 10 kW	208/240V AC	1 or 3	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH102	25D239
10 kW	208V AC	1 or 3	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH108	25D251
10 kW	277V AC	1	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH107	20CA17
10 kW	480V AC	3	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH104	25D240
10 kW	480 V AC	3	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	—	—	MUH104-PRO	793EK3
10 kW	600V AC	3	49 °F	650 cfm	21 3/4 in	19 in	7 1/2 in	14 ft	18 ft	MUH106	20CA16
10 kW	600V AC	3	52 °F	910 cfm	21 3/4 in	19 in	12 3/4 in	20 ft	35 ft	MUH156	20CA20
11.2 kW, 15 kW	208/240V AC	3	52 °F	910 cfm	21 3/4 in	19 in	12 3/4 in	20 ft	35 ft	MUH152	25D254
15 kW	208V AC	1 or 3	52 °F	910 cfm	21 3/4 in	19 in	12 3/4 in	20 ft	35 ft	MUH158	25D253
15 kW	480V AC	3	52 °F	910 cfm	21 3/4 in	19 in	12 3/4 in	20 ft	35 ft	MUH154	25D241
15 kW, 20 kW	208/240V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	12 3/4 in	23 ft	41 ft	MUH202	20CA22
20 kW	208V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	12 3/4 in	23 ft	41 ft	MUH208	20CA25
20 kW	480V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	12 3/4 in	23 ft	41 ft	MUH204	20CA23
20 kW	600V AC	3	48 °F	1,320 cfm	21 3/4 in	19 in	12 3/4 in	23 ft	41 ft	MUH206	20CA24
25 kW	480V AC	3	38°F/44°F	1,800/2,100 cfm	30 in	26 3/4 in	11 3/4 in	23 ft	50 ft	MUH254	20CA27
25 kW	600V AC	3	38°F/44°F	1,800/2,100 cfm	30 in	26 3/4 in	11 3/4 in	23 ft	50 ft	MUH256	20CA28
30 kW	480V AC	3	53 °F	1,800/2,100 cfm	30 in	26 3/4 in	11 3/4 in	20 ft	50 ft	MUH304	20CA30
<b>TPI Heaters</b>											
3 kW, 4 kW	208/240V AC	1	53 °F	238 cfm	11 in	10 1/4 in	9 3/4 in	7 to 12 ft	10 ft	HF5840TC	31XL69
3.6 kW, 4.8 kW	208/240V AC	1	74 °F	238 cfm	11 in	10 1/4 in	9 3/4 in	7 to 12 ft	10 ft	HF5848TC	31XL70



3UG73



4TDH7



25D231



20CA07



31XL69