

**BROAN**  **Panasonic**  
**Speed Control and Switches**

Fit a single-gang box.

**Speed Control**—Adjusts sound, speed, CFM, and energy usage. Faceplate not included.

**Switches**—Use to control fans and lights, except 6XAU2 is only for fan control.

**Timer**—Operates as both a fan and light switch, and features programmable delay and ventilation settings.



Switch Color	Plate Color	Type	Voltage	Max. Amps	Brand	Mfr. Model	Item No.
<b>Speed Control</b>							
White	White	Adjustable Speed	120	3 A	Broan	SC100W	6ONT44
<b>Switches</b>							
Black	White	Percentage Timer	24	—	Soler & Palau	SPTL	6XAU2
White	—	Rocker, 2-Function	120	—	Broan	P2RW	55NM01
White	—	Rocker, 3-Function	120	—	Broan	P3RW	55NM02
White	White	2-Function	120	15	Panasonic	FV-WCSW21-W	20JR13
<b>Timer</b>							
White	White	Delay Timer	120	15	Panasonic	FV-WCPT1-W	20JR18



**BROAN**  
**Ducting Accessories**

Designed for 3" and 4" ductwork. Use to vent heat, moisture, and odors from bathrooms, showers, and recreation rooms.

Description	Includes	Mfr. Model	Item No.
Roof Vent Kit, 4" Round	(2) 4 in Clamps, 4 in Dia. Metal Duct Connector, 4 to 3 in Reducer, 8 ft Long x 4 in Dia. Flexible Metal Ducting, Mfr. No. 636 Roof Jack for 3 & 4 in Ducts	RVK1A	3WE95
Wall Vent Kit, 4" Round	(2) Nylon Zip Ties, 4 in Clamps, 4 to 3 in Foam Reducer, 5 ft Long x 4 in Dia. Flexible Metal Ducting, Square Louvered Wall Vent w/ Rigid Ducting On Back	WVK2A	3WE96
3 1/4 x 10" to 6 in Round Transition Duct		411	5C200
3 1/4 x 10" to 7 in Round Transition Duct		412H	4MG71
4 1/2 x 18" 1/2 to 10" in Round Transition Duct		423	4TP55
8 x 12" to 12" Round Transition Duct		T81212	5ZR17

**BROAN** 

**Roof and Wall Caps**

For use on vent terminations.

**Roof Caps**—Steel caps have black epoxy finish. Aluminum caps feature built-in flashing and long riser, and can be used on flat or slightly pitched roofs. 4CK03 and 4CK05 have 1 3/4" H flanges.



Fits Duct Size (in.)	Flange Size (in.)	Construc. Material	Includes	Brand	Mfr. Model	Item No.
<b>Roof Caps</b>						
3 in, 4 in	10 1/4 x 11	Steel	Built-in Bird Screen w/ Removable Damper	Broan	636	2C905
4 in Round	9 1/4 in x 11 3/4 in	Steel	Bird Screen, Built-In Backdraft Damper	Dayton	45PE70	45PE70
6 in	14 1/4 x 18 3/4	Steel	Built-in Bird Screen w/ Cushioned Backdraft Damper	Broan	634M	4YG79
6 in Round	14 1/4 in x 18 3/4 in	Steel	Bird Screen, Built-In Backdraft Damper	Dayton	45PE69	45PE69
8 in	15 3/8 x 15 1/4	Aluminum	Built-in Bird Screen, Built-in Flashing, Long Riser & 1 3/4 in Flange	Broan	611CM	4CK03
10 in	27 1/4 x 18 1/2	Steel	Built-in Bird Screen w/ Backdraft Damper	Broan	437	4YG76
10 1/4 in x 10 3/4 in	14 1/4 in x 18 3/4 in	Steel	Bird Screen, Built-In Backdraft Damper	Dayton	45PE68	45PE68
12 in	17 3/8 x 17 1/2	Aluminum	Built-in Bird Screen, Built-in Flashing, Long Riser & 1 3/4 in Flange	Broan	612CM	4CK05
<b>Wall Caps</b>						
3 in Round, 4 in Round	5 25/32 in x 5 25/32 in	Aluminum	Built-In Backdraft Damper	Dayton	45PE71	45PE71
3 in, 4 in	6 x 6	Aluminum	Built-in Backdraft Damper	Broan	642	4C388
3 3/8 in x 10 1/4 in	5 9/16 in x 12 3/4 in	Steel	Bird Screen, Built-In Spring-Loaded Damper	Dayton	45PE72	45PE72
6 in	9 x 9	Aluminum	Built-in Backdraft Damper & Bird Screen	Broan	641	4C849
6 in Round	9 in x 9 in	Aluminum	Bird Screen & Built-In Spring-Loaded Damper	Dayton	45PE74	45PE74
7 in	9 x 9	Aluminum	9 x 9 in, Built-in Backdraft Damper, Flange & Bird Screen Shields Cap	Broan	647	5E835
8 in	12 1/2 x 13	Aluminum	Built-in Damper	Broan	643	4YG80
8 in Round	12 29/64 in x 12 1/2 in	Aluminum	Built-In Backdraft Damper	Dayton	45PE73	45PE73
10 in	13 x 13	Steel With Aluminum Louvers	Gravity Dampers & Collar w/ Bird Screen	Broan	441	4YG77

**westaflex**   
**Expandable/Flexible Aluminum Ductwork**

- Internal/external temp. range up to 500°F
- Compressed Size: 30"

Strong, lightweight aluminum alloy and installs within walls, wall chases, or ceilings where inaccessibility requires a durable duct. Use in ventilation equipment for air and gas free of corrosive fumes or particles.

15 ft		30 ft		15 ft		30 ft	
Inside Dia.	Brand	Item No.	Brand	Item No.	Brand	Item No.	Brand
3 in	Westaflex	3C590	Westaflex	3XK03	7 in	Stretchflex	59ZX57
4 in	Westaflex	3C591	Westaflex	3XK04	8 in	Westaflex	3XK02
5 in	Stretchflex	59ZX56	Stretchflex	59ZX60	10 in	Stretchflex	59ZX58
6 in	Westaflex	5C201	Westaflex	3XK05	12 in	Stretchflex	59ZX59
							Westaflex
							59ZX61
							3XK06
							3XK07
							3XK08

**Dryer Booster Fans**

Use where dryer duct runs exceed 25 ft. equivalent.

**Soler and Palau**—Feature totally enclosed motor with Class F insulation and backward inclined wheel to overcome extreme pressure in tough installations. 6XAR4 has attached pressure sensor. 6XAR5 has current sensor. Each includes mounting bracket.

**Tjernlund**—Handles up to 150 equivalent ft. of duct: straight duct length plus 5 ft. per elbow. Auto-syncs with clothes dryer. 6-ft. grounded plug. Horizontal or vertical duct connection. External motor switch. 6XAR5 has current sensor and lintproof blower.



CFM @ Static Pressure Shown						Voltage	Housing Dia.	Housing Height	Duct Dia.	Inlet Dia.	Watts	Max. Amps	Brand	Mfr. Model	Item No.
0.000"	0.200"	0.400"	0.600"	0.800"	1.000"										
153 cfm	130 cfm	114 cfm	97 cfm	84 cfm	80 cfm	115 V AC	9 1/2 in	7 7/8 in	4 in	4 in	84 W	0.7 A	Soler & Palau	PV-100XPS	6XAR4
153 cfm	130 cfm	114 cfm	97 cfm	84 cfm	80 cfm	115 V AC	9 1/2 in	7 7/8 in	4 in	4 in	84 W	0.7 A	Soler & Palau	DBF-100XC	6XAR5
160 cfm	140 cfm	120 cfm	114 cfm	105 cfm	87 cfm	120 V AC	14 in	10 1/2 in	4 in	4 in	50 W	0.53 A	Tjernlund	LB2	45EA67