



Portable Blowers/Carpet Dryers

- Space-saving design
- 3-conductor power cords

Dry carpets, furniture, and hard floors after spills and cleaning treatments. Have a thermally protected motor that will automatically shut down if overheated, then will restart automatically once motor has cooled. Models are stackable up to 5 units high except 4XLE2. All blowers/dryers are suitable for use in commercial janitorial and plumbing applications. 4XLE2 is UL and CUL Listed.



Airflow Direction	CFM High	Number of Speeds	Power Cord Length	Number of Power Outlets	Item No.
Horizontal	1,800 cfm	2	25 ft	0	61HL71
	300 cfm	1	10 ft	0	61HL68
Horizontal, Vertical	700 cfm	3	10 ft	2	61HL69
	1,050 cfm	2	25 ft	2	61HL70
	1,648 cfm	3	25 ft	0	4XLE2



Industrial/Jobsite Blowers and Carpet Dryers

- Stackable compact design
- Hospital-grade cord with lit plug, except 425X94

Rugged, compact, and efficient units are ideal for ventilation and for drying floors, structures, and walls. Accessories are available on Grainger.com.

39C367—Quickly dries up to 80 sq. ft. of carpet or hard floors. Compact and lightweight model is ideal for bathrooms, cabinets, or closets. ETL tested to UL/CSA standards.

- 360° airflow

38MC15—Lightweight air mover dries floors, stairways, and walls. Variable speed control and digital amp readout.

- Daisy chain up to 10 units on 1 circuit

5UNZ4—Use to ventilate confined spaces, create negative air pressure, and remove odors or dust. UL and C-UL Listed.

- High static pressure
- Duct up to 125 ft.

425X94—High-velocity, variable air flow for ventilating and drying ceilings, floors, and walls. Focus airflow with integrated pivot-and-lock stand. ETL tested to UL/CSA standards.

- Up to 2.7A draw
- Can daisy chain up to 4 units on 1 circuit

786F11—Low-profile unit is suitable for use in confined space ventilating and has a GFCI-protected power outlet socket with reset switch. ETL tested to UL/CSA standards.

- Up to 2.1A draw
- Can daisy chain up to 6 units on 1 circuit



Airflow Direction	CFM High	Number of Speeds	Power Cord Length	Number of Power Outlets	Amps	Motor HP	Housing Height	Housing Length	Housing Width	Item No.
360°	750 cfm	1	10 ft	0	1.1 A	1/6 hp	9 in	15 1/4 in	15 1/4 in	39C367
Horizontal	885 cfm	Variable	15 ft	2	1.2 A	1/4 hp	9 in	24 in	18 in	38MC15
Horizontal, Vertical	2,041 cfm	1	20 ft	0	7.4 A	1 hp	19 1/4 in	15 3/4 in	18 3/4 in	5UNZ4
Horizontal, Vertical	2,600 cfm	Variable	16 ft	1	2.7 A	1 1/2 hp	24 1/2 in	10 1/2 in	24 3/8 in	425X94
Horizontal; Lateral; Vertical	885 cfm	2	15 ft	1	2.1 A	1/4 hp	9 in	24 in	18 in	786F11

Item	For Use With	Mfr. Model	Item No.
Filters			
HEPA Filter	Mfr. No. F504	F518	34CF05
Replacement HEPA Filter	Mfr. No. F504/F505	F519	38ZL91
Replacement Pre-Filter	Mfr. No. F504/F505	F520	38ZL92
Accessories			
Extension Duct	5UNZ4 Vortex Axial Fan and 4AYF5 Portable Air Scrubber	F405	5UNZ9



Pivoting Utility Blowers

- 120V, 60 Hz
- 3 speeds
- OSHA-compliant guards

High-velocity, focused air flow and innovative 225° or 270° pivoting fan heads ventilate and cool work areas while keeping dust and debris in check. 2 grounded 120V outlets accommodate power tools or other devices up to 10A total. 3-conductor 10-ft. cords: 1XGG3 and 2EKZ9 Type S with 5-15P GFCI plug; 1XGG2 Type S with 5-15P plug.

2EKZ9 is safety yellow. See instructions for applicable limitations of use. ETL and C-ETL Listed.



Blower Wheel Dia.	CFM High	CFM Med.	CFM Low	Amps	Motor HP	Housing Dim.			Outlet Dim.		Mfr. Model	Item No.
						W	H	L	W	H		
6 in	310 cfm	260	190	0.65/0.55/0.50 A	1/8 hp	9 1/4 in	11 1/4 in	11 1/2 in	6 1/2 in	3 in	9550	1XGG2
7 in	350 cfm	300	250	0.95/0.80/0.70 A	1/3 hp	11 in	14 1/2 in	13 in	8 in	4 in	9555	1XGG3
7 in	350 cfm	300	250	0.95/0.80/0.70 A	1/3 hp	11 in	14 1/2 in	13 in	8 in	4 in	9566	2EKZ9