Air Conditioners

FRIGIDAIRE (1) LG









Residential-Grade Window Air Conditioners

- Programmable, except 470D39 and 61CZ61
- 24-hr. timer, except 470D39 and 61CZ61 Units are made of residential-grade materials and have a decorative front grille that blends in with home interiors. Typically used to cool rooms in houses and apartments. Remote capability, except 470D39 and 61CZ61.

Frigidaire-FHW models are Wi-Fi capable.

LG-61CZ62 has a variable-speed compressor that adjusts the compressor motor speed to regulate temperature for greater energy efficiency.

Perfect Aire—Feature a remote control with a built-in room temperature - Auto restart sensor that regulates room temperature • Left/right reversible power cord around the remote, allowing the remote • Washable filter to become the thermostat.

Friedrich—CCW and CEW models can be installed in a window or through the wall. All units can be managed via Wi-Fi to allow centralized control of settings. Compatible with Amazon Alexa and Google Home. Units have Seacoast Protection to guard against corrosion.

- Quiet operation



55KJ56



Cooling	Average	CEER	Valtage	NEMA Plug	No. of	н	w	D	Chassis	Brand	Mfr. Model	Item No.
Cap. Cooling Only	Coverage Area	Rating	Voltage	Configuration	Speeds	н	W	и	Туре	вгапа	Model	NO.
5,000 BtuH	100 to 150 sa ft	12.1	115 V AC	LCDI, 5-15P	2	12 in	16 in	15 ¼ in	Fixed	Frigidaire	FFRE053WA1	61DD85
5,000 BtuH	100 to 150 sq ft	11.0	115 V AC	LCDI, 5-15P	2	11 1/8 in	17 3/8 in	14 % in	FIXEU	La Commercial	LW5016	61CZ61
5,000 BtuH	100 to 150 sq ft	12.1	115 V AC	LCDI, 5-15P		12 ½ in	16 in	13 ½ in		Perfect Aire	5PAC5000	60FV08
5,050 BtuH	100 to 150 sq ft	11.0	115 V AC	LCDI, 5-15P	2	11 % in	16 ½ in	16 ½ in	Fixed	Frigidaire	FFRA051WA1	470D39
6,000 BtuH	150 to 250 sq ft	12.1	115 V AC	LCDI, 5-15P	3	13 ½ in	18 ½ in	19 ¾ in	Slide Out	Friedrich	CCW06B10B	60RE42
6,000 BtuH	150 to 250 sq ft	12.1	115 V AC	LCDI, 5-15P	Variable	13 ¼ in	18 ½ in	15 1/4 in	Fixed	Frigidaire	FHWW063WB1	55KJ54
6,000 BtuH	150 to 250 sq ft	12.1	115 V AC	LCDI, 5-15P	_	13 ½ in	18 ¾ in	13 ¾ in		Perfect Aire	5PAC6000	60FV09
8,000 BtuH	300 to 350 sq ft	12.0	115 V AC	LCDI, 5-15P	3	13 ½ in	18 ½ in	19 ¾ in	Slide Out	Friedrich	CCW08B10B	60RE43
8,000 BtuH	300 to 350 sq ft	12.0	115 V AC	LCDI, 5-15P	Variable	13 1/4 in	18 ½ in	17 ½ in	Fixed	Frigidaire	FHWW083WB1	55KJ55
10,000 BtuH	400 to 450 sq ft	12.0	115 V AC	LCDI, 5-15P	3	14 % in	19 ¾ in	23 ¾ in	Slide Out	Friedrich	CCW10B10	55HF05
10,000 BtuH	400 to 450 sq ft	12.0	115 V AC	LCDI, 5-15P	Variable	14 ½ in	19 in	21 ½ in	Fixed	Frigidaire	FHWW103WB1	55KJ56
10,000 BtuH	400 to 450 sq ft	12	115 V AC	LCDI, 5-15P	3	14 ½ in	19 in	21 ½ in	Fixed	Frigidaire	FFRE103WA1	61DD88
12,000 BtuH	450 to 550 sq ft	12.0	115 V AC	LCDI, 5-15P	3	14 % in	19 ¾ in	23 ¾ in	Slide Out	Friedrich	CCW12B10	55HF06
12,000 BtuH	450 to 550 sq ft	12.0	115 V AC	LCDI, 5-15P	Variable	14 ½ in	19 in	21 ½ in	Fixed	Frigidaire	FHWW123WB1	55KJ57
12,000 BtuH	450 to 550 sq ft	12	115 V AC	LCDI, 5-15P	3	14 ½ in	19 in	21 ½ in	Fixed	Frigidaire	FFRE123WA1	61DD89
15,000 BtuH	550 to 700 sq ft	11.8	115 V AC	LCDI, 5-15P	3	18 in	23 % in	25 % in	Slide Out	Friedrich	CCW15B10	55HF07
15,000 BtuH	550 to 700 sq ft	11.8	115 V AC	LCDI, 5-15P	Variable	17 % in	23 % in	25 ¾ in	Fixed	Frigidaire	FHWW153WB1	55KJ58
15,000 BtuH	700 to 1000 sq ft	10.7	115 V AC	LCDI, 5-15P		18 in	23 ¾ in	0=0/1		Perfect Aire	5PAC15000	216UU5
15,100 BtuH	550 to 700 sq ft	11.8	115 V AC	LCDI, 5-15P	3	17 % in	23 % in	25 % in	Slide Out	Frigidaire	FFRE153WA1	61DD90
18,000 BtuH	700 to 1000 sq ft	11.8	208/230 V AC	LCDI, 6-20P	3	18 in	23 % in	25 ¾ in	Slide Out	Friedrich	CCW18B30	55HF08
18,000 BtuH	700 to 1000 sq ft	11.8	230 V AC	LCDI, 6-15P	3	17 % in	23 % in	25 ¾ in	Slide Out	Frigidaire	FHWC183WB2	61DD91
22,000 BtuH 24,000 BtuH	1000 to 12000 sq ft	10.0/10.0 10.3	208/230 V AC 208/230 V AC	LCDI, 5-15P LCDI, 6-20P	4 3	17 ¾ in 18 % in	26 in 27 in	26 ¼ in 26 % in	Slide Out Slide Out	Lg Commercial Friedrich	LW2217IVSM CCW24B30	61CZ62 55HF09
25.000 BtuH	1400 to 1500 sq ft 1400 to 1500 sq ft	10.3	230 V AC	LCDI, 6-20P	3	18 % in	26 ½ in	26 ½ in	Slide Out	Frigidaire	FHWC253WB2	61DD92
25,000 BtuH	1400 to 1500 sq ft	9.5	230 V AC	LCDI, 6-20P		18 ¾ in	26 ½ in	26 ¾ in	Slide Out	Perfect Aire	3PACH25000	379A66
28,000 BtuH	1400 to 1500 sq ft	9.4	230 V AC	LCDI 6-30P	3	18 % in	26 ½ in	26 ½ in	Slide Out	Frigidaire	FHWC282WB2	61DD93
Slider/Caseme		J.7	200 V A0	LODI, O OOI		10 78 111	20 /2 111	20 /2 111	Olide Out	Trigidano	TTTWOZOZWDZ	010030
8.000 BtuH	300 to 350 sa ft	11.2	115 V AC	LCDI, 5-15P	3	20 1/4 in	14 ½ in	25 ½ in	Fixed	Frigidaire	FFRS0822SE	45RK41
10.000 BtuH	400 to 450 sq ft	10.4	115 V AC	LCDI, 5-15P	3	20 1/4 in	14 ½ in	23 ½ in	Fixed	Frigidaire	FFRS1022RE	22XR23
	g, Electric Heat											
8.000 BtuH	300 to 350 sq ft	10.9	115 V AC	LCDI, 5-15P	3	14 % in	19 ¾ in	23 ¾ in	Slide Out	Friedrich	CEW08B11A	55HF10
12,000 BtuH	450 to 550 sq ft	10.9	208/230 V AC	LCDI, 6-20P	3	14 % in	19 ¾ in	23 ¾ in	Slide Out	Friedrich	CEW12B33	55HF11
12,000 BtuH	450 to 550 sq ft	10.9	230 V AC	6-20P		16 1/4 in	22 ¾ in	23 1/4 in		Perfect Aire	3PACH12000	60FV10
18,000 BtuH	700 to 1000 sq ft	10.7	208/230 V AC	LCDI, 6-20P	3	18 in	23 % in	25 % in	Slide Out	Friedrich	CEW18B33	55HF12
24,000 BtuH	1400 to 1500 sq ft	9.4	208/230 V AC	LCDI, 6-20P	3	18 % in	27 in	26 % in	Slide Out	Friedrich	CEW24B33	55HF13
Cooling/Heating, Cooling Only, Electric Heat												
18,000 BtuH	700 to 1000 sq ft	10.7	230 V AC	LCDI, 6-30P	3	17 % in	23 % in	25 % in	Slide Out	Frigidaire	FHWE182WA2	61DD96
25,000 BtuH	1400 to 1500 sq ft	9.4	230 V AC	LCDI, 6-30P	3	18 % in	26 ½ in	26 ½ in	Slide Out	Frigidaire	FHWE252WA2	61DD97
	g, Cooling Only, Electr						00.57.1	00.1/.1			E1 11 4 11 10 0 0 14 14 1	
8,000 BtuH	300 to 350 sq ft	9.8	115 V AC	LCDI, 5-15P	3	15 % in	22 % in	23 ¼ in	Slide Out	Frigidaire	FHWH082WA1	61DD94
	g, Electric Heat, Heat	Pump 9.8	115 V AC	LCDI, 5-15P	2	15 % in	22 5/8 in	23 1/4 in	Slide Out	Erigidaire	FHWH112WA1	61DD95
11,000 BtuH Cooling/Heatin	400 to 450 sq ft	9.0	IID V AU	LUDI, 5-15P	3	10 9/8 10	ZZ 9/8 III	23 /4 111	Silue Out	Frigidaire	rnvvn112vvA1	פפעעוויי
7,500 BtuH	250 to 300 sq ft	11.0	115 V	5-15P	2	13 ²² / ₂₅ in	18 11/25 in	20 ²² / ₂₅ in	Sliding	Lg	LW8016HR	63ZA18
I,JUU DIUN	230 to 300 Sq It	11.0	113 V	J-13F		10 -725 111	10 1/25 111	ZU -725 III	Julily	∟y	LWUUIUIIN	00LH 10

Air Conditioner Covers

Fit over the front grille or outside cabinet of an idle AC unit to block drafts, dirt, and allergens

from entering a building.					
Description	For Use With	Includes	Mfr. Model	Item No.	
Window Air (Conditioner Covers, Frost King				
Outdoor	Small Window Air Conditioners	(1) 18 in x 27 in x 16 in Polyurethane Reinforced Vinyl Air Conditioner Cover	AC2H	426R64	
Outdoor	Large Window Air Conditioners	(1) 20 in x 28 in x 30 in Polyurethane Reinforced Vinyl Air Conditioner Cover	AC5H	426R65	
Indoor	Small Window Air Conditioners	(1) 17 in x 25 in Quilted Fabric Air Conditioner Cover	AC9H	426R66	
Indoor	Large Window Air Conditioners	(1) 20 in x 28 in Quilted Fabric Air Conditioner Cover	AC11H	426R67	
Through-the	-Wall Air Conditioner Cover, Chill Stop'R	• •			
Indoor	Through-The-Wall Air Conditioners Up	_	1212-06	5E169	



FRIEDRICH



426R65



Hazardous Location Throughthe-Wall Air Conditioners

■ Hot gas bypass for cooling operation at low ambient temps., down to 45°F (7°C) without freezing Sealed motor and solid-state relays prevent sparking while cooling potentially hazardous environments. Can be used where flammable gases, vapors, and liquids are handled or used within enclosed containers or systems, but are not normally present in concentrations high enough to be ignitable. Commonly used to cool laboratories, control rooms, and storage areas. These commercial-grade units have an e-coated coil and powder-coated steel cabinet to resist corrosion. Units are hardwired and have a 15A circuit with a timedelay fuse. Meet ANSI/UL 484 Room A/C, SASO 2681, UL Listed for use in Class I, Div. 2, Groups A, B, C and D, ISA 12.12.101, and NFPA 70.

Cooling		Average	No. of						Mfr.	Item
	Cap.	Coverage Area	EER	Voltage	Speeds	Н	W	D	Model	No.
	14,000/14,500 BtuH	550 to 700 sq ft	9.7/9.7	208/230V AC	1	15 15/16 in	25 15/16 in	27 % in	SH15M30	22D138
	21 000/21 000 RtuH	700 to 1000 cg ft	0.6/0.7	2U8/33U/\ VC	- 1	17 15/c in	25 15/4c in	27.3% in	CHJUMJO	35MW/48

