



FRIEDRICH

Commercial-Grade Through-the-Wall **Air Conditioners**

- Programmable Auto restart
- Control panel lockout (ON-OFF) Quiet operation
- 24-hr. timer Anti-intrusion protection

These through-the-wall air conditioners are made for commercial-grade applications with components that withstand more demanding environments. They're commonly used for cooling offices, retail stores, multifamily buildings, barracks, and dorms. Units have remote capability and can be managed via Wi-Fi to allow centralized control of settings for one or more units. They're also compatible with Amazon Alexa and Google Home. New installations require a wall sleeve and fit in Friedrich and Fedders A and B 27" sleeves.

Cooling Cap.	Average Coverage Area	CEER Rating	Voltage	NEMA Plug Configuration	No. of Speeds	н	W	D†	Mfr. Model	Item No.
Cooling Only	ooro.ugoou	· · · · · · · · · · · · · · · · · · ·	Tonago		оросио					
8,000 BtuH	300 to 350 sq ft	10.6	115V AC	LCDI, 5-15P	3	15 ¾ in	26 ½ in	21 in	WCT08A10	494L39
10,000 BtuH	400 to 450 sq ft	10.6	115V AC	LCDI, 5-15P	3	15 ¾ in	26 ½ in	21 in	WCT10A10	494L40
10,000 BtuH	400 to 450 sq ft	10.6	230V AC	LCDI, 5-15P	3	15 ¾ in	26 ½ in	21 in	WCT10A30	494L41
12,000 BtuH	450 to 550 sq ft	9.5	115V AC	LCDI, 5-15P	3	15 ¾ in	26 ½ in	21 in	WCT12A10B	494L42
12,000 BtuH	450 to 550 sq ft	9.5	230V AC	LCDI, 6-15P	3	15 ¾ in	26 ½ in	21 in	WCT12A30B	494L43
16,000 BtuH	550 to 700 sq ft	9.3	230V AC	LCDI, 6-15P	3	15 ¾ in	26 ½ in	21 in	WCT16A30	494L44
Cooling/Heating										
10,000 BtuH	400 to 450 sq ft	10.6	230V AC	LCDI, 6-20P	3	15 ¾ in	26 ½ in	21 in	WET10A33	494L36
12,000 BtuH	450 to 550 sq ft	9.5	230V AC	LCDI, 6-20P	3	15 ¾ in	26 ½ in	21 in	WET12A33	494L37
15,400 BtuH	550 to 700 sq ft	9.3	230V AC	LCDI, 6-20P	3	15 ¾ in	26 ½ in	21 in	WET16A33	494L38
Cooling/Heating. Heat Pump										
12,000 BtuH	450 to 550 sq ft	9.3	230V AC	LCDI, 6-20P	3	15 ¾ in	26 ½ in	21 in	WHT12A33	494L45
Accessories										
Architectural Grille									AG	3UD86
Drain Kit									DK	3UD88
Wall Sleeve, 16 ¾ inH x 27 inW x 16 ¾ inD, For Use With Wall master through the wall air conditioners									WSE	4PKZ3
† Depth includes front cover.										



Residential-Grade Throughthe-Wall Air Conditioners







■ 24-hr. timer Auto restart

470D57

Washable filter

Through-the-wall air conditioners that are made of residentialgrade materials and have a decorative front grille that blends in with home interiors. They're typically used to cool rooms in houses and apartments. Units include a remote control.

Friedrich-Units can be managed with Wi-Fi and are compatible with Amazon Alexa and Google Home. Units have Seacoast Protection to guard against corrosion. Trim kit is included to give units a finished appearance. Chassis fits 241/2" to 27" sleeves.

Quiet operation

Frigidaire—Chassis fits most existing wall sleeves. New installations require Wall Sleeve Kit 5PP42.

■ Programmable

GE—Units are ADA compliant. Wall sleeve is included.

■ Programmable

Perfect Aire—Feature a remote control with a built-in room temperature sensor that regulates room temperature around the remote, allowing the remote to become the thermostat.

Programmable

	- Programmable								
Cooling Cap.	Average Coverage Area	CEER Rating	Voltage - Plug Type	Fits Wall Sleeve Dimensions	Brand	Mfr. Model	Item No.		
Cooling Only									
8,000 BtuH	300 to 350 sq ft	10.6	115V AC, 5-15P	15 ½ in x 25 ¾ in x 16 ¾ in	Friedrich	UCT08A10	494L30		
8,000 BtuH	400 to 450 sq ft	9.5	115V AC, LCDI 5-15P	15 ¼ in x 25 ½ in x 17 ½ in	Perfect Aire	4PATW8000	216UU7		
9,800/10,000 BtuH	400 to 450 sq ft	10.6	208/230V AC, 6-15P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTA103WA2	470D59		
10,000 BtuH	400 to 450 sq ft	10.6	115V AC, 5-15P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UCT10A10	494L31		
10,000 BtuH	400 to 450 sq ft	10.6	230V AC, 6-15P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UCT10A30B	494L32		
10,000 BtuH	400 to 450 sq ft	10.6	115V AC, 5-15P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTA103WA1	470D58		
10,000 BtuH	400 to 450 sq ft	9.5	115V AC, LCDI 5-15P	15 ¼ in x 25 ½ in x 17 ½ in	Perfect Aire	4PATW10000	379A69		
11,700/12,000 BtuH	450 to 550 sq ft	10.5	208/230V AC, 6-15P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTA123WA2	470D62		
12,000 BtuH	450 to 550 sq ft	10.5	115V AC, 5-15P	15 ½ in x 25 ¾ in x 16 ¾ in	Friedrich	UCT12A10	494L33		
12,000 BtuH	450 to 550 sq ft	10.5	230V AC, 6-15P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UCT12A30	494L34		
12,000 BtuH	450 to 550 sq ft	10.3	115V AC, 5-15P	15 ¼ in x 25 ½ in x 17 ½ in	Perfect Aire	4PATW12000	379A71		
14,000/14,000 BtuH	550 to 700 sq ft	9.3	208/230V AC, 6-15P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTA142WA2	470D64		
14,000 BtuH	550 to 700 sq ft	9.3	230V AC, 6-20P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UCT14A30B	494L35		
14,000 BtuH	550 to 700 sq ft	9.5	230V AC, LCDI 6-15P	15 ¼ in x 25 ½ in x 17 ½ in	Perfect Aire	3PATW14002	216UV1		
Cooling/Heating, Electric Heat									
4,100/8,300 BtuH	300 to 350 sq ft		115V AC, 5-20P	15 % in x 26 in x 16 % in	GE	AJEQ08AWH	6AMC2		
8,000 BtuH	300 to 350 sq ft	9.6	115V AC, 5-15P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UET08A11	494L26		
8,000 BtuH	300 to 350 sq ft	9.6	115V AC, 5-15P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTH082WA1	470D57		
9,800/10,000 BtuH	400 to 450 sq ft	9.6	208/230V AC, 6-20P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTH102WA2	470D60		
10,000 BtuH	400 to 450 sq ft	9.6	230V AC, 6-20P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UET10A33	494L27		
11,400/11,600 BtuH, 9,500/11,600 BtuH	400 to 450 sq ft		208/230V AC, 6-20P	15 % in x 26 in x 16 % in	GE	AJEQ12DCH	6AMC3		
12,000 BtuH	450 to 550 sq ft	9.6	230V AC, 6-20P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UET12A33	494L28		
12,000 BtuH	450 to 550 sq ft	9.5	230 V, 6-20P	15 % in x 25 ¾6 in	Frigidaire	FFTH122WA2	61DD99		
14,000/14,000 BtuH	550 to 700 sq ft	9.3	208/230V AC, 6-20P	15 ¼ in x 25 ½ in x 16 in, 17 ½ in or 22 in	Frigidaire	FFTH142WA2	470D65		
14,000 BtuH	550 to 700 sq ft	9.3	230V AC, 6-20P	15 ½ in x 25 % in x 16 ¾ in	Friedrich	UET14A33	494L29		
14,000 BtuH	550 to 700 sq ft	9.5	230V AC, 5-20P	15 ¼ in x 25 ½ in x 17 ½ in	Perfect Aire	3PATWH14002	60FV11		
Accessories									
Architectural Grille, For Use with Friedric	h Uni-Fit Through Th	e Wall USC	Sleeve		Friedrich	UXAA	46E371		
Architectural Grille, For Use with Frigidain	re Through The Wall	Air Conditio	ners		Frigidaire	5304515640	5H443		
Through-The-Wall AC Sleeve, 15 1/4 in He	Perfect Aire	PAWS1	60KZ92						
Wall Sleeve with Weather Seals, 151/4 H >	Frigidaire	5304522751	5PP42						
Wall Sleeve, 15½ H x 25% W x 16¾"D, F	or Use With Friedric	h Uni-Fit Air	Conditioners		Friedrich	USC	2RLC7		

2992