



55KJ59



40JZ85



60RE40

FRIGIDAIRE **Dayton** **FRIEDRICH** **LG**
Light-Duty Portable Air Conditioners

- 115V
- Outside venting required
- Window adapter kit included

Can be wheeled into place to cool a small room or supplement the primary air conditioning system in offices, schools, and other areas. Require ducting to discharge hot exhaust air to the outdoors.

Friedrich—Window slider kit fits vertical and horizontal openings.

BtuH Cooling - DOE SACC	Average Coverage Area	NEMA Plug Configuration	No. of Speeds	Max. Exhaust Hose Length	Max. Supply Hose Length	H	W	D	Key Features	Brand	Mfr. Model	Item No.
Cooling Only, Air-Cooled Ducted												
3,800 BtuH	100 to 150 sq ft	LCDI, 5-15P	3	5 ft	17 ft	31 3/4 in	19 1/2 in	16 1/2 in	Remote Control, WiFi-Capable	Frigidaire	GHPG132AB1	55KJ59
5,225 BtuH	100 to 150 sq ft	LCDI, 5-15P	3	6 ft 7 in	—	24 3/4 in	11 3/4 in	17 3/4 in	Programmable, Remote Control	Dayton	40JZ85	40JZ85
5,300 BtuH	100 to 150 sq ft	LCDI, 5-15P	2	5 ft	—	27 3/4 in	13 3/4 in	14 in	Programmable, Remote Control	Dayton	60YP69	60YP69
7,000 BtuH	250 to 300 sq ft	LCDI, 5-15P	2	5 ft	—	27 3/4 in	13 3/4 in	14 in	Programmable, Remote Control	Dayton	60YP70	60YP70
8,000 BtuH	300 to 350 sq ft	LCDI, 5-15P	3	5 ft	—	27 3/4 in	17 1/2 in	14 3/4 in	Programmable, Remote Control	Dayton	60YP71	60YP71
Cooling Only, Air-Cooled Vented												
5,000 BtuH	Up to 200 sq ft	LCDI, 5-15P	4	5 ft	5 ft	27 3/4 in	16 1/2 in	12 3/4 in	LCD Remote, Sleep Control Function, WiFi Capable	Friedrich	ZCP08SA	60RE37
6,000 BtuH	Up to 300 sq ft	LCDI, 5-15P	4	5 ft	5 ft	27 3/4 in	16 1/2 in	12 3/4 in	LCD Remote, Sleep Control Function, WiFi Capable	Friedrich	ZCP10SA	60RE38
7,500 BtuH	Up to 400 sq ft	LCDI, 5-15P	3	5 ft	5 ft	28 3/4 in	17 1/2 in	14 1/4 in	Condensate Overflow Protection, LCD Remote, Self-Evaporative Condensate System, WiFi Capable	Friedrich	ZCP12DB	60RE40
8,000 BtuH	450 to 550 sq ft	LCDI, 5-15P	4	5 ft	5 ft	27 3/4 in	16 1/2 in	12 3/4 in	LCD Remote, Sleep Control Function, WiFi Capable	Friedrich	ZCP12SA	60RE39
10,000 BtuH	400 to 450 sq ft	LCDI, 5-15P	Variable	—	—	30 3/4 in	19 3/4 in	18 3/4 in	24 hr On/Off Timer, Cellular Control, Electronic, On/Off and Temp. Control, WiFi Control	Lg Commercial	LP1419IVSM	61CZ65
Cooling/Heating, Heat Pump, Air-Cooled Vented												
9,500 BtuH	Up to 500 sq ft	LCDI, 5-15P	3	5 ft	5 ft	28 3/4 in	17 1/2 in	14 1/4 in	Condensate Overflow Protection, LCD Remote, Self-Evaporative Condensate System, WiFi Capable	Friedrich	ZHP14DB	60RE41



43LD80



6RH7



Heavy-Duty Air-Cooled Portable Air Conditioners

- 24-hr. timer

Provide cool, dehumidified air for cooling people, processes, and equipment. Ideal for rack enclosures, network closets, and areas without access to facility HVAC. Condensate is re-evaporated for drip-free operation, so no floor drain is required and no water tank needs to be emptied.

Cooling Cap.	Average Coverage Area	Voltage	NEMA Plug Configuration	No. of Speeds	Max. Exhaust Hose Length	Max. Supply Hose Length	H	W	D	Key Features	Item No.
Cooling Only, Air-Cooled Ducted											
18,000 BtuH	700 to 1,000 sq ft	208/240V AC	L6-20P	4	10 ft	6 ft	38 1/4 in	20 1/2 in	21 3/4 in	Cellular Control, Programmable, Tamper Resistant	43LD80
24,000 BtuH	1,400 to 1,500 sq ft	208/240V AC	L6-20P	4	10 ft	6 ft	38 1/4 in	20 1/2 in	21 3/4 in	Cellular Control, Programmable, Tamper Resistant	43LD81
33,000 BtuH	2,000 to 2,500 sq ft	208/240V AC	L6-30P	Variable	—	—	78 3/4 in	23 3/4 in	42 3/4 in	Cellular Control, Programmable, Tamper Resistant	43ME35
Cooling Only, Air-Cooled Vented											
12,000 BtuH	450 to 550 sq ft	120V AC	LCDI, 5-15P	3	10 ft	6 ft	32 3/4 in	12 3/4 in	19 3/4 in	Programmable, Remote Control	6RH7



4PKR1



Heavy-Duty Water-Cooled Portable Air Conditioners

- Ambient temp. range: 70° to 113°F
- 2 cooling speeds

Provide high-capacity air conditioning where no window or outside air source is available. Units connect to a water supply and drain. 18" quick-connect hose included; additional hose kits sold separately. Automatic regulating valve shuts off water flow when the compressor is not running. Great for computer rooms, medical equipment rooms, and telecommunication equipment rooms.

Cooling Cap.	Average Coverage Area	Voltage	NEMA Plug Configuration	H	W	D	Heating Cap.	Mfr. Model	Item No.
Cooling Only									
6,300 BtuH	150 to 250 sq ft	115V AC	LCDI, 5-15P	17 1/2 in	22 3/4 in	12 in	—	5WK07BEA1AAA0	4PKP3
10,800 BtuH	400 to 450 sq ft	115V AC	LCDI, 5-15P	31 1/2 in	25 in	10 1/4 in	—	5WK14BEA1AAA0	4PKP4
16,100 BtuH	550 to 700 sq ft	230V AC	LCDI, 6-15P	28 3/4 in	36 in	12 1/4 in	—	5WK18BGA1AAA0	4PKP5
23,000 BtuH	1,200 to 1,400 sq ft	230V AC	LCDI, 6-15P	28 3/4 in	36 in	12 1/4 in	—	5WK26BGA1AAA0	4PKP7
Cooling/Heating, Heat Pump									
7,000 BtuH	250 to 300 sq ft	115V AC	LCDI, 5-15P	17 1/2 in	22 3/4 in	12 in	7,800	5WK07BEA1AAH0	4PKP9
10,800 BtuH	400 to 450 sq ft	115V AC	LCDI, 5-15P	31 1/2 in	25 in	10 1/4 in	12,000	5WK14BEA1AAH0	4PKR1
19,100 BtuH	700 to 1,000 sq ft	230V AC	LCDI, 6-15P	28 3/4 in	36 in	12 1/4 in	18,000	5WK18BGA1AAH0	4PKR2
27,300 BtuH	1,400 to 1,500 sq ft	230V AC	LCDI, 6-15P	28 3/4 in	36 in	12 1/4 in	26,000	5WK26BGA1AAH0	4PKR4

L	Mfr. Model	Item No.
Hose Kits with Quick-Connect Fittings		
10 ft	88SA0763504	13M332
20 ft	88SA0763505	13M330
40 ft	88SA0763506	13M331