

## Armored Type MC Cable

Wire Size	No. of Cond.	Spool Length	Jacket Material	Jacket Color	Wire Color	Brand	SOLID Item No.	STRANDED Item No.
<b>MC Lite</b>								
14 AWG	2 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/White	AFC	4JC34	—
14 AWG	3 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/Red/White	AFC	4JC35	—
12 AWG	2 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/White	AFC	4JC30	4JC31
12 AWG	3 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/Red/White	AFC	4JC32	4JC33
<b>MC ap</b>								
14 AWG	2 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/White	Southwire	2VGf3	—
14 AWG	2 with Bare AL Ground	1000 ft	Aluminum	Silver	Bare/Black/White	Southwire	2VGf4	—
14 AWG	3 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/Red/White	Southwire	2VGf5	—
12 AWG	2 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/White	Southwire	2VGf6	—
12 AWG	2 with Bare AL Ground	1000 ft	Aluminum	Silver	Bare/Black/White	Southwire	2VGf7	—
12 AWG	3 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/Red/White	Southwire	2VGf8	—
10 AWG	2 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/White	Southwire	2VGf9	—
10 AWG	3 with Bare AL Ground	250 ft	Aluminum	Silver	Bare/Black/Red/White	Southwire	2VGg1	—
<b>HCF Lite</b>								
12 AWG	2 with Insulated CU Ground	250 ft	Aluminum	Green	Black/Green/White	AFC HCF	1YTF9	1YTG1
<b>MC</b>								
14 AWG	2 with Insulated CU Ground	1000 ft	Aluminum	Silver	Black/Green/White	Southwire	20K244	—
14 AWG	3 with Insulated CU Ground	25 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K245	—
14 AWG	3 with Insulated CU Ground	50 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K246	—
14 AWG	3 with Insulated CU Ground	100 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K247	—
14 AWG	3 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K248	—
14 AWG	3 with Insulated CU Ground	1000 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K249	—
14 AWG	4 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Blue/Green/Red/White	Southwire	20K250	—
12 AWG	2 with Insulated CU Ground	25 ft	Aluminum	Silver	Black/Green/White	Southwire	20K251	—
12 AWG	2 with Insulated CU Ground	50 ft	Aluminum	Silver	Black/Green/White	Southwire	20K252	—
12 AWG	2 with Insulated CU Ground	100 ft	Aluminum	Silver	Black/Green/White	Southwire	20K253	20K257
12 AWG	2 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/White	Southwire	20K254	20K258
12 AWG	3 with Insulated CU Ground	100 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	—	20K259
12 AWG	3 with Insulated CU Ground	250 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K255	20K260
12 AWG	3 with Insulated CU Ground	1000 ft	Aluminum	Silver	Black/Green/Red/White	Southwire	20K256	20K261
<b>MC FPLP Fire Alarm</b>								
14 AWG	2 with Insulated CU Ground	250 ft	Galvanized Steel	Red	Black/Green/White	AFC Fire Alarm	1YTG2	—
<b>MC HCF</b>								
12 AWG	2 with Insulated CU Ground	250 ft	Aluminum	Green	Black/Green/White	Southwire	20K262	20K264



Cables are rated for 600V and rated 194°F dry. UL Listed, NEC compliant.

**MC**

**Fire Alarm®**—For fire alarm systems from panels to devices. Features aluminum-bond ground, red armor, and dual-rated MC/FPLP. UL Listed for plenum use. NFPA compliant. UL Classified 1-, 2-, and 3-hr. through penetration

**MCAP®** Constructed for superior ground-ing performance compared to regular MC and AC cables. Features integral grounding/bonding conductor.

**HCF**—Designed for hospital and healthcare use. Armor and aluminum bond provides ground NEC 250.118 (8)



## Armored Type MC Cable Whips

- MC Lite Interlocked steel
- 6-ft. length armor with factory installed conductors.
- 6" leads
- 600V



25K875

Wire Size	Stranded/Solid	Wire Type	Max. Amps	Item No.
<b>With Lock Nut Fittings</b>				
<b>2 Insulated</b>				
14 AWG	Stranded	MC, THHN	15	25K878
<b>3 with Insulated CU Ground</b>				
12 AWG	Stranded	MC, THHN	20	25K880
14 AWG	Solid	MC, THHN	15	25K873
18 AWG	Solid	MC, TFFN, TFN	7	25K870
<b>4 with Insulated CU Ground</b>				
14 AWG	Solid	MC, THHN	15	25K874
<b>With Snap In Fittings</b>				
<b>3 with Insulated CU Ground</b>				
14 AWG	Solid	MC, THHN	15	25K876
14 AWG	Stranded	MC, THHN	15	25K881
18 AWG	Solid	MC, TFFN, TFN	7	25K875



3FLE9

## Flexible Metal Conduit



Easy to cut, no bending required—replaces EMT conduit in difficult or impractical locations. For dry locations only except PVC coated rated NEMA 4X.

L	Flexible Conduit Type	Brand	3/8 in Item No.	1/2 in Item No.	3/4 in Item No.	1 in Item No.	1 1/4 in Item No.	1 1/2 in Item No.	2 in Item No.
<b>Steel</b>									
25 ft	Extra Flex	—	53CK01	—	—	—	—	—	—
25 ft	Reduced Wall	—	3FLE1	3FLE2	3FLE4	—	—	3FLE7	3FLE8
50 ft	Extra Flex	—	53CK02	—	—	—	—	—	—
50 ft	Reduced Wall	—	6A419	6A420	4JC52	4JC53	3FLE6	—	—
100 ft	Extra Flex	—	53CK03	—	—	—	—	—	—
100 ft	Reduced Wall	—	5YH59	5YH60	5YH61	—	—	—	—
500 ft	Reduced Wall	—	3FND7	3FLE3	3FLE5	—	—	—	—
<b>Stainless Steel</b>									
25 ft	Bare	Calbrite	—	40KG10	40KF98	40KG06	40KG04	40KG01	40KG09
<b>Aluminum</b>									
25 ft	Reduced Wall	—	3FLE9	3FLF2	3FLF4	—	—	3FLF7	3FLF8
50 ft	Reduced Wall	—	4JC54	4JC55	4JC56	4JC57	3FLF6	—	—
100 ft	Reduced Wall	—	5YH62	5YH63	5YH64	—	—	—	—
500 ft	Reduced Wall	—	3FLF1	3FLF3	3FLF5	—	—	—	—
<b>316 Stainless Steel</b>									
25 ft	PVC Clear Coat	Calbrite	—	40KF99	40KG03	40KG12	—	40KG11	40KG02
25 ft	PVC Coated	Calbrite	—	40KG07	40KG08	40KF97	40KG13	40KG14	40KG05



## Connectors for Flexible Metal Conduit, AC &amp; MC Cable

- For AC, Flexible Conduit, MC

Connectors join unthreaded flexible metal conduit (FMC), armored cable (AC), and metal clad cable (MC) to junction boxes and enclosures.



90° Connectors Clamp Style



90° Connectors Saddle Style



Straight Connectors Saddle Style



Straight Connectors Set Screw Clamp Style



Straight Connectors Snap-In Style



Straight Connectors Squeeze Clamp Style



Straight Duplex Box Connectors

Trade Size	Compatible Knockout Size	Connector	Insulated	Material	Brand	Item No.
<b>90° Connectors - Clamp Style</b>						
3/4 in	3/4 in	Snap-In Box Connection	No	Zinc	Raco	43G336
1/2 in	1/2 in	Snap-In Box Connection	No	Zinc	Raco	43G385
3/4 in	3/4 in	Snap-In Box Connection	Yes	Iron	Raco	206G91
1 in	1 in	Snap-In Box Connection	No	Zinc	Raco	43G393
1 in	1 in	Snap-In Box Connection	Yes	Iron	Raco	206D15
1 1/4 in	1 1/4 in	Snap-In Box Connection	No	Zinc	Raco	43G392
1 1/4 in	1 1/4 in	Snap-In Box Connection	No	Zinc	Raco	206G64
1 1/2 in	1 1/2 in	Snap-In Box Connection	Yes	Iron	Raco	206G93
1 1/2 in	1 1/2 in	Snap-In Box Connection	No	Zinc	Raco	206G65
2 in	2 in	Snap-In Box Connection	Yes	Iron	Raco	206G94
2 in	2 in	Snap-In Box Connection	No	Zinc	Bell	206D16
2 in	2 in	Snap-In Box Connection	No	Zinc	Bell	35U093
<b>90° Connectors - Saddle Style</b>						
3/4 in	1/2 in	Threaded End Box Connection	Yes	Steel	Thomas & Betts	2RET2
3/4 in	1/2 in	Threaded End Box Connection	No	Steel	Thomas & Betts	2RET3
<b>Straight Connectors - Saddle Style</b>						
3/4 in	3/4 in	Threaded End Box Connection	No	Steel	Thomas & Betts	2RER9
3/4 in	3/4 in	Threaded End Box Connection	Yes	Steel	Thomas & Betts	2RET1

Trade Size	Compatible Knockout Size	Connector	Insulated	Material	Brand	Item No.
<b>Straight Connectors - Set Screw Clamp Style</b>						
1/2 in	1/2 in	Snap-In Box Connection	No	Steel	Raco	1RVU8
<b>Straight Connectors - Squeeze Clamp Style</b>						
3/4 in	3/4 in	Snap-In Box Connection	No	Iron	Raco	2DDE4
3/4 in	3/4 in	Threaded End Box Connection	No	Zinc	Bell	35U191
3/4 in	3/4 in	Threaded End Box Connection	Yes	Iron	Raco	4JC41
1/2 in	1/2 in	Snap-In Box Connection	No	Iron	Raco	3LK38
1/2 in	1/2 in	Snap-In Box Connection	No	Zinc	Raco	43G762
1/2 in	1/2 in	Snap-In Box Connection	Yes	Iron	Raco	4JC42
1/2 in	1/2 in	Snap-In Box Connection	No	Iron	Raco	3LK39
3/4 in	3/4 in	Threaded End Box Connection	No	Zinc	—	3LV68
3/4 in	3/4 in	Snap-In Box Connection	No	Zinc	Raco	43G771
3/4 in	3/4 in	Snap-In Box Connection	Yes	Iron	Raco	4JC43
3/4 in	3/4 in	Snap-In Box Connection	No	Iron	Raco	3LK40
1 in	1 in	Snap-In Box Connection	No	Zinc	Raco	43G202
1 in	1 in	Snap-In Box Connection	Yes	Iron	Raco	4JC44
1 1/4 in	1 1/4 in	Snap-In Box Connection	Yes	Iron	Raco	206H01
1 1/4 in	1 1/4 in	Snap-In Box Connection	No	Zinc	Bell	35U145
1 1/2 in	1 1/2 in	Snap-In Box Connection	No	Zinc	Bell	35U133
1 1/2 in	1 1/2 in	Snap-In Box Connection	Yes	Iron	Raco	206G57
2 in	2 in	Snap-In Box Connection	No	Zinc	Raco	206D07
2 in	2 in	Snap-In Box Connection	Yes	Iron	Bell	35U107