



52AX66



A Division of Hubbell Incorporated (Delaware)

## 2-Screw Connectors

Die-cast zinc plating connectors are used to connect NM sheathed and oval type SE or USE cable to box or enclosure. UL Listed for use with NM-B cable.

Box Connection	Use With - Nonmetallic Building Cable	Item No.
<b>Threaded Metal Connectors</b>		
1/2 in MNPT	(1) 10/2, (1) 12/2, (1) 12/3 with Ground; (1) 14/2, (1) 12/3 without Ground, (1) 14/3, Oval Cable: (1) 14/2	52AX66
3/4 in MNPT	(1) 10/3, (1) 6/3, Round Cable: (1) 6/2	52AX70
1 in MNPT	(1) 4/3, Round Cable: (1) 6/3	52AX71
1 1/4 in MNPT	(1) 10/2, (1) 12/2, (1) 12/3 with Ground; (1) 14/2, (1) 12/3 without Ground, (1) 14/3, Oval Cable: (1) 14/2	52AX67
1 1/2 in MNPT	(1) 9/4, Oval Cable: (1) 6/3	52AX68
2 in MNPT	(1) 0000/3, Oval Cable: (1) 000/3	52AX69



5D884



5D899



5D724



5D798



5D924



5D971



Wiring Device-Kellems

## Liquid-Tight Cord Connectors

- Nylon: for washdown areas
- Aluminum: where light weight and corrosion resistance are needed
- Zinc-plated steel: where high impact resistance and tensile strength are needed

Proprietary split-hinge Gotcha® ring, color-coded by cord size, grips conductor through cord jacket. Factory-lubricated bushing provides even compression, ensures liquid-tight seal around cord, and minimizes tension on terminals. UL Listed, CSA Certified.

Note: Order locknuts on page 292.

Conduit Size	Cord Dia. Range	NYLON		ALUMINUM		ZINC-PLATED STEEL	
		Straight Item No.	90° Item No.	Straight Item No.	90° Item No.	Straight Item No.	90° Item No.
3/8"	0.19 in to 0.25 in	5D876	—	5D712	—	—	—
	0.25 in to 0.31 in	5D877	—	5D713	2XYJ4	2XYL8	—
	0.25 in to 0.38 in	2XYL9	—	5D714	—	—	—
	0.38 in to 0.44 in	2XYN1	—	5D715	2XYJ6	5D919	—
	0.31 in to 0.38 in	—	—	—	2XYJ5	—	—
	0.13 in to 0.19 in	5D881	2XYJ8	5D721	2XYJ7	2XYN3	—
1/2"	0.19 in to 0.25 in	5D882	2XYJ9	5D716	5D798	5D922	2XYK1
	0.25 in to 0.38 in	5D883	5D899	5D723	5D799	5D923	5D971
	0.38 in to 0.50 in	5D884	5D900	5D724	5D800	5D924	5D972
	0.50 in to 0.63 in	5D885	5D901	5D725	5D801	5D925	5D973
	0.06 in to 0.13 in	2XYN2	—	5D720	—	—	—
	0.63 in to 0.75 in	—	—	5D726	—	2XYN4	—
3/4"	0.75 in to 0.88 in	—	—	5D727	—	2XYN5	—
	0.25 in to 0.31 in	—	—	5D717	—	—	—
	0.31 in to 0.38 in	—	—	5D718	—	—	—
	0.38 in to 0.44 in	—	—	5D719	—	—	—
	0.19 in to 0.25 in	—	—	5D722	—	—	—
	0.38 in to 0.50 in	5D886	2XYK3	5D732	2XYK2	5D932	2XYK4
1"	0.50 in to 0.63 in	5D887	5D903	5D733	2XYK5	5D933	2XYK6
	0.63 in to 0.75 in	5D888	5D904	5D735	5D804	5D934	2XYK7
	0.75 in to 0.88 in	5D889	2XYK8	5D736	5D805	5D935	5D977
	0.25 in to 0.38 in	—	—	5D731	—	5D931	—
	0.63 in to 0.75 in	5D892	—	5D739	2XYK9	5D966	5D978
	0.75 in to 0.88 in	5D893	5D909	5D740	2XYL2	5D967	—
1 1/4"	0.88 in to 1.00 in	5D894	5D910	5D741	2XYL3	5D936	—
	0.50 in to 0.63 in	2XYN6	—	5D738	5D807	2XPY2	—
	1.00 in to 1.13 in	2XYN7	—	5D742	2XYL4	—	—
	1.00 in to 1.13 in	—	—	5D749	2XYL5	5GTf8	—
	1.13 in to 1.25 in	—	—	5D750	2XYL6	—	—
	1.25 in to 1.38 in	—	—	2XYN8	2XYL7	—	—
1 1/2"	1.00 in to 1.13 in	—	—	2XYN9	5D817	5GTG0	—
	1.25 in to 1.38 in	—	—	2XPY1	5D819	5GTG2	—
	1.13 in to 1.25 in	—	—	5D755	—	5GTG1	—
	1.38 in to 1.50 in	—	—	—	5D821	—	—



Straight 6C101



90° 6D170

Trade Size	Cable Dia. Range	STRAIGHT Item No.	90° Item No.
3/8"	0.25 in to 0.31 in	6D124	2TGJ4
	0.31 in to 0.38 in	6D125	—
	0.38 in to 0.44 in	—	2TGJ6
	0.19 in to 0.25 in	6D126	6D170
	0.25 in to 0.38 in	6D127	6D171
	0.38 in to 0.50 in	6C101	6D172
1/2"	0.50 in to 0.63 in	6C102	6D137
	0.63 in to 0.75 in	6D128	—
	0.25 in to 0.38 in	6D131	—
	0.38 in to 0.50 in	6D132	6D174
	0.50 in to 0.63 in	6C103	6D175
	0.63 in to 0.75 in	6C104	6D176
3/4"	0.75 in to 0.88 in	6D133	6D177



Wiring Device-Kellems

## Liquid-Tight Cord Mesh Grips

Deluxe stainless steel cord/cable grips completely eliminate pull tension on terminals, indoors or outdoors, sealing out moisture and cutting oils. Grips control cable arc-of-bend and prevent cord pullout. Corrosion resistant with aluminum fitting that connects to box or hub, effectively sealing out contaminants. Useful in wiring enclosures, pendant stations, construction sites, processing and material handling equipment, pumps, motors, and machine tools.

Trade Size	Cable Dia. Range	STRAIGHT Item No.	90° Item No.
3/8"	0.50 in to 0.63 in	5C801	—
	0.63 in to 0.75 in	5C802	—
	0.75 in to 0.88 in	6C105	6D179
	0.87 in to 1.00 in	6C106	2VVRV
	1.00 in to 1.13 in	6D135	2TGK3
	0.87 in to 1.00 in	6D136	—
1 1/4"	1.00 in to 1.13 in	6D137	2TGK2
	1.13 in to 1.25 in	6D138	2TGJ7
	1.25 in to 1.38 in	6D139	—
	1.00 in to 1.13 in	6D142	2TGJ8
	1.13 in to 1.25 in	6D143	2TGJ9
	1.25 in to 1.38 in	6D144	—
2"	1.44 in to 1.56 in	6D152	2TGK4
	1.56 in to 1.69 in	6D153	—

2A246



A Division of Hubbell Incorporated (Delaware)

Thomas & Betts  
A Member of the ABB Group



2DDK4

## Liquid-Tight Cord Grip Connectors

Connectors can be tightened with pliers or screwdrivers when working in tight areas. Type 304 stainless steel connectors withstand harsh environments, including heat and UV.

Conduit Size	Cord Dia. Range	Brand	Item No.
<b>Straight</b>			
<b>Aluminum</b>			
1/2"	0.06 in to 0.13 in	Raco	52AY03
	0.25 in to 0.31 in	Raco	52AY07
	0.31 in to 0.38 in	Raco	52AY15
	0.50 in to 0.63 in	Raco	52AY10
	0.19 in to 0.25 in	Raco	52AX42
	0.50 in to 0.63 in	Raco	52AY09
1"	0.38 in to 0.50 in	Raco	52AX52
	0.50 in to 0.63 in	Raco	52AX45
	0.63 in to 0.75 in	Raco	52AX46
	0.70 in to 0.95 in	T&B	2DDJ7
<b>Malleable Iron/Steel</b>			
1/2"	0.12 in to 0.25 in	Raco	2A246
	0.25 in to 0.38 in	Raco	2A247
<b>Nylon</b>			
1/2"	0.06 in to 0.13 in	Raco	52AY06
	0.25 in to 0.38 in	Raco	52AY08
	0.50 in to 0.63 in	Raco	52AY12
	0.13 in to 0.38 in	T&B	2DDH2
	0.38 in to 0.50 in	Raco	52AY20
	0.50 in to 0.63 in	Raco	52AY14
1"	0.31 in to 0.56 in	T&B	2DDJ2
	0.63 in to 0.75 in	Raco	52AX49
<b>Stainless Steel</b>			
1/2"	0.13 in to 0.38 in	T&B	3EHV6
	0.36 in to 0.56 in	T&B	3EHV7
	0.50 in to 0.75 in	T&B	3EHV8
	0.13 in to 0.38 in	T&B	3EHV9
	0.31 in to 0.56 in	T&B	3EHW1
	0.50 in to 0.75 in	T&B	3EHW2
1"	0.31 in to 0.56 in	T&B	3EHW3
	0.70 in to 0.95 in	T&B	3EHW4
<b>Steel</b>			
1/2"	0.25 in to 0.35 in	Raco	52AX47
	0.50 in to 0.75 in	T&B	2DDG6
	0.25 in to 0.38 in	Raco	52AY13
	0.38 in to 0.50 in	Raco	52AY11
	0.45 in to 0.56 in	Raco	52AY05
	0.60 in to 0.70 in	Raco	52AX43
1"	0.70 in to 0.85 in	Raco	52AY18
<b>90°</b>			
<b>Aluminum</b>			
1/2"	0.13 in to 0.38 in	T&B	2DDK4
	0.31 in to 0.56 in	T&B	2DDK7
	0.13 in to 0.38 in	T&B	2DDL2
	0.31 in to 0.56 in	T&B	2DDL5
	0.50 in to 0.75 in	T&B	2DDL8
	0.31 in to 0.56 in	T&B	2DDN2
<b>Malleable Iron</b>			
1/2"	0.15 in to 0.25 in	Raco	52AY16
	0.25 in to 0.38 in	Raco	52AY17
	0.45 in to 0.56 in	Raco	52AY19
	0.25 in to 0.38 in	Raco	52AX44
	0.45 in to 0.56 in	Raco	52AY21
	0.45 in to 0.56 in	Raco	52AX53
<b>Nylon</b>			
1/2"	0.13 in to 0.38 in	T&B	2DDK5
	0.31 in to 0.56 in	T&B	2DDK8
	0.13 in to 0.38 in	T&B	2DDL3
	0.31 in to 0.56 in	T&B	2DDL6
	0.50 in to 0.75 in	T&B	2DDL9
<b>45°</b>			
<b>Malleable Iron</b>			
1/2"	0.15 in to 0.25 in	Raco	52AX50
	0.25 in to 0.35 in	Raco	52AX51
1"	0.45 in to 0.56 in	Raco	52AX48