

## Portable Infrared Radiant Electric Jobsite & Garage Heaters

Efficiently and quietly warm people and objects without having to bring up the ambient air temperature. Provide spot heating to enclosed and semiprotected areas. Also used to cure a variety of finishes with a lower chance of blistering or overheating than other types of heaters.

45EM35

Note: Not for use in hazardous or chemical-laden atmospheres, or unprotected wet locations. Heaters should be used outdoors temporarily only.

Multiple heaters may be required to achieve required watts for desired coverage.

	Heated Ar Below	Àbove	Semi-Protected Heated Area (sq. ft.) Below Above			
Watts	35°F	35°F	35°F	35°F		
1450	25	36	40	50		
3150	64	75	90	125		
4300	85	100	120	150		
9500	192	225	270	375		



786DY0

9500	192	225	270	3	75				
Wattage Output	Voltage	Phase	NEMA Plug Config.	Beam Pattern	Overall Height	Overall Width	Overall Length	Mfr. Model	ltem No.
	Stationary, Flat Panel Emitter								
1450W	120V AC	1	5-15P	60°	13 ½ in	11 ½ in	_	FSP-1412-1C	
3150W	480V AC	- 1	Hardwired		13 ½ in	11 ½ in	_	FSP-3148-1	45EM37
Wheeled, I	Flat Panel I	Emitter,	Includes S						
3150 W	240V AC	1	Hardwired		45 3/16 in	11 ½ in	12 ¾ in		786DX6
4300W	240V AC	1 or 3	Hardwired		17 in	19 % in	_	FSP-4324-3	45EM38
4300W	480V AC	1 or 3	Hardwired		17 in	19 % in	_	FSP-4348-3	45EM39
9500W	480V AC	1 or 3	Hardwired	60°	19 in	19 % in	_	FSP-9548-3	45EM41
9550 W	240V AC	1, 3	Hardwired	60°	53 ¾ in	19 ¾ in	16 1/4 in	H95-FSP-3	786DY0
Wheeled, 0	Duartz Lamı	o. Inclu	des Casters	s and Hir	nged Pane	ls to Direc	t Infrare	d Heat	
4800W	240V AC		Hardwired		30 in	44 % in	_	HP-5-QT	3HML1
6400W	240V AC	1 or 3	Hardwired	_	30 in	66 % in		HP-6-QT	3HML2
11.200W	240V AC	1 or 3	Hardwired	_	30 in	66 5/8 in	_	HP-11-QT	3HML3
Wheeled, 0	Wheeled, Quartz Tube, Includes Adjustable Stand								
1500W	120V AC	1	5-15P	60°	72 in	53 in		PCH-48C	5JNK7
Description							Mfr. Model	Item No.	
Cart									
	ith Mfr. No.							FHK-1	4E527
Field Insta					, Include (	Cable Grip	, Wire SI		
8/4 SO, For Use With Mfr. No. FSP-9520-3						SO 8/4	3LY31		
14/3 SO, For Use With Mfr. No. FSP-3120-1, FSP-3124-					SO 14/3	3LY34			
1, FSP-432	24-3, FSP-4	327-1, I	FSP-9557-3	}				30 14/3	JLI J4
14/4 SO, F FSP-4348-	14/4 SO, For Use With Mfr. No. FSP-4320-3, FSP-4324-3, FSP-4348-3, FSP-4357-3, FSP-9548-3, FSP-9557-3-3					SO 14/4	3LY35		
		Descr	iption			Volta	qe	Mfr. Model	Item No.
Safety Swi	tches for F	lat Pane	el Emitter H	leaters					
Disconnec	Disconnect Switch, For Use With All FSA/FSS & FSP Models			600V	AC	DC-SK-1	2KDC8		
Tip Over Switch, For Use With FSP 43/95kW Models					TO-SK-1	2KDC9			



## **Under-Floor Electric Heating Systems**

Provide concentrated warmth at ground level. Systems consist of mats with built-in heating coils that are positioned between the subfloor and finished floor. Easy to install and used in renovations or new construction. Compatible with most subfloors. Remote-mounted thermostat required (sold separately).

For Ceramic Tile, Marble, Porcelain, Stone, Carpet, Vinyl Tile—Can be installed under carpet, vinyl, laminate, and glued-down floors with self-leveling cement. Include factory-attached 10-ft. lead wire.

For Laminate, Wood—Suitable for floating and glue-down laminate, wood, and engineered wood floors; no cement required. Include 20-ft. lead wire.

Overall	Overall	Heating	·	Mfr.	Item
Length	Width	Area	Voltage	Model	No.
		le, Porcelain, St		1404/5 400	440400
5 ft	18 in	7.5 sq ft	120V AC	WW5-120	14C436
7 ft	18 in	10.5 sq ft	120V AC	WW7-120	14C437
10 ft	18 in	15 sq ft	120V AC	WW10-120	14C438
10 ft	18 in	15 sq ft	240V AC	WW10-240	14C446
14 ft	18 in	21 sq ft	240V AC	WW14-240	14C447
15 ft	18 in	22.5 sq ft	120V AC	WW15-120	14C439
20 ft	18 in	30 sq ft	120V AC	WW20-120	14C440
20 ft	18 in	30 sq ft	240V AC	WW20-240	14C448
30 ft	18 in	45 sq ft	120V AC	WW30-120	14C441
30 ft	18 in	45 sq ft	240V AC	WW30-240	14C449
40 ft	18 in	60 sq ft	120V AC	WW40-120	14C442
40 ft	18 in	60 sq ft	240V AC	WW40-240	14C450
50 ft	18 in	75 sq ft	120V AC	WW50-120	14C443
60 ft	18 in	90 sq ft	120V AC	WW60-120	14C444
60 ft	18 in	90 sq ft	240V AC	WW60-240	14C451
80 ft	18 in	120 sq ft	240V AC	WW80-240	14C452
100 ft	18 in	150 sq ft	240V AC	WW100-240	14C453
120 ft	18 in	180 sq ft	240V AC	WW120-240	14C454
or Laminate, V					
5 ft	18 in	7.5 sq ft	120V AC	1505-120	14C455
5 ft	36 in	15 sq ft	120V AC	3005-120	14C457
5 ft	36 in	15 sq ft	240V AC	3005-240	14C461
10 ft	18 in	15 sq ft	120V AC	1510-120	14C456
10 ft	18 in	15 sq ft	240V AC	1510-240	14C459
10 ft	36 in	30 sq ft	120V AC	3010-120	14C458
10 ft	36 in	30 sq ft	240V AC	3010-240	14C462
20 ft	18 in	30 sq ft	240V AC	1520-240	14C460
20 ft	36 in	60 sq ft	240V AC	3020-240	14C463
				Mfr.	Item
	Model	No.			
Accessories		cription			
Electric Floor H	eater Thermosta	t, 120V AC, Includ	des Floor Sensor	MTC-2991	14C46
Electric Floor H	eater Thermosta	t, 240V AC, Includ	des Floor Sensor	MTC-1991	14C468
InstAlarm Mon	tor, Includes 9V	Battery, Instruction	ons, Screw Driver	INSTALRM	14C470
TT Deluxe Insta	III Kit. % in Plast	ic Trowel, InstAlai	m		
	neter, Ultra Light			IK-TAMK	14C47
	3/ :- C N-4	1		TDM/I 0000	COLLOC
Plastic Trowel,	% in Square Not stic Trowel, ½ ir	cn		TRWL3838	20UG5





## **Kickspace Electric Heaters**

Black grille color

Recess in under-cabinet spaces and provide supplemental heat where space is limited, such as kitchens, bathrooms, and checkout counters. They wire into an opening at the base of a cabinet. Can be controlled with a required surfacemount thermostat or a wall thermostat (sold separately).

Wattage Output	Voltage	Rough-In Width	Rough-In Height	Rough-In Depth	Brand	M: Mo		Item No.
Heaters	_		_					
750W/1000W:	208/240V AC	14 ½ in	3 ½ in	8 1/4 in	Cadet	UC1	02B	31LK47
750W/1500W	120V AC	14 1/4 in	3 ½ in	8 % in	Dayton	2Y\	/10	2YV10
1000W	120V AC	14 ½ in	3 ½ in	8 1/4 in	Cadet	UC1	01B	31LK48
					_		Mfr.	Item
	Description	1		For Use Wit	h	Brand	Model	No.
Mechanical 1	Thermostats							
120/240V A	AC, 45° to 85°	F, Single Po	le	2YV10		Dayton	2YV12	2YV12
120/208/240\	/ AC, 40° to 8	35°F, Single	Pole Mfr. N	No. UC101B,	UC102B	Cadet	UCT1B	31LK49
120/208/240\	/ AC: 40° to 8	5°F Double	Pole Mfr N	Vo LIC101B	IIC102B	Cadet	IICT2B	311 K50



**Thermo**Soft

## **Accessories For Electric Floor Heaters**

Description	Mitr. Model	No.	
InstAlarm Monitor, Includes 9V Battery, Instructions, Screw Driver	INSTALRM	14C470	
TT Deluxe Install Kit, % in Plastic Trowel, InstAlarm Monitor, Multimeter, Ultra Light Kneepads	IK-TAMK	14C471	
Plastic Trowel, % in Square Notch	TRWL3838	20UG51	
Heavy Duty Plastic Trowel, ½ in X ¾ in Notch	TRWL3812	20UG52	