

1-800-GRAINGER (472-4643)



## Suspended Electric Wall and Ceiling Unit Heaters

■ Accessories available on page 3078 and Grainger.com

Suspend from a bracket or threaded rod for use in downflow or horizontal applications and to save limited floorspace. Units use fan-forced air to provide primary or supplementary heating in large or exposed areas like factories, warehouses, and stock rooms. Find more Electric Wall and Ceiling Heaters on Grainger.com.

| Wattage Output   | Voltage     | Phase  | Air Temp. Rise | Air Flow      | Overall Height | Overall Width | Overall Depth | Vertical Mounting H | Horizontal Air Throw | Mfr. Model   | Item No. |
|--|-------------|--------|----------------|---------------|----------------|---------------|---------------|---------------------|----------------------|--------------|----------|
| <b>Dayton Heaters (Accessories available on page 3078)</b> |             |        |                |               |                |               |               |                     |                      |              |          |
| 1.8kW/3.7kW  | 208/240V AC | 1      | 60°F           | 270 cfm       | 12 1/2 in      | 14 in         | 11 1/4 in     | 11 ft               | 12 ft                | 3UG73        | 3UG73    |
| 2.5kW/5kW  | 208/240V AC | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU58        | 2YU58    |
| 2.2kW/3kW  | 208/240V AC | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU59        | 2YU59    |
| 2.5kW/1.9kW  | 208/240V AC | 1      | 46°F, 60°F     | 150/130 cfm   | 12 1/2 in      | 14 in         | 14 in         | —                   | —                    | 2HDA1        | 2HDA1    |
| 2.5kW/3.7kW  | 208/240V AC | 1      | 71°F           | 210 cfm       | 16 in          | 21 in         | 8 in          | 15 ft               | 12 ft                | 4E169        | 4E169    |
| 3kW  | 208V AC     | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU61        | 2YU61    |
| 3kW  | 277V AC     | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU60        | 2YU60    |
| 3kW  | 480V AC     | 3      | 27°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU59        | 2YU59    |
| 3.7kW/5kW  | 208/240V AC | 1 or 3 | 45°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU62        | 2YU62    |
| 5kW  | 208V AC     | 1 or 3 | 45°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU65        | 2YU65    |
| 5kW  | 277V AC     | 1      | 45°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU64        | 2YU64    |
| 5kW  | 480V AC     | 3      | 45°F           | 350 cfm       | 16 in          | 14 in         | 8 1/2 in      | 9 ft                | 12 ft                | 2YU63        | 2YU63    |
| 5.6kW/7.5kW  | 208/240V AC | 1 or 3 | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU66        | 2YU66    |
| 7.5kW  | 208V AC     | 1 or 3 | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU68        | 2YU68    |
| 7.5kW  | 480V AC     | 3      | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU67        | 2YU67    |
| 7.5kW/10kW   | 208/240V AC | 1 or 3 | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU69        | 2YU69    |
| 10kW   | 208V AC     | 1 or 3 | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU71        | 2YU71    |
| 10kW   | 480V AC     | 3      | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 8 1/2 in      | 14 ft               | 18 ft                | 2YU70        | 2YU70    |
| 11.2kW/15kW  | 208/240V AC | 3      | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 13 3/4 in     | 20 ft               | 35 ft                | 2YU72        | 2YU72    |
| 15kW   | 208V AC     | 1 or 3 | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 13 3/4 in     | 20 ft               | 35 ft                | 2YU74        | 2YU74    |
| 15kW   | 480V AC     | 3      | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 13 3/4 in     | 20 ft               | 35 ft                | 2YU73        | 2YU73    |
| 15kW/20kW  | 208/240V AC | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 13 3/4 in     | 23 ft               | 41 ft                | 2YU75        | 2YU75    |
| 20kW   | 480V AC     | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 13 3/4 in     | 23 ft               | 41 ft                | 2YU76        | 2YU76    |
| 22.5kW/30kW  | 208/240V AC | 3      | 45°F/53°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 13 3/4 in     | 20 ft               | 50 ft                | 2YU77        | 2YU77    |
| 25kW   | 480V AC     | 3      | 38°F/44°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 13 3/4 in     | 20 ft               | 50 ft                | 3END3        | 3END3    |
| 30kW   | 208V AC     | 3      | 45°F/53°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 13 3/4 in     | 20 ft               | 50 ft                | 2YU79        | 2YU79    |
| 30kW   | 480V AC     | 3      | 45°F/53°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 13 3/4 in     | 20 ft               | 50 ft                | 2YU78        | 2YU78    |
| 37.5kW/50kW  | 208/240V AC | 3      | 53°F/61°F      | 2600/3000 cfm | 30 in          | 26 3/4 in     | 18 1/2 in     | 25 ft               | 60 ft                | 2YU80        | 2YU80    |
| 40kW   | 480V AC     | 3      | 42°F/49°F      | 2600/3000 cfm | 30 in          | 26 3/4 in     | 18 1/2 in     | 25 ft               | 60 ft                | 3END4        | 3END4    |
| 50kW   | 480V AC     | 3      | 53°F/61°F      | 2600/3000 cfm | 30 in          | 26 3/4 in     | 18 1/2 in     | 25 ft               | 60 ft                | 2YU81        | 2YU81    |
| 60kW   | 480V AC     | 3      | 60°F           | 3,400 cfm     | 35 1/2 in      | 30 1/2 in     | 14 1/2 in     | 31 ft               | 50 ft                | 4TDH7        | 4TDH7    |
| 80kW   | 480V AC     | 3      | 55°F           | 5000 cfm      | 39 1/2 in      | 37 1/2 in     | 18 1/2 in     | 40 ft               | 65 ft                | 4TDH9        | 4TDH9    |
| <b>Markel Products</b>                                     |             |        |                |               |                |               |               |                     |                      |              |          |
| 2.5 kW, 3.3 kW   | 240/208 V   | 1, 3   | 26°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5103NHF2B    | 786LL9   |
| 3.3 kW   | 208 V       | 1, 3   | 26°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5103NHF2F    | 786LL8   |
| 3.7 kW, 5 kW   | 240/208 V   | 1, 3   | 40°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5105NHF2B    | 786LM2   |
| 5 kW   | 208 V       | 1, 3   | 40°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5105NHF2F    | 786LM0   |
| 5 kW   | 277 V       | 1      | 40°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5105NG1G     | 786LM1   |
| 5 kW   | 480 V       | 3      | 40°F           | 400 cfm       | 17 3/4 in      | 14 1/2 in     | 6 1/2 in      | 9 ft                | 12 ft                | 5105CAMP3P   | 786LM3   |
| 5.6 kW, 7.5 kW   | 240/208 V   | 1, 3   | 34°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 12 ft               | 22 ft                | 5107CA1LHF2B | 786LM5   |
| 7.5 kW   | 480 V       | 3      | 34°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 12 ft               | 22 ft                | 5107CA1NPF3P | 786LM7   |
| 9.9 kW   | 208 V       | 1, 3   | 45°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 14 ft               | 22 ft                | 5110CA1LFP2  | 786LM8   |
| 10 kW  | 277 V       | 1      | 45°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 14 ft               | 22 ft                | 5110CA1LGF1G | 786LN0   |
| 10 kW  | 480 V       | 3      | 45°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 14 ft               | 22 ft                | 5110CA1NPF3P | 786LN1   |
| 10 kW, 7.5 kW  | 240/208 V   | 1, 3   | 45°F           | 700 cfm       | 24 1/2 in      | 21 1/2 in     | 6 1/2 in      | 14 ft               | 22 ft                | 5110CA1LHF2B | 786LN9   |
| 11.2 kW, 15 kW   | 240/208 V   | 3      | 43°F           | 1100 cfm      | 28 1/2 in      | 21 1/2 in     | 6 1/2 in      | 20 ft               | 32 ft                | 5115CA1LHF3B | 786LN2   |
| 18.7 kW, 25 kW   | 240/208 V   | 3      | 40/44°F        | 1800/2000 cfm | 34 in          | 29 1/2 in     | 10 1/2 in     | 22 ft               | 45 ft                | 5125CA1LHF3B | 786LN4   |
| 25 kW  | 480 V       | 3      | 40/44°F        | 1800/2000 cfm | 34 in          | 29 1/2 in     | 10 1/2 in     | 22 ft               | 45 ft                | 5125CA1NPF3P | 786LN5   |
| 30 kW  | 480 V       | 3      | 47/53°F        | 1800/2000 cfm | 34 in          | 29 1/2 in     | 10 1/2 in     | 20 ft               | 40 ft                | 5130CA1NPF3P | 786LN7   |
| 39 kW  | 480 V       | 3      | 40/45°F        | 2800/3100 cfm | 34 in          | 29 1/2 in     | 10 1/2 in     | 24 ft               | 55 ft                | 5140CA1NPF3P | 786LN8   |
| 50 kW  | 480 V       | 3      | 51/56°F        | 2800/3100 cfm | 34 in          | 29 1/2 in     | 10 1/2 in     | 22 ft               | 50 ft                | 5150CA1NPF3P | 786LP0   |
| <b>QMark Heaters (Accessories available on page 3078)</b>  |             |        |                |               |                |               |               |                     |                      |              |          |
| 2.2kW/3kW  | 208/240V AC | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0321      | 25D231   |
| 3kW  | 208V AC     | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0381      | 25D233   |
| 3kW  | 277V AC     | 1      | 27°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0371      | 20CA07   |
| 3kW  | 480V AC     | 3      | 27°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0341      | 25D232   |
| 3.7kW/5kW  | 208/240V AC | 1 or 3 | 45°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0521      | 25D234   |
| 5kW  | 208V AC     | 1 or 3 | 45°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0581      | 25D236   |
| 5kW  | 277V AC     | 1      | 45°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0571      | 20CA10   |
| 5kW  | 480V AC     | 3      | 45°F           | 350 cfm       | 16 in          | 14 in         | 7 1/2 in      | 9 ft                | 12 ft                | MUH0541      | 25D235   |
| 5.6kW/7.5kW  | 208/240V AC | 1 or 3 | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH072       | 25D237   |
| 7.5kW  | 208V AC     | 1 or 3 | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH078       | 25D252   |
| 7.5kW  | 277V AC     | 1      | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH077       | 20CA11   |
| 7.5kW  | 347V AC     | 1      | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH073       | 20CA11   |
| 7.5kW  | 480V AC     | 3      | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH074       | 25D238   |
| 7.5kW  | 600V AC     | 3      | 37°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH076       | 20CA12   |
| 7.5kW/10kW   | 208/240V AC | 1 or 3 | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH102       | 25D239   |
| 10kW   | 208V AC     | 1 or 3 | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH108       | 25D251   |
| 10kW   | 277V AC     | 1      | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH107       | 20CA17   |
| 10kW   | 480V AC     | 3      | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH104       | 25D240   |
| 10kW   | 600V AC     | 3      | 49°F           | 650 cfm       | 21 3/4 in      | 19 in         | 7 1/2 in      | 14 ft               | 18 ft                | MUH106       | 20CA16   |
| 10kW   | 600V AC     | 3      | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 12 3/4 in     | 20 ft               | 35 ft                | MUH156       | 20CA20   |
| 11.2kW/15kW  | 208/240V AC | 3      | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 12 3/4 in     | 20 ft               | 35 ft                | MUH152       | 25D254   |
| 15kW   | 208V AC     | 1 or 3 | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 12 3/4 in     | 20 ft               | 35 ft                | MUH158       | 25D253   |
| 15kW   | 480V AC     | 3      | 52°F           | 910 cfm       | 21 3/4 in      | 19 in         | 12 3/4 in     | 20 ft               | 35 ft                | MUH154       | 25D241   |
| 15kW/20kW  | 208/240V AC | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 12 3/4 in     | 23 ft               | 41 ft                | MUH202       | 20CA22   |
| 20kW   | 208V AC     | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 12 3/4 in     | 23 ft               | 41 ft                | MUH208       | 20CA25   |
| 20kW   | 480V AC     | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 12 3/4 in     | 23 ft               | 41 ft                | MUH204       | 20CA23   |
| 20kW   | 600V AC     | 3      | 48°F           | 1320 cfm      | 21 3/4 in      | 19 in         | 12 3/4 in     | 23 ft               | 41 ft                | MUH206       | 20CA24   |
| 25kW   | 480V AC     | 3      | 38°F/44°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 11 3/4 in     | 23 ft               | 50 ft                | MUH254       | 20CA27   |
| 25kW   | 600V AC     | 3      | 38°F/44°F      | 1800/2100 cfm | 30 in          | 26 3/4 in     | 11 3/4 in     | 23 ft               | 50 ft                | MUH256       | 20CA28   |
| 30kW   | 480V AC     | 3      | 53°F           | 1800/2100 cfm | 30 in          | 26 3/4 in     | 11 3/4 in     | 20 ft               | 50 ft                | MUH304       | 20CA30   |
| <b>TPI Heaters</b>   |             |        |                |               |                |               |               |                     |                      |              |          |
| 3kW/4kW  | 208/240V AC | 1      | 53°F           | 238 cfm       | 11 in          | 10 3/4 in     | 9 3/4 in      | 7 to 12 ft          | 10 ft                | HF5840TC     | 31XL69   |
| 3.6kW/4.8kW  | 208/240V AC | 1      | 74°F           | 238 cfm       | 11 in          | 10 3/4 in     | 9 3/4 in      | 7 to 12 ft          | 10 ft                | HF5848TC     | 31XL70   |



3UG73



4TDH7



25D231



20CA07



31XL69