



Suspended Electric Wall and Ceiling Unit Heater Accessories

Find more accessories on Grainger.com

Item	Fits kW	For Use With	Mr. Model	Item No.
Dayton Accessories				
Cord Set 6 Ft	3.5 to 5	4E169	4E170	4E170
Disconnect Switch	3 kW, 5 kW, 7 kW, 10 kW, 15 kW, 20 kW 15 kW, 20 kW, 25 kW, 30 kW, 40 kW, 50 kW	2YU58, 2YU59, 2YU60, 2YU61, 2YU62, 2YU63, 2YU64, 2YU65, 2YU67, 2YU70, 2YU73, 2YU76 2YU66, 2YU69, 2YU72, 2YU74 (When Wired for 3-Phase), 2YU76, 2YU78, 3END3, 3END4 2YU58, 2YU60, 2YU61, 2YU74, 2YU77, 2YU79, 2YU80, 2YU81 4TDH6-4TDH9, 4TDJ1, 4TDJ2	2YU93 2YU94 2YU95 30KA31	2YU93 2YU94 2YU95 30KA31
Electric Wall & Ceiling Heater Thermostat	60, 80, 100	All Dayton Electric Unit Heater Models Except 4TDH6, 4TDH7, 4TDH8, 4TDH9, 4TDJ1, 4TDJ2	2YU33 2YU90	2YU33 2YU90
Fan Switch	All Wattages 15 to 20 30 30 to 50 3 to 10	All Dayton Electric Unit Heater Models 15 to 20 kW Dayton Electric Unit Heater 25 & 30 kW Dayton Electric Unit Heater 25 to 50 kW Dayton Electric Unit Heater 3 to 10 kW Dayton Electric Unit Heater	2YU82 2YV17 2YU91 2YU85	2YU82 2YV17 2YU91 2YU85
Mounting Bracket	3.5 50 60 to 100 80 to 100 7.5 to 20	3 to 5 kW Dayton Electric Unit Heater 40 & 50 kW Dayton Electric Unit Heater 4TDH7, 4TDH8, 4TDH9, 4TDJ1, 4TDJ2, 4TDH6 4TDH9, 4TDJ1, 4TDJ2, 4TDH8 7.5 to 20 kW Dayton Electric Unit Heater	2YU83 2YU92 4TDJ5 4TDJ4 2YU84	2YU83 2YU92 4TDJ5 4TDJ4 2YU84
Step Controller	60 kW, 80 kW, 100 kW	4TDH6, 4TDH7, 4TDH8, 4TDJ1, 4TDJ2, 4TDH9	30KA30	30KA30
Qmark Accessories				
Disconnect Switch	3 kW, 15 kW 25 kW, 50 kW	All MUH Heaters Mr. Model No. MUH072, MUH077, MUH078, MUH102, MUH107, MUH108, MUH152, MUH158 30 Only, MUH202, MUH208, MUH252, MUH254, MUH304, MUH404, MUH504	DS25 MPDS60	25D248 20CA43
Fan Switch	3 kW, 15 kW	All MUH Series Heaters	MCFS	25D247
Mounting Bracket	15 to 20 25 to 30 3 to 10	15 to 20 kW MUH Unit Heaters 25 to 30 kW MUH Unit Heaters 3 to 10 kW MUH Unit Heaters	B20 B30 B10	25D243 20CA40 25D242
Thermostat	40 to 50	40 to 50 kW MUH Unit Heaters 3UG73, 3UG74	B50	20CA41 1ZKW6



Washdown Electric Wall and Ceiling Unit Heaters



- 480VAC
- 3-phase
- Mechanical selector dial

Provide warmth where equipment frequently needs to be washed or hosed off, like wastewater treatment plants, coal handling areas, food processing

plants, and car washes. Heaters feature an automatic temperature reset switch, pilot light, and mode selector switch. Corrosion-resistant housing and enclosed internal parts prevent damage. May be mounted on walls or ceilings with a mounting bracket. Heaters use a forced-air heating system.

Wattage Output	Air Temp. Rise	Air Flow	Overall Height	Overall Width	Overall Depth	Mr. Model	Item No.
5 kW	23°F	700 cfm	19 1/2 in	13 in	18 in	QWD05432BTL5	29AT97
10 kW	22°F	1,450 cfm	31 in	20 in	27 in	QWD10432BTL5	29AT98
20 kW	26°F	2,400 cfm	31 in	20 in	27 in	QWD20432BTL5	29AU01
25 kW	33°F	2,400 cfm	31 in	20 in	27 in	QWD25432BTL5	29AU02



Hazardous-Location Suspended Electric Wall and Ceiling Unit Heaters



- 480V
- 3-phase
- 24V contactor
- Class I, Group C and D, Division 1 and 2;
- Class II, Group E, F and G, Division 1 and 2 rated for use in hazardous locations

Fan-forced heaters suspend from the wall or ceiling and can be mounted horizontally with an optional

bracket. They feature an automatic reset thermal limit and disconnect switch, and take up less room than cabinet heaters. Suitable for use in hazardous industrial environments like petroleum chemical treatment and storage facilities. Wall-mount thermostat required.

Note: Required remote thermostat or other control sold separately; see page 3026.

Wattage Output	Air Temp. Rise	Air Flow	Overall Height	Overall Width	Overall Depth	Mr. Model	Item No.
3 kW	13°F	700 cfm	19 1/2 in	23 3/4 in	21 in	GUX3004832	5NF04
7.5 kW	27°F	840 cfm	19 1/2 in	23 3/4 in	21 in	GUX7504832	5NF06
10 kW	36°F	840 cfm	19 1/2 in	23 3/4 in	21 in	GUX10004832	5NF01
15 kW	31°F	1,450 cfm	25 in	27 1/2 in	21 in	GUX15004832	5NF02
20 kW	43°F	1,400 cfm	25 in	27 1/2 in	21 in	GUX20004832	5NF03



Electric Heater Coil Re-String Kits



Repair worn or damaged heating elements in electric heaters if the original replacement elements are no longer available. Kits include

heating wire, isolators, and hardware to allow users to replace elements in duct heaters, electric furnaces, air curtains, and strip heaters.

Coil Length	Outside Dia.	Watts @ 208 V	Watts @ 240 V	Watts @ 277 V	Watts @ 480 V	Mr. Model	Item No.
12 in	3/8 in	3,750 W	5,000 W	—	—	KIT24500625-25S	32MY03
18 in	3/8 in	—	—	2,000 W	—	KIT27200	32MY05
18 1/2 in	3/8 in	2,250 W	3,000 W	—	—	KIT24300	32MY07
22 in	3/8 in	2,600 W	3,500 W	—	—	KIT24350	32MY04
23 in	3/8 in	—	—	—	5,000 W	KIT48500	32MY02
2 ft 2 1/2 in	3/8 in	—	4,000 W	—	—	KIT24400	32MY06
2 ft 2 in	3/8 in	4,500 W	6,000 W	—	—	KIT24600	32MY09
2 ft 4 in	3/8 in	3,750 W	5,000 W	—	—	KIT24501	32MY01
2 ft 4 in	3/8 in	4,200 W	5,600 W	—	—	KIT24560	32MY10
2 ft 7 1/2 in	3/8 in	5,000 W	6,600 W	—	—	KIT24660	32MY08