(Tank Not Included)

Scan. Order. Done. Details on page A1.





Portable Gas Tank-Top Radiant Heaters

Dyna-Glo MRHEATER





■ Fuel type: propane Heaters mount on standard DOT 20-lb LP cylinders, making them ideal as a temporary heat source in cold buildings, garages, and jobsites. No electricity required.

| Heating Capacity | Heating | Fuel | Win. Cylinder | | Overall | Overall | Overall | | Mfr. | Item |
|---------------------|---------------|-------------|------------------|-----------------|-------------|-----------|----------|---------------|----------|--------|
| Output | Area | Consumption | Size | Ignition Type | Height | Width | Depth | Brand | Model | No. |
| 1-Head, 360° | ° Cylinder He | ead Shape | | | _ | | | | | |
| 40,000 BtuH | 1,000 sq ft | 1.8 lb/hr | 20 lb | Standing Pilot | 20 11/16 in | 8 % in | 8 % in | Dyna-Glo | TT360DG | 54EP09 |
| 45,000 BtuH | 1,125 sq ft | 2.08 lb/hr | 20 lb | Standing Pilot | 15 ¾ in | 11 in | 11 in | Mr. Heater | MH540T | 197JR0 |
| 1-Head, Reci | tangle Head | Shape | | | | | | | | |
| 16,000 BtuH | 400 sq ft | 0.66 lb/hr | 11 lb | Standing Pilot | 13 1/8 in | 10 1/6 in | 4 ½ in | Re-Verber-Ray | P-16T | 2E392 |
| 32,000 BtuH | 500 sq ft | 1.3 lb/hr | 14 lb | Standing Pilot | 18 % in | 10 1/6 in | 4 ½ in | Re-Verber-Ray | P-32T | 2E393 |
| 1-Head, Roui | nd Head Sha | pe | | | | | | | | |
| 15,000 BtuH | 176 sq ft | 0.66 lb/hr | 20 lb | Standing Pilot | 12 ½16 in | 8 1/4 in | 7 1/8 in | Dyna-Glo | TT15CDGP | 453V10 |
| 15,000 BtuH | 250 sq ft | 0.66 lb/hr | 20 lb | Matchless Piezo | 12 in | 7 1/8 in | 8 1/4 in | Ďayton | 5RCC0 | 5RCC0 |
| 2-Head, Roui | nd Head Sha | pe | | | | | | • | | |
| 30,000 BtuH | 490 sq ft | 1.4 lb/hr | 20 lb | Standing Pilot | 17 ¼ in | 6 7/16 in | 6 ½ in | Dyna-Glo | TT30CDGP | 453V11 |
| 30,000 BtuH | 500 sq ft | 1.32 lb/hr | 20 lb | Matchless Piezo | 15 ½ in | 17 1/4 in | 6 ½ in | Ďayton | 5RCC1 | 5RCC1 |
| | | | | | | | | | | |





Portable Gas Table-Top Heaters

- Fuel type: propane
- Matchless piezo ignition

Heaters are placed on work surfaces or floors to provide supplemental, close-up warmth, making them ideal for personal heating.

| Heating Capacity Output | Heating Area | Fuel Consumption | Min. Cylinder Size | Body Shape | Housing Color | Overall Height | Overall Width | Overall Depth | Mfr. Model | Item No. |
|-------------------------------|-----------------|---------------------|--------------------------|-------------|------------------|-------------------|------------------|------------------|----------------|-------------|
| 3,800 BtuH | 95 sq ft | 0.2 lb/hr | 1 lb | Cylindrical | Grey, Red | 12 in | 10 ¾ in | 10 in | MH4B-F215120 | 197JM5 |
| 9,000 BtuH | 225 sq ft | 0.33 lb/hr | 1 lb | Rectangular | Black, Red | 14 % in | 9 in | 14 % in | MH9BX-F232050 | 197JN2 |
| 12,000 BtuH | 300 sq ft | 0.6 lb/hr | 1 lb | Rectangular | Black, Camo | 14 1/4 in | 9 in | 14 1/4 in | MH12HB-F232045 | 197JN1 |
| 18,000 BtuH | 450 sq ft | 0.83 lb/hr | 2 lb | Rectangular | Black, Red | 19 in | 11 % in | 17 ½ in | MH18B-F274806 | 197JW7 |



Portable Gas Patio Heaters

CROWN TO VERITY DONG

Provide 360° radiant heat for restaurant, hotel, and retail patios as well as other outdoor locations. Heaters have a wide, angled canopy-style reflector that directs heat downward, keeping people warm at ground level. They can be moved around as heating needs change. Models conceal LP cylinders inside a cabinet in the base.

| Heating | | | Min. | | | | | | | | | | |
|-------------|------------|--------------|----------|--------------------|---------|---------|-----------|-----------|---------|---------|--------------|------------|--------|
| Capacity | Heat | Housing | Cylinder | | Overall | Overall | Overall | Overall | Overall | Overall | | Mfr. | Item |
| Input | Pattern | Color | Size | Ignition Type | | | Width | | | | Brand | Model | No. |
| 45,000 BtuH | 6 to 10 ft | Bronze | 20 lb | Electrical Spark | 90 in | 90 in | 18 1/4 in | 18 1/4 in | 35 ½ in | 35 ½ in | Crown Verity | CV-2620-AB | 60YG45 |
| 45,000 BtuH | 6 to 10 ft | Matte Silver | 20 lb | Electrical Spark | 90 in | 90 in | 18 1/4 in | 18 1/4 in | 35 ½ in | 35 ½ in | Crown Verity | CV-2620-SV | 60YG47 |
| 45,000 BtuH | 6 to 10 ft | Silver | 20 lb | Electrical Spark | 90 in | 90 in | 18 1/4 in | 18 1/4 in | 35 ½ in | 35 ½ in | Crown Verity | CV-2620-SS | 60YG46 |
| 46,000 BtuH | 8 to 10 ft | Bronze | 20 lb | Intermittent Spark | 87 in | 87 in | 32 in | 32 in | 32 in | 32 in | Bond | 52156 | 786Y45 |
| 46,000 BtuH | 8 to 10 ft | Silver | 20 lb | Intermittent Spark | 87 in | 87 in | 32 in | 32 in | 32 in | 32 in | Bond | 52157 | 786Y46 |



Portable Gas Convection Can Heaters

LBWHITE

Dayton

Dyna-Glo

Dyna-Glo

• Matchless piezo ignition
Heaters use convection
heating to create currents
that warm and circulate the
air. They're typically used
in construction applications
and are placed in the center
of a small area to provide
360° supplemental heating.

| | Capacity Output | Heating Area | Fuel Consumption | Cylinder Size | Overall Depth | Brand | Mfr. Model | Item No. |
|---|--------------------|-----------------|---------------------|------------------|------------------|------------|-----------------|-------------|
| | Natural Gas | | | | - | | | |
| | 100,000 BtuH | _ | 100 cfh | _ | 13 in | L.B. White | CV100CZND12001B | 16W293 |
| | Propane | | | | | | | |
| | 25,000 BtuH | 600 sq ft | 1.16 lb/hr | 20 lb | 11 % in | Dayton | _ | 6BY71 |
| | 25,000 BtuH | 600 sq ft | 11.6 lb/hr | 20 lb | 11 ¾ in | Dyna-Glo | RMC-LPC25DG | 453V04 |
| | 80,000 BtuH | 2,000 sq ft | 2.32 / 3.71 lb/hr | 20 lb | 15 % in | Dyna-Glo | RMC-LPC80DG | 453V05 |
| - | 80,000 BtuH | 2,000 sq ft | 3.71 lb/hr | 100 lb | 15 % in | Dayton | _ | 6BY73 |
| | 200,000 BtuH | 4,700 sq ft | 9.28 lb/hr | 100 lb | 15 % in | Dayton | _ | 6BY74 |
| | 200,000 BtuH | 4,700 sq ft | 9.28 lb/hr | 100 lb | 15 % in | Dyna-Glo | RMC-LPC200DG | 453V06 |
| | 200,000 BtuH | | 9.28 lb/hr | 100 lb | 15 in | L.B. White | 900-320C | 16W295 |
| | 250,000 BtuH | 7,000 sq ft | 2.1/10.4 lb/hr | 100 lb | 13 in | L.B. White | CV225CZPD11001B | 16W292 |
| | 250,000 BtuH | | 11.6 lb/hr | 100 lb | 15 in | L.B. White | 900-341H | 16W294 |



1WVL8

Portable Gas Radiant Can Heaters

of a small area to provide 360° supplemental heating.

Heaters use infrared radiant heating, which is absorbed by people and objects to warm them faster and more efficiently than convection heaters that warm the ambient air. They're typically used in construction applications and are placed in the center

| Capacity Output | Heating Area | Fuel Consumption | Ignition Type | Overall Height | Overall Width | Overall Depth | Brand | Mfr. Model | Item No. |
|--------------------|-----------------|---------------------|------------------|-------------------|------------------|------------------|----------|---------------|-------------|
| Natural Gas | | | | • | | | | | |
| 100,000 BtuH | 2,900 sq ft | 104 cfh | Matchless Piezo | 29 % in | 16 ¾ in | 16 ¾ in | Dayton | _ | 1WVL8 |
| 100,000 BtuH | 2,900 sq ft | 104 cfh | Matchless Piezo | 29 15/16 in | 16 5/16 in | 16 5/16 in | Dyna-Glo | RA100NGDGD | 453V07 |
| 250,000 BtuH | 5,900 sq ft | 250 cfh | Matchless Piezo | 44 5/16 in | 14 % in | 14 % in | Ďayton | _ | 6BY72 |
| 250,000 BtuH | 5,900 sq ft | 250 cfh | Continuous Spark | 44 5/16 in | 14 11/16 in | 14 11/16 in | Dyna-Glo | RA250NGDGD | 453V09 |
| Propane, Minimu | m Cylinder Size | 100 lb | | | | | | | |
| 125.000 BtuH | 2.900 sa ft | 5.8 lb/hr | Matchless Piezo | 29 15/16 in | 16 5/16 in | 16 5/16 in | Dvna-Glo | RA125LPDGD | 453V08 |

