

Direct-Fired Portable Gas Torpedo Heaters

These heaters are used as the primary source of heat in ventilated enclosed spaces or in open spaces, like jobsites and construction sites. Heaters have an open flame that directly heats the air to warm a space.

Heating Capacity Output	Heating Area	Key Features	Fuel Consumption	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
Natural Gas, Ele	ectric Ignition	D '11 A' D	140 (101/:	44.407	05.07	D 01	DIAO FALFONODOD	4501/00
150,000 BtuH	3,500 sq ft	Built-In Air Pressure Gauge, Digital Readout, On/Off Switch, Thermostat	146 cfh	16 1/8 in	11 13/16 in	25 %16 in	Dyna-Glo	RMC-FA150NGDGD	
	3,500 sq ft	Flame-Out Sensor, On/Off Switch, Thermostat	146 cfh	16 1/8 in	25 % in	11 13/16 in	Dayton		3VE56
	3,800 sq ft	Digital Readout, Flame-Out Sensor, On/Off Switch, Thermostat	146 cfh	15 in	9 in	26 in	Master	MH-150NGT-GFA	32MY62
155,000 BtuH	3,500 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, LED Diagnostics, On/Off Switch, Thermostat	155 cfh	16 in	9 ½ in	24 in	L.B. White	CP170EUNN21163T	16W281
	3,500 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, On/Off Switch, Thermostat	155 cfh	16 in	9 ½ in	24 in	L.B. White	CP170DSNN21163T	16W278
Natural Gas, Pr	opane, Electri	c Ignition							
250,000 BtuH, 400,000 BtuH	20,000 sq ft	Flame-Out Sensor, LED Diagnostics	18.6 lb/hr	21 ½ in	12 ½ in	34 ½ in	L.B. White	CH400	60NT66
400,000 BtuH	20,000 sq ft	Flame-Out Sensor, LED Diagnostics	18.6 lb/hr, 400 cfh	22 ½ in	21 1/4 in	50 in	L.B. White	CP400DF	60NT68
	20,000 sq ft	Flame-Out Sensor, On/Off Switch, Thermostat	400 cfh, 4.4 gph	24 in	18 in	46 in	Sure Flame	S405	5PFW3
750,000 BtuH	37,000 sq ft	Flame-Out Sensor, LED Diagnostics, On/Off Switch, Thermostat	750 cfh, 8.25 gph	30 in	26 in	48 ½ in	Heat Wagon		52JP77
950,000 BtuH	47,500 sq ft	Flame-Out Sensor, LED Diagnostics, On/Off Switch, Thermostat	950 cfh, 10.45 gph	39 in	30 ½ in	73 in	Heat Wagon	950H	52JP78
Propane, Batte									
68,000 BtuH	1,700 sq ft	Flame-Out Sensor, On/Off Switch	3.15 lb/hr	17 ¼ in	21 1/8 in	12 1/4 in	DeWalt	DXH70CFA	197JZ5
Propane, Electi	ric Ignition								
40,000 BtuH	940 sq ft	Flame-Out Sensor	1.9 lb/hr	13 ½ in	19 5/16 in	8 1/8 in	Dayton		3VE55
60.000 BtuH	1,350 sq ft	Flame-Out Sensor	2.3 lb/hr	13 ½ in	19 5/16 in	8 1/8 in	Dayton		3VE54
	1,500 sq ft	Flame-Out Sensor, On/Off Switch	1.9 lb/hr	13 in	7 ½ in	18 in	Master	MH-60V-GFA	32MY59
	3,100 sq ft	Built-In Air Pressure Gauge, On/Off Switch	3.5 lb/hr	16 in	12 in	25 % in	L.B. White	Tradesman 125	53CU96
125,000 BtuH	3,100 sq ft	Flame-Out Sensor	8 lb/hr	16 1/8 in	25 % in	11 13/16 in	Dayton		3VE57
	3,125 sq ft	Flame-Out Sensor, On/Off Switch	5.8 lb/hr	15 in	9 in	25 in	Master	MH-125V-GFA	32MY60
150,000 BtuH	3,500 sq ft	Built-In Air Pressure Gauge, On/Off Switch	7 lb/hr	16 1/8 in	11 13/16 in	25 %16 in	Dyna-Glo	RMC-FA150DGD	453V01
	3,500 sq ft	Flame-Out Sensor	7 lb/hr	16 1/8 in	25 % in	11 13/16 in	Dayton		3VE58
	3,800 sq ft	Flame-Out Sensor, On/Off Switch	5.5 lb/hr	15 in	9 in	25 in	Master	MH-150V-GFA	32MY61
170,000 BtuH	4,000 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, LED Diagnostics, On/Off Switch, Thermostat	7.2 lb/hr	16 in	9 ½ in	24 in	L.B. White	CP170DUPN21163T	16W280
	4,000 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, On/Off Switch, Thermostat	7.2 lb/hr	16 in	9 ½ in	24 in	L.B. White	CP170DSPN21163T	16W277
300,000 BtuH	7,000 sq ft	Built-In Air Pressure Gauge, Digital Readout, Fuel Gauge, On/Off Switch, Thermostat	13.9 lb/hr	18 ½ in	12 % in	33 ¹1⁄16 in	Dyna-Glo	RMC-FA300DGD	453V03
	7,000 sq ft	Flame-Out Sensor, On/Off Switch, Thermostat	13.9 lb/hr	18 ½ in	33 ¾ in	12 % in	Dayton	_	3VE59
375,000 BtuH	9,300 sq ft	Digital Readout, Flame-Out Sensor, On/Off Switch, Thermostat	10.4 lb/hr	23 in	13 in	35 in	Master	MH-375T-GFA	32MY63
400,000 BtuH	9,000 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, On/Off Switch, Thermostat	3 gph	21 ½ in	12 ½ in	34 ½ in	L.B. White	CP400HSPN21163T	16W279
	9,000 sq ft	Built-In Air Pressure Gauge, Flame-Out Sensor, On/Off Switch, Thermostat	3 gph	21 ½ in	12 ½ in	34 ½ in	L.B. White	CP400HUPN21163T	16W282
Propane, Manu	al Ignition								
42,000 BtuH	1,000 sq ft	Flame-Out Sensor, On/Off Switch	1.9 lb/hr	13 in	7 ½ in	18 in	Master	MH-40-GFA	32MY58

Dyna-Glo

Portable Gas Radiant Cabinet Heater

■ Propane

Heater uses infrared radiant heating, which is absorbed by people and objects to warm them faster and more efficiently than convection heaters. It's placed on the floor and provides directional supplemental heat to small areas like garages.

Heating			Min.					
Capacity	Heating	Fuel	Cylinder	Overall	Overall	Overall	Mfr. Model	Item
Output	Area	Consumption	Size	Height	Width	Depth	Model	No.
18 000 RtuH	600 sa ft	0.83 lh/hr	20 lh	23 3/2 in	14 ¾ in	15 ½ in	RA18I PDG	453V12



3083