



Natural Gas,
Propane
16W290



Propane
16W283



Direct-Fired Portable Gas Ducted & Tent Heaters

Heaters have an open flame that directly heats the air, warming a space. The exhaust gases mix into the air, so these heaters are used in ventilated spaces. They provide the primary source of heat in tented spaces and construction sites where the heat can be ducted. Heaters feature built-in air pressure gauge, LED diagnostics, power failure indicator, and remote-mounted thermostat.

| Heating Capacity Output | Heating Area | Fuel Consumption | Overall Height | Overall Width | Overall Depth | Mfr. Model | Item No. |
|--|--------------|--------------------|----------------|---------------|---------------|-----------------|-----------------|
| Natural Gas, Propane | | | | | | | |
| 80,000 BtuH | 20,000 sq ft | 3.7 lb/hr, 80 cfh | 22 in | 28 in | 13 1/2 in | CS080BSDN22168T | 407M21 |
| 170,000 BtuH | 40,000 sq ft | 7.9 lb/hr, 170 cfh | 32 in | 32 5/8 in | 24 5/8 in | CS170BSDN22168T | 16W287 |
| 350,000 BtuH | 80,000 sq ft | 350 cfh, 2.63 gph | 41 in | 48 5/8 in | 28 in | CS350SDSN22168T | 16W290 |
| Propane | | | | | | | |
| 80,000 BtuH | 20,000 sq ft | 3.7 lb/hr | 22 in | 28 in | 13 1/2 in | TS080CSPN22168T | 16W283 |
| 170,000 BtuH | 40,000 sq ft | 7.9 lb/hr | 32 in | 32 5/8 in | 24 5/8 in | TS170BSPN22168T | 16W285 |
| Description | | | | | | | Item No. |
| Accessories | | | | | | | |
| Ducting with Adapter, Gray, 12 ft L x 12 in Dia., For Use with 16W283, 16W285, 16W287 | | | | | | 500-26346 | 16W307 |
| Ducting with Adapter, White, 12 ft L x 12 in Dia., For Use with 16W283, 16W285, 16W287 | | | | | | 500-26347 | 16W308 |
| Ducting with Adapter, White, 12 ft L x 18 in Dia., For Use with 16W288, 16W290 | | | | | | 500-22835 | 16W311 |
| End Diffuser, 13 5/8 in H x 32 1/2 in W x 22 1/2 in D, For Use with 16W307, 16W308, 16W309 | | | | | | 500-26350 | 16W310 |
| End Diffuser, 19 1/2 in H x 52 3/4 in W x 28 1/2 in D, For Use with 16W311, 16W312 | | | | | | 500-23189 | 16W313 |
| Unit Diffuser, 19 1/2 in H x 23 3/8 in W x 24 1/2 in D, For Use with 16W283 | | | | | | 132902 | 16W305 |
| Unit Diffuser, 19 1/2 in H x 32 1/2 in W x 24 1/2 in D, For Use with 16W285 | | | | | | 500-26351 | 16W306 |



52JP73



Indirect-Fired Portable Gas Ducted & Tent Heaters

These heaters have a chamber that is isolated from the flame, allowing the exhaust fumes to be vented outside and the heated air to remain clean. They provide the primary source of heat in tented spaces and construction sites where the heat can be ducted.

| Heating Capacity Output | Heating Area | Key Features | Fuel Consumption | Overall Height | Overall Width | Overall Depth | Brand | Mfr. Model | Item No. |
|--|--------------|--|------------------|----------------|---------------|---------------|------------|-------------------|-----------------|
| Heaters | | | | | | | | | |
| 400,000 BtuH | 17,000 sq ft | Automatic Safety Shut-Off, Power Failure Indicator, Thermostat | 400 cfh, 4.4 gph | 59 in | 29 in | 82 in | Sure Flame | IX405 | 52JP73 |
| 400,000 BtuH | 17,000 sq ft | Automatic Safety Shut-Off, Thermostat | 400 cfh, 4.4 gph | 45 in | 24 in | 60 in | Heat Wagon | VG400 | 5PFW5 |
| Description | | | | | | | | Mfr. Model | Item No. |
| Accessories | | | | | | | | | |
| Gas Pressure Regulator, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5 | | | | | | | B42R | 6DMN6 | |
| Ducting, 25 ft, For Use with 5PFW5, 6DMP0, 6DMP2, 6DMP4 | | | | | | | WD1225 | 6DMR0 | |
| 3/4 in High Pressure Gas Hose, 25 ft, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5 | | | | | | | 7525 | 6DMR4 | |
| 3/4 in High Pressure Gas Hose, 50 ft, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5 | | | | | | | 7550 | 6DMR5 | |

5PFW5



Direct-Fired Portable Gas Remediation & Tent Heaters

Units raise and maintain the ambient air temperature high enough to kill insects, making them ideal for treating insect infestations. They can also act as a primary source of heat for tented spaces and construction sites. They have an open flame that directly heats the air to heat a space.

| Heating Capacity Output | Heating Area | Key Features | Air Temp. Rise | Fuel Consumption | Overall Height | Overall Width | Overall Depth | Mfr. Model | Item No. |
|--|--------------|--|----------------|------------------|----------------|---------------|---------------|-------------------|-----------------|
| Heat Wagon Heaters | | | | | | | | | |
| 250,000 BtuH | 12,500 sq ft | Automatic Safety Shut-Off, Power Failure Indicator | 170°F | 255 cfh, 2.6 gph | 36 in | 31 in | 45 in | DG250 | 11Z967 |
| 400,000 BtuH | 20,000 sq ft | Automatic Safety Shut-Off, Power Failure Indicator | 180°F | 404 cfh, 4.3 gph | 39 in | 34 in | 61 in | DG400 | 11Z968 |
| Description | | | | | | | | Mfr. Model | Item No. |
| Accessories | | | | | | | | | |
| Duct Adapter, For Use with 11Z967 | | | | | | Heat Wagon | AR250 | 11Z969 | |
| Duct Adapter, For Use with 11Z968 | | | | | | Heat Wagon | AR400 | 11Z970 | |
| Ducting, 25 ft L x 18 in Dia., For Use with 11Z967 | | | | | | Heat Wagon | WD1625HT5 | 11Z971 | |
| Ducting, 25 ft L x 20 in Dia., For Use with 11Z968 | | | | | | Heat Wagon | WD2025HT5 | 11Z972 | |
| Gas Pressure Regulator, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5 | | | | | | Itron | B42R | 6DMN6 | |
| Thermostat, 120 V AC, For Use with 11Z967, 11Z968 | | | | | | Heat Wagon | DIGTHDF-5 | 11Z973 | |

11Z967



453V13



453V15

Dyna-Glo Portable Kerosene Radiant Floor Heaters

They efficiently warm small spaces like garages up to 500 sq. ft. Heaters use radiant heating to emit warmth that gets absorbed by people and objects, warming them faster than others that warm the ambient air. They're placed on the floor and can be moved as heating needs change.

| Heating Capacity Output | Tank Cap. | Hours on One Filling | Color | Overall Height | Overall Width | Overall Depth | Mfr. Model | Item No. |
|-------------------------|-----------|----------------------|-------|----------------|---------------|---------------|------------|----------|
| 10,000 BtuH | 0.7 gal | 13 hr | Black | 19 3/8 in | 22 3/8 in | 11 1/2 in | RMC-55R7B | 453V14 |
| 10,000 BtuH | 0.7 gal | 13 hr | White | 19 3/8 in | 22 3/8 in | 11 1/2 in | RMC-55R7 | 453V13 |
| 10,500 BtuH | 0.8 gal | 12 hr | White | 21 3/8 in | 12 3/8 in | 12 3/8 in | WK11C8 | 453V15 |