



Indirect-Fired Portable Oil & Kerosene Torpedo Heaters

▪ LED diagnostics

Units have a chamber that is isolated from the flame, allowing the exhaust fumes to be vented outside and the heated air to remain clean. They provide the primary source of heat in large spaces like construction sites where the heat can be ducted.



5PFW9

| Heating Capacity Output | Heating Area | Tank Capacity/ Hours on One Filling | Overall Height | Overall Length | Overall Depth | Brand | Mfr. Model | Item No. |
|---------------------------------|--------------|-------------------------------------|----------------|----------------|---------------|------------|------------|----------|
| Heaters, Wheeled Mounted | | | | | | | | |
| 91,900 BtuH | 4,600 sq ft | 17.2 gal/22 hr | 31 in | 49 in | 49 in | Heat Wagon | HVF110 | 5PFW8 |
| 174,900 BtuH | 8,800 sq ft | 27.7 gal/19 hr | 38 in | 57 in | 57 in | Heat Wagon | HVF210 | 5PFW9 |
| 231,000 BtuH | 17,500 sq ft | 57 gal/20 hr | 48 in | 83 in | 83 in | Heat Wagon | HVF410 | 5PFX1 |
| 254,400 BtuH | 13,000 sq ft | 35.7 gal/16 hr | 38 in | 69 in | 69 in | Heat Wagon | HVF310 | 5PFX0 |

| Description | Brand | Mfr. Model | Item No. |
|---|------------|------------|----------|
| Accessories | | | |
| Duct Adapter, 10 in. For Use with 5PFW9 | Heat Wagon | AR210 | 6DMP1 |
| Duct Adapter, 10 in. For Use with 5PFX0 | Heat Wagon | AR310 | 6DMP3 |
| Duct Adapter, 12 in. For Use with 5PFW9 | Heat Wagon | AR212 | 6DMP2 |
| Duct Adapter, 12 in. For Use with 5PFX0 | Heat Wagon | AR312 | 6DMP4 |
| Duct Adapter, 12 in. For Use with 5PFX1 | Heat Wagon | AR401 | 6DMP5 |
| Duct Adapter, 18 in. For Use with 5PFX1 | Heat Wagon | AR402 | 6DMP6 |
| Duct Adapter, 8 in. For Use with 5PFW8 | Heat Wagon | AR110 | 6DMP0 |
| Ducting, 20 ft. For Use with 6DMP0, 6DMP2, 6DMP4 | Heat Wagon | WD1220 | 6DMP9 |
| Ducting, 25 ft. For Use with 5PFW5, 6DMP0, 6DMP2, 6DMP4 | Heat Wagon | WD1225 | 6DMR0 |
| Ducting, 25 ft. For Use with 5PFW6, 6DMP5, 6DMP7 | Heat Wagon | WD2025 | 6DMR3 |
| Ducting, 25 ft. For Use with 6DMP1 | Heat Wagon | WD1425 | 6DMR1 |
| Ducting, 25 ft. For Use with 6DMP3, 6DMP6 | Heat Wagon | WD1825 | 6DMR2 |
| Flue Stack, 18 in. For Use with 5PFW8, 5PFW9, 5PFX0, 5PFX1 | Selkirk | EF1 | 6DMN9 |
| Thermostat, For Use with 52JP74, 52JP75, 52JP76, 5PFW8, 5PFW9, 5PFX0, 5PFX1 | Heat Wagon | THIDF | 6DMN8 |



Natural Gas
36FK50

In-Floor Vented Gas Heaters



Heaters install in an opening in the floor and provide supplemental heat in drafty areas with limited space. They lower into the floor and mount either parallel or perpendicular to the floor joists. Venting is required. They can be controlled with a unit-installed thermostat or a separate wall thermostat.

| Heating Capacity Input | Heating Capacity Output | Heating Area | Thermostat Incl. | Grille Dim. - L x W | Rough-In Dim. - L x W x D | Mfr. Model | Item No. |
|------------------------|-------------------------|--------------|------------------|---------------------|-------------------------------|------------|----------|
| Natural Gas | | | | | | | |
| 45,000 BtuH | 31,000 BtuH | 1,000 sq ft | No | 32 in x 24 in | 32 3/8 in x 24 1/4 in x 28 in | 4505622A | 36FK50 |
| 60,000 BtuH | 42,000 BtuH | 1,400 sq ft | No | 42 in x 24 in | 42 3/8 in x 24 1/4 in x 28 in | 6005622A | 36FK51 |
| Propane | | | | | | | |
| 45,000 BtuH | 31,000 BtuH | 1,000 sq ft | No | 32 in x 24 in | 32 3/8 in x 24 1/4 in x 25 in | 4505621A | 36FK52 |
| 60,000 BtuH | 42,000 BtuH | 1,400 sq ft | No | 42 in x 24 in | 42 3/8 in x 24 1/4 in x 28 in | 6005621A | 36FK53 |



Natural Gas,
Solid Face Style
36FK36

Freestanding Vented Gas Floor Heaters



These units provide supplemental heat and can be placed on the floor anywhere in a room without cutting into the floor. They're usually set close to a wall since they require venting that's ducted out of the room.

| Heating Capacity Input | Heating Capacity Output | Thermostat Incl. | Vent Diameter | Overall Height | Overall Width | Overall Depth | Brand | Mfr. Model | Item No. |
|--|-------------------------|------------------|---------------|----------------|---------------|---------------|----------|------------|----------|
| Natural Gas, Solid Face Style | | | | | | | | | |
| 20,000 BtuH | 15,500 BtuH | No | 3 in | 21 1/2 in | 23 in | 11 in | Williams | 2001622A | 36FK36 |
| 20,000 BtuH | 16,300 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV20ENAT | 4LFZ6 |
| 35,000 BtuH | 24,500 BtuH | Unit-Mounted | 4 in | 26 in | 37 in | 18 3/8 in | Empire | RH35NAT | 4LGF7 |
| 35,000 BtuH | 25,000 BtuH | No | 4 in | 28 1/2 in | 25 in | 15 1/2 in | Williams | 3501522A | 36FK37 |
| 40,000 BtuH | 32,600 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV40ENAT | 4LGA5 |
| 50,000 BtuH | 34,500 BtuH | No | 4 in | 32 1/2 in | 30 in | 16 in | Williams | 5001522A | 36FK38 |
| 55,000 BtuH | 44,825 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV55ENAT | 4LGA7 |
| 65,000 BtuH | 47,000 BtuH | No | 5 in | 32 1/2 in | 34 in | 19 1/2 in | Williams | 6501522A | 36FK39 |
| Natural Gas, Visual Flame Style | | | | | | | | | |
| 25,000 BtuH | 17,500 BtuH | Unit-Mounted | 4 in | 26 in | 37 in | 18 3/8 in | Empire | RH25NAT | 4LGF5 |
| 35,000 BtuH | 25,000 BtuH | No | 4 in | 28 1/2 in | 25 in | 15 1/2 in | Williams | 3502522A | 36FK44 |
| 50,000 BtuH | 25,000 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 23 3/8 in | Empire | RH50BNAT | 2R2C8 |
| 50,000 BtuH | 34,500 BtuH | No | 4 in | 32 1/2 in | 30 in | 16 in | Williams | 5002522A | 36FK45 |
| 50,000 BtuH | 35,000 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 23 3/8 in | Empire | RH50CNAT | 4LGG2 |
| 65,000 BtuH | 33,000 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 27 1/8 in | Empire | RH65NAT | 2R2C5 |
| 65,000 BtuH | 45,500 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 27 1/8 in | Empire | RH65CNAT | 4LGG6 |
| 65,000 BtuH | 47,000 BtuH | No | 5 in | 32 1/2 in | 34 in | 19 1/2 in | Williams | 6502522A | 36FK46 |
| Propane, Solid Face Style | | | | | | | | | |
| 20,000 BtuH | 15,500 BtuH | No | 3 in | 21 1/2 in | 23 in | 11 in | Williams | 2001621A | 36FK40 |
| 20,000 BtuH | 16,300 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV20ELP | 4LFZ5 |
| 25,000 BtuH | 17,500 BtuH | Unit-Mounted | 4 in | 26 in | 37 in | 18 3/8 in | Empire | RH25LP | 4LGF4 |
| 35,000 BtuH | 24,500 BtuH | Unit-Mounted | 4 in | 26 in | 37 in | 18 3/8 in | Empire | RH35LP | 4LGF6 |
| 35,000 BtuH | 25,000 BtuH | No | 4 in | 28 1/2 in | 25 in | 15 1/2 in | Williams | 3501521A | 36FK41 |
| 40,000 BtuH | 32,600 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV40ELP | 4LGA4 |
| 50,000 BtuH | 34,500 BtuH | No | 4 in | 32 1/2 in | 30 in | 16 in | Williams | 5001521A | 36FK42 |
| 50,000 BtuH | 35,000 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 23 3/8 in | Empire | RH50CLP | 4LGG1 |
| 55,000 BtuH | 44,825 BtuH | Unit-Mounted | 3 1/2 in | 26 in | 37 in | 15 3/4 in | Empire | DV55ELP | 4LGA6 |
| 65,000 BtuH | 45,500 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 27 1/8 in | Empire | RH65CLP | 4LGG5 |
| 65,000 BtuH | 47,000 BtuH | No | 5 in | 32 1/2 in | 34 in | 19 1/2 in | Williams | 6501521A | 36FK43 |
| Propane, Visual Flame Style | | | | | | | | | |
| 50,000 BtuH | 25,000 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 23 3/8 in | Empire | RH50BLP | 2R2C2 |
| 65,000 BtuH | 32,500 BtuH | Unit-Mounted | 5 in | 29 3/8 in | 34 in | 27 1/8 in | Empire | RH65BLP | 2R2C5 |

| Accessory Type | Compatible Grainger Part No. | Mfr. Model | Item No. |
|--------------------|--|------------|----------|
| Accessories | | | |
| Blower | 36FK37, 36FK38, 36FK39, 36FK41, 36FK42, 36FK43, 36FK44, 36FK45, 36FK46, 36FK47, 36FK48, 36FK49 | 2102 | 36FK85 |
| Floor Pad | 36FK38, 36FK39, 36FK42, 36FK43, 36FK45, 36FK46, 36FK48, 36FK49 | 4163 | 36FK86 |