



6JJK8



31TP30



414X14

Duct-Mount Humidifiers

Add moisture to indoor air to make the space feel warmer, minimize static shocks, and help prevent wood surfaces from drying out. For use in office buildings, homes, and warehouses.

Bypass—Allow warm air from a building's furnace to pass over the humidifiers' water tray, and the air absorbs the water.

Honeywell Home **Aprilaire** **White-Rodgers** **BESTAIR**
INSPIRODUCT PRO

Fan-Powered—Use a fan to push air across the humidifiers' water tray allowing the air to absorb the water. Add more moisture to indoor air and can fit into smaller spaces than bypass models.

Steam—Have electrodes to create steam and add moisture to air that is moving through the HVAC system. Use less water to humidify the air than fan-powered and bypass models.

Note: Max. Sq. Foot Cap. is an approximation based on 8-ft. ceiling height.

Daily Humidification Output	Coverage Area	Humidity Settings	Plenum Opening Req.	Humidistat Control Modes	Overall HxWxD	Brand	Mfr. Model	Item No.
Humidifiers								
Bypass, Gravity Drain								
12 gal	2,000 sq ft	20% to 60%	9 1/4 in H x 9 3/4 in W	Automatic/Manual	14 in x 14 1/2 in x 10 1/2 in	Honeywell Home	HE150A1005	6JJK8
	2,000 sq ft	20% to 60%	9 1/4 in H x 9 3/4 in W	Manual	14 in x 14 1/2 in x 10 1/2 in	Honeywell Home	HE100A1000	6JKJ7
	3,000 sq ft	30% to 60%	9 1/2 in H x 9 1/2 in W	Automatic/Manual	13 in x 15 1/2 in x 10 3/4 in	Aprilaire	500M	31TP26
17 gal	3,000 sq ft	30% to 60%	9 1/2 in H x 9 1/2 in W	Manual	13 in x 15 1/2 in x 10 3/4 in	Aprilaire	500M	31TP27
	2,500 sq ft	20% to 60%	12 1/2 in H x 9 3/4 in W	Automatic/Manual	17 1/2 in x 15 in x 10 1/2 in	Honeywell Home	HE200A1000	6JKJ9
	2,500 sq ft	20% to 60%	12 1/2 in H x 9 3/4 in W	Automatic/Manual	17 1/2 in x 15 in x 10 1/2 in	Honeywell Home	HE250A1005	6JLL0
	4,000 sq ft	30% to 60%	10 in H x 12 1/4 in W	Automatic/Manual	15 1/4 in x 15 1/2 in x 10 3/4 in	Aprilaire	600M	31TP28
	4,000 sq ft	30% to 60%	12 3/4 in H x 10 in W	Manual	15 1/4 in x 15 1/2 in x 10 3/4 in	Aprilaire	600M	31TP29
19 gal	2,880 sq ft	—	16 3/4 in H x 13 1/2 in W	Manual	18 3/4 in x 13 3/4 in x 9 3/4 in	White-Rodgers	HFT 2900FP	36L348
Bypass, Gravity Drain Optional								
17 gal	4,000 sq ft	30% to 60%	10 in H x 12 1/4 in W	Automatic/Manual	15 1/4 in x 15 1/2 in x 10 3/4 in	Aprilaire	400M	31TP24
	4,000 sq ft	30% to 60%	10 in H x 12 1/4 in W	Manual	15 1/4 in x 15 1/2 in x 10 3/4 in	Aprilaire	400M	31TP25
Fan-Powered, Gravity Drain								
18 gal	3,000 sq ft	20% to 60%	14 1/4 in H x 13 1/2 in W	Automatic/Manual	16 3/4 in x 15 1/2 in x 10 3/4 in	Honeywell Home	HE300A1005	6JLL1
	4,200 sq ft	30% to 60%	14 3/4 in H x 14 1/4 in W	Automatic/Manual	18 in x 15 1/4 in x 10 3/4 in	Aprilaire	700M	31TP30
	4,200 sq ft	30% to 60%	14 3/4 in H x 14 1/4 in W	Manual	18 in x 15 1/4 in x 10 3/4 in	Aprilaire	700M	31TP31
Steam, Auto Flush								
17 gal	2,575 sq ft	—	10 1/2 in H x 8 in W	—	7 3/4 in x 12 3/4 in x 12 1/2 in	White-Rodgers	HSP 2600	36L350
Steam, Gravity Drain								
22 gal	4,000 sq ft	40% to 60%	—	—	20 1/4 in x 10 in x 7 in	Honeywell Home	HM750A1000/U	414X14
35 gal	6,200 sq ft	30% to 60%	—	—	21 in x 10 1/2 in x 7 1/2 in	Aprilaire	800	31TP32
Compatible Mfr. Model No.								
							Brand	Item No.
							Aprilaire	31TP34 *
							Honeywell Home	2TE75
							Aprilaire	31TP36 *
							Honeywell Home	2TE76
							Bestair Pro	2FRR9
							Aprilaire	31TP37 *

Replacement Pads

- 110, 220, 500, 500A, 500M, 550, 550A, 558
- 110, 220, 550, 558, HE100, HE150, HE220, HE225
- 350, 360, 560, 560A, 568, 600, 600A, 600M, 700, 700A, 700M, 760, 760A, 768
- 350, 360, 560, 568, 600, 700, 760, 769, HE200, HE250, HE260, HE265, HE300, HE360, HE365
- 360, 560, 560A, 568, 600, 700, 760, 760A, 768, Aprilaire 350, HC26A1008, HC26E1004, HE260A/B, HE265A/B, HE360A/B, ME360, WB2-17, WP2-18
- 400, 400A, 400M

* OEM replacements.

Ductable Dehumidifiers

Dry the air and help prevent mold, mildew, and odors in offices, schools, and other indoor spaces where continual moisture removal is needed. Can operate as a freestanding unit.

Honeywell Home **Aprilaire**

Ductable Humidifiers with Fresh-Air Intake—Separate control allows models to pull in fresh air from outside to dissipate stale air and help reduce trapped airborne contaminants in indoor areas.



443W15

Daily Water Removal Capacity (80F/60 RH)	Air Flow @ 0.0 in wg	Coverage Area	For Duct Dia.	Operating Humidity Range	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
Ductable Dehumidifiers										
65 pt	160 cfm	1,800 sq ft	8 in	0% to 90%	12 in	12 in	28 1/2 in	Honeywell Home	DR65A3000/U	443W15
80 pt	185 cfm	4,400 sq ft	10 in	40% to 60%	15 in	14 in	26 in	Aprilaire	E080	787CM7
100 pt	280 cfm	5,500 sq ft	10 in	40% to 60%	15 in	14 in	26 in	Aprilaire	E100	787CM8
Ductable Dehumidifiers with Fresh-Air Intake										
90 pt	320 cfm	2,800 sq ft	10 in	0% to 90%	19 3/4 in	14 3/4 in	32 3/4 in	Honeywell Home	DR90A3000/U	443W16
120 pt	400 cfm	3,500 sq ft	10 in	0% to 90%	20 1/2 in	14 3/4 in	32 3/4 in	Honeywell Home	DR120A3000/U	443W17
Filter Type										
Replacement Filter		Compatible Grainger Part No.		Performance Rating	Overall HxWxD		Brand	Mfr. Model		Item No.
Pleated		443W16, 443W17		MERV 11	14 in x 17 1/2 in x 1 3/4 in		Honeywell Home	50070171-002/U		20Y116

GRANGO Heat Pump Reversing Valves and Solenoid Coils

Slide-type, 4-way valves. Solenoid coils include wiring harness.

Cap. in Tons (R-22)	Cap. in Tons (R-502)	Suction Tube I.D.	High Pressure Tube I.D.	Mfr. Model	Item No.
1.0 to 2.5	1.0 to 2.5	3/8 in	1/2 in	V2-410060-470	5AV34
1.0 to 5.0	1.0 to 5.0	3/4 in	1/2 in	V6-412080-170	5AV35
1.0 to 5.0	1.0 to 5.0	3/4 in	1/2 in	V6-414080-170	5AV36
3.0 to 8.5	3.0 to 11.9	1 1/8 in	1/2 in	V10-414080-170	5AV32
3.0 to 9.5	3.0 to 11.9	1 1/8 in	1/2 in	V10-418140-170	5AV33
Voltage @ 50 Hz		Watts @ 60 Hz		Mfr. Model	Item No.
24		5 W		LDK-110000-070	5AV38
208/240		5 W		LDK-410000-070	5AV39



5AV39

DIVERSITECH Condensate Drain Pans

Rolled edges are easy on the hands.

Steel—Seamless, nestable pans have 2 possible drain outlet positions.

Plastic—Ribbed bottoms and reinforced corners for strength.



3HAJ3

Dim. (in.)*			Mfr. Model	Item No.
L	W	D		
26-ga. Galv. Steel, 3/4" Drain Line Fitting & Plug				
48	27	2	6-M2748	3HAD7
60	30	2	6-M3060	3HAD8
Black Plastic, 3/4" PVC Fitting				
27	39	2	6-2739L	3HAK1
27	48	2	6-2748L	3HAJ5
27	63	2	6-2763L	3HAJ6
30	30	2	6-3030L	3HAJ4
30	50	2	6-3050L	3HAJ9
30	60	2	6-3060L	3HAJ3
32	63	2	6-3263L	3HAJ7
36	36	2	6-3636L	3HAJ8
36	60	2	6-3660L	3HAJ2

Accessories	Mfr. Model	Item No.
Condensation Flood Detector Switch	WS-1	6XJG7
Condensation Overflow Safety Switch	SOS-1	6XJH7
Condensation Pan Switch	CC-1	6XJH8

* L and W dimensions are for the base of the pan.



10L931

Sponge Rubber Seal Strip

Adhesive backing bonds to wood, metal, glass, and other smooth surfaces. For indoor use as weather stripping, cushion, insulator, seal, and gap-filler. Max. temp.: 200°F.

L	W	Thick-ness	Item No.
50 ft	0.5 in	3/16"	10L933
50 ft	0.75 in	1/4"	10L934
50 ft	1 in	1/4"	10L935
50 ft	1 in	3/16"	10L936
25 ft	0.75 in	3/16"	10L931
25 ft	1 in	3/16"	10L932