



6C132

Surge Suppression Receptacles

- 125V
- Power On indicator light

Provide point-of-use protection that can cause premature electronic equipment failure. Audible alarm alerts occupants when device needs replacement. Features a high-impact, nylon face that resists damage. Isolated ground-grade models protect equipment from effects of noise on the ground circuit. For use in accordance with NEC/NFPA Article 250-74, Exception 2. UL Listed and CSA Certified.



Wiring Device-Kellems

Current Rating	NEMA Recept. Config.	Special Features	Isolated Grounding	Mfr. Model	Brand	BLUE Item No.	IVORY Item No.	ORANGE Item No.
Commercial								
15 A	5-15R	—	—	HL5260SA	Hubbell	3D184	3D183	—
	5-15R	Audible Alarm	—	SP52A	—	49YZ33	52HE21	—
	5-20R	—	—	HL5360SA	Hubbell	3D205	3D204	—
20 A	5-20R	Audible Alarm	—	SP53A	—	49YZ34	52HE23	—
	5-20R	Audible Alarm	Yes	SP53IGA	—	49YZ35	52HE24	—
Harsh and Heavy Use Industrial								
15 A	5-15R	Audible Alarm	—	HL5262SA	Hubbell	6C132	—	—
20 A	5-20R	Audible Alarm	—	HL5362SA	Hubbell	6C133	6C605	—
Hospital Grade								
15 A	5-15R	Audible Alarm	—	SP82A	—	49YZ36	52HE25	—
	5-15R	Audible Alarm	Yes	SP82IGA	—	49YZ37	52HE26	52HE27
	5-20R	Audible Alarm	—	HL8362SA	Hubbell	6C136	3D287	—
20 A	5-20R	Audible Alarm	Yes	IG8362SA	Hubbell	3D407	4D331	—
	5-20R	Audible Alarm	—	SP83A	—	49YZ38	52HE31	—
	5-20R	Audible Alarm	Yes	SP83IGA	—	49YZ39	52HE33	52HE34
Industrial								
15 A	5-15R	Audible Alarm	—	IG5262SA	Hubbell	6C134	—	—
20 A	5-20R	Audible Alarm	—	IG5362SA	Hubbell	6C135	—	—



4FTW7



3D400

Isolated Ground Receptacles

- 125V

Insulation-barrier construction isolates ground contacts from mounting strap for a noise-free ground. Reinforced thermoplastic polyester base with impact-resistant nylon face. For use in accordance with NEC/NFPA Article 250-74, Exception 4.

Current Rating	NEMA Recept. Config.	Receptacle Type	Description	Brand	Mfr. Model	GRAY Item No.	IVORY Item No.	LIGHT ALMOND Item No.	ORANGE Item No.	WHITE Item No.
Commercial										
15 A	5-15R	Decorator Duplex	—	Hubbell	IG15DR	4ENJ1	4ENJ2	—	—	4ENJ4
	5-15R	Duplex	Smooth	Hubbell	IG15CR	—	4ENH5	—	4ENH2	4ENH7
	5-15R	Duplex	—	—	CR15IG	—	—	—	49Y219	—
20 A	5-20R	Duplex	Smooth	Hubbell	IG20CR	4FTW5	4FTW6	4FTW7	4ENJ5	4FTW8
	5-20R	Decorator Duplex	—	Hubbell	IG20DR	—	4FTX3	—	—	4FTX5
Harsh and Heavy Use Industrial										
15 A	5-15R	Duplex	—	—	BRY5262G	52HD11	—	—	49YZ03	52HD13
15 A	5-15R	Duplex	—	—	BRY5262G1	—	52HD12	—	—	—
	5-20R	Duplex	—	—	BRY5362IG	—	52HD25	—	49YZ05	—
Industrial										
15 A	5-15R	Duplex	—	Hubbell	IG5262	3D401	—	—	5A075	—
	5-15R	Single	—	Hubbell	IG5261	—	—	—	3D400	—
	5-15R	Single	—	—	5261IG	—	—	—	49YY68	—
20 A	5-20R	Single	—	Hubbell	IG5361	—	—	—	3D404	—
	5-20R	Duplex	—	Hubbell	IG5362	—	3D406	—	5A083	—
	5-20R	Single	—	—	5361IG	—	—	—	49YY72	—
5-20R	Duplex	Smooth	Hubbell	IG5352	4FTY5	4FTY6	4FTY7	4FTY3	4FTY8	4FTY8



Wiring Device-Kellems



437K70



437K89

USB Charger Tamper-Resistant Receptacles

- 125VAC
- LED indicates USB power
- USB charging 5.0A @ 5VDC

Devices combine USB DC power and tamper-resistant AC electrical power in a standard single-gang opening, so you can charge personal electronics and power appliances from the same receptacle. Back and side wire for solid or stranded wire. UL and C-UL Listed.

Current Rating	NEMA Recept. Config.	Receptacle Type	No. of USB Ports	USB Connection Type	Brand	BLACK Item No.	BROWN Item No.	GRAY Item No.	IVORY Item No.	RED Item No.	WHITE Item No.
Commercial											
15 A	5-15R	Duplex	2	A	Hubbell	437K37	437K36	437K38	437K39	—	437K40
	5-15R	Duplex	2	A, C	Hubbell	437K61	437K63	437K60	437K58	—	437K59
	5-15R	Duplex	2	C	Hubbell	437K85	437K87	437K84	437K82	437K86	437K83
20 A	5-20R	Duplex	2	A	Hubbell	437K42	437K41	437K43	437K44	—	437K45
	5-20R	Duplex	2	A, C	Hubbell	437K67	437K69	437K66	437K64	—	437K65
	5-20R	Duplex	2	C	Hubbell	—	437K93	—	437K88	437K92	437K89
General Purpose											
15 A	5-15R	Duplex	2	A, C	Legrand	56FM94	56FM95	56FM96	—	—	56FM99
	5-15R	Duplex	2	A	—	—	—	—	—	—	492P70
Hospital Grade											
15 A	5-15R	Duplex	2	A	Hubbell	437K47	437K46	437K48	—	437K50	437K51
	5-15R	Duplex	2	C	Hubbell	437K97	—	—	437K94	—	437K95
	5-15R	Duplex	2	A, C	Hubbell	437K73	437K75	437K72	437K70	437K74	437K71
20 A	5-15R	Duplex	2	A	Leviton	792UR6	—	—	792UR7	—	792UR8
	5-20R	Duplex	2	C	Hubbell	437L04	437L06	437L03	437L01	437L05	437L02
	5-20R	Duplex	2	A	Hubbell	437K53	437K52	437K54	437K55	437K56	437K57
20 A	5-20R	Duplex	2	A, C	Hubbell	437K79	437K81	437K78	437K76	437K80	437K77
	5-20R	Duplex	2	A	Leviton	—	—	—	—	—	792UT3



Wiring Device-Kellems



5Z841



5Z893



Wiring Device-Kellems



High-Ampere Receptacles

UL Listed and CSA Certified.

See page 311 for NEMA plug configurations.

Current Rating	NEMA Recept. Config.	No. of Poles	No. of Wires	Voltage Rating	Hubbell Mfr. Model	Hubbell Item No.	Approved Vendor Mfr. Model	Approved Vendor Item No.	Leviton Mfr. Model	Leviton Item No.
20 A	10-20R	3	3	125/250V AC	HBL6810	5Z839	9326	49YY66	—	—
	14-20R	3	4	125/250V AC	HBL8410	6C630	—	—	—	—
	15-20R	3	4	250V AC	HBL8420	5C793	—	—	—	—
30 A	5-30R	2	3	125V AC	HBL9308	5Z904	9530FR	49YY94	5371	792TU1
	6-30R	2	3	250V AC	HBL9330	5Z895	9630FR	49YY96	5372-S00	792TU2
	6-30R	2	3	250V AC	—	—	—	—	5376-P00	792TU5
30 A	10-30R	3	3	125/250V AC	HBL9350	5Z841	9303	49YY64	5054-P00	792TJ6
	14-30R	3	4	125/250V AC	HBL9430A	5Z883	9430FR	49YY92	278-S00	792TC0
	15-30R	3	4	250V AC	HBL8430A	5Z889	8430FR	49YY88	8430	792U52
50 A	TT-30R	2	3	125V AC	HBLTT30R	54DY13	—	—	7313-S00	792TY1
	5-50R	2	3	125V AC	HBL9360	5Z896	9550FR	49YY95	—	—
	6-50R	2	3	250V AC	HBL9367	5Z897	9650FR	49YY97	5374-S00	792TU4
50 A	10-50R	3	3	125/250V AC	HBL7962	5Z840	9306	49YY65	5050-P00	792TU6
	14-50R	3	4	125/250V AC	HBL9450A	5Z885	9450FR	49YY93	279-S00	792TC1
	14-50R	3	3	125/250V AC	—	—	—	—	55050-P00	792TV3
60 A	15-60R	3	4	250V AC	HBL8450A	5Z891	8450FR	49YY89	8450	792U54
	14-60R	3	4	125/250V AC	HBL9460A	5Z887	—	—	9460	792U65
	15-60R	3	4	250V AC	HBL8460A	5Z893	8460FR	49YY90	8460	792U56
18-60R	4	4	120/208V AC	HBL7301A	3D240	—	8360FR	49YY87	8360	792U45