



Liquid-Tight Cord Connectors

- Nylon: for washdown areas
- Aluminum: where lighter weight or better corrosion resistance is desired
- Zinc-plated steel: where higher impact resistance and tensile strength are desired

Proprietary split-hinge Gotcha® ring, color-coded by cord size, grips conductor through cord jacket. Factory-lubricated bushing provides even compression, ensures liquid-tight seal around cord, and minimizes tension on terminals. UL Listed, CSA Certified.

NYLON

Tough, durable, and highly resistant to corrosion.

MACHINED METAL

More durable and reliable than cast metal parts.

Note: Order locknuts on page 306.

Conduit Size	Cord Dia. Range	NYLON		ALUMINUM		ZINC-PLATED STEEL	
		Straight Item No.	90° Item No.	Straight Item No.	90° Item No.	Straight Item No.	90° Item No.
3/8"	0.19 in to 0.25 in	5D876	—	5D712	—	—	—
	0.25 in to 0.31 in	5D877	—	5D713	2XYJ4	2XYL8	—
	0.25 in to 0.38 in	2XYL9	—	5D714	—	—	—
	0.38 in to 0.44 in	2XYN1	—	5D715	2XYJ6	5D919	—
	0.31 in to 0.38 in	—	—	—	2XYJ5	—	—
	0.13 in to 0.19 in	5D881	2XYJ8	5D721	2XYJ7	2XYN3	—
1/2"	0.19 in to 0.25 in	5D882	2XYJ9	5D716	5D798	5D922	2XYK1
	0.25 in to 0.38 in	5D883	5D899	5D723	5D799	5D923	5D971
	0.38 in to 0.50 in	5D884	5D900	5D724	5D800	5D924	5D972
	0.50 in to 0.63 in	5D885	5D901	5D725	5D801	5D925	5D973
	0.06 in to 0.13 in	2XYN2	—	5D720	—	—	—
	0.63 in to 0.75 in	—	—	5D726	—	2XYN4	—
3/4"	0.75 in to 0.88 in	—	—	5D727	—	2XYN5	—
	0.25 in to 0.31 in	—	—	5D717	—	2XYN5	—
	0.31 in to 0.38 in	—	—	5D718	—	—	—
	0.38 in to 0.44 in	—	—	5D719	—	—	—
	0.19 in to 0.25 in	—	—	5D722	—	—	—
	0.38 in to 0.50 in	5D886	2XYK3	5D732	2XYK2	5D932	2XYK4
1"	0.50 in to 0.63 in	5D887	5D903	5D733	2XYK5	5D933	2XYK6
	0.63 in to 0.75 in	5D888	5D904	5D735	5D804	5D934	2XYK7
	0.75 in to 0.88 in	5D889	2XYK8	5D736	5D805	5D935	5D977
	0.25 in to 0.38 in	—	—	5D731	—	5D931	—
	0.63 in to 0.75 in	5D892	—	5D739	2XYK9	5D966	5D978
	0.75 in to 0.88 in	5D893	5D909	5D740	2XYL2	5D967	—
1 1/4"	0.50 in to 0.63 in	5D894	5D910	5D741	2XYL3	5D936	—
	0.63 in to 0.75 in	2XYN6	—	5D738	5D807	2XYP2	—
	1.00 in to 1.13 in	2XYN7	—	5D742	2XYL4	—	—
	1.00 in to 1.13 in	—	—	5D749	2XYL5	5GTF8	—
	1.13 in to 1.25 in	—	—	5D750	2XYL6	—	—
	1.25 in to 1.38 in	—	—	2XYN8	2XYL7	—	—
1 1/2"	1.00 in to 1.13 in	—	—	2XYN9	5D817	5GTG0	—
	1.25 in to 1.38 in	—	—	2XYP1	5D819	5GTG2	—
	1.13 in to 1.25 in	—	—	5D755	—	5GTG1	—
	1.38 in to 1.50 in	—	—	—	5D821	—	—

* Compact 1.45" vs. 1.65" length.



Liquid-Tight Cord Mesh Grips

Deluxe stainless steel cord/cable grips completely eliminate pull tension on terminals, indoors or outdoors, sealing out moisture and cutting oils. Grips control cable arc-of-bend and prevent cord pullout. Corrosion resistant with aluminum fitting that connects to box or hub, effectively sealing out contaminants. Useful in wiring enclosures, pendant stations, construction sites, processing and material handling equipment, pumps, motors, and machine tools.



Trade Size	Cable Dia. Range	STRAIGHT Item No.	90° Item No.	Trade Size	Cable Dia. Range	STRAIGHT Item No.	90° Item No.
3/8"	0.25 in to 0.31 in	6D124	2TGJ4	1"	0.50 in to 0.63 in	5C801	—
	0.31 in to 0.38 in	6D125	—		0.63 in to 0.75 in	5C802	—
	0.38 in to 0.44 in	—	2TGJ6		0.75 in to 0.88 in	6C105	6D179
1/2"	0.19 in to 0.25 in	6D126	6D170	1 1/4"	0.87 in to 1.00 in	6C106	2VRV9
	0.25 in to 0.38 in	6D127	6D171		1.00 in to 1.13 in	6D135	2TGK3
	0.38 in to 0.50 in	6C101	6D172		0.87 in to 1.00 in	6D136	—
3/4"	0.50 in to 0.63 in	6C102	6D173	1 1/2"	1.00 in to 1.13 in	6D137	2TGK2
	0.63 in to 0.75 in	6D128	—		1.13 in to 1.25 in	6D138	2TGJ7
	0.25 in to 0.38 in	6D131	—		1.25 in to 1.38 in	6D139	—
2"	0.38 in to 0.50 in	6D132	6D174	2"	1.00 in to 1.13 in	6D142	2TGJ8
	0.50 in to 0.63 in	6C103	6D175		1.13 in to 1.25 in	6D143	2TGJ9
	0.63 in to 0.75 in	6C104	6D176		1.25 in to 1.38 in	6D144	—
	0.75 in to 0.88 in	6D133	6D177		1.44 in to 1.56 in	6D152	2TGK4
					1.56 in to 1.69 in	6D153	—

2A246



2DDK4

Liquid-Tight Cord Grip Connectors

Connectors can be tightened with pliers or screwdrivers when working in tight areas. Type 304 stainless steel connectors withstand harsh environments, including heat and UV.

Conduit Size	Cord Dia. Range	Brand	Item No.	Conduit Size	Cord Dia. Range	Brand	Item No.	
Straight				Steel				
Aluminum				1/2"	0.25 in to 0.35 in	Raco	52AX47	
0.06 in to 0.13 in	Raco	52AY03	0.50 in to 0.75 in		T&B	2DDG6		
1/2"	0.25 in to 0.31 in	Raco	52AY07	3/4"	0.25 in to 0.38 in	Raco	52AY13	
	0.31 in to 0.38 in	Raco	52AY15		0.38 in to 0.50 in	Raco	52AY11	
	0.50 in to 0.63 in	Raco	52AY10		0.45 in to 0.56 in	Raco	52AY05	
3/4"	0.19 in to 0.25 in	Raco	52AX42	1"	0.60 in to 0.70 in	Raco	52AX43	
	0.50 in to 0.63 in	Raco	52AY09		0.70 in to 0.85 in	Raco	52AY18	
	1"	0.38 in to 0.50 in	Raco	52AX52	90°			
0.50 in to 0.63 in		Raco	52AX45	Aluminum				
0.63 in to 0.75 in		Raco	52AX46	1/2"	0.13 in to 0.38 in	T&B	2DDK4	
0.70 in to 0.95 in	T&B	2DDJ7	0.31 in to 0.56 in		T&B	2DDK7		
Malleable Iron/Steel				1/2"	0.13 in to 0.38 in	T&B	2DDL2	
1/2"	0.12 in to 0.25 in	Raco	2A246		3/4"	0.31 in to 0.56 in	T&B	2DDL5
	0.25 in to 0.38 in	Raco	2A247			0.50 in to 0.75 in	T&B	2DDL8
Nylon				1"	0.31 in to 0.56 in	T&B	2DDN2	
1/2"	0.06 in to 0.13 in	Raco	52AY06		Malleable Iron			
	0.25 in to 0.38 in	Raco	52AY08	1/2"	0.15 in to 0.25 in	Raco	52AY16	
	0.50 in to 0.63 in	Raco	52AY12		0.25 in to 0.38 in	Raco	52AY17	
3/4"	0.13 in to 0.38 in	T&B	2DDH2	3/4"	0.45 in to 0.56 in	Raco	52AY19	
	0.38 in to 0.50 in	Raco	52AY20		1"	0.25 in to 0.38 in	Raco	52AX44
	0.50 in to 0.63 in	Raco	52AY14			0.45 in to 0.56 in	Raco	52AY21
1"	0.31 in to 0.56 in	T&B	2DDJ2	1"	0.45 in to 0.56 in	Raco	52AX53	
	0.63 in to 0.75 in	Raco	52AX49		Nylon			
Stainless Steel				1/2"	0.13 in to 0.38 in	T&B	2DDK5	
1/2"	0.13 in to 0.38 in	T&B	3EHV6		0.31 in to 0.56 in	T&B	2DDK8	
	0.36 in to 0.56 in	T&B	3EHV7		0.13 in to 0.38 in	T&B	2DDL3	
	0.50 in to 0.75 in	T&B	3EHV8	0.31 in to 0.56 in	T&B	2DDL6		
3/4"	0.13 in to 0.38 in	T&B	3EHV9	1"	0.50 in to 0.75 in	T&B	2DDL9	
	0.31 in to 0.56 in	T&B	3EHW1		45°			
	0.50 in to 0.75 in	T&B	3EHW2		Malleable Iron			
1"	0.31 in to 0.56 in	T&B	3EHW3	1/2"	0.15 in to 0.25 in	Raco	52AX50	
	0.70 in to 0.95 in	T&B	3EHW4		0.25 in to 0.35 in	Raco	52AX51	
					0.45 in to 0.56 in	Raco	52AX48	