

## Hubbellock Devices

Spring-loaded safety shutter ejects plug if not properly locked into connector/receptacle; shutter snuffs out arcs when devices are connected or disconnected under load. Key/detent ensures positive lock. UL Listed.



Receptacle  
3D017



Connector Body  
3D018



Plug  
3D019

Amps	No. of Poles	No. of Wires	Voltage	Color	RECEPTACLE Mfr. Model	Item No.	Color	CONNECTOR BODY Mfr. Model	Item No.	Color	PLUG Mfr. Model	Item No.
<b>Industrial Hubbellock</b>												
20	2	3	125VAC	—	—	—	—	—	—	Black	HBL23035B	3D553
20/10/10	2	3	125VAC/DC, 250VDC, 480VAC	—	—	—	Gray	HBL23002GB	3D029	Gray	HBL23005GB	3D031
20/10/10	2	3	125V AC/DC, 250V DC, 480V AC	Black	HBL23000G	3D026	Red	HBL20444B	3D018	Red	HBL20445B	3D019
30	3	4	480VAC	Black	HBL20443	3D017	Black	HBL21414B	5C993	Black	HBL21415B	5C994
30	3	4	480V AC	Black	HBL20403	3D015	Black	HBL25414B	3D058	Black	HBL25415B	3D059
30/20	3	4	600VAC/250VDC	Black	HBL20403	3D015	Black	HBL25414B	3D058	Black	HBL25415B	3D059
30/20	3	4	600V AC/250V DC	Black	HBL20403	3D015	Black	HBL25414B	3D058	Black	HBL25415B	3D059
30/20	4	5	600VAC/250VDC	Blue	HBL25403	3D057	Yellow	HBL26418	3D080	Yellow	HBL26419	3D081
30/20	4	5	600V AC/250V DC	Blue	HBL25403	3D057	Yellow	HBL26418	3D080	Yellow	HBL26419	3D081
60	3	4	600VAC	Black	HBL26410	3D079	Blue	HBL26516	3D083	Blue	HBL26519	3D084
60	3	4	600V AC	Black	HBL26410	3D079	Blue	HBL26516	3D083	Blue	HBL26519	3D084
60	4	5	600VAC	Blue	HBL26520	2AXH9	—	—	—	—	—	—
60	4	5	600V AC	Blue	HBL26520	2AXH9	—	—	—	—	—	—
<b>Hospital Hubbellock</b>												
20	2	3	125VAC	—	—	—	Gray	HBL23001HGB	3D028	Gray	HBL23004HG	3D030
20	2	3	125VAC	—	—	—	Gray	HBL23001HGB	3D028	Gray	HBL23004HG	3D030
20	2	3	125V AC	Black	HBL23000HG	3D027	—	—	—	—	—	—
50	2	3	250VAC	Black	HBL25503	3D061	—	—	—	—	—	—
50	2	3	250V AC	Black	HBL25503	3D061	—	—	—	—	—	—
<b>Flanged Inlet</b>												
30/20	3	4	600V AC/250V DC	—	—	—	—	—	—	Gray	HBL20418	3D505
50	3	4	600V AC/250V DC	—	—	—	—	—	—	Gray	HBL3775	3D735
50	3	4	600V AC/250V DC	—	—	—	—	—	—	Gray	HBL3768	3D734

Description	Color	Mfr. Model	Item No.
Accessories and Other Hubbellock Devices			
Weatherproof Plate for No. 3D015 (for FS/FD box mounting)	Aluminum	HBL20405	3D016
Receptacle Box for Nos. 3D085 and 3D086 Only	Silver	HBL26401	3D076
Adapter Plate, For Use with Receptacle Box No. 3D076	Silver	HBL26402	2AXJ1
45° Adapter for Receptacle Box No. 3D076	Silver	HBL26404	3D078
Explosionproof Plug with Epoxy Kit, 2-Pole, 3-Wire, 20A, 125V, Hospital Rated	Gray	HBL24312	3D051

\* Includes FS/FD indoor cover. † 30A at 600VAC, 20A at 250VDC. ‡ Includes lift cover. \*\* Epoxy filled. # Weatherproof plate for FS/FD box mounting available, use 6C615, see page 288.

## IEC Nonmetallic Watertight Pin and Sleeve Devices

Feature a tough, nylon housing that protects against cracking, warping, corrosion, and chemical abrasion. Neoprene sealing glands provide a water-tight seal. Solid brass pins provide contact reliability and superior conductivity.

Amps	Color	Voltage	Phase	CONNECTOR Mfr. Model	Item No.	PLUG Mfr. Model	Item No.	RECEPTACLE Mfr. Model	Item No.
<b>2 Pole, 3 Wire</b>									
20	Blue	250VAC	Single	—	—	BRY320P6W	49YX88	BRY320R6W	49YY01
<b>3 Pole, 4 Wire</b>									
20	Red	480VAC	Three	BRY420C7W	49YX81	BRY420P7W	49YX92	BRY420R7W	49YY05
30	Blue	250VAC	Three	—	—	BRY430P9W	49YX94	—	—
30	Red	480VAC	Three	BRY430C7W	49YX82	BRY430P7W	49YX93	—	—
30	Red	480VAC	Single, Three	—	—	—	—	BRY430R7W	49YY06
60	Blue	250VAC	Three	BRY460C9W	49YX85	BRY460P9W	49YX97	BRY460R9W	49YY08
60	Red	480VAC	Three	BRY460C7W	49YX84	BRY460P7W	49YX96	—	—
60	Black	600VAC	Three	BRY460C5W	49YX83	BRY460P5W	49YX95	—	—
100	Blue	250VAC	Three	BRY4100C9W	49YX80	BRY4100P9W	49YX91	BRY4100R9W	49YY04
100	Red	480VAC	Three	BRY4100C7W	49YX79	BRY4100P7W	49YX90	BRY4100R7W	49YY03
<b>4 Pole, 5 Wire</b>									
60	Blue	120/208VAC	Three	BRY560C9W	49YX87	BRY560P9W	49YX99	BRY560R9W	49YY11
100	Blue	120/208VAC	Three	BRY5100C9W	49YX86	BRY5100P9W	49YX98	BRY5100R9W	49YY10



Connector  
49YX81



Plug  
49YX91



Receptacle  
49YY04



## Hubbell Single-Pole Connectors

Nonmetallic retaining screw locks contacts in place so they don't move within the housing. Special screw thread prevents installation 180° out of rotation and requires fewer turns, reducing the chance of a conductive screw being substituted. Multiple guides ease cutting to correct cable size. Large raised alignment arrow eases mating of devices. 600VAC/250VDC. Rated NEMA 3R, 4X and 12K. UL and C-UL Listed.

Amps AC/DC	Cable Range	Terminal Connc.	Black Item No.	Blue Item No.	FEMALE Green Item No.	Red Item No.	White Item No.	Black Item No.	Blue Item No.	MALE Green Item No.	Red Item No.	White Item No.
<b>Connectors</b>												
300AC/DC	6 to 2/0	Double Set Screw	2XB25	2XB26	2XB27	2XB28	2XB29	2XB30	2XB31	2XB32	2XB33	2XB34
400AC/DC	2/0 to 4/0	Double Set Screw	2XB35	2XB36	2XB37	2XB38	2XB39	2XB40	2XB41	2XB42	2XB43	2XB44
<b>Receptacles</b>												
400AC/DC	4 to 4/0	Double Set Screw	2XB50	2XB51	2XB52	2XB53	2XB59	2XB65	2XB66	2XB67	2XB68	2XB74
400AC/DC	N/A	Threaded Stud	2XB54	2XB55	2XB56	2XB57	2XB58	2XB69	2XB70	2XB71	2XB72	2XB73
<b>Accessories</b>												
Protective Caps for Connectors			2XB45	2XB46	2XB47	2XB48	2XB49	2XB60	2XB61	2XB62	2XB63	2XB64
Snap Back Covers for Receptacles, Fits Male and Female			2XB75	2XB76	2XB77	2XB78	2XB79	2XB75	2XB76	2XB77	2XB78	2XB79